

# Measuring the Variability of Human Movement

Miguel Xochicale<sup>1</sup>, Chris Baber<sup>1</sup> and Mourad Ouassalah<sup>2</sup>; [map479@bham.ac.uk]

<sup>1</sup> School of Electronic, Electrical and Systems Engineering, University of Birmingham, UK


<sup>2</sup> Center for Ubiquitous Computing, University of Oulu, Finland

## PROBLEM

Variability is an inherent characteristic of human movement [1]. Generally, humans perform the same action slightly differently trial by trial. For these reasons we are interested in studying methods that can give insight into the variability between individuals and repetitions of the same movement. We believe that this preliminary study might provide useful information for activity recognition, e.g. in terms of detecting changes of user's behaviour (enthusiasm, boredom, tiredness or confusion) in the way in which activities are performed over the course of training, practice or rehabilitation.

## ACTIVITY RECOGNITION

Activity Recognition Chain (ARC) for inertial sensors [2] where traditional feature extraction techniques are time domain, frequency domain and discrete domain [3].



## MATERIALS AND METHODS

Raw time-series data is collected from a triaxial accelerometer ( $a_x, a_y, a_z$ ) and a triaxial gyroscope ( $g_x, g_y, g_z$ ). Then, a  $N$  samples length time-series, e.g.  $a_x$ , is used to obtain the time-delay embedded matrix,  $E\{a_x\}$ , with  $m = 20$  and  $\tau = 6$  [4, 5]. Finally, PCA is applied to  $E\{a_x\}$  to compute the percentage of cumulative energy [6]. The method is applied to six simple movements which were performed by six participants wearing an inertial sensor on their right wrist, each movement were continuously repeated for 20 seconds.

## CONCLUSION AND OUTLOOK

Measuring variability in human activity offers an approach to understand user's performance over the course of training, practice or rehabilitation. In the future, we will collect data from a wider range of individuals (gender and age) and from additional sensors. Also, different classification techniques will be explored.

## REFERENCES



- [1] Karl M. Newell and Daniel M. Corcos. 1993. Variability and motor control. Human Kinetics Publishers.
- [2] Oresti Banos, Juan-Manuel Galvez, Miguel Damas, Hector Pomares and , Ignacio Rojas. 2014. Window size impact in human activity recognition. In *Sensors (Basel, Switzerland)*, 14, 6474-99
- [3] Davide Figo, Pedro C. Diniz, Diogo R. Ferreira and João M. P. Cardoso. 2010. Preprocessing techniques for context recognition from accelerometer data. In *Personal and Ubiquitous Computing*, 7, 645-662.
- [4] Jordan Frank, Shie Mannor and Doina Precup. 2010. Activity and Gait Recognition with Time-Delay Embeddings. In *Proceedings of the 24-th AAAI Conference on Artificial Intelligence*, 1581-1586.
- [5] Albert Samà, Francisco J. Ruiz, Núria Agell, Carlos Pérez-López, Andreu Català and Joan Cabestany. 2013. Gait identification by means of box approximation geometry of reconstructed attractors in latent space. In *Neurocomputing*, 121, 79-88.
- [6] Nils Y Hammerla, Thomas Plötz, Peter Andras and Patrick Olivier. 2011. Assessing Motor Performance with pca. In *International Workshop on Frontiers in Activity Recognition using Pervasive Sensing*, 18-23.

## VARIABILITY OF SIMPLISTIC MOVEMENTS



The values of percentage of cumulative energy (PCE) are presented for triaxial accelerometer (ACC) and triaxial gyroscope (GYR) sensors accross partipants and their average denoted by "avg".

It is apparent that circular and 8-shape movements show a constant trend between participants; however, such a trend is not evident for the other movements. We assume that the evident variability for the static, horizontal, vertical and diagonal movements is due to the flexibility in the experiment where participants were only asked to perform the movements at a comfortable speed.



Static





Horizontal





Vertical



Diagonal



Circular



8-shape

