

Towards the Analysis of Movement Variability in Human-Humanoid Interaction

Miguel P. Xochicale¹, Chris Baber¹ and Mourad Oussalah²

¹School of Engineering, University of Birmingham, U.K.

²Center for Ubiquitous Computing, University of Oulu, Finland

HCI Seminars

School of Computer Science, University of Birmingham, UK

26 April 2017

Outline

I. Introduction – Movement Variability

II. Methods – Reconstructed State Space (RSS)

A. RSS in Human-Activity Recognition (HAR)

III. Experiment – Human-Humanoid Imitation

A. Experiment Design

B. Participants

III. Some Preliminary Results

A. Timeseries of Accelerometer

B. Reconstructed State Space

IV. Conclusions and Future Work

Outline

I. Introduction – Movement Variability

II. Methods – Reconstructed State Space (RSS)

A. RSS in Human-Activity Recognition (HAR)

III. Experiment – Human-Humanoid Imitation

A. Experiment Design

B. Participants

III. Some Preliminary Results

A. Timeseries of Accelerometer

B. Reconstructed State Space

IV. Conclusions and Future Work

Movement Variability is not NOISE




Figure 1: Find the piñata [Herzfeld and Shadmehr, 2014].

Movement Variability

Movement Variability is an inherent feature that occurs not only within individual but also between individual systems of movement **[Newell and Corcos, 1993]**.

How to measure Movement Variability?

According to **[Preatoni et al., 2013]**, some nonlinear dynamics tools (dynamic invariants) can be used to explore the nature of movement variability and its relationship with skills development are:

- **Reconstructed State Space (RSS),**
- Lyapunov Exponent.

Outline

I. Introduction – Movement Variability

II. Methods – Reconstructed State Space (RSS)

A. RSS in Human-Activity Recognition (HAR)

III. Experiment – Human-Humanoid Imitation

A. Experiment Design

B. Participants

III. Some Preliminary Results

A. Timeseries of Accelerometer

B. Reconstructed State Space

IV. Conclusions and Future Work

Reconstruct State Space (RSS)




Figure 2: Reconstruction of a multidimensional attractor
[Quintana-Duque, 2012].

RSS in HAR




Figure 3: 3D Reconstructed State Spaces ($m = 3, \tau = 4$) for walking (left), running (middle), and cycling (right).

[Frank et al., 2010, Frank et al., 2012].

RSS in HAR




Figure 4: 2D Reconstructed State Spaces for gait patterns of two persons ($m = 20$ for $\tau = 1$, $\tau = 4$ and $\tau = 9$, respectively).
[Samà et al., 2013].

How to build a ReconstructedStateSpace

For a given discrete time-series $x(n) = [x(1), x(2), \dots, x(N)]$, a reconstructed state space can be created by

$$\bar{x}(n) = [x(n), x(n - \tau), x(n - 2\tau), \dots, x(n - (m - 1)\tau)]$$

which creates a concatenated column-wise matrix of the time-delay versions of the original signal:

$$\mathbf{X} = \begin{pmatrix} x(1) & x(1 - \tau) & x(1 - 2\tau) & \dots & x(1 - (m - 1)\tau) \\ x(2) & x(2 - \tau) & x(2 - 2\tau) & \dots & x(2 - (m - 1)\tau) \\ \vdots & & & \ddots & \vdots \\ x(N) & x(N - \tau) & x(N - 2\tau) & \dots & x(N - (m - 1)\tau) \end{pmatrix}$$

where m is the **embedding dimension** and τ is the **embedding delay** **[Takens, 1981]**.

Takens' Theorem

The Takens' Theorem states that for a large enough m it is possible to unfold the attractor and $\tau > 0$ is chosen to maximize the information content of $x(n)$.

False Nearest Neighborhood and Mutual Information algorithms are used to compute the optimal value of m and τ . However, as pointed out by **[Samà et al., 2013]** the optimal values don't necessarily represent the best rate of recognition.

RSS using PCA




Figure 5: Framework to build the RSS

Outline

I. Introduction – Movement Variability

II. Methods – Reconstructed State Space (RSS)

A. RSS in Human-Activity Recognition (HAR)

III. Experiment – Human-Humanoid Imitation

A. Experiment Design

B. Participants

III. Some Preliminary Results


A. Timeseries of Accelerometer

B. Reconstructed State Space

IV. Conclusions and Future Work

Experiment Design

HORIZONTAL



* HNORMAL

* HFASTER

VERTICAL



* VNORMAL

* VFASTER

Figure 6: Front-to-Front Human-Humanoid Imitation Using Wearable Inertial Sensors

Outline

I. Introduction – Movement Variability

II. Methods – Reconstructed State Space (RSS)

A. RSS in Human-Activity Recognition (HAR)

III. Experiment – Human-Humanoid Imitation

A. Experiment Design

B. Participants

III. Some Preliminary Results

A. Timeseries of Accelerometer

B. Reconstructed State Space

IV. Conclusions and Future Work

Participants

Twenty right-handed healthy participants (two females and ten males) with a mean age of 19.5 ± 0.79 (from now on abbreviated as p01 to p12) were invited to participate in this study.

Outline

I. Introduction – Movement Variability

II. Methods – Reconstructed State Space (RSS)

A. RSS in Human-Activity Recognition (HAR)

III. Experiment – Human-Humanoid Imitation

A. Experiment Design

B. Participants

III. Some Preliminary Results


A. Timeseries of Accelerometer

B. Reconstructed State Space


IV. Conclusions and Future Work

Raw Data from the Humanoid


AccX



AccY




AccZ




Smoothed Data from the Humanoid


sgAccX



sgAccY




sgAccZ




Raw Data from the Human


AccX



AccY




AccZ




Smoothed Data from the Human


sgAccX



sgAccY



sgAccZ



Outline

I. Introduction – Movement Variability

II. Methods – Reconstructed State Space (RSS)

A. RSS in Human-Activity Recognition (HAR)

III. Experiment – Human-Humanoid Imitation

A. Experiment Design

B. Participants

III. Some Preliminary Results

A. Timeseries of Accelerometer


B. Reconstructed State Space

IV. Conclusions and Future Work




RSS for Humanoid trial01 sgAccX

RSS with $m = 40$, $\tau = 10$

HN



HF




VN


RSS for Humanoid trial10 sgAccX

RSS with $m = 40$, $\tau = 10$


HN




HF



VN





VF





RSS for Humanoid trial20 sgAccX

RSS with $m = 40$, $\tau = 10$

HN



HF




VN

VF


RSS for Human p01 sgAccX

RSS with $m = 40$, $\tau = 10$

HN



HF





VN

VF



RSS for Human p10 sgAccX

RSS with $m = 40$, $\tau = 10$

HN



HF





VN

VF



RSS for Human p20 sgAccX

RSS with $m = 40$, $\tau = 10$

HN



HF




VN

VF

Euclidean Distances in the RSS

RSS with $m = 40$, $\tau = 10$



Outline

I. Introduction – Movement Variability

II. Methods – Reconstructed State Space (RSS)

A. RSS in Human-Activity Recognition (HAR)

III. Experiment – Human-Humanoid Imitation

A. Experiment Design

B. Participants

III. Some Preliminary Results

A. Timeseries of Accelerometer

B. Reconstructed State Space

IV. Conclusions and Future Work

Conclusions and Future Work

Pros and Cons of RSS

- (+) The RSS provide a visually a good representation of the variability of the activities.
- (-) The quality of the Euclidean distances in the RSS is debatable and needs further investigation.

TODO List:

- Have better understanding of the time-delay embedding theorem
- Implement the Lyapunov Exponent.
- Use Convolutional Neural Networks to classify Movement Variability

QUESTIONS?

Miguel P. Xochicale

Doctoral Researcher in Human-Robot Interaction (2014-2018)
University of Birmingham, U.K.

<http://mxochicale.github.io/>



My own pictures are release under CC BY-NC 4.0

<http://creativecommons.org/licenses/by-nc/4.0/>

Give credits to: Miguel P. Xochicale

References I

-  Frank, J., Mannor, S., Pineau, J., and Precup, D. (2012).
Time Series Analysis Using Geometric Template Matching.
IEEE Transactions on Pattern Analysis and Machine Intelligence, 35(3):1–1.
-  Frank, J., Mannor, S., and Precup, D. (2010).
Activity and Gait Recognition with Time-Delay Embeddings.
AAAI Conference on Artificial Intelligence, pages 407–408.
-  Herzfeld, D. J. and Shadmehr, R. (2014).
Motor variability is not noise, but grist for the learning mill.
Nature neuroscience, 17(2):149–50.
-  Newell, K. and Corcos, D. (1993).
Variability and Motor Control.
Human Kinetics Publishers.
-  Preatoni, E., Hamill, J., Harrison, A. J., Hayes, K., Emmerik, R. E. A. V., Wilson, C., and Rodado, R. (2013).
Movement variability and skills monitoring in sports.
Sports Biomechanics, 12(2):69–92.

References II



Quintana-Duque, J. (2012).

Non-linear Dynamic Invariants Based on Embedding Reconstruction of Systems for Pedaling Motion Concepts :.

In *Proceedings Sportinformatik 2012 9. Symposium der dvs-Sektion Sportinformatik*, pages 28–38.



Samà, A., Ruiz, F. J., Agell, N., Pérez-López, C., Català, A., and Cabestany, J. (2013).

Gait identification by means of box approximation geometry of reconstructed attractors in latent space.

Neurocomputing, 121:79–88.



Takens, F. (1981).

Detecting strange attractors in turbulence.

Dynamical Systems and Turbulence, Warwick 1980, 898:366–381.