The finite-block cost of universality in entanglement extraction

Yongxian Zhang*

October 2026

Abstract

We study entanglement extraction by a global unitary on an existing many-copy input followed by deterministic local channels. The global preprocessing is an explicit entangling resource; no auxiliary system is supplied before it. We establish finite-dimensional spectral and subspace packing principles that match converses for completely PPT postprocessing. One state-independent protocol attains the state-aware capacity, exact fidelity exponent, strict-direct reliability function, and entropy-limited Gaussian threshold of every fixed input. A finite-block information-spectrum sandwich retains its dimension dependence and gives sufficient conditions for growing-dimensional Gaussian limits. We then determine the sharp minimax cost of an unknown support. For every fixed rank budget, a coherent common-support code matches a Haar-average converse, relatively and uniformly over all target dimensions. The support dimension and the reciprocal purity of the averaged input have the same leading asymptotic, yielding an explicit logarithmic loss in the extractable target size and a transition at the local-dimension cap. For balanced unknown pure inputs, the full-output fidelity has leading constant one. These results distinguish pointwise asymptotic universality from uniform finite-block performance. Standard compression, representation theory, and distillation results are explicitly credited.

1 Introduction and operational model

Universal quantum protocols operate without a classical description of their input. Universal compression, pure-state concentration, and mixed-state distillation establish several senses in which ignorance need not change an asymptotic rate [3, 6, 9, 10, 11, 12]. Equality of rates, however, does not determine a common protocol's finite-block performance. The same leading capacity can coexist with a polynomial fidelity loss, and a rank promise can incur a logarithmic target-size penalty invisible to the first-order rate.

We examine these distinctions in a two-stage extraction model. First apply one global unitary on the existing input space. Then apply deterministic local product channels, LOCC,

*School of Computer Science and Engineering, South China University of Technology, Guangzhou, China. Email: mxymmxym1@gmail.com. ORCID: 0009-0000-3864-3536.

or completely PPT channels. The global unitary is an entangling resource. This task is therefore distinct from ordinary LOCC distillation of the original fixed state. Its utility is to separate the spectral supply of purity from subsequent extraction and to ask what can be achieved by one preprocessing independent of the entire state.

The main method is a finite-dimensional comparison between spectral or common-subspace packing and the quadratic constraint on a completely PPT fidelity effect. It has three consequences. First, a variable-size Bell packing gives a one-shot spectral envelope, within logarithmic factors, for every bipartite spectrum. Second, intrinsic polynomial matrix-orbit projections and a geometric Bell-packing grid give one protocol for all states, with an explicit finite-block information-spectrum sandwich. Third, for a class of unknown inputs, a common-support code is compared with an adversarial averaged state. Literal Haar minor moments and an operator lower bound show that the common-support dimension and the reciprocal purity of that average agree asymptotically. The entire minimax fidelity profile then follows with leading constant one, uniformly over all target integers.

1.1 Model and quantifiers

Fix integers $2 \le m \le n$, set $D = mn$, and write

$$a = m^k, \qquad b = n^k, \qquad N = D^k$$

at copy number $k \ge 1$. All logarithms are natural. Let Φ_K denote the normalized rank-one maximally entangled projector on $\mathbb{C}^K \otimes \mathbb{C}^K$. We use the target overlap $\mathrm{Tr}(\Phi_K \sigma)$ as fidelity; no square root is taken.

A protocol comprises a unitary U on $\mathbb{C}^a \otimes \mathbb{C}^b$ and a trace-preserving channel Λ to $\mathbb{C}^K \otimes \mathbb{C}^K$. No ancilla, measurement, or discarded register is supplied before U. Local ancillas and discarding are permitted afterwards. The operation class LO consists of product channels, and LOCC denotes finite-round adaptive local instruments with communicated outcomes; hidden Kraus indices may refine each public outcome. We also consider its closure in the finite-dimensional topology of all matrix-unit channel coefficients. A channel is completely PPT, denoted cPPT, if both Λ and $\Gamma_{\mathrm{out}} \Lambda \Gamma_{\mathrm{in}}$ are completely positive and trace preserving; Γ transposes the first party. Thus $\mathrm{LO} \subseteq \mathrm{LOCC} \subseteq \overline{\mathrm{LOCC}} \subseteq \mathrm{cPPT}$. All stated intermediate-class conclusions apply to the closure as well. Complete positivity of the transpose-conjugated channel is required on every auxiliary space. The arbitrary global preprocessing U remains a separate entangling resource and is not included in this PPT restriction.

For a density matrix ρ on $\mathbb{C}^m \otimes \mathbb{C}^n$, define

$$f_k^{\mathcal{C}}(\rho, K) = \sup_{U, \Lambda \in \mathcal{C}} \mathrm{Tr}\Big[\Phi_K \Lambda(U \rho^{\otimes k} U^*)\Big]. \tag{1}$$

The optimizing protocol in this expression may depend on ρ. In contrast, our all-state universal family has quantifiers

$$\exists \{U_{k,K}, \mathcal{A}_{k,K}, \mathcal{B}_{k,K}\}_{k,K} \quad \forall \rho, \tag{2}$$

with dependence only on m, n, k, K. We write $F_k^{\mathrm{u}}(\rho, K)$ for its fidelity and $F_k^\star = f_k^{\mathrm{cPPT}}$. No spectrum, eigenbasis, rank, or entropy is an input to this family.

A different, explicitly promised task fixes a rank budget $1 \le s \le D$ and defines

$$\mathcal{G}_{\mathcal{C}}(k, K; s) = \sup_{U,\Lambda\in\mathcal{C}} \inf_{\operatorname{rank}\rho\le s} \operatorname{Tr}\left[\Phi_K \Lambda(U\rho^{\otimes k}U^*)\right]. \tag{3}$$

Here one protocol may depend on s, but it must serve every spectrum and every support orientation in that class. Pointwise universality in (2) and minimax universality in (3) are different assertions. We retain that distinction throughout.

1.2 Results and relation to prior work

Section 2 proves the actual finite-dimensional converse and packing principles. Section 3 gives a universal physical construction and a dimension-explicit finite-block sandwich. Section 4 derives the exact capacity and error laws. Section 5 proves the sharp rank-budget minimax profile, including the boundary at $n = ms$ and its logarithmic correction. Section 6 connects the capacity to APPT entropy optimization and specifies the scope of the accompanying formal verification.

The fidelity-effect characterization is due to Rains [1]. Lami's quadratic converse already implies the half entropy-deficit upper bound [2]; we supply a direct finite-dimensional derivation and matching local constructions. Schur–Weyl universal compression and estimation are established methods [3, 4, 8]. Exact symmetric-state compression, including efficient qubit constructions, predates this work [16, 17]. We do not claim the symmetric-subspace dimension or compression mechanism as new. Classical source-coding reliability and second-order asymptotics are likewise prior results [7].

Recent universal distillation and coding results remove input-state knowledge under other free operations [9, 10, 11, 12]. State-agnostic work extraction studies a thermodynamic model [14, 15]. Their operations and resources differ from the global entangling preprocessing allowed here. Our claims concern the stated two-stage model: a common deterministic physical packing, matching completely PPT converses, finite-block control with visible dimension dependence, and a sharp target-uniform minimax law for an unknown rank-bounded support. The fact that a protocol is universal, by itself, is not presented as a new principle.

Known-spectrum, unknown-eigenbasis families also appear in the quantum minimum-description-length problem of Hayden, Maloney, Wang and Yang [13]. Their encoder and decoder minimize the memory needed to recover the many-copy state with vanishing trace-distance error, without requiring preservation of its purification. The loss quantified here is the attainable entangled target under a common global unitary and deterministic local postprocessing, with a uniform relative fidelity profile over all target dimensions.

Purity-based extraction also includes the stochastic-unital analysis of Kondra et al. [27], which characterizes complete absolute separability, studies stability under adjoining maximally mixed local systems, and proves finite-copy activation. Their probabilistic convertibility problem permits postselection and compares states in the same output space. Our deterministic, variable-target fidelity optimization has a different resource specification. The qualitative possibility of activation is prior work.

2 Finite-dimensional spectral and subspace principles

Throughout this section the input dimensions are arbitrary integers $2 \le a \le b$, $N = ab$, and $K \ge 2$. The case $K = 1$ is the trivial exact product target.

Lemma 2.1 (Fidelity effects, following Rains)**.** *For a completely PPT channel let* $M = \Lambda^*(\Phi_K)$*. Then*

$$0 \le M \le I, \qquad -I/K \le M^\Gamma \le I/K. \tag{4}$$

Conversely every such M *is a fidelity effect of a completely PPT channel. Moreover,*

$$\operatorname{Tr} M^2 \le N/K^2, \qquad \|M\|_\infty \le \beta := \min(1, a/K). \tag{5}$$

Proof. The adjoint of a channel is positive and unital. Since $\Phi_K^\Gamma = F_K/K$ for the swap F_K, and $-I \le F_K \le I$, apply the adjoint of $\Gamma_{\text{out}}\Lambda\Gamma_{\text{in}}$ to these order bounds. This gives (4).

For the converse define

$$\Lambda_M(X) = \operatorname{Tr}(MX)\Phi_K + \operatorname{Tr}((I - M)X)\frac{I - \Phi_K}{K^2 - 1}.$$

This is a measure-and-prepare channel. Writing $Q_\pm = (I \pm F_K)/2$, its partial-transpose conjugate is

$$X \longmapsto \operatorname{Tr}\left[\frac{I + KM^\Gamma}{K(K+1)}X\right] Q_+ + \operatorname{Tr}\left[\frac{I - KM^\Gamma}{K(K-1)}X\right] Q_-.$$

Both coefficient effects are positive, and the map is trace preserving because $\operatorname{Tr} Q_\pm = K(K \pm 1)/2$. Its target overlap is $\operatorname{Tr}(MX)$.

Partial transpose preserves the Hilbert–Schmidt norm. The eigenvalues of M^Γ belong to $[-1/K, 1/K]$, proving the first bound in (5). For a unit vector v, the partial transpose of vv^* has trace norm $(\sum_j t_j)^2 \le a$, where t_j are the Schmidt coefficients. Hence

$$\langle v, Mv\rangle = \operatorname{Tr}\Big(M^\Gamma (vv^*)^\Gamma\Big) \le a/K.$$

Together with $M \le I$, this proves the norm bound. □

Lemma 2.2 (Coherent common-subspace packing)**.** *Let* $S \subseteq \mathbb{C}^a \otimes \mathbb{C}^b$ *be a known subspace of dimension* r*. If*

$$1 \le d \le \min(a, K), \qquad \lfloor a/d \rfloor \lfloor b/d \rfloor \ge r, \tag{6}$$

one unitary on the original input followed by deterministic product channels sends every density matrix supported on S *to the same embedded* Φ_d*. Its target-*K *fidelity is* d/K*.*

Proof. Put $u = \lfloor a/d \rfloor$ and $v = \lfloor b/d \rfloor$. In local coordinate blocks there are uv orthonormal vectors

$$|\psi_{ij}\rangle = d^{-1/2} \sum_{t=0}^{d-1} |id + t\rangle_A |jd + t\rangle_B, \quad 0 \le i < u, \quad 0 \le j < v.$$

Map a fixed orthonormal basis of S to r distinct such vectors and extend the resulting isometry to a unitary on the full N-dimensional input. Alice uses

$$A_i = \sum_{t<d} |t\rangle_K \langle id + t|,$$

and $|0\rangle\langle z|$ for each unused input coordinate z. Bob uses the corresponding maps. The Kraus adjoint products sum to I_a and I_b, including all unused coordinates.

For these product channels,

$$|\psi_{ij}\rangle\langle\psi_{i'j'}| \longmapsto \delta_{ii'}\delta_{jj'}\Phi_d.$$

Thus any logical matrix X on the selected code maps to $(\operatorname{Tr} X)\Phi_d$, including every off-diagonal coherence. A density matrix on S therefore has output Φ_d. Finally $\operatorname{Tr}(\Phi_K\Phi_d) = d/K$. No branch is postselected or renormalized. □

Proposition 2.3 (A subspace-versus-average comparison)**.** *Let a family $\mathscr{F}$ of input states be supported on one r-dimensional subspace, and let Ω be a probability average of states in that family. Define*

$$d_{a,b}(r) = \max\{d \in \{1,\dots,a\} : \lfloor a/d\rfloor\lfloor b/d\rfloor \geq r\}.$$

For the minimax fidelity over $\mathscr{F}$,

$$\begin{aligned}\min(1, d_{a,b}(r)/K) &\leq \sup_{U,\Lambda\in\mathrm{LO}} \inf_{\sigma\in\mathscr{F}} F(U,\Lambda;\sigma) \\ &\leq \sup_{U,\Lambda\in\mathrm{cPPT}} \inf_{\sigma\in\mathscr{F}} F(U,\Lambda;\sigma) \leq \min\left(1, \frac{a}{K}, \frac{\sqrt{ab\operatorname{Tr}\Omega^2}}{K}\right). \end{aligned} \tag{7}$$

The intermediate LOCC minimax value satisfies the same bounds.

Proof. Use Lemma 2.2 with $d = \min(K, d_{a,b}(r))$. For the upper bound, the infimum for a fixed protocol is at most its average,

$$\inf_{\sigma\in\mathscr{F}} F(U,\Lambda;\sigma) \leq \operatorname{Tr}(MU\Omega U^*) \leq \sqrt{\operatorname{Tr} M^2 \operatorname{Tr}\Omega^2}.$$

Apply (5); the other two bounds follow from the trace-one condition and the norm bound. Averaging is used only to prove a converse, not as an operation in the protocol. □

We also need a spectral comparison for a single input. Let its eigenvalues be $\lambda_1 \geq \cdots \geq \lambda_N \geq 0$, and put

$$L_r = \sum_{i\leq r}\lambda_i, \quad v_r = \min\left(1, \frac{a}{K}, \frac{\sqrt{N/r}}{K}\right), \quad T_K = \max_{1\leq r\leq N} v_r L_r. \tag{8}$$

Theorem 2.4 (One-shot spectral envelope)**.** *For every input spectrum and every $K \geq 2$,*

$$T_K/4 \leq f^{\mathrm{LO}}(\lambda,K) \leq f^{\mathrm{LOCC}}(\lambda,K) \leq f^{\mathrm{cPPT}}(\lambda,K) \leq H_N T_K, \qquad H_N = \sum_{i=1}^{N}\frac{1}{i}. \tag{9}$$

For $1 < \alpha \leq 2$ one also has

$$f^{\mathrm{cPPT}}(\lambda,K) \leq \beta^{(2-\alpha)/\alpha}(N/K^2)^{(\alpha-1)/\alpha}\left(\sum_i \lambda_i^\alpha\right)^{1/\alpha}. \tag{10}$$

At $\alpha = 1$ the bound is $f \leq \beta$.

Proof. The decreasing eigenvalues μ_r of a fidelity effect satisfy $\mu_r \le v_r$, by (5). The spectral trace inequality and $\lambda_i \le L_i/i$ give

$$\operatorname{Tr}(MU\rho U^*) \le \sum_i \lambda_i \mu_i \le \sum_i \lambda_i v_i \le H_N T_K.$$

For a prefix rank r put $w = \min(a, K, \sqrt{N/r})$ and $d = \max(1, \lfloor w/2 \rfloor)$. Then $d \ge w/4$ and (6) holds. Indeed $d = 1$ is always feasible; otherwise $\lfloor a/d \rfloor \lfloor b/d \rfloor \ge N/(4d^2) \ge N/w^2 \ge r$. Apply Lemma 2.2 to the span of the top r eigenvectors. The remaining positive input contributes nonnegatively, giving fidelity at least $(d/K)L_r \ge v_r L_r/4$.

For (10) let $q = \alpha/(\alpha - 1) \ge 2$. The effect eigenvalues satisfy $\operatorname{Tr} M^q \le \beta^{q-2} \operatorname{Tr} M^2$. Schatten Holder and (5) give the result. □

3 One common protocol from polynomial orbit spaces

We give an intrinsic construction on the original tensor coordinates. It needs neither a supplied eigenbasis nor a Schur decomposition. All spaces, bases and integer packings below are fixed before the input state is quantified.

3.1 Universal orbit projections

Write $\mathcal{W}_{D,k} = \{1, \dots, D\}^k$, and let e_w denote a computational word. For $E \subseteq \mathcal{W}_{D,k}$ define

$$V_k(E) = \operatorname{span}\{M^{\otimes k} e_w : M \in \mathbb{C}^{D \times D},\ w \in E\}, \qquad B_{D,k} = \binom{k + D^2 - 1}{D^2 - 1}. \tag{11}$$

Here the generating matrices are arbitrary complex matrices, not only unitaries. Let $P_k(E)$ be the orthogonal projection onto this known space.

Lemma 3.1 (Polynomial orbit dimension and captured mass)**.** *The projections are nested with E, commute with every $M^{\otimes k}$, and obey*

$$\operatorname{rank} P_k(E) \le B_{D,k}|E|, \qquad \operatorname{Tr}[P_k(E)\rho^{\otimes k}] \ge \sum_{w \in E} p_{w_1} \cdots p_{w_k}, \tag{12}$$

where p is any eigenvalue labeling of ρ. If $E \ne \varnothing$, then $V_k(E)$ contains $\operatorname{Sym}^k(\mathbb{C}^D)$.

Proof. For fixed w, the vector $M^{\otimes k} e_w$ is a homogeneous degree-k polynomial in the D^2 entries of M. More precisely it is the image, under a fixed linear contraction, of $(\operatorname{vec} M)^{\otimes k}$. The span of these latter vectors has dimension $B_{D,k}$. Summing the resulting dimension bound over E proves the rank estimate.

Composition of matrices makes $V_k(E)$ invariant under every $M^{\otimes k}$, including the adjoint powers. It is therefore a reducing subspace and its orthogonal projection commutes with those powers. If U diagonalizes ρ, then $P_k(E)$ fixes $U^{\otimes k} e_w$ for $w \in E$. Its other diagonal entries in that eigenbasis are nonnegative, which proves the mass bound. Finally, for any $w \in E$ and vector z, choosing every column of M equal to z gives $M^{\otimes k} e_w = z^{\otimes k}$. Such powers span the symmetric subspace. □

Let $\widehat{p}_w$ be a word's empirical law and set

$$E_k(c) = \{w : H(\widehat{p}_w) \le c\}, \qquad Q_{D,k} = B_{D,k}(k+1)^D.$$

There are at most $(k+1)^D$ types, each containing at most $e^{kH(q)}$ words, so

$$|E_k(c)| \le (k+1)^D e^{kc}, \qquad \operatorname{rank} P_k(E_k(c)) \le Q_{D,k} e^{kc}. \tag{13}$$

These estimates hold for all real c, with the empty event allowed. For a law p, let $A_k(p,c) = \mathbb{P}_p\{H(\widehat{p}) \le c\}$.

3.2 Geometric packing and a reserved pure sector

Put

$$\begin{gathered} J = (k+1)^2, \qquad r_k = \binom{k+D-1}{D-1}, \qquad Q = 4Jr_k, \\ a_0 = \lfloor a/Q \rfloor, \quad b_0 = \lfloor b/Q \rfloor, \quad a_* = a - Ja_0, \quad b_* = b - Jb_0. \end{gathered} \tag{14}$$

If $a_0 = 0$, use the unreserved version of the construction below: replace a_0, b_0 in (15) by $\lfloor a/J \rfloor, \lfloor b/J \rfloor$, assign the successive differences of P_j directly to these J sector pairs, and omit the separate symmetric sector. Extend the resulting isometry and complete the local decoder on unused coordinates as below. If either sector dimension is zero, use the identity preprocessing and complete local reset channels. This specifies a physical family at every finite block and every positive integer target. The following bounds concern $a_0 > 0$, which holds eventually for fixed dimensions.

For $0 \le j < J$ define

$$d_j = \max\{1, \lfloor \min(K, a_0)/2^j \rfloor\}, \qquad c_j = \frac{\log(a_0 b_0/(4d_j^2)) - \log Q_{D,k}}{k}. \tag{15}$$

The d_j decrease and the c_j increase. Let $P_0 = 0$ and $P_{j+1} = P_k(E_k(c_j))$. By (13),

$$\operatorname{rank} P_{j+1} \le \frac{a_0 b_0}{4d_j^2} \le \lfloor a_0/d_j \rfloor \lfloor b_0/d_j \rfloor. \tag{16}$$

The last inequality follows from $1 \le d_j \le a_0 \le b_0$ and $\lfloor x \rfloor \ge x/2$ for $x \ge 1$.

Let H_k be the symmetric projector. Define $R_j = P_j - H_k$ when $P_j \ne 0$, and $R_j = 0$ otherwise. Lemma 3.1 shows that these are nested projections orthogonal to H_k. Assign each orthogonal difference $R_{j+1} - R_j$ to its own pair of a_0, b_0 local sectors and use Bell width d_j. Its rank satisfies (16). Assign H_k to the remaining a_*, b_* sectors, with Bell width

$$d_* = \min\{K, d_{a_*,b_*}(r_k)\}.$$

The reservation $Q = 4Jr_k$ ensures $r_k \le a_* b_*$ and $d_{a_*,b_*}(r_k) \ge a_0$, so $d_* \ge d_0$. Indeed each large local sector contains at least $(4r_k - 1)$ times its small local sector; width a_0 is consequently feasible for the symmetric rank r_k.

Apply Lemma 2.2 coherently to all assigned source sectors. Their images are orthogonal; their isometry extends to one unitary on the existing N-dimensional input. Sector-specific

discard maps, together with reset Kraus maps on every remaining local coordinate, give two complete local channels. Orthogonal sector labels remove all cross-sector terms; commutation with $\rho^{\otimes k}$ also removes coherences with the unused source complement. This construction defines our single family F_k^{u}.

Proposition 3.2 (All prefixes and the pure promise in one family)**.** *For every input density matrix and every $0 \le j < J$,*

$$F_k^{\mathrm{u}}(\rho, K) \ge \frac{d_j}{K} A_k(p, c_j). \tag{17}$$

For every state Y supported on H_k, the same protocol has fidelity at least

$$\min\{1, d_{a_*,b_*}(r_k)/K\} \operatorname{Tr} Y.$$

Proof. Write $w_j = d_j/K$ and $B_j = \operatorname{Tr}[(H_k + R_j)\rho^{\otimes k}]$. The sector construction gives

$$F_k^{\mathrm{u}} \ge (d_*/K)B_0 + \sum_{j=0}^{J-1} w_j (B_{j+1} - B_j).$$

Since $d_*/K \ge w_0$, summation by parts makes its right side at least

$$w_{J-1} B_J + \sum_{j=1}^{J-1} (w_{j-1} - w_j) B_j.$$

Every coefficient is nonnegative. Lemma 3.1 bounds B_{j+1} below by $A_k(p, c_j)$, and the corresponding classical cumulative masses increase. The resulting weighted sum is at least $w_j A_k(p, c_j)$ for every j. The pure-sector statement follows directly from coherent packing; it uses the same unitary and local channels. □

For fixed m, n, all reservation and orbit factors have logarithm $O_{m,n}(\log k)$. The removed local fraction is at most $J/Q = 1/(4r_k) \to 0$, so $a_*/a, b_*/b \to 1$. An efficient implementation for arbitrary mixed inputs remains a separate question.

3.3 An information-spectrum sandwich

Sample X with law p on its positive support, put $Z = -\log p_X$, and let $S_k = Z_1 + \cdots + Z_k$. Define the exact overhead

$$h_{D,k} = \log(16 Q^2 Q_{D,k}). \tag{18}$$

Theorem 3.3 (Dimension-explicit finite-block sandwich)**.** *Whenever $K \le a_0$, put $x = \log(N/K^2)$. For every $t \ge 0$,*

$$\mathbb{P}\{S_k \le x - h_{D,k}\} \le F_k^{\mathrm{u}}(\rho, K) \le f_k^{\mathcal{C}}(\rho, K) \le F_k^{\star}(\rho, K) \le \mathbb{P}\{S_k \le x + t\} + e^{-t/2}, \tag{19}$$

for each physical operation class containing product channels and contained in cPPT*. Zero eigenvalues are permitted. If $D \ge 2$ and $k \ge 1$, then*

$$0 \le h_{D,k} \le 10 D^2 \log(k + D). \tag{20}$$

Proof. For $d_0 = K$, Proposition 3.2 gives $F_k^{\mathrm{u}} \geq A_k(p, c_0)$. Since $a_0 \geq a/(2Q)$ and $b_0 \geq b/(2Q)$, one has $kc_0 \geq x - h_{D,k}$. For every positive-probability word,

$$kH(\widehat{p}_w) \leq -\log p^{\otimes k}(w),$$

by nonnegativity of relative entropy. This proves the lower bound.

For the converse, diagonalize the input and absorb the arbitrary preprocessing unitary into the fidelity effect. Its diagonal entries z_i satisfy $0 \leq z_i \leq 1$ and $\sum_i z_i^2 \leq N/K^2$. With $r = N/K^2$, eigenvalues below $e^{-\log r - t}$ contribute at most

$$\sqrt{\sum_{\text{small}} (p_i^{(k)})^2 \sum_{\text{small}} z_i^2} \leq \sqrt{e^{-\log r - t} r} = e^{-t/2}.$$

The remaining contribution is bounded by the event in (19).

For (20), use $B_{D,k} \leq (k + D^2)^{D^2-1}$, $r_k \leq (k + D)^{D-1}$ and $\log(k + D^2) \leq 2\log(k + D)$. Substitution into (18), with $Q = 4(k + 1)^2 r_k$, gives the displayed conservative constant, retaining every floor loss above. □

Corollary 3.4 (Finite Gaussian error and shrinking variance)**.** *Let $V = \operatorname{Var} Z > 0$, $T = \mathbb{E}|Z - H(p)|^3$, $\sigma = \sqrt{kV}$,*

$$\beta = \frac{C_{\mathrm{BE}} T}{V^{3/2}\sqrt{k}}, \qquad y = \frac{\log(N/K^2) - kH(p)}{\sigma}.$$

There is an absolute Berry–Esseen constant C_{BE} such that, under the integer budget $K \leq a_0$, both F_k^{u} and each $f_k^{\mathcal{C}}$ in (19) differ from $\Phi(y)$ by at most

$$\beta + \frac{\max(h_{D,k}, t)}{\sqrt{2\pi}\,\sigma} + e^{-t/2} \qquad (t \geq 0). \tag{21}$$

For changing dimensions and input laws, sufficient conditions are the eventual integer budget and

$$kV \to \infty, \qquad T/(V^{3/2}\sqrt{k}) \to 0, \qquad h_{D,k}/\sqrt{kV} \to 0. \tag{22}$$

In particular these follow if DV is eventually bounded below by a positive constant, DT is eventually bounded above, and $D^5 \log^2(k + D) = o(k)$. The moving threshold y need not converge.

Proof. Apply the finite iid Berry–Esseen inequality to both probability terms in (19); the normal CDF has Lipschitz constant $1/\sqrt{2\pi}$. For (22) choose $t = \sqrt{\sigma}$. This makes the smoothing ratio and exponential remainder vanish. For the concrete condition, $\sqrt{kV} \geq \sqrt{c}\sqrt{k/D}$ when $DV \geq c > 0$, while $T/V^{3/2} \leq C\sqrt{D}/c^{3/2}$ when $DT \leq C$. Equation (20) reduces the overhead ratio to a constant times $D^{5/2}\log(k + D)/\sqrt{k}$. Its square tends to zero by hypothesis, and the same hypothesis forces $k/D \to \infty$. These are sufficient conditions for this construction, not necessary conditions or automatic APPT moment properties. Standard Berry–Esseen and source-coding results are credited in [20, 7]. □

4 Exact asymptotic extraction laws

The limits in this section fix m, n and an input state ρ. Let p be its eigenvalue law, let $s = \operatorname{rank}\rho$, and put

$$A = \log m, \quad L = \log D, \quad C(p) = \min\left(A, \frac{L - H(p)}{2}\right), \quad C_0(p) = \min\left(A, \frac{L - \log s}{2}\right).$$

Write $S_\alpha(p) = (1-\alpha)^{-1}\log\sum_i p_i^\alpha$, with $S_1 = H$, and take $K_k = \lceil e^{kR}\rceil$ for a fixed $R \geq 0$. At $R = 0$ the target is one dimensional and fidelity is exactly one.

Theorem 4.1 (One all-state family with the optimal laws)**.** *The single family constructed in Section 3 has the following properties for every fixed input state, including rank-deficient states.*

1. *The faithful extraction capacities for* LO, LOCC, *and* cPPT *all equal* $C(p)$*. The common family achieves fidelity tending to one for each* $R < C(p)$*.*

2. *At every rate, its fidelity exponent equals that of the state-aware optimum in each of the three operation classes:*

$$\lim_{k\to\infty} -\frac{1}{k}\log F_k^{\mathrm{u}}(\rho, K_k) = \lim_{k\to\infty} -\frac{1}{k}\log f_k^{\mathcal{C}}(\rho, K_k) = E_p(R), \tag{23}$$

   where

$$E_p(R) = (R - A)_+ + \max_{1\leq\alpha\leq 2}\frac{\alpha - 1}{\alpha}\Big(S_\alpha(p) - c_R\Big), \qquad c_R = L - 2\min(R, A). \tag{24}$$

   The summand at $\alpha = 1$ *is zero. In particular* $R > C(p)$ *gives a strictly positive strong-converse exponent.*

3. *In the strict direct regime* $C_0(p) < R < C(p)$*, put* $c = L - 2R$*. Then*

$$\begin{aligned}\lim_{k\to\infty} -\frac{1}{k}\log(1 - F_k^{\mathrm{u}}) = \lim_{k\to\infty} -\frac{1}{k}\log(1 - F_k^{\star}) = I_p(c),\\ I_p(c) := \min_{H(q)\geq c} D(q\|p) = \sup_{0<\alpha<1}\frac{1-\alpha}{\alpha}(c - S_\alpha(p)).\end{aligned} \tag{25}$$

   Relative entropy is evaluated on the positive support of p*.*

4. *For* $R < C_0(p)$ *the same universal protocol has fidelity exactly one for all sufficiently large* k*. The eventual-exact capacity is* $C_0(p)$*, even for state-aware completely PPT postprocessing.*

Proof of the fidelity exponent. The converse follows from (10) on tensor powers and $k^{-1}\log K_k \to R$. For achievability assume first $R > 0$ and fix a law q on the positive support of p with $H(q) < L$. Choose

$$0 < b < \min\{R, A, (L - H(q))/2\}, \qquad d_k = \lceil e^{kb}\rceil.$$

For large k, $d_k \le \min(K_k, a_0)$, and the geometric grid contains a width between $d_k/2$ and d_k. Indeed the required grid index is $O_{m,n}(k)$, whereas $J = (k+1)^2$. Its entropy cutoff tends to $L - 2b > H(q)$. An empirical type $q_k \to q$ is therefore included eventually; its probability is at least $(k+1)^{-D} e^{-kD(q_k\|p)}$. Proposition 3.2 yields a fidelity exponent at most $D(q\|p) + R - b$. Let b approach the displayed minimum and approximate the equality cases in entropy by laws on the same positive support. The only full-entropy boundary is the uniform full-support law, which is approached by nonuniform laws. Rate zero has target one and fidelity exactly one. Consequently

$$\limsup_k -\frac{1}{k} \log F_k^{\mathrm{u}} \le \min_q \left\{ D(q\|p) + \max\left(0, R - A, R - L/2 + H(q)/2\right) \right\}. \tag{26}$$

All orbit, reservation and rounding factors have logarithm $O_{m,n}(\log k)$; the strict width approximation above removes them without a diagram or ordering assumption on q. The maximum in (26) is $(R - A)_+ + (H(q) - c_R)_+/2$.

For completeness the matching scalar identity, with no exchange of minimax operations, is

$$\min_q \{ D(q\|p) + (H(q) - c)_+/2 \} = \max_{1 \le \alpha \le 2} \frac{\alpha - 1}{\alpha} (S_\alpha(p) - c), \qquad c \ge 0. \tag{27}$$

Let $q_{\alpha,i} = p_i^\alpha / Z_\alpha$, $Z_\alpha = \sum_i p_i^\alpha$, and call the maximand $J_c(\alpha)$. Direct differentiation gives

$$J_c'(\alpha) = \frac{H(q_\alpha) - c}{\alpha^2}, \qquad \frac{d}{d\alpha} H(q_\alpha) = -\alpha \operatorname{Var}_{q_\alpha}(\log p_i) \le 0.$$

If $H(p) \le c$, use $q = p$, and both sides vanish. If $H(q_2) \ge c$, use $q = q_2$, giving $(S_2(p) - c)/2$. Otherwise an escort with $1 < \alpha < 2$ has $H(q_\alpha) = c$, and its relative entropy is $J_c(\alpha)$. Boundary cases agree. Conversely, for every q and $1 \le \alpha \le 2$,

$$D(q\|p) = \alpha^{-1} D(q\|q_\alpha) + \frac{\alpha - 1}{\alpha} (S_\alpha(p) - H(q)),$$

while $(H - c)_+/2 \ge (\alpha - 1)(H - c)/\alpha$. This proves (27). Since $c_R \ge \log(n/m) \ge 0$, the identity applies and proves (23) by squeezing all three operation classes between the common LO protocol and the cPPT converse. □

Proof of faithful and eventual-exact capacities. For $0 < R < C(p)$ one has $R < A$, so eventually $K_k \le a_0$. In (19), $x - h = k(L - 2R) + O(\log k) > k(H(p) + \delta)$ for a fixed $\delta > 0$. The ordinary law of large numbers implies fidelity tending to one. Rate zero is trivial. Above $C(p)$ the exponent in (24) is positive: either $R > A$, or $J'_{L-2R}(1) > 0$.

If $R < C_0(p)$, every positive-probability word has empirical entropy at most $\log s$, while the first grid cutoff tends to $L - 2R > \log s$. Thus the entire classical mass in (17) is one eventually, giving exact fidelity. Conversely, exact fidelity for a rank-s^k state forces its rotated support into the eigenvalue-one space of M. Hence $s^k \le \operatorname{Tr} M^2 \le N/K^2$ and $K \le a$. Capacities here are suprema of rates realized by actual positive-integer target sequences and actual protocol sequences. These sets contain zero, since every trace-preserving channel to the one-dimensional target has fidelity exactly one. The upper bounds and every strict subcritical achievable rate therefore identify the suprema even when $C(p)$ or $C_0(p)$ is zero; no boundary attainability is inferred. □

Proof of strict-direct reliability. The hypotheses imply $H(p) < c < \log s$. Proposition 3.2 at $d_0 = K_k$ bounds the actual error above by the probability that the empirical entropy exceeds $c - o(1)$. The number of types is polynomial, and each type has probability at most $e^{-kD(q\|p)}$. This gives the lower bound $I_p(c)$ on the error exponent of the same common protocol. The strict interval permits approximation of a boundary minimizer by laws of entropy strictly above the requested threshold.

To prove optimality, fix $0 < t < 1$. At most $N/(K^2t^2)$ eigenvalues of M exceed t. If L_j is the mass of the largest j input eigenvalues, capped at one beyond their support, the spectral trace inequality gives

$$1 - F_k^\star \geq (1-t)\left(1 - L_{\lfloor N/(K^2t^2)\rfloor}(p^{\otimes k})\right). \tag{28}$$

For integers M_k with $k^{-1}\log M_k \to c \in (H(p), \log s)$, the optimal-prefix tail has exponent $I_p(c)$. Here is the needed type argument. Include all types with entropy at most $c - \delta$; their total cardinality is at most $(k+1)^s e^{k(c-\delta)} \leq M_k$ eventually. The excluded mass is at most $(k+1)^s e^{-kI_p(c-\delta)}$. Conversely, a type approaching any q with $H(q) > c$ has exponentially more words than M_k, and at least fraction $1 - M_k/r_q$ of its equiprobable words must be excluded. Its mass is at least $(k+1)^{-s}e^{-kD(q\|p)}$. Approximate an entropy-c minimizer and let $\delta \downarrow 0$. With $t = 1/2$, (28) gives the matching upper bound on every error exponent.

The requisite continuity and the last expression in (25) follow from escorts with $0 < \alpha < 1$. Since $H(p) < c < \log s$, the positive eigenvalues are nonuniform and a unique escort has entropy c. The identity

$$D(q\|p) = \alpha^{-1}D(q\|q_\alpha) + \frac{1-\alpha}{\alpha}(H(q) - S_\alpha(p))$$

proves the variational formula, equality at that escort, and continuity in the strict interval. □

Remark 4.2 (The exact zero-error boundary). Formula (25) excludes $R = C_0(p)$. For a rank-four state on 4×4, $K_k = 2^k$ permits exact packing of its 4^k-dimensional support into Φ_{2^k} and garbage. Thus the state-aware error can be exactly zero at $R = \log 2 = C_0(p)$ even for nonuniform positive eigenvalues. A finite reliability expression at $c = \log 4$ would miss this integer packing effect.

Theorem 4.3 (Entropy-limited Gaussian threshold)**.** *Suppose* $0 < C(p) < A$ *and*

$$V(p) = \sum_{p_i > 0} p_i(-\log p_i - H(p))^2 > 0.$$

For any target sequence with $\log K_k = kC(p) + z\sqrt{k} + o(\sqrt{k})$,

$$F_k^{\mathrm{u}}(\rho, K_k) \longrightarrow \Phi(-2z/\sqrt{V(p)}), \qquad F_k^\star(\rho, K_k) \longrightarrow \Phi(-2z/\sqrt{V(p)}). \tag{29}$$

For each operation class $\mathcal{C}$ *above and fixed* $0 < \varepsilon < 1$, *let* $K_{k,\mathcal{C}}^{\mathrm{opt}}(\varepsilon)$ *be the largest positive integer target for which an actual state-aware protocol in that class attains fidelity at least* $1 - \varepsilon$. *These maxima exist for all sufficiently large* k *and obey*

$$\log K_{k,\mathcal{C}}^{\mathrm{opt}}(\varepsilon) = kC(p) + \tfrac{1}{2}\sqrt{kV(p)}\,\Phi^{-1}(\varepsilon) + o(\sqrt{k}),$$

and the common family attains the same expansion.

Proof. The strict local-dimension gap ensures $K_k \le a_0$ eventually. Here $h_{D,k} = O(\log k)$ and $\log(N/K_k^2) = kH(p) - 2z\sqrt{k} + o(\sqrt{k})$. Apply the ordinary central limit theorem to the two sides of (19), for example with $t = k^{1/4}$; alternatively use Corollary 3.4. The same squeeze applies to the genuine state-aware supremum in every intermediate physical class. For fixed error, define each optimum as the maximum of the set of positive integers admitting the requested actual fidelity. Bracket that entire set above and below a fixed Gaussian quantile: the converse excludes every larger integer, and rounded smaller targets provide actual witnesses. The feasible integer sets are eventually nonempty and bounded, hence their natural suprema are attained maxima. This establishes both expansions without assuming target monotonicity of the particular universal family. □

Theorem 4.3 retains both strict hypotheses. The local-dimension cap and zero varentropy are not included by continuity. The next section treats a cap-boundary phenomenon of a different, minimax kind.

5 The sharp cost of an unknown support

5.1 A common support and an adversarial average

Fix $1 \le s \le D$. Define the intrinsic common support

$$S_{k,s} = \operatorname{span}\{z_1 \otimes \cdots \otimes z_k : \dim \operatorname{span}(z_1, \ldots, z_k) \le s\}, \qquad r_{k,s} = \dim S_{k,s}. \tag{30}$$

Every $\rho^{\otimes k}$ with $\operatorname{rank}\rho \le s$ is supported here. Let P_s be a fixed rank-s orthogonal projection on $\mathbb{C}^D$, and form the literal Haar average

$$\Omega_{k,s} = \int_{U(D)} (UP_sU^*/s)^{\otimes k}\, dU. \tag{31}$$

Haar measure constructs an adversarial ensemble and is never implemented as preprocessing. The range of $\Omega_{k,s}$ is exactly $S_{k,s}$: a vector has zero quadratic form against this average precisely when it is orthogonal to every rotated tensor-product range. The integrand is continuous and nonnegative and Haar measure has full support. Those ranges span (30). This also proves minimality of the common support, without assuming a character or eigenvalue formula.

Theorem 5.1 (Support dimension and reciprocal average purity)**.** *For fixed D and $1 \le s < D$, put*

$$g = s(D-s), \qquad A_{D,s} = \prod_{1 \le i \le s < j \le D} (j-i), \qquad c_{D,s} = s^{-g}/A_{D,s}. \tag{32}$$

Then

$$r_{k,s} \sim c_{D,s} s^k k^g, \qquad \operatorname{Tr}\Omega_{k,s}^2 \sim (c_{D,s} s^k k^g)^{-1}, \qquad r_{k,s} \operatorname{Tr}\Omega_{k,s}^2 \longrightarrow 1. \tag{33}$$

Proof. Let $C : \mathbb{C}^s \to \mathbb{C}^D$ be the coordinate isometry, so $P_s = CC^*$. For Haar U set

$$G(U) = C^*UP_sU^*C, \qquad X(U) = \det G(U) = |\det(C^*UC)|^2, \qquad Y(U) = \operatorname{Tr} G(U)/s.$$

The matrix G is a positive contraction. Write $D = s + t$ and $M_q = \mathbb{E}X^q$. The standard unitary-minor moment calculation gives

$$M_q = \prod_{i=0}^{s-1} \frac{\binom{q+i}{q}}{\binom{q+t+i}{q}}, \qquad q^g M_q \longrightarrow \prod_{i=0}^{s-1} \frac{(t+i)!}{i!} = A_{D,s}. \tag{34}$$

Here is a recursive derivation. After fixing the first Haar column, align its projections into the s-dimensional coordinate space and its orthogonal complement by block unitaries. In the determinant expansion the remaining coisometry has $s-1$ rows in dimension $D-1$; averaging over the stabilizer gives the same smaller minor moment. The squared projected column length has moment $(s)_q/(D)_q$, as follows by expanding coordinate monomials on the complex unit sphere. Thus $M_{s,t}(q) = \binom{q+s-1}{q}\binom{q+t+s-1}{q}^{-1} M_{s-1,t}(q)$, with $M_{0,t}(q) = 1$. This proves the product; cancellation of its finite factorial ratios proves the limit. We use these standard Haar calculations as ingredients, not as novelty claims; see also the general polynomial integration framework in [5].

Haar invariance and the tensor trace identity give

$$s^k \operatorname{Tr} \Omega_{k,s}^2 = \mathbb{E}Y^k. \tag{35}$$

If $\lambda_1, \dots, \lambda_s \in [0,1]$ are the eigenvalues of G, arithmetic–geometric mean and $1 - \prod_i \lambda_i \le \sum_i (1-\lambda_i)$ show

$$X \le Y^s, \qquad Y \le (s - 1 + X)/s.$$

Consequently $\mathbb{E}Y^k \ge M_{\lceil k/s \rceil}$. To match this bound, fix an integer $N \ge 1$, put $b = s(N+1)$ and $\delta = 1 - [2(N+1)^2]^{-1}$. For $\delta \le x \le 1$,

$$((s - 1 + x)/s)^b \le x^N.$$

For $u = 1 - x$, the logarithm of the left side divided by the right side vanishes at $u = 0$ and has derivative

$$\frac{-1 + [(N+1) - N/s]u}{(1-u)(1-u/s)} \le 0 \quad \text{for } 0 \le u \le [2(N+1)^2]^{-1}.$$

This proves the comparison. Splitting according to $X \ge \delta$ and setting $q = \lfloor k/b \rfloor$ therefore gives the exact bound

$$\mathbb{E}Y^k \le M_{Nq} + ((s - 1 + \delta)/s)^{bq}.$$

The exponential remainder is negligible after multiplication by k^g. Equation (34) bounds the resulting limsup by $A_{D,s}[s(N+1)/N]^g$. Let $N \to \infty$ and combine with the lower bound. This proves $s^k k^g \operatorname{Tr} \Omega_{k,s}^2 \to s^g A_{D,s} = 1/c_{D,s}$.

It remains to match the support rank; purity alone supplies only its lower bound. For a positive contraction G and $k \le sq$, its $U(s)$ tensor twirl satisfies

$$\int_{U(s)} (VGV^*)^{\otimes k} \, dV \;\ge\; (\det G)^q I. \tag{36}$$

To prove this, diagonalize G and cyclically permute its s eigenvalues. On each tensor word the product of the s resulting diagonal entries is $(\det G)^k$. Arithmetic–geometric mean bounds

their average below by $(\det G)^q$, since $0 \le \det G \le 1$ and $k \le sq$. Applying the positive Haar twirl makes every cyclic conjugate have the same average, proving (36).

The compression $C^{\otimes k*}\Omega_{k,s}C^{\otimes k}$ is fixed by this $U(s)$ twirl. Integrating (36) for the actual $G(U)$ gives

$$C^{\otimes k*}\Omega_{k,s}C^{\otimes k} \ge s^{-k}M_q I.$$

The averaged matrix belongs to the permutation-operator algebra by the tensor commutant identity, so it commutes with every rotated $(UP_sU^*)^{\otimes k}$. Haar invariance transfers the same lower bound to each such range. An eigenvector of $\Omega_{k,s}$ with eigenvalue below $s^{-k}M_q$ must therefore be orthogonal to all these ranges. Their span is $S_{k,s}$, so every positive eigenvalue is at least $s^{-k}M_q$. Taking traces and then $q = \lceil k/s \rceil$ proves

$$r_{k,s} \le s^k / M_{\lceil k/s \rceil}.$$

On the other side, Cauchy–Schwarz gives $r_{k,s} \operatorname{Tr} \Omega_{k,s}^2 \ge 1$. The already proved purity limit and (34) squeeze $r_{k,s}/(s^k k^g)$ to $c_{D,s}$. Multiplying the two limits proves the last assertion. No concentration hypothesis for Young diagrams or supplied spectral certificate is used. □

At $s = 1$, these identities reduce to

$$S_{k,1} = \operatorname{Sym}^k(\mathbb{C}^D), \qquad r_{k,1} = \binom{k+D-1}{D-1}, \qquad \Omega_{k,1} = \Pi_{\mathrm{sym}}/r_{k,1}.$$

At $s = D$ one instead has exactly $r_{k,D} = N$ and $\Omega_{k,D} = I/N$.

5.2 A target-uniform minimax law

Define the finite, explicitly computable quantities

$$d_k = d_{a,b}(r_{k,s}), \qquad w_k = \min\left(a, \sqrt{N/r_{k,s}}\right), \qquad \eta_k = \sqrt{r_{k,s} \operatorname{Tr} \Omega_{k,s}^2}. \tag{37}$$

Proposition 2.3 gives for every finite k and every integer $K \ge 1$

$$\begin{aligned} &\min(1, d_k/K) \le \mathcal{G}_{\mathrm{LO}}(k, K; s) \le \mathcal{G}_{\mathrm{LOCC}}(k, K; s) \le \mathcal{G}_{\mathrm{cPPT}}(k, K; s), \\ &\mathcal{G}_{\mathrm{cPPT}}(k, K; s) \le \min\left(1, \frac{a}{K}, \frac{\sqrt{N \operatorname{Tr} \Omega_{k,s}^2}}{K}\right). \end{aligned} \tag{38}$$

The lower construction knows s, but no property of the particular input within the rank-budget class.

Theorem 5.2 (Entire sharp minimax profile)**.** *For every fixed $2 \le m \le n$ and $1 \le s < D$, and every $\mathcal{C} \in \{\mathrm{LO}, \mathrm{LOCC}, \mathrm{cPPT}\}$,*

$$\sup_{K \in \mathbb{N},\ K \ge 1} \left| \frac{\mathcal{G}_{\mathcal{C}}(k, K; s)}{\min(1, w_k/K)} - 1 \right| \longrightarrow 0. \tag{39}$$

An explicit finite-k bound for the supremum is

$$\max\{1 - d_k/w_k, \eta_k - 1\}. \tag{40}$$

Thus the relative equivalence includes every target integer, even when fidelity is exponentially small.

Proof. It remains to prove $d_k/w_k \to 1$, since $\eta_k \to 1$ by Theorem 5.1. If $n > ms$, then $r_{k,s}/(b/a) \to 0$ and eventually $d = a$ is feasible. Consequently $d_k = w_k = a$ eventually.

If $n \le ms$, Theorem 5.1 gives eventually

$$w_k = \sqrt{N/r_{k,s}}, \qquad w_k/a \to 0, \quad w_k/b \to 0, \quad w_k \to \infty.$$

The polynomial factor is essential when $n = ms$. Put $q_k = w_k/a + w_k/b$, $\epsilon_k = \sqrt{q_k}$, and $d = \lfloor w_k/(1+\epsilon_k) \rfloor$. For large k this is a positive integer with $d/w_k \to 1$. Dividing a lower bound for the product of floors by $r = N/w_k^2$ gives

$$\frac{\lfloor a/d \rfloor \lfloor b/d \rfloor}{r} \ge (w_k/d)^2 - (w_k/d)q_k + 1/r.$$

For $0 < q_k < 1$ the function $z^2 - zq_k$ is increasing on $z \ge 1$, and $w_k/d \ge 1 + \sqrt{q_k}$. The last display is therefore at least $1 + 2\sqrt{q_k} - q_k^{3/2} > 1$. Thus d is feasible. Also every feasible integer is at most w_k, so $d_k/w_k \to 1$.

Finally (38) bounds the ratio in (39) between d_k/w_k and η_k, independently of K. This proves both assertions. □

For $s = D$ the exact minimax value is $1/K$ at every blocklength: the maximally mixed state gives this upper bound and a product output attains it. Consequently its largest exact target is one, and, for $0 \le \varepsilon < 1$, its largest target with worst-class fidelity at least $1 - \varepsilon$ is exactly $\lfloor (1-\varepsilon)^{-1} \rfloor$.

Corollary 5.3 (Exact and fixed-error target sizes)**.** *Let $K_{\mathcal{C}}^0(k; s)$ be the largest target dimension admitting exact fidelity for every state in the rank-budget class. Then*

$$d_k \le K_{\mathrm{LO}}^0 \le K_{\mathrm{LOCC}}^0 \le K_{\mathrm{cPPT}}^0 \le \lfloor w_k \rfloor. \tag{41}$$

If $n \le ms$ and $s < D$,

$$\log K_{\mathcal{C}}^0(k; s) = \frac{k}{2} \log(D/s) - \frac{s(D-s)}{2} \log k - \frac{1}{2} \log c_{D,s} + o(1). \tag{42}$$

If $n > ms$, instead $K_{\mathcal{C}}^0(k; s) = m^k$ eventually. For $s < D$ and fixed $0 < \varepsilon < 1$, the largest target admitting worst-class fidelity at least $1 - \varepsilon$ satisfies

$$\log K_{\mathcal{C}}^{\varepsilon}(k; s) = \log w_k - \log(1-\varepsilon) + o(1). \tag{43}$$

Proof. Exact performance gives $\mathrm{Tr}[\Omega_{k,s}(I - U^*MU)] = 0$. Positivity and strict positivity of $\Omega_{k,s}$ on $S_{k,s}$ force U^*MU to be the identity on that subspace. Hence $r_{k,s} \le \mathrm{Tr}\, M^2 \le N/K^2$ and $K \le a$. This proves the upper bound in (41); packing proves its lower bound. Use $d_k/w_k \to 1$ and (33) for (42). For fixed error, the actual lower construction works at $K = \lfloor d_k/(1-\varepsilon) \rfloor$, while (38) bounds every feasible target by $\eta_k w_k/(1-\varepsilon)$. Since $w_k \to \infty$ for $s < D$, integer rounding contributes $o(1)$ to the logarithm. □

The boundary $n = ms$ has first-order capacity $\log m$, but still incurs the logarithmic correction in (42). The coefficient $s(D-s)/2$ is one quarter of the real dimension of the Grassmannian of s-dimensional supports. This interpretation follows from the two-moment proof; parameter counting is not used as a substitute for it.

Corollary 5.4 (A known spectrum with unknown orientation)**.** *Fix any positive rank-s spectrum. Requiring one exact protocol for its entire global-unitary orbit gives the same bounds* (41) *and hence the same exact-target asymptotic. If the known spectrum is flat on rank s, the full target-uniform minimax profile* (39) *also holds for that orbit alone.*

Proof. For any positive rank-s spectrum, each rotated tensor state is strictly positive on the tensor power of its rotated s-dimensional support. Those ranges span exactly $S_{k,s}$, so its orbit average has that range. The exact converse and common-subspace packing are unchanged. For the flat spectrum its average is precisely (31), so the entire previous minimax argument applies. No fixed-error profile for an arbitrary nonuniform spectrum is inferred from this support statement. □

5.3 Balanced unknown pure inputs and an exact circuit

When $m = n$, $D = m^2$, and $s = 1$, put $r_k = \binom{k+D-1}{D-1}$. Theorem 5.2 gives, uniformly in every target integer,

$$\mathcal{G}_{\mathcal{C}}(k, K; 1) \sim \min\left(1, \frac{m^k}{K\sqrt{r_k}}\right).$$

In particular

$$\mathcal{G}_{\mathcal{C}}(k, m^k; 1) \sim r_k^{-1/2} \sim \sqrt{(D-1)!}\, k^{-(D-1)/2}. \tag{44}$$

A known pure state admits fidelity one at this same target. The common-protocol loss is therefore sharp and invisible to the first-order capacity.

The symmetric compression mechanism is established prior work [16, 17, 18]; coherent streaming concentration also predates this work [19]. The following specialization records its exact resource conversion in our model.

Proposition 5.5 (Optimal integer Bell pairs with no supplied memory)**.** *For $m = n = 2$ and every $k \geq 1$, one circuit on the original $2k$ qubits, followed by local discarding, extracts exactly*

$$h_k = \left\lfloor k - \frac{1}{2}\log_2 \binom{k+3}{3} \right\rfloor$$

Bell pairs from every unknown pure iid input. This integer is optimal even for a common global unitary followed by completely PPT postprocessing. The circuit can be synthesized with $O(k^7 \log^2(k+3))$ CNOT and arbitrary single-qubit gates, with no qubit supplied, reset, measured, or discarded before the global circuit. For any fixed finite inverse-closed library whose generated subgroup is dense in $SU(2)$, and every $\delta > 0$, there is a circuit using that library and CNOT on those same wires whose operator-norm error, up to global phase, is at most δ, whose length is at most $CG\,[\log_2 \max(1, G/\delta) + 2]^5$, and whose output fidelity is at least $1 - 2\delta$. Here G is the larger of one and the actual continuous-gate circuit size, which has the preceding asymptotic bound, and C depends only on the fixed library. This is a circuit-size assertion; a classical finite-precision synthesis-time bound is not included.

Proof. Let $r_j = \binom{j+3}{3}$ and $\ell_j = \lceil \log_4 r_j \rceil$. Fix an enumeration enc_j of the four-component occupations of j. Sequentially compress the first j four-level systems into ℓ_j of those same

systems; all other processed systems become zero on the entire symmetric subspace. This is possible because $r_j/r_{j-1} = (j+3)/j \le 4$, so $\ell_j \le \ell_{j-1} + 1 \le j$.

At step j, the only active systems are the ℓ_{j-1} memory systems and the next original input. In their computational basis the symmetric branching vectors are

$$v_\nu = \sum_{i:\nu_i>0} \sqrt{\nu_i/j}\,|\mathrm{enc}_{j-1}(\nu - e_i)\rangle|i\rangle.$$

Their computational supports are disjoint, and each has at most four entries. At most three real Givens rotations per occupation send it to one selected basis state. Complete these states to the desired $\mathrm{enc}_j(\nu)$ labels by a fixed permutation of the full active basis. If the active register has $q_j = 2(\ell_{j-1}+1)$ qubits and dimension $L_j = 2^{q_j}$, at most $4L_j$ two-level operations suffice, and $L_j \le 16 r_{j-1} = O(j^3)$. All rotations and the permutation are computable from polynomially many occupation labels, not from the input state.

For clarity an elementary ancilla-free synthesis bound for a two-level operation on q qubits is $O(q^2 2^q)$. A Gray path reduces it to pattern-controlled one-qubit rotations and phases. A phase on one selected string is $\exp(i\theta P_x)$ with

$$P_x = 2^{-q} \prod_l (I + (-1)^{x_l} Z_l).$$

Expand into at most 2^q commuting Pauli strings; implement each nonempty string by a parity circuit, a one-qubit rotation, and the inverse parity circuit, using an existing participating wire. Controlled Y rotations have the same expansion after a local change of basis. A Gray path uses at most $2q$ selective transpositions. Thus a conservative total bound is

$$1000 \sum_{j=2}^{k} q_j^2 L_j^2 + 100k^2 = O(k^7 \log^2(k+3)).$$

This agrees with the general synthesis context [21, 22], while making the absence of a supplied workspace explicit.

After compression at $j = k$, at most $2\ell_k = 2(k - h_k)$ memory qubits can be nonzero. Redistribute them among the two garbage registers of $k - h_k$ qubits each. All remaining original qubits are already zero. Hadamards and cross-party CNOTs on the remaining h_k pairs create the desired Bell states; local discarding removes the garbage. The zero wires were generated from the promised input by the unitary compression, not supplied externally.

For necessity, exact fidelity for every pure input makes the effect the identity on the whole symmetric subspace. Lemma 2.1 then gives $r_k \le 4^k/4^h$, proving the exact integer optimum.

For the finite-library size statement, compactness and the density assumption give a fixed finite basic net. Every $SU(2)$ residual admits an exact balanced commutator $[A, B]$, with each factor at distance at most the square root of the residual's distance to the identity. Cancellation in an approximate commutator gives the error bound $4\delta\varepsilon + 2\varepsilon^2$ when the exact factors are δ-close to identity and their approximations have error ε. Recursive correction gives actual finite words of error 2^{-p} and length at most $C(p+1)^5$. These are the standard Solovay–Kitaev ingredients [23]; the stated conservative power is sufficient here. Remove the overall phase of each original single-qubit gate, approximate its $SU(2)$ representative to error δ/G, and place its word on the same original wire. The wire embedding preserves the

operator norm. Telescoping over the whole original gate list gives error at most δ up to a total phase. The same actual local discard then has output fidelity at least $1 - 2\delta$.

The exact occupation masses have integer numerators and a common denominator, and every nonzero mass is at least $1/(k+1)$. These facts support finite-precision analysis of the Givens angles. They do not by themselves prove a uniform classical bit-complexity bound for net selection, stable commutator evaluation and the full recursive compiler. We keep that algorithmic question separate from the proved finite-word and circuit-size statements. □

This proposition implements the pure-promise task. It does not provide an efficient implementation of the complete all-state mixed-input family of Section 3.

5.4 Compatibility with an all-state family

The family in Section 3 already reserves the symmetric sector, so it retains the sharp balanced pure profile without a purity flag. Let $a = b = m^k$. In (14) the remaining local dimensions satisfy $a_*/a, b_*/a \to 1$. Integer packing of their symmetric rank r_k then gives

$$\frac{d_{a_*,a_*}(r_k)}{a/\sqrt{r_k}} \longrightarrow 1.$$

For example $\lfloor a_*/\lceil\sqrt{r_k}\rceil\rfloor$ is feasible; $r_k \to \infty$ and $a/\sqrt{r_k} \to \infty$ remove its relative rounding loss. Proposition 3.2 therefore proves, for every $\varepsilon > 0$, one blocklength threshold such that simultaneously for all positive integer K and every unknown pure input,

$$F_k^{\mathrm{u}}(\rho, K) \geq (1-\varepsilon)\min\left(1, \frac{m^k}{K\sqrt{r_k}}\right).$$

The averaged-state converse supplies the matching upper profile for any uniform guarantee over pure inputs. The same selected family retains all the mixed-state laws, the finite Gaussian estimates and the fixed-error inverse above. The general rank-s sharp minimax theorem retains its rank-budget promise; simultaneous sharp constants for every $s > 1$ without such a promise are not inferred.

6 Applications, verification, and open questions

6.1 APPT entropy as an extraction budget

A state on $\mathbb{C}^m \otimes \mathbb{C}^n$ is absolutely PPT if every global unitary conjugate has positive partial transpose. The capacity formula connects its spectral entropy to a collective extraction resource, even though no single-copy global rotation can produce an NPT state. Qualitative activation from purity is known [27]; the following identity records the quantitative link needed here.

Let

$$E_1(m,n) = \log D - \min_{\rho \in \mathrm{APPT}(m,n)} S(\rho).$$

The APPT set is compact: it is the intersection, inside the compact set of density matrices, of closed partial-transpose positivity conditions. Von Neumann entropy is continuous, so the minimum is attained. Theorem 4.1 immediately gives

$$\max_{\rho\in\mathrm{APPT}(m,n)} C(p_\rho) = \min\left(\log m, \frac{E_1(m,n)}{2}\right). \tag{45}$$

Thus a minimum-entropy theorem for APPT spectra calibrates the maximal capacity in the present model. A companion all-dimension entropy profile can be substituted in this identity [30]; its proof and its verification status are separate from the present paper.

One can obtain a self-contained operational comparison from the already verified purity asymptotic [31]. For $P_{\max}(m,n) = \max_{\mathrm{APPT}} \operatorname{Tr}\rho^2$, Jensen's inequality gives $S(\rho) \geq -\log \operatorname{Tr}\rho^2$, and hence

$$\max_{\mathrm{APPT}} C \leq \frac{1}{2}\log(DP_{\max}). \tag{46}$$

For balanced systems $D = m^2 \to \infty$, the purity law $P_{\max} = D^{-1} + 8D^{-2} + o(D^{-2})$ yields $\max_{\mathrm{APPT}} C \leq 4/D + o(D^{-1})$.

For a lower example take $\rho = (I + 2vv^*)/(D+2)$. It is APPT for every unit vector v: after every global rotation, the smallest eigenvalue of $(vv^*)^\Gamma$ is at least $-1/2$, by the Schmidt coefficient inequality $t_i t_j \leq 1/2$. Its spectrum is $(3, 1, \ldots, 1)/(D+2)$, and the local cap is inactive for every $2 \leq m \leq n$. Hence

$$C(p_\rho) = \frac{1}{2}\left[\log\frac{D}{D+2} + \frac{3\log 3}{D+2}\right] = \frac{3\log 3 - 2}{2D} + O(D^{-2}).$$

With $c_{\mathrm{sp}} = (3\log 3 - 2)/2$, an explicit error bound is

$$0 \leq c_{\mathrm{sp}}/D - C(p_\rho) \leq \frac{3\log 3}{D(D+2)}.$$

Together with (46), this gives, along every sequence of balanced dimensions tending to infinity,

$$c_{\mathrm{sp}} \leq \liminf D \max_{\mathrm{APPT}} C \leq \limsup D \max_{\mathrm{APPT}} C \leq 4.$$

The actual maximum and the displayed comparison are established without solving the entropy optimizer. These are applications of the two-stage spectral capacity and do not assert ordinary fixed-state LOCC distillation at these rates.

Equation (45) fixes the dimensions before taking the many-copy capacity limit. A joint growing-dimension conclusion requires uniform finite-block control. Theorem 3.3 supplies such control without spectral assumptions; a Gaussian conclusion additionally requires the moment and output-size conditions in (22). No assertion that every APPT near optimizer satisfies those conditions is made.

6.2 Formalization and independent verification

The development uses Lean 4.34.1 and a fixed Mathlib commit. Its objects are the original complex density matrices, arbitrary global unitaries, actual finite Kraus channels and partial

transpose on the stated first party. Complete positivity is defined by positivity of every finite auxiliary amplification; the Choi criterion and actual complete Kraus representations are derived. Finite LOCC is an adaptive local-instrument tree with public outcomes and hidden Kraus indices. Closure LOCC is its genuine finite-dimensional coefficient closure, and its completely PPT inclusion follows from closedness of the Choi positivity and trace identities.

The coherent packing theorem includes unitary extension on the existing input, all unused-coordinate decoder branches and arbitrary logical coherences. The Rains converse is realized by the actual measure-and-prepare channel in Lemma 2.1. Asymptotic endpoints use the selected common family itself and genuine physical suprema. Capacities and integer target optima are defined by actual protocol witnesses and success conditions; exact feasibility is not inferred from an unattained fidelity supremum. The probability development includes zero eigenvalues, finite Berry–Esseen control and true varying-law limits.

The revision uses intrinsic orbit projections in Section 3 and Haar minor moments plus an operator lower bound in Theorem 5.1. Its finite overhead is (18), rather than the different Schur-block overhead in the preserved predecessor. The tensor commutant result is proved internally; a caller-supplied Young decomposition, moment identity, asymptotic rank law or optimal-performance certificate is not a hypothesis of these endpoints.

The current working revision distinguishes authored Lean endpoints from final independent verification:

Mathematical component	Verification status
Actual coherent packing and channel-to-effect bounds	Preserved scoped Lean audits
Complete positivity, Kraus equivalence, LOCC and Rains realization	Lean; completion audit pending
One common family, capacities, exponents, Gaussian and integer targets	Lean; completion audit pending
Actual Haar moments, rank, purity and physical minimax profiles	Lean; completion audit pending
Original-register circuit and finite-library gate-count bound	Lean; completion audit pending
APPT capacity extrema and explicit first-order comparisons	Lean; completion audit pending
Uniform classical finite-precision compiler bit complexity	Open; excluded from the circuit-size claim

All new completion packages currently have ordinary build evidence. Independent snapshot checks have covered selected dependency closures and proof-substitution controls; the final whole-scope source manifest, replay and CI for this revision have not yet been frozen. The older 608-root and APPT audit evidence retains its original inputs and cannot certify the later extensions. The final reproduction archive must bind the precise theorem types, model definitions, source/configuration inputs and these eight TeX files, with separate successful replay and same-type forged-proof rejection records. Until that final check is complete, this working revision does not claim a fully independently verified manuscript.

6.3 Implementation and further questions

The pure-promise result supplies an original-register circuit with a proved gate-count bound. Turning its finite-library word existence theorem into a uniform finite-precision compiler additionally requires effective gate and target access, a usable fixed net, stable numerical branches, and a full classical cost model. The general mixed-state construction remains an existence theorem for a specified finite unitary and local channels. Efficient representation transforms [24, 25, 26] provide related tools; a complete implementation must also account for reversible sector indexing, variable Bell dimensions and unitary completion on the available register.

The sharp minimax results fix D and s. Their finite inequalities remain valid when these parameters vary, but the inverse-moment asymptotic requires additional uniform estimates before such a joint limit can be claimed. The explicit conditions in (22) concern a different, information-spectrum route and do not replace those estimates. The exact reliability law at the zero-error boundary, cap-boundary Gaussian laws for arbitrary mixed inputs, and optimal circuit costs likewise remain open here.

Acknowledgments and disclosure. The author received no external funding. OpenAI AI assistants assisted with research, formalization, writing, and internal review. Responsibility for the mathematical statements and the distinction between written and machine-verified proofs remains with the author. Internal AI review is not external human peer review. Original materials retain all rights reserved; third-party results and software retain their own attribution and licenses.

Predecessors and reproducibility. This manuscript consolidates the author's repository preprints on state-aware and state-independent extraction [28, 29]. Their original versions are preserved. The finite-block construction at all blocklengths, target-uniform rank-budget minimax theorem, support/average two-moment comparison, and exact pure-promise resource accounting are identified separately in the contribution and source maps. The reproduction bundle contains this manuscript, its sources, the mathematical verification records, and the separately scoped Lean packages; it does not turn earlier preprints into distinct additional discoveries.

References

[1] E. M. Rains, "A semidefinite program for distillable entanglement," *IEEE Trans. Inf. Theory*, vol. 47, pp. 2921–2933, 2001. arXiv:quant-ph/0008047.

[2] L. Lami, "On PPT entanglement distillation," 2026. arXiv:2610.12454.

[3] R. Jozsa, M. Horodecki, P. Horodecki, and R. Horodecki, "Universal quantum information compression," *Phys. Rev. Lett.*, vol. 81, p. 1714, 1998. arXiv:quant-ph/9805017.

[4] M. Keyl and R. F. Werner, "Estimating the spectrum of a density operator," *Phys. Rev. A*, vol. 64, p. 052311, 2001. arXiv:quant-ph/0102027.

[5] B. Collins and P. Śniady, "Integration with respect to the Haar measure on unitary, orthogonal and symplectic group," *Commun. Math. Phys.*, vol. 264, pp. 773–795, 2006. arXiv:math-ph/0402073.

[6] K. Matsumoto and M. Hayashi, "Universal distortion-free entanglement concentration," *Phys. Rev. A*, vol. 75, p. 062338, 2007. See also M. Hayashi and K. Matsumoto, arXiv:quant-ph/0109028.

[7] M. Hayashi, "Second-order asymptotics in fixed-length source coding and intrinsic randomness," *IEEE Trans. Inf. Theory*, vol. 54, pp. 4619–4637, 2008. arXiv:cs/0503089.

[8] M. Hayashi, "Universal approximation of multi-copy states and universal quantum lossless data compression," *Commun. Math. Phys.*, vol. 293, pp. 171–183, 2010. arXiv:0806.1091.

[9] R. Takagi, K. Watanabe, T. Matsuura, H. Arai, and M. Hayashi, "Universal distillation of quantum entanglement," 2026. arXiv:2609.40215.

[10] S. Tirone, F. A. Mele, V. Giovannetti, and L. Lami, "Universal entanglement distillation," 2026. arXiv:2609.40080.

[11] Z. Lin, K. Li, and K. Fang, "Finite-blocklength and exponential analyses for universal entanglement and coherence distillation under various free operations," 2026, version 3. arXiv:2601.10190v3.

[12] J. Rizzo, L. Lami, J. Eisert, and L. Leone, "Universal quantum coding," 2026. arXiv:2609.38038.

[13] P. Hayden, A. Maloney, J. Wang, and Y. Yang, "Free entropy and quantum minimum description length," 2026. arXiv:2610.06741.

[14] K. Watanabe and R. Takagi, "Universal work extraction in quantum thermodynamics," *Nat. Commun.*, vol. 17, art. 1857, 2026. doi:10.1038/s41467-026-69143-3.

[15] S. Zeng, "Reliability is not free in universal quantum work extraction," 2026. arXiv:2607.16702.

[16] M. Plesch and V. Bužek, "Efficient compression of quantum information," *Phys. Rev. A*, vol. 81, p. 032317, 2010. arXiv:0907.1764.

[17] A. Bärtschi and S. Eidenbenz, "Deterministic preparation of Dicke states," 2019. arXiv:1904.07358.

[18] Z. Chen, C. Xiong, K. Khadiev, and J. Wu, "Efficient quantum compression for identically prepared states with arbitrary dimension," version 2, 2026. arXiv:2307.12024v2.

[19] R. Blume-Kohout, S. Croke, and D. Gottesman, "Streaming universal distortion-free entanglement concentration," 2009. arXiv:0910.5952.

[20] I. Shevtsova, "On the absolute constants in the Berry–Esseen type inequalities for identically distributed summands," 2011. arXiv:1111.6554.

[21] A. Barenco *et al.*, "Elementary gates for quantum computation," *Phys. Rev. A*, vol. 52, pp. 3457–3467, 1995. arXiv:quant-ph/9503016.

[22] V. V. Shende, S. S. Bullock, and I. L. Markov, "Synthesis of quantum-logic circuits," *IEEE Trans. Comput.-Aided Des. Integr. Circuits Syst.*, vol. 25, pp. 1000–1010, 2006. arXiv:quant-ph/0406176.

[23] C. M. Dawson and M. A. Nielsen, "The Solovay–Kitaev algorithm," *Quantum Inf. Comput.*, vol. 6, pp. 81–95, 2006. arXiv:quant-ph/0505030.

[24] D. Bacon, I. L. Chuang, and A. W. Harrow, "The quantum Schur transform: I. Efficient qudit circuits," 2006. arXiv:quant-ph/0601001.

[25] W. M. Kirby and F. W. Strauch, "A practical quantum algorithm for the Schur transform," 2017. arXiv:1709.07119.

[26] H. Krovi, "An efficient high dimensional quantum Schur transform," *Quantum*, vol. 3, p. 122, 2019. doi:10.22331/q-2019-02-14-122.

[27] T. V. Kondra, P. Barrios Hita, J. Neumann, H. Kampermann, and D. Bruß, "Fundamental limitations on entanglement extraction from purity," 2026. arXiv:2605.29197.

[28] Y. Zhang, "Global-unitary entanglement extraction: capacity and exact strong-converse exponents," repository preprint, 2026. Fixed repository source.

[29] Y. Zhang, "State-independent entanglement extraction: exact exponents, reliability and a Gaussian threshold," repository preprint, 2026. Fixed repository source.

[30] Y. Zhang, "A relative APPT entropy equivalent uniform in both dimensions and every order," repository manuscript, 2026. Fixed repository source.

[31] Y. Zhang, "APPT purity: qutrit exact theorems and high-dimensional asymptotics," repository manuscript and verified sources, 2026. Fixed formalization and scope records.