

Theme block targeting 主题块定位

Theme block targeting allows theme developers to specify which blocks can be used in a section. In a theme section, theme developers can choose to:

主题块定位允许主题开发人员指定哪些块可以在分区中使用。在主题版块中，主题开发者可以选择：

1. Accept all theme blocks for use
接受所有主题块以供使用
2. Accept specific theme blocks for use
接受特定主题块以供使用

Accept all theme blocks 接受所有主题块

To accept all theme blocks in a section by adding a generic entry of type `@theme` to the `blocks attribute` of the `schema` of that section. To be more restrictive about which blocks can be use in specific sections, use `block targeting`.

通过将类型 为 `@theme` 的泛型条目添加到该部分架构的 `blocks 属性`来接受该部分中的所有主题块。要更可以在特定版块中使用哪些块进行更多限制，请使用块定位。

In the following example, the Section will have access to all theme blocks.

在以下示例中，分区将有权访问所有主题块。

```
1 /sections/section.liquid
2
3 {% content_for 'blocks' %}
4
5 {% schema %}
6 {
7   "name": "Section",
8   "blocks": [{"type": "@theme"}]
9 }
10 {% endschema %}
```

Accept specific theme blocks 接受特定主题块

To accept specific theme blocks, theme developers can explicitly reference blocks in their schema. In the following example, the Slideshow section will have access to only the Slide theme block. In the editor, the block picker for Slideshow will only have a single block: slide. By default, theme blocks are available in all sections and theme blocks. In this example, the slide block will be in the block picker for all sections, not just the slideshow section.

要接受特定的主题块，主题开发人员可以在其架构中显式引用块。在以下示例中，幻灯片部分将只能访问幻灯片主题块。在编辑器中，幻灯片的块选择器将只有一个块：幻灯片。默认情况下，主题块在所有部分和主题块中都可用。在此示例中，幻灯片块将位于所有部分的块选择器中，而不仅仅是幻灯片部分。

```
1 /blocks/slide.liquid /块/slide.liquid
2
3 {% content_for 'blocks' %}
4
5 {% schema %}
6 {
7   "name": "Slide"
8 }
9 {% endschema %}
```

```
1 /sections/slideshow.liquid
2
3 {% content_for 'blocks' %}
4
5 {% schema %}
6 {
7   "name": "Slideshow",
8   "blocks": [{"type": "slide"}]
9 }
10 {% endschema %}
```

Private blocks 私人区块

There are cases where you might want to limit the blocks that are available in sections. For example, slides are a type of block that should only be available in slideshow sections. To prevent the default behavior, theme developers can name the block with an underscore prefix.

在某些情况下，您可能希望限制分段中可用的块。例如，幻灯片是一种块，只能在幻灯片部分中使用。为了防止默认行为，主题开发人员可以使用下划线前缀命名块。

In this case, `slide.liquid` can be renamed to `_slide.liquid`. All underscore prefixed blocks would be excluded from appearing in the block picker for blocks and sections that accept blocks with type `@theme`. Those blocks and sections will need to explicitly add the block by base filename. Ex: `"blocks": [ { "type": "_slide" } ]`

在这种情况下，`slide.liquid` 可以重命名为 `_slide.liquid`。对于接受类型为 `@theme` 的块的块和部分，所有带下划线前缀的块都将被排除在块选择器中。这些块和部分需要按基本文件名显式添加块。前任：`"blocks": [ { "type": "_slide" } ]`

```
1 /blocks/_slide.liquid /块/_slide.liquid
2
3 {% schema %}
4 {
5   "name": "Slide"
6 }
7 {% endschema %}
```

```
1 /sections/slideshow.liquid
2
3 {% content_for 'blocks' %}
4
5 {% schema %}
6 {
7   "name": "Slideshow",
8   "blocks": [{"type": "_slide"}]
9 }
10 {% endschema %}
```

- Accept all theme blocks
接受所有主题块
- Accept specific theme blocks
接受特定主题块
- Private blocks 私人区块

Was this page helpful? 此页面对您有帮助吗? Yes 是的 No 不

GETTING STARTED 开始

Overview 概述

> Quick start 快速入门

KEY CONCEPTS 关键概念

Architecture 建筑

> Layouts 布局

> Templates 模板

> Sections 部分

> Section groups 部分组

> Blocks 块

Overview 概述

> Theme blocks 主题块

Quick Start 快速入门

Block schema 块架构

Block targeting 块定位

Static blocks 静态块

Dynamic sources 动态源

Section blocks 分区块

Updates 更新	Business growth 业务增长	Legal 法律	Shopify Shopify 网站
Developer changelog 开发者变更日志	Shopify Partners Program	Terms of service 服务条款	About Shopify 关于 Shopify
Shopify Partners Slack	Shopify 合作伙伴计划	API terms of use	Shopify Plus
Slack	Shopify App Store	API 使用条款	Careers 职业
Shopify Editions	Shopify 应用商店	Privacy policy 隐私策略	Investors 投资者
Shopify 版本	Shopify Academy	Partners Program Agreement	Press and media 新闻和媒体
	Shopify 学院	合作伙伴计划协议	