OS & SP

Name : M Ramya Sree **Roll No :** 2520030094

SKILL – 10

1.Skill10.c

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <sys/wait.h>

int main(void)
{
   char cwd[1024];

   /* pwd functionality */
   if (getcwd(cwd, sizeof(cwd)) != NULL) {
      printf("Current Directory: %s\n", cwd);
```

```
} else {
    perror("getcwd");
}

/* Export functionality */
printf("\nBefore export:\n");

char *value = getenv("OSSP_VAR");

if (value != NULL) {
    printf("OSSP_VAR = %s\n", value);
} else {
    printf("OSSP_VAR is not set\n");
}

printf("\nSetting OSSP_VAR=Hello_OSSP\n");

if (setenv("OSSP_VAR", "Hello_OSSP", 1) == -1) {
```

```
    perror("setenv");
    return 1;
}

printf("After export:\n");
printf("OSSP_VAR = %s\n", getenv("OSSP_VAR"));

/* Check that child inherits variable */
pid_t pid = fork();

if (pid < 0) {
    perror("fork");
    return 1;
}

if (pid == 0) {
    printf("\nChild Process:\n");
    printf("OSSP_VAR = %s\n", getenv("OSSP_VAR"));
```

```
        exit(0);
    }

    waitpid(pid, NULL, 0);

    printf("\nProgram completed successfully.\n");

    return 0;
}
```

OUTPUT :

```
ramyasree@DESKTOP-DP2O9U6:~/Skill$ nano skill10.c
ramyasree@DESKTOP-DP2O9U6:~/Skill$ gcc -Wall -Wextra -g skill10.c -o skill10
ramyasree@DESKTOP-DP2O9U6:~/Skill$ ./skill10
Current Directory: /home/ramyasree/Skill

Before export:
OSSP_VAR is not set

Setting OSSP_VAR=Hello_OSSP
After export:
OSSP_VAR = Hello_OSSP

Child Process:
OSSP_VAR = Hello_OSSP

Program completed successfully.
ramyasree@DESKTOP-DP2O9U6:~/Skill$
```