

25

Convolutional Neural Network

- A CNN is a type of artificial neural network used in image recognition and processing. #
- It is not fully Connected.
- It works well with images.
- In previous, we were comparing pixel to pixel.
But
- In CNN, we compare the patch of 1 sample to another sample.

26


- We can also apply CNN with text classification.
- CNN is data hungry. It requires lots of data (images) to perform well.
- CNN learns the features based on images.

• Difference in CNN and ANN?

In CNN, the only last layer of Network is fully connected whereas in ANN, each neuron is connected to every other neuron.

27

CNN Architecture



28

29

- ① Input [image]
 - ② Convolutional Layer
 - ③ pooling layer
 - ④ fully-Connected
 - ⑤ Output layer
- } You can use
 convo-pooling layer
 more than once.
- stack

30

* Convolutional Layer: Operation:

It is a mathematical operation that allows merging of two sets of information. In CNN, it is applied to the input data to filter the information and produce a map.

$$\begin{bmatrix} 0 & 1 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 & 1 \end{bmatrix}_{5 \times 5} * \begin{bmatrix} 1 & 0 & 1 \\ 1 & 0 & 1 \\ 0 & 0 & 1 \end{bmatrix}_{3 \times 3}$$

31

Input

Kernel / Filter Size = 3

stride by 1

$$\begin{bmatrix} 0 & 1 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 & 1 \end{bmatrix}_{5 \times 5} * \begin{bmatrix} 1 & 0 & 1 \\ 1 & 1 & 1 \\ 0 & 0 & 1 \end{bmatrix}_{3 \times 3} = \begin{bmatrix} 2 & 3 & 5 \\ & & \\ & & \end{bmatrix}_{3 \times 3}$$

$$2 = 0 \times 1 + 1 \times 0 + 1 \times 1 + 0 \times 1 + 1 \times 1 + 0 \times 1 + 1 \times 0 + 1 \times 0 + 0 \times 1$$

$$3 = 1 \times 1 + 1 \times 0 + 0 \times 1 + 1 \times 1 + 1 \times 1 + 0 \times 1 + 1 \times 0 + 1 \times 0 + 0 \times 1$$

$$5 = 1 \times 1 + 0 \times 0 + 1 \times 1 + 1 \times 1 + 0 \times 1 + 1 \times 1 + 1 \times 0 + 0 \times 0 + 1 \times 1$$

So on

01

- **Filter/Kernel:** This filter is also called a kernel, or feature detector and its dimension can be for example 3×3 ...

- **padding:** padding expands the input matrix by adding fake pixels to the borders of the matrix.

This is done because Convolution reduces the size of the matrix.

For example: a 5×5 matrix turns into 3×3 matrix when a filter goes over it.

02

- **Stride:** The idea behind Stride is to skip some areas when the kernel slides over:

For example, skipping every 2 or 3 pixels.

It reduces spatial resolution and make computation efficient.

03

* Convolution with Stride:

$$\begin{bmatrix} 0 & 1 & 1 & 0 \\ 0 & 1 & 1 & 0 \\ 0 & 1 & 1 & 0 \\ 0 & 1 & 1 & 0 \end{bmatrix} * \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}_{2 \times 2} = \begin{bmatrix} 2 & 1 \\ & \end{bmatrix}_{2 \times 2}$$

Stride by 2

$$0 \times 0 + 1 \times 1 + 0 \times 1 + 1 \times 0 = 0 + 1 + 0 + 1 = 2$$

04

* Convolution with padding:

05

$$\begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 1 & 0 & 0 \\ 0 & 0 & 1 & 1 & 0 & 0 \\ 0 & 0 & 1 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}_{6 \times 6} * \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}_{2 \times 2} = \begin{bmatrix} & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \end{bmatrix}_{3 \times 3}$$

Adding fake pixels
by adding row and
column.

- **pooling layer:** A pooling layer receives the result from a Convolutional layer and compresses it. The filter of pooling layer is smaller than a feature map.

Usually it takes a 2×2 square (patch) and compresses it into one value.

* Pooling Operation:

→ max pooling
→ min pooling
→ average pooling

} 3-types of pooling

07

1	3	4	2
6	8	7	2
1	6	2	3
0	2	4	1

4x4

- Stride by 1
- max pooling

Consider the maximum value for each patch.

=

8	8	7
8	8	7
6	4	4

3x3

The process of pooling with stride will further downsize the image.

* fully-connected

* output layer.