Recording-window sensitivity of the candidate features

C_speed_by_time.pc1
FPCA_C_K2
TCNB_C
TCNA_C
C_speed_by_time.pc2
TCNB_A
C_alt_origin_at_ref_speed.pc1
TCNB_A_E16
FPCA_A_K2
TCNA_A
accel_initial
A_speed_by_distance.pc1
p95_a_tan
accel_v2_5
A_speed_by_distance.pc2
A_alt_origin_at_ref_speed.pc1
accel_sustained
B_alt_boundary_kept.pc1
accel_v2_7
TCNA_A_E16
C_alt_origin_at_ref_speed.pc2
TCNB_B
peak_a_tan_interior
peak_a_tan
model_a_at_ref
FPCA_B_K5
model_tau_s
B_accel_by_speed.pc1
model_a0
TCNA_B
B_accel_by_speed.pc2
B_alt_boundary_kept.pc2
time_v4_to_v8_s
A_alt_origin_at_ref_speed.pc2
accel_0p5s_from_v4
accel_1s_from_v4
accel_v4_7
p95_decel
peak_speed
B_accel_by_speed.pc4
p95_speed
B_alt_boundary_kept.pc3
speed_gain_10yd_from_v4
peak_speed_interior
model_vmax
peak_decel
B_accel_by_speed.pc3
B_alt_boundary_kept.pc6
B_alt_boundary_kept.pc5
B_alt_boundary_kept.pc8
B_accel_by_speed.pc5
B_alt_boundary_kept.pc4
B_alt_boundary_kept.pc7

× draft cohort (share of athlete variance; vectors: probe gain)
reference 0.25

0.0 0.2 0.4 0.6 0.8 1.0

share of the attempt-to-attempt change explained by the change of the recording window

Unit: athlete with two attempts (up to 56). Dot = R^2 of (attempt 2 − attempt 1) of the feature on the change of first-frame speed, recorded duration and frames after the speed peak; bar = 95 % athlete bootstrap. An athlete does not change between two attempts, his recording does: a large share means the feature follows the recording. Cross = dependence on the draft cohort (sensor generation). Colour = family; vectors use the trace R^2 of notebook 03.