

# Predicting Sales Win or Lose

*Herman Toeante*

*February 12, 2019*

## Machine Learning for predicting sales win or loss

The goal of this project is to use machine learning to predict whether or not a sales lead is either win or loss and the probability of each class. This project is a supervised classification problem.

Two models will be used to test the data; Logistic regression and Random Forest. These two models are part of the caret package or R. Before preparing the model, the first step is to choose the independent variable that will be used in the model.

```
library(tidyverse)
```

```
## Warning: package 'tidyverse' was built under R version 3.5.2
```

```
library(caret)
```

```
## Warning: package 'caret' was built under R version 3.5.2
```

```
sales_win_loss <- read_csv("DATA/WA_Fn-UseC_-Sales-Win-Loss.csv")
```

```
colnames(sales_win_loss) <- c("ID", "SuppliesSubgroup", "SuppliesGroup", "Region", "Route",  
  "ElapsedDays", "Result", "SalesStageCount",  
  "TotalDaysClosing", "TotalDaysQualified",  
  "Opportunity", "ClientSizeRev", "ClientSizeCount",  
  "Revenue", "Competitor", "RDaysIdentified",  
  "RDaysValidated", "RDaysQualified",  
  "DealSize")
```

```
ModelData <- sales_win_loss %>% select(SuppliesSubgroup, Region, Route, TotalDaysClosing,  
  TotalDaysQualified, Opportunity, ClientSizeRev,  
  ClientSizeCount, Competitor, DealSize, Result)
```

The next step is partitioning the data set into training, validation, and testing dataset. We start with the seed for reproducibility followed using createDataPartition function from caret.

```
set.seed(3456)
```

```
TrainingValidationIndex <- caret::createDataPartition(ModelData$Result, p = .80,  
  list = FALSE,  
  times = 1)
```

```
str(TrainingValidationIndex)
```

```
## int [1:62421, 1] 3 6 8 9 10 11 13 14 15 16 ...  
## - attr(*, "dimnames")=List of 2  
## ..$ : NULL  
## ..$ : chr "Resample1"
```

```

TrainingValidation <- ModelData[ TrainingValidationIndex,]
TrainingIndex <- caret::createDataPartition(TrainingValidation$Result, p = .75,
                                             list = FALSE,
                                             times = 1)

Training <- TrainingValidation[TrainingIndex,]
Validation <- TrainingValidation[-TrainingIndex,]
Testing <- ModelData[-TrainingValidationIndex,]

```

Using glimpse function, we can see the selected variables for the model.

```
glimpse(Training)
```

```

## Observations: 46,817
## Variables: 11
## $ SuppliesSubgroup <chr> "Shelters & RV", "Batteries & Accessories",...
## $ Region <chr> "Pacific", "Northwest", "Pacific", "Northwe...
## $ Route <chr> "Reseller", "Fields Sales", "Reseller", "Fi...
## $ TotalDaysClosing <int> 114, 156, 50, 165, 31, 208, 138, 32, 130, 1...
## $ TotalDaysQualified <int> 0, 156, 50, 165, 31, 208, 138, 32, 130, 125...
## $ Opportunity <int> 232522, 250000, 55003, 0, 10000, 232522, 20...
## $ ClientSizeRev <int> 5, 1, 1, 1, 2, 1, 4, 5, 4, 1, 3, 1, 1, 5, 1...
## $ ClientSizeCount <int> 1, 5, 1, 2, 1, 1, 5, 1, 3, 5, 5, 1, 4, 3, 5...
## $ Competitor <chr> "Unknown", "None", "Unknown", "Unknown", "U...
## $ DealSize <int> 5, 6, 4, 1, 2, 5, 5, 1, 4, 5, 4, 3, 4, 4, 7...
## $ Result <chr> "Loss", "Loss", "Loss", "Loss", "Loss", "Lo...

```

Next, we setup the model parameter

```

control <- caret::trainControl(method = "cv", number = 2, classProbs = TRUE)
seed <- 7
metric <- "Accuracy"
set.seed(seed)

```

Training Logistic with training dataset

```

GLMModel <- caret::train(
  Result ~ SuppliesSubgroup + Region + Route + TotalDaysClosing + TotalDaysQualified +
    Opportunity + ClientSizeRev + ClientSizeCount + Competitor + DealSize,
  data = Training,
  method = "glm",
  trControl = control
)

```

Training Random Forest model with training dataset

```

RFModel <- caret::train(
  Result ~ SuppliesSubgroup + Region + Route + TotalDaysClosing + TotalDaysQualified +
    Opportunity + ClientSizeRev + ClientSizeCount + Competitor + DealSize,
  data = Training,
  method = "rf",
  trControl = control
)

```

Using predict function from caret package, I will use the result to find the best model. Caret package also have the confusion matrix function to calculate sensitivity, specificity, negative predicted value, positive predicted values, and F1 score. The F1 score is a harmonic average of precision and recall to select the best model.

```
PredGLM <- predict(GLMModel, Validation)
```

```
ConfMatGLM <- caret::confusionMatrix(
  PredGLM, factor(Validation$Result), positive = "Won", mode = "everything")
```

```
ConfMatGLM
```

```
## Confusion Matrix and Statistics
##
##           Reference
## Prediction  Loss   Won
##           Loss 11604 2703
##           Won   475   822
##
##           Accuracy : 0.7963
##           95% CI : (0.7899, 0.8026)
##           No Information Rate : 0.7741
##           P-Value [Acc > NIR] : 9.572e-12
##
##           Kappa : 0.2498
##           Mcnemar's Test P-Value : < 2.2e-16
##
##           Sensitivity : 0.23319
##           Specificity : 0.96068
##           Pos Pred Value : 0.63377
##           Neg Pred Value : 0.81107
##           Precision : 0.63377
##           Recall : 0.23319
##           F1 : 0.34094
##           Prevalence : 0.22590
##           Detection Rate : 0.05268
##           Detection Prevalence : 0.08312
##           Balanced Accuracy : 0.59693
##
##           'Positive' Class : Won
##
```

The F1 score for the Logistic model is 0.3409374 Next, we did the same thing using Random Forest model with validation data set

```
PredRF <- predict(RFModel, Validation)
```

```
ConfMatRF <- caret:: confusionMatrix(PredRF, factor(Validation$Result), positive = "Won", mode = "everything")
```

```
ConfMatRF
```

```
## Confusion Matrix and Statistics
##
```

```

##           Reference
## Prediction  Loss   Won
##      Loss 11233 1893
##      Won   846 1632
##
##           Accuracy : 0.8245
##           95% CI : (0.8184, 0.8304)
##      No Information Rate : 0.7741
##      P-Value [Acc > NIR] : < 2.2e-16
##
##           Kappa : 0.4391
## Mcnemar's Test P-Value : < 2.2e-16
##
##           Sensitivity : 0.4630
##           Specificity : 0.9300
##      Pos Pred Value : 0.6586
##      Neg Pred Value : 0.8558
##           Precision : 0.6586
##           Recall : 0.4630
##           F1 : 0.5437
##           Prevalence : 0.2259
##      Detection Rate : 0.1046
##      Detection Prevalence : 0.1588
##      Balanced Accuracy : 0.6965
##
##      'Positive' Class : Won
##

```

The F1 score for the Random Forest model is 0.5437281