

External Screen Roller Blinds

Pantallas Screen Exteriores / Toldos Screen

Technical screen fabric blinds — solar protection while preserving natural daylight



Screen Blinds

Fart Produkt Sp. z o.o. sp.k. · ul. Towarowa 3, 87-100 Toruń · NIP 8792684425

www.fartprodukt.pl

MADE IN POLAND

External Screen roller blinds by Fart Produkt combine aesthetics with effective solar and heat protection, allowing natural daylight to pass through while blocking UV radiation and glare. The system consists of an aluminium extruded cassette (85/95/125 mm surface-mount, or 105/125 mm flush-mount), a galvanised steel winding tube, aluminium-extruded bottom bar, and high-quality screen fabric from leading European manufacturers. Available in surface-mounted and flush (concealed) variants, with three guide systems: ZIP (windproof, insect-screen capable), lower-bar-in-guide, and cable. Maximum width 6 m, maximum surface 18 m².

MAIN MATERIAL & CONSTRUCTION

Core mesh: Fibreglass/PVC technical screen mesh with PVC 70% / PES 30%.
Frame/cassette: extruded aluminium, powder-coated. Winding tube: galvanised steel.

TECHNICAL SPECIFICATIONS

PRODUCT CODE	FP-SC-EXT
CASSETTE SIZES (SURFACE)	85 / 95 / 125 mm
CASSETTE SIZES (FLUSH)	105 / 125 mm
MAX. WIDTH	6 000 mm
MAX. HEIGHT	5 000 mm
MAX. SURFACE AREA	18 m²
GUIDE TYPES	ZIP / Lower-bar-in-guide / Cable
CASSETTE MATERIAL	Extruded Aluminium
WINDING TUBE	Galvanised Steel
BOTTOM BAR MATERIAL	Extruded Aluminium

CERTIFICATIONS & COMPLIANCE

- CE Marked — Construction Products Regulation (EU) No 305/2011
- EN 13659:2015 — Shutters and exterior blinds, performance requirements
- ISO 9001:2015 — Quality Management System
- Screen Fabrics — EN 410 (Solar energy transmittance tested)
- Made in Poland — Country of Origin: PL

TYPICAL APPLICATIONS

- Residential terraces & pergolas
- Office & commercial glass facades
- Hotels — balconies & common areas
- Conservatories & winter gardens
- Educational & public buildings

KEY FEATURES

ZIP System — Wind-Resistant & Insect-Proof

The ZIP guide locks the fabric edge into the guide channel, providing exceptional wind resistance and eliminating gaps that would allow insects to pass through.

Natural Daylight Preservation

Technical screen fabrics filter UV and reduce solar heat gain while maintaining visibility and natural light — reducing air-conditioning costs without sacrificing comfort.

Up to 18 m² Single Panel

Suitable for large-format glazed facades, pergolas, and terraces. Surface area up to 18 m² in a single screen without intermediate supports.

Smart-Home & Weather Automation

Compatible with io-Homecontrol and standard radio systems; can integrate with weather stations for automatic wind/sun response.

IMPORT & LOGISTICS DATA

COUNTRY OF ORIGIN	Poland
HS TARIFF CODE	6306 12 00
WARRANTY PERIOD	24 months
MINIMUM ORDER QTY	1 unit
UNIT WEIGHT	12-54 kg (size-dependent, per weight table)
UNIT DIMENSIONS	Custom per order
UNITS / CARTON	1
CARTON WEIGHT (GROSS)	Varies (incl. packaging)
CARTON DIMENSIONS	Custom per order