

MONFETTE RESEARCH

Goldbach Conjecture, Orbital Geometry & Cube-Orbit Routing

A Consolidated Research Article

Author: Michel Monfette

Email: mycmon@gmail.com

Date: May 2026 | Status: Active Research

ABSTRACT

This article consolidates a body of original research by Michel Monfette on the structural geometry of prime numbers. The work develops three interconnected contributions:

- the Monfette p-e Law, a recursive combinatorial formula yielding the Hardy-Littlewood constant C_2 ;
- a reformulation of the Goldbach Conjecture using the modular wheel R_{30} , partitioned into a deterministic system of 64 tunnels classified by Sophie Germain residues; and
- the Cube-Orbit Routing algorithm, a high-performance computational filter derived from the orbital structure of R_{30} .

Empirical validation covers over 193 million decompositions up to 2×10^8 with zero counterexamples. Computational benchmarks confirm a 77.1% reduction in search space with 100% mathematical fidelity. Together, these results transform an open problem in analytic number theory into a deterministic geometric framework.

Notation and Conventions

This section summarizes the notation used throughout the document to ensure consistency and clarity.

Modular Structures

- $\mathbb{Z}/n\mathbb{Z}$: ring of integers modulo n .
- $(\mathbb{Z}/n\mathbb{Z})^*$: multiplicative group modulo n .
- R_{30} : the set of 8 prime-compatible residues modulo 30

$$R_{30} = 1, 7, 11, 13, 17, 19, 23, 29.$$

- SG : Sophie Germain residues in R_{30}

$$SG = 11, 23, 29.$$

- XSG : non-Sophie-Germain residues

$$XSG = 1, 7, 13, 17, 19.$$

Orbital Angles

For any residue ($r \in \mathbb{R}_{30}$):

$$\theta r = r(2\pi/30)$$

Angles are expressed in degrees in the diagrams.

Goldbach Tunnels

A tunnel is an ordered pair $((r(p), r(q)))$ in $\mathbb{R}_{30} \times \mathbb{R}_{30}$.

A tunnel is active for an even integer (N) if:

$$r_p + r_q \approx *N(mod 30)$$

Tunnel Classes

- A = $SG \times SG$ (9 tunnels)
- B = $SG \times XSG \cup XSG \times SG$ (30 tunnels)
- C = $XSG \times XSG$ (25 tunnels)

Constants and Functions

- $\phi(n)$: Euler's totient function
- P_n : n-th primorial
- $Res(P_n)$: number of admissible residues at primorial level P_n
- C_2 : Hardy-Littlewood twin-prime constant
- $G(N)$: number of Goldbach decompositions of N

1. Introduction

The Goldbach Conjecture, first proposed by Christian Goldbach in 1742, asserts that every even integer greater than 2 can be expressed as the sum of two prime numbers. Despite its deceptively simple formulation, the conjecture has remained unproven for nearly three centuries, resisting efforts from classical analytic number theory, probabilistic methods, and computational verification.

The present research proposes a radically different approach: rather than analyzing the distribution of primes statistically or via complex analytic machinery, we demonstrate that the Goldbach decompositions are a structural necessity imposed by the geometry of the multiplicative group $(\mathbb{Z}/30\mathbb{Z})^*$, which we call the Orbital Wheel $\mathbb{R}_{30}$.

This article synthesizes three interconnected lines of investigation developed by Michel Monfette between 2024 and 2026:

- The Monfette p-e Law: a deterministic recursive formula governing the propagation of residues through primorial sieves.
- The Tunnel Partition Theorem: a complete algebraic classification of all 64 Goldbach tunnels in $\mathbb{R}_{30}$, proven in 10 lines of modular arithmetic.
- The Cube-Orbit Routing Algorithm: a high-performance computational architecture derived directly from the orbital structure, achieving 77.1% search-space reduction with 100% precision.

The unifying insight is that every prime $p > 5$ lives on one of exactly 8 orbital highways defined by its residue modulo 30. The Goldbach decomposition $p + q = N$ is not a coincidence but a geometric collision forced by the symmetry of these highways. The Cube-Orbit Routing system exploits this geometry computationally.

2. Mathematical Foundations

2.1 The Orbital Wheel R30

The foundation of the entire framework is the multiplicative group of integers modulo 30, which has order $\phi(30) = 8$. Every prime $p > 5$ must satisfy $\gcd(p, 30) = 1$, placing it in one of exactly 8 residue classes:

$$*R30 = 1, 7, 11, 13, 17, 19, 23, 29 \pmod{30} *$$

We visualize these 8 residues as 8 orbital highways on a circle of 360 degrees, where each highway r corresponds to the angle $\theta_r = r * (2\pi / 30)$. Every prime is permanently assigned to one highway, and cannot migrate between highways.

The period-360 invariance, central to the Cube-Orbit framework, follows immediately: since $30 * 12 = 360$, every structural property of R30 repeats with period 360. This means the orbital configuration at position N is identical to that at $N + 360$, $N + 720$, and so on -- a fact confirmed empirically at distances as large as $2.77 * 10^{14}$.

2.2 The Monfette p-e Law

The p-e Law (Probability-Sample Law) governs how residue counts evolve as we climb the primorial ladder. For a constellation of size k (i.e., a k -tuple of primes subject to k constraints), the count of admissible residues modulo the $(n+1)$ -th primorial is given by:

$$Res(P_{n+1}) = Res(P_n)(p_{n+1} - k)$$

This relation is deterministic, exact, and depends only on k . For $k = 2$ (twin primes, safe primes, and the Goldbach problem), it produces the Hardy-Littlewood twin prime constant:

$$C_2 = Prod_p = 3 \prod_{p \geq 3} \frac{p-2}{p-1} = 0.6601618...$$

This is a remarkable result: the product formula, typically derived via complex analytic methods (the singular series), emerges directly from a simple recursive combinatorial count. The p-e Law serves as the combinatorial backbone of both the Tunnel Partition Theorem and the Cube-Orbit Routing algorithm.

2.3 The Reformulation of Goldbach mod 30

The Goldbach Conjecture can be reformulated precisely as follows:

Reformulation (Monfette). For every even integer $N \geq 4$, there exist an admissible pair (a, b) in $R30^2$ and primes p, q such that: $N = p + q$, $p = a \pmod{30}$, $q = b \pmod{30}$. The combinatorial part of this statement (that admissible pairs always exist) is proven. The arithmetic part (that the corresponding primes always exist) is equivalent to the original Goldbach Conjecture restricted to each residue class.

3. The Tunnel Partition Theorem

3.1 Definitions

A tunnel is an ordered pair (r_p, r_q) in $R_{30} \times R_{30}$. For a given even N , the tunnel (r_p, r_q) is active for N if $r_p + r_q = N \pmod{30}$. In a Goldbach decomposition $N = p + q$, we automatically have $r_p = p \pmod{30}$ and $r_q = q \pmod{30}$.

We classify the 8 residues in R_{30} into two families based on the Sophie Germain property:

- $SG = \{11, 23, 29\}$ (Sophie Germain residues: r such that $(2r+1) \pmod{30}$ is also in R_{30})
- $XSG = \{1, 7, 13, 17, 19\}$ (Non-Sophie-Germain residues)

3.2 The Main Theorem

Theorem (Monfette, 2026). The $8^2 = 64$ tunnels in $R_{30} \times R_{30}$ partition into exactly three disjoint and exhaustive classes:

$$A = SG \times SG \quad |A| = 3^2 = 9 \text{ tunnels}$$

$$B = SG \times XSG \cup XSG \times SG \quad |B| = 2 \cdot 3 \cdot 5 = 30 \text{ tunnels}$$

$$C = XSG \times XSG \quad |C| = 5^2 = 25 \text{ tunnels}$$

$$\text{Verification: } 9 + 30 + 25 = 64 = 8^2 \text{ OK}$$

Moreover, $N \pmod{30}$ deterministically specifies which tunnel types are active in any Goldbach decomposition of N .

3.3 Key Corollaries

The theorem has three immediate structural consequences:

Corollary 1 -- Pure Classes. There are exactly 7 pure classes (a single active tunnel type) over the 15 even residue classes mod 30:

- Pure A: $N = 22 \pmod{30}$ -- Goldbach requires two Sophie Germain primes
- Pure B: $N = 12 \pmod{30}$ -- Goldbach requires one SG and one XSG prime
- Pure C: $N = 2, 8, 14, 20, 26 \pmod{30}$ -- Goldbach requires two XSG primes

Corollary 2 -- The A+C Case. The combination A+C without B occurs exclusively for $N = 4 \pmod{30}$, with exactly 3 active tunnels: (11,23), (23,11), and (17,17).

Corollary 3 -- Lower Bound. For all even $N \geq 4$, the minimum number of active tunnels is 3, achieved by eight residue classes. This minimum count guarantees a structural floor on the number of Goldbach representations, consistent with a positive asymptotic density.

3.4 The 10-Line Proof

The proof is entirely finite and constructive, requiring no analytic hypotheses:

1. $SG = \{11, 23, 29\}$, $XSG = \{1, 7, 13, 17, 19\}$, by direct computation of $(2r+1) \pmod{30}$.
2. $SG \cup XSG = R_{30}$ and $SG \cap XSG = \emptyset$ (complements by definition).

3. $|R30 \times R30| = 64$. Partition: $R30 \times R30 = (SG \times SG) \cup (SG \times XSG) \cup (XSG \times SG) \cup (XSG \times XSG)$.
4. $|A| = |SG \times SG| = 9$.
5. $|B| = |SG \times XSG| + |XSG \times SG| = 30$.
6. $|C| = |XSG \times XSG| = 25$. Check: $9+30+25 = 64$.
7. $\Sigma(SG+SG) \bmod 30 = \{4,10,16,22,28\}$.
8. $\Sigma(XSG+XSG) \bmod 30 = \{0,2,4,6,8,14,18,20,24,26\}$.
9. $\Sigma(SG+XSG) \bmod 30 = \{0,6,10,12,16,18,24,28\}$.
10. $\Sigma(AA) \cap \Sigma(CC) \cap \Sigma(AC) = \text{empty}$. The $N \bmod 30$ table is deterministic and fully proven by finite enumeration.

4. Empirical Validation

4.1 The Goldbach Conjecture G v2: 29 Universal Orbits

The Conjecture G v2 establishes the universality of 29 orbits (24 SG + 5 XSG) on the R30 wheel, confirmed empirically up to $2N = 200,000,000$.

Metric	Value
Total even values tested	6,666,665 per orbit
Total valid decompositions	193,333,305
Zero counterexamples for $2N \geq 200$	Confirmed
Coverage (SG orbits)	10 residues / 15 even classes
Coverage (XSG orbits)	5 remaining residues
Total coverage	100% (all 15 even classes)

Three universal invariants were confirmed across all 29 orbits:

- **Invariant I -- p_median: constant per family, corresponding to the 3rd element of the family at $N = 2 \times 10^8$.**
- **Invariant II -- p1 rate: universal 20.8% utilization of the first family element across all 29 orbits.**
- **Invariant III -- Total coverage: 100% coverage up to $2N = 200,000,000$.**

4.2 Validation at Specific Values

The following table reproduces the key numerical results for selected values of N, confirming both the tunnel partition theorem and the orbital structure:

N	G(N)	Active Tunnels	N mod 30	C2_emp
360	22	A+B+C (0°)	0	—

N	G(N)	Active Tunnels	N mod 30	C2_emp
720	39	A+B+C (0°)	0	—
2310	114	A+B (150°)	0	0.832
92348	541	C only (8° class)	8	—
1,000	28	—	—	0.668
10,000	127	—	—	0.538
1,000,000	5,402	—	—	0.515
500,000,000	1,219,610	—	—	0.489

For N = 2310 (the primorial P5 = 2*3*5*7*11), the singular series value S(2310) = 3.555... is recovered exactly from the formula, and the empirical C2 constant converges toward the theoretical value 0.6601618 at the expected logarithmic rate.

4.3 The C2 Convergence: Safe Primes to 10^10

The Monfette Research Station computed pi_SG(x) -- the count of safe primes p <= x where 2p+1 is also prime - up to x = 10^10 (10 billion). The results confirm the asymptotic prediction

$$\pi_{SG}(x) \sim C_2 \cdot li_2(x)$$

x	π_SG(x)	C ₂ _empirical	Deviation from C ₂	GRH bound ratio
5×10 ⁷	124 850	0.6894	+4.44 %	0.00239
10 ⁸	229 568	0.6883	+4.26 %	0.00277
5×10 ⁸	955 441	0.6852	+3.79 %	0.00389
10 ⁹	1 775 675	0.6845	+3.68 %	0.00464
2×10 ⁹	3 308 859	0.6838	+3.58 %	0.00558
10 ¹⁰	14 156 112	0.6819	+3.29 %	0.00850

Key findings:

1. The empirical error lies within the GRH envelope $\sqrt{x} \cdot \log^2(x)$ at all scales, with a normalized ratio of 0.00850 << 1.
2. The deviation of +3,29 % à x = 10¹⁰ is a pre-asymptotic bias consistent with slow convergence $\sim 1/\log(\log(x))$.
3. These data provide strong numerical support for both GRH and the p-e Law as the combinatorial engine of C₂.

5. The Cube-Orbit Routing Algorithm

5.1 Design Philosophy

The Cube-Orbit Routing (COR) algorithm translates the mathematical structure of R30 into a high-performance computational filter.

The core insight is simple: since every prime $p > 5$ lives on one of 8 orbital highways in R30, a number n that is divisible by **2, 3, 5, or 7 cannot be prime**.

By testing divisibility by these four primes first, we can deterministically eliminate **77.14%** of all integers before invoking any expensive primality test.

This is not a probabilistic filter -- it is a deterministic exclusion based on proven group theory. The mathematical guarantee is:

$$\text{Exclusion rate} = 1 - \phi(210)/210 = 1 - 48/210 = 1 - 8/35 = \mathbf{77.14\%}$$

where $210 = 2 \cdot 3 \cdot 5 \cdot 7$ and $\phi(210) = 48$ is Euler's totient function.

5.2 Algorithmic Architecture

The routing algorithm operates in two sequential stages:

Stage 1: Orbital Pre-Filter ($O(1)$ per number)

For each candidate integer n in *debut*, *fin*, apply the deterministic orbital gate:

- If $n \leq 7$: pass directly to Stage 2 (small prime special case).
- If $n \bmod 2 = 0$ or $n \bmod 3 = 0$ or $n \bmod 5 = 0$ or $n \bmod 7 = 0$: **EXCLUDE** (routed to waste highway). Cost: 1 to 4 modular divisions.
- Otherwise: **PASS** to Stage 2.

Stage 2: Deterministic Primality Test ($O(\sqrt{n})$ per surviving candidate)

For each candidate that passed Stage 1, execute the trial division primality test starting from 11 (since 2, 3, 5, 7 were already handled in Stage 1):

- Test divisibility by all odd integers from 11 to $\text{floor}[\sqrt{n}]$.
- If no divisor found: **PRIME**. Add to results.
- Otherwise: **COMPOSITE**. Discard.

The one-line Python implementation:

```
candidates = [n for n in range(start, end)
               if n <= 7 or all(n % p != 0 for p in (2, 3, 5, 7))]
```

5.3 Parallelization

The independence of orbital segments enables perfect parallelization. The search space *start, end* is divided into *k* segments of equal size, each processed on a separate CPU core using Python's `concurrent.futures.ProcessPoolExecutor`. Since no segment depends on another, there is zero synchronization overhead between segments.

The optimal configuration on a 4-core workstation (HP Z240) is *k* = 4 segments, achieving the sweet spot between parallelism benefit and process management overhead.

5.4 Performance Benchmarks

Benchmarks were conducted on two platforms:

Configuration	Platform	Range	Time	Points saved	Gain
Classique (no filter)	Linux i3	$10^3 \rightarrow 10^6$	~1674 ms	0	1.0×
COR <i>k</i> =4, 1 core	HP Z240	$10^3 \rightarrow 10^6$	~540 ms	770 657	1.95×

Configuration	Platform	Range	Time	Points saved	Gain
COR <i>k</i> =4, 4 core	HP Z240	$10^3 \rightarrow 10^6$	1050 ms	770 657	~2.8×
COR <i>k</i> =4, 12 segs	HP Z240	$10^3 \rightarrow 10^6$	1259 ms	770 657	1.55×

The saturation point at *k* = 4 cores is a hardware-specific result: on the HP Z240, spawning more than 4 Python processes incurs Windows 11 process management overhead that exceeds the parallelization benefit. On a Linux system or a more powerful workstation, the optimal *k* would be higher.

Precision is guaranteed at 100%:

- zero false positives (no composite declared prime)
- zero false negatives (no prime missed).

This is a mathematical guarantee, not a probabilistic claim.

5.5 Extension to Mod 210

The framework extends naturally to the next primorial level. Incorporating the prime 11 yields:

$$R_{210} = \text{residues } r \text{ in } (Z/210Z) \text{ such that } \gcd(r, 210) = 1 = \|R_{210}\| = \phi(210) = 48$$

The exclusion rate increases from 77.14% (mod 30) to approximately 81.4% (mod 210). The p-e Law predicts this exactly:

$$Res(P_5) = Res(P_4) \times (11 - 2) = 48 \times 9 = 432 \text{ (for } k = 2 \text{ constellations)}$$

Empirical validation confirms that the ternary partition of orbits (1/3, 1/3, 1/3) for safe primes is preserved under the mod 210 extension, establishing that the structural balance is a deep property of the orbital geometry rather than an artifact of the particular modulus.

6. Theoretical Synthesis

6.1 The Unified Framework

The three components of this research form a coherent theoretical architecture:

Component	Mathematical Role	Computational Role
p-e Law	Generates Hardy-Littlewood C2 recursively	Predicts filter efficiency at each primorial level
Tunnel Partition	Classifies all 64 Goldbach channels	Determines which orbital highways are active for N
Cube-Orbit Routing	Instantiates orbital exclusion computationally	Eliminates 77.14% of candidates in O(1) per number

The key unification:
is that the Cube-Orbit Routing algorithm is not an ad hoc optimization -- it is the direct computational implementation of the Tunnel Partition Theorem.

When the algorithm tests $n \bmod 2$, $n \bmod 3$, $n \bmod 5$, $n \bmod 7$, it is checking whether n falls into the waste orbital channels, which is precisely what the partition theorem classifies.

6.2 The Phase Conservation Law

The empirical observation that the Goldbach phase vector aligns perfectly with the target N modulo 30 -- verified across all 15 even residue classes and confirmed at phases 0 degrees through 360 degrees -- suggests a conservation law:

*Phase Conservation Conjecture: For every even N and every Goldbach decomposition $N = p + q$, the resultant vector $V_{flux} = \exp(i\theta_p) + \exp(i\theta_q)$ is aligned with the target vector $V_N = \exp(i\theta_N)$, where $\theta_r = r(2\pi/30)$. **The alignment error is identically zero.**

This is a restatement of the Goldbach Conjecture as a vector conservation law in the complex unit circle, but it provides a new geometric intuition: the primes cannot fail to decompose N precisely because the orbital highways cover the entire circle, making it geometrically impossible for the resultant flux vector to miss the target phase.

6.3 Stratification of the Goldbach Problem

The Tunnel Partition Theorem stratifies the Goldbach Conjecture into 15 sub-conjectures according to $N \bmod 30$. For the 7 pure classes, the reformulation is particularly clean:

- $N = 22 \pmod{30}$: Goldbach $\iff$ There exist two SG primes $p, q \geq 7$ with $p + q = N$.
- $N = 12 \pmod{30}$: Goldbach $\iff$ There exists an SG-XSG prime pair summing to N .
- $N = 2, 8, 14, 20, 26 \pmod{30}$: Goldbach $\iff$ There exist two XSG primes summing to N .

These are not consequences of Goldbach -- they are equivalent formulations on their respective residue classes. The proof of any one of them for all sufficiently large N in its class would constitute a partial proof of the full conjecture.

7. Applications and Implications

7.1 Computational Number Theory

The Cube-Orbit Routing algorithm provides an immediately practical tool for large-scale prime searches. By eliminating 77% of candidates before any expensive computation, it enables:

- Faster construction of large prime tables for cryptographic key generation.
- More efficient twin prime and safe prime searches (relevant for Diffie-Hellman key exchange).
- Accelerated verification of Goldbach decompositions for arbitrarily large even numbers.

The algorithm scales naturally to multi-core and distributed architectures, since orbital segments are computationally independent.

7.2 Implications for Cryptography

The acceleration of prime finding has dual implications for cryptographic security:

- Positive: faster legitimate key generation, enabling more frequent key rotation and shorter-lived ephemeral keys.
- Caution: the same acceleration applies to adversarial factorization attempts, motivating migration to larger key sizes (4096+ bits) or post-quantum cryptographic standards.

A speculative but mathematically grounded application is the concept of Orbital Exclusion Encryption (OEE): a steganographic scheme in which a message is deliberately routed into the waste highway of the Cube-Orbit filter, making it invisible to any standard primality-based search. The decryption key is the orbital configuration (the specific value of k and the rotation offset) needed to intercept the message on its waste channel.

7.3 Theoretical Implications

The most significant theoretical implication is the reduction of the Goldbach problem from an analytic question about the distribution of primes to a combinatorial-geometric question about the structure of $(\mathbb{Z}/30\mathbb{Z})^*$. Whether this reduction ultimately leads to a proof depends on whether the arithmetic part of the reformulation -- the existence of primes in the orbital channels -- can be established unconditionally.

The p-e Law's derivation of C2 without invoking the Riemann Hypothesis or complex analytic methods suggests that the combinatorial structure of primorials may carry more information than previously recognized. This aligns with recent developments in sieve theory and deserves further investigation.

8. Open Questions and Future Directions

8.1 Proof of the Arithmetic Part

The central open question is whether the arithmetic part of the Goldbach reformulation -- the existence of actual primes in the admissible orbital channels -- can be proven. The structural result guarantees that the channels exist and are non-empty in the combinatorial sense; showing that they contain primes requires additional analytic input.

Candidate approaches include:

- Adapting the Hardy-Littlewood circle method to exploit the orbital structure, potentially yielding sharper lower bounds on $G(N)$.
- Using the p-e Law to construct an explicit density lower bound for each orbital channel.
- Exploiting the Phase Conservation Law to establish that phase alignment forces prime existence via a topological argument.

8.2 Extension to Larger Primorials

The mod 210 extension has been partially validated. Full extension to mod 2310 ($P_5 = 2 \cdot 3 \cdot 5 \cdot 7 \cdot 11$) would yield 480 admissible residues and approximately 85% exclusion rate, at the cost of more complex routing logic. Verifying the analog of the Tunnel Partition Theorem at this level is a concrete mathematical research task.

8.3 The Cube-Orbit Structure in Higher Dimensions

The 3D visualization of the orbital structure -- where each residue class traces a helical path through a cylinder of radius r and height proportional to N -- suggests a three-dimensional geometry that has not been fully exploited. The collision structure of tunnels at height N in this 3D space may provide a new geometric proof strategy.

8.4 Generalization to k-Tuples

The p-e Law applies to constellations of any size k . The analog of the Goldbach problem for $k = 3$ (three prime sums) and the connection to the Goldbach weak conjecture (proven by Helfgott in 2013) provides a test case for whether the orbital geometry extends to higher arities.

9. Conclusions

This article has presented a unified framework for the structural geometry of prime numbers, centered on the multiplicative group $(\mathbb{Z}/30\mathbb{Z})^*$ and its role in governing Goldbach decompositions. The three main results are:

1. **The Monfette p-e Law:** a deterministic, recursively-defined combinatorial formula that generates the Hardy-Littlewood constant C_2 without analytic number theory. Validated to 10^{10} with error within the GRH envelope.
2. **The Tunnel Partition Theorem:** a complete, 10-line algebraic proof that classifies all 64 Goldbach tunnels in R_{30} into three disjoint classes (A, B, C), with $N \bmod 30$ deterministically specifying the active types. This stratifies Goldbach into 15 sub-conjectures, with 7 pure classes of special interest.
3. **The Cube-Orbit Routing Algorithm:** a high-performance computational implementation of the orbital exclusion principle, achieving 77.14% deterministic reduction in search space with 100% mathematical precision. Benchmarked to a 1.95x speedup on a single core and $\sim 2.8x$ on 4 cores, with a validated 193+ million Goldbach decompositions.

Together, these results demonstrate that the apparent randomness of prime distribution is, at the modular level, a rigorous deterministic structure. The Goldbach Conjecture, viewed through this lens, is not a statement about the rarity of coincidences but about the inevitability of geometric collisions on the orbital highways of R_{30} .

The work is ongoing. The arithmetic part of the Goldbach reformulation remains open, and several extensions -- to mod 210, to k-tuples, and to the full 3D orbital geometry -- are under active development. We believe that the orbital framework provides the most natural setting in which the Goldbach problem can ultimately be resolved.

References

1 Hardy, G. H. and Littlewood, J. E. (1923). Some problems of partitio numerorum III: On the expression of a number as a sum of primes. Acta Mathematica, 44, 1-70.

2 Helfgott, H. A. (2013). Major arcs for Goldbach's theorem. arXiv:1305.2897.

3 Koch, H. von (1901). Sur la distribution des nombres premiers. Acta Mathematica, 24, 159-182.

4 Monfette, M. (2026). Loi p-e et Reformulation de Goldbach modulo 30. Unpublished research notes. [Github](#)

5 Monfette, M. (2026). Theoreme de Partition des 64 Tunnels de Goldbach dans $(\mathbb{Z}/30\mathbb{Z})^*$. Unpublished manuscript.[Github](#)

6 Monfette, M. (2026). Conjecture G Version 2: Universalite des 29 Orbites SG/XSG sur la roue R30. Research report with empirical validation to 210^8 .[Github](#)

7 Monfette, M. (2026). Station de Recherche Monfette Pro: Demonstration Officielle [Software and CSV dataset, 541 Goldbach pairs] [.Github](#)

8 Viggo Brun (1919). La serie $1/5+1/7+1/11+1/13+\dots$ est convergente. Christiania Videnskabs-Selskabs Skrifter.

Appendix: Reference Tables

A.1 The 15 Residue Classes and Their Active Tunnel Types


N mod 30	Active Types	# Active Tunnels	Goldbach Implication
0	B + C	8	SG+XSG or XSG+XSG pairs
2	C only	3	Requires XSG+XSG (PURE C)
4	A + C	3	SG+SG or XSG+XSG (no B)
6	B + C	6	SG+XSG or XSG+XSG pairs
8	C only	3	Requires XSG+XSG (PURE C)
10	A + B	4	SG+SG or SG+XSG (no C)
12	B only	6	Requires SG+XSG (PURE B)
14	C only	3	Requires XSG+XSG (PURE C)
16	A + B	3	SG+SG or SG+XSG (no C)
18	B + C	6	SG+XSG or XSG+XSG pairs

N mod 30	Active Types	# Active Tunnels	Goldbach Implication
20	C only	4	Requires XSG+XSG (PURE C)
22	A only	3	Requires SG+SG (PURE A, UNIQUE)
24	B + C	6	SG+XSG or XSG+XSG pairs
26	C only	3	Requires XSG+XSG (PURE C)
28	A + B	3	SG+SG or SG+XSG (no C)


A.2 The 8 Orbital Highways of R30

Residue r	Angle (degrees)	Class	Sophie Germain?	(2r+1) mod 30
1	12°	XSG	No	3 (not in R30)
7	84°	XSG	No	15 (not in R30)
11	132°	SG	Yes	23 (in R30)
13	156°	XSG	No	27 (not in R30)
17	204°	XSG	No	5 (not in R30)
19	228°	XSG	No	9 (not in R30)
23	276°	SG	Yes	17 (in R30)
29	348°	SG	Yes	29 (in R30)


A.3 Figure: R30 — The 8 Orbital Highways



A.4 Cube-Orbit Routing Flowchart**



A.5 Figure: A/B/C Tunnel Partition Simple version (SG vs XSG)



A.6 Full 8×8 Matrix (A/B/C classes)



Class	Color	Definition	Number
A	Red	<u>SG</u> × <u>SG</u>	9
B	Blue	<u>SG</u> × <u>XSG</u> ou <u>XSG</u> × <u>SG</u>	30
C	Green	<u>XSG</u> × <u>XSG</u>	25