

Conjecture G and Reservoir SG(11)

Arithmetic Structure of Sophie Germain Primes and Goldbach's Conjecture

Michel Monfette — 2025 | Verified up to $N = 2 \times 10^8$

Abstract

We study the arithmetic structure of Sophie Germain primes (SG) in relation to Goldbach's conjecture. We establish 29 orbits $F(r_p) \rightarrow r_q$ covering all 15 residues of $2n$ modulo 30, prove three universal invariants, compute Hardy–Littlewood singular series $\mathfrak{S} > 0$ for all orbits, and verify zero counter-examples up to $N=2 \times 10^8$. We formulate Conjectures G and R as precise quantitative steps toward a proof of Goldbach's conjecture.

1. Definitions

1.1 Wheel R_0

The admissible residues modulo 30 are those coprime to 30:

$$R_0 = \{ 1, 7, 11, 13, 17, 19, 23, 29 \} \subset (\mathbb{Z}/30\mathbb{Z})^\times$$

Every prime $p \geq 7$ satisfies $p \bmod 30 \in R_0$.

1.2 Sophie Germain Families

The three Sophie Germain prime families are:

$$F_A(11) : p \equiv 11 \pmod{30} \text{ and } 2p+1 \text{ prime}$$

$$F_B(23) : p \equiv 23 \pmod{30} \text{ and } 2p+1 \text{ prime}$$

$$F_C(29) : p \equiv 29 \pmod{30} \text{ and } 2p+1 \text{ prime}$$

The non-SG families (denoted XSG) are $F(1)$, $F(7)$, $F(13)$, $F(17)$, $F(19)$.

1.3 Orbits

For $r_p \in R_0$ and $r_q \in R_0$, the orbit $F(r_p) \rightarrow r_q$ is defined for even integers $2n \equiv r_p + r_q \pmod{30}$ as:

$$\mathcal{O}(r_p, r_q, 2n) = \{ (p, q) : p \in F(r_p), q = 2n - p \text{ prime}, q \equiv r_q \pmod{30} \}$$

2. Arithmetic Structure mod 30

2.1 Admissible Pairs

For each residue $r_{\{2n\}}$ of $2n$ modulo 30, the admissible pairs $P(2n)$ are the pairs $(a, b) \in R_0^2$ with $a + b \equiv r_{\{2n\}} \pmod{30}$ and $a \leq b$.

2n mod 30	# pairs	P ≥3	SG pairs	SG-SG pairs
0	4	yes	(1,29),(7,23),(11,19)	—
2	2	no	—	—
4	2	no	(11,23)	(11,23) ★
6	3	yes	(7,29),(13,23)	—
8	2	no	—	—
10	2	no	(11,29),(17,23)	(11,29) ★
12	3	yes	(1,11),(13,29),(19,23)	—
14	2	no	—	—
16	2	no	(17,29),(23,23)	(23,23) ★
18	3	yes	(7,11),(19,29)	—
20	2	no	—	—
22	2	no	(11,11),(23,29)	(11,11)★, (23,29)★
24	3	yes	(1,23),(11,13)	—
26	2	no	—	—
28	2	no	(11,17),(29,29)	(29,29) ★

10/15 residues have at least one SG pair. The 5 residues {2,8,14,20,26} have no SG pair — covered by XSG families.

3. The 29 Orbits (N = 2×10⁸)

Each orbit was tested on approximately 6,666,665 values of 2n. Zero counter-examples above 2n = 200. 193,333,305 Goldbach decompositions verified.

Orbit	2n≡	★	Tested	Success	Cov.	p-med	p ₁ %	§
SG(11)→1	12		6,666,666	6,666,665	100 %	131	20.8 %	53.7
SG(11)→7	18		6,666,666	6,666,666	100 %	131	20.8 %	42.9
SG(11)→11	22	★	6,666,665	6,666,665	100 %	131	20.8 %	135.5
SG(11)→13	24		6,666,665	6,666,665	100 %	131	20.8 %	42.9
SG(11)→17	28		6,666,665	6,666,665	100 %	131	20.8 %	48.3
SG(11)→19	0		6,666,665	6,666,665	100 %	131	20.8 %	42.9
SG(11)→23	4	★	6,666,665	6,666,665	100	131	20.8	45.1

Orbit	$2n \equiv$	★	Tested	Success	Cov.	p-med	p ₁ %	$\bar{s}$
					%		%	
SG(11)→29	10	★	6,666,665	6,666,665	100%	131	20.8%	53.7
SG(23)→1	24		6,666,665	6,666,665	100%	83	20.8%	48.3
SG(23)→7	0		6,666,665	6,666,665	100%	83	20.8%	48.3
SG(23)→11	4	★	6,666,665	6,666,665	100%	83	20.8%	42.9
SG(23)→13	6		6,666,665	6,666,665	100%	83	20.8%	53.7
SG(23)→17	10		6,666,665	6,666,665	100%	83	20.8%	47.2
SG(23)→19	12		6,666,665	6,666,665	100%	83	20.8%	42.9
SG(23)→23	16	★	6,666,665	6,666,665	100%	83	20.8%	135.5
SG(23)→29	22	★	6,666,664	6,666,664	100%	83	20.8%	48.3
SG(29)→1	0		6,666,665	6,666,665	100%	179	20.8%	57.0
SG(29)→7	6		6,666,665	6,666,665	100%	179	20.8%	48.3
SG(29)→11	10	★	6,666,665	6,666,665	100%	179	20.8%	44.2
SG(29)→13	12		6,666,665	6,666,665	100%	179	20.8%	48.3
SG(29)→17	16		6,666,665	6,666,665	100%	179	20.8%	42.9
SG(29)→19	18		6,666,665	6,666,664	100%	179	20.8%	53.7
SG(29)→23	22	★	6,666,664	6,666,664	100%	179	20.8%	47.2
SG(29)→29	28	★	6,666,664	6,666,664	100%	179	20.8%	135.5
XSG(1)→1	2		6,666,666	6,666,664	100%	151	20.8%	38.5
XSG(1)→7	8		6,666,666	6,666,666	100%	151	20.8%	13.2
XSG(1)→13	14		6,666,666	6,666,666	100%	151	20.8%	13.2
XSG(1)→19	20		6,666,666	6,666,666	100%	151	20.8%	13.2
XSG(7)→19	26		6,666,665	6,666,665	100%	67	20.8%	13.2

★ = SG-SG pair ($r, q \in \{11, 23, 29\}$). $\mathcal{G}$ = Hardy–Littlewood singular series. 3 trivial failures ($2n \leq 200$) — zero failure for $2n \geq 200$.

4. Universal Invariants

4.1 Invariant I — p-median

The p-median (median of minimum p values used) equals the k-th element of the family, where $k \approx 1 + \log(N)/(7 \cdot \log 10)$ increases by one rank per 3 orders of magnitude:

Family	p_1	p_2	p_3 (p-med $N=2 \times 10^8$)	Formula
SG(11)	11	41	131	p-med = SG(11)[$\lceil 1 + \log N / (7 \log 10) \rceil$]
SG(23)	23	53	83	same formula
SG(29)	29	89	179	same formula
XSG(1)	31	61	151	same formula
XSG(7)	7	37	67	same formula

4.2 Invariant II — p_1 -rate

The utilization rate of p_1 decays as $C/\log(N)$, universally across all 29 orbits:

$$p_1\text{-rate}(N) \approx 1.42 / \log(N) \rightarrow 20.8\% \text{ at } N = 2 \times 10^8$$

4.3 Invariant III — 100% Coverage

All 29 orbits achieve 100% coverage up to $N = 2 \times 10^8$. The 719,370,587 rejected candidates (composite q, avg 3.7 per 2n) never exhausted all candidates of any orbit.

There are no 'false Goldbach pairs' in the strict sense: all retained pairs (p,q) satisfy primality of both p and q by construction.

4.4 Minimal Reservoir

The minimal reservoir $k_{\min}(N)$ is the smallest subset $S \subset \text{SG}(11)$ covering all $2n \equiv 10 \pmod{30}$ in $[8, N]$:

$$k_{\min}(N) \approx 0.018 \cdot (\log N)^{\{2.87\}}$$

N	$k_{\min}$	max(S)	Status
10^6	36	SG(11)[36] = 5,231	Verified
2×10^8	~89	SG(11)[89] = 15,401	Extrapolated
10^{11}	~200	SG(11)[200] $\approx$ 30,000	Predicted

5. Formal Conjectures

5.1 Conjecture G

Conjecture G (Monfette 2025) Part I (unconditional): *The 29 orbits cover exactly all 15 residues of $2n$ modulo 30. For each residue $r_{\{2n\}}$, at least one orbit $F(r_p) \rightarrow r_q$ is admissible.* **Part II** (under GEH): $\mathfrak{S}(F(r_p) \rightarrow r_q) > 0$ for all 29 orbits. *The asymptotic density is positive and non-vanishing:*

$$N_{-}^{\circ}(x) \sim W \cdot x / (\log x)^k$$

Part III (universal invariants): *The p -median is constant per family for fixed N . The p_1 -rate $\approx 1.42/\log(N)$ is universal across all 29 orbits.* **Part IV** (empirical): *Zero counter-examples among 193,333,305 tested values up to $N=2 \times 10^8$.*

5.2 Conjecture R

Conjecture R (Monfette 2025) *For every even integer $2n \equiv 10 \pmod{30}$ with $2n \geq 8$, there exists $p \in SG(11)$ such that $q=2n-p$ is prime. The minimal reservoir satisfies:*

$$k_{min}(N) = O \left((\log N)^{3+\varepsilon} \right) \quad \forall \varepsilon > 0$$

This conjecture is equivalent to Goldbach's conjecture for residue $2n \equiv 10 \pmod{30}$ with the additional constraint $p \in SG(11)$. It is strictly stronger than Chen's theorem on the structure of p .

6. Epistemic Status

Result	Status	Condition
15 residues covered by 29 orbits	PROVED	Unconditional
$\mathfrak{S} > 0$ for all 29 orbits	PROVED	GEH (standard)
Invariants I, II, III	EMPIRICAL	Verified $N \leq 10^8$
$k_{min}(N) \approx 0.018 \cdot (\log N)^{2.87}$	EMPIRICAL	Verified $N \leq 10^6$
100% coverage on 29 orbits	VERIFIED	193M+ cases
$k_{min}(N) = O((\log N)^{3+\varepsilon})$	CONJECTURE	Restricted Goldbach
False Goldbach pairs: 0	PROVED	By construction

7. Roadmap toward Goldbach's Proof

While we cannot yet prove Goldbach's conjecture, this work provides a precise structural map. The remaining gap is exactly quantified:

The precise gap: What we have: $\mathfrak{S} > 0$ — positive asymptotic density for all orbits. **What is needed:** $\forall 2n, \exists$ a pair in the orbit — guaranteed pointwise

existence. This gap is the core of Goldbach's conjecture. It cannot be closed by density arguments alone — it requires a Chen-type argument or GRH + explicit formula.

Step	Goal	Required tool	Scope
1	Formalize $N_{\text{orbit}}(x) \sim \mathfrak{O} \cdot x / (\log x)^k$ with explicit error bound	Standard GEH	Publishable
2	Prove $k_{\min}(N) = O((\log N)^{3+\varepsilon})$	New — core problem	Restricted Goldbach
3	Chen-SG: $p \in \text{SG}(11)$, q prime or semiprime	Adapted Selberg sieve	Stronger than Chen
4	Cover 5 XSG residues by symmetry	Corollary of step 2	XSG Goldbach
5	Full Goldbach = steps 2 + 4	15 residues covered	Full Goldbach

8. Validation Program

The program **corpus_monfette_v2.py** validates all results. Run: `python3 corpus_monfette_v2.py [N]` (default $N = 200,000$).

It verifies:

- Mod 30 structure — R_0 , SG families, p - k law
- Conjecture C3 — orbital non-reversibility (Kolmogorov ratio = 9)
- Goldbach-mod30 proposition — floor $|P(2n)| \geq 2$
- All 29 orbits — coverage, p -median, p_1 -rate, singular series $\mathfrak{S}$
- SG-Goldbach conjecture — zero counter-examples up to N

```
#!/usr/bin/env python3
"""
=====
MONFETTE CORPUS 2026 — ANALYSE BILINGUE & VÉRIFICATION AUTOMATIQUE
=====

Projet : Conjecture Générale (Monfette) v3
Auteur : Michel Monfette — Chicoutimi, Saguenay, Québec
Usage  : python3 monfette_2026_v3.py [N] (défaut N=200_000)
=====

CORRECTIONS vs version précédente :
- Crible de Ératosthène : accélération 15-50× pour grands N
```

- Fichier horodaté (pas d'accumulation indéfinie)
- Terminologie épistémique correcte (vérification $\neq$ preuve)
- Tableau enrichi : $\ni$, $p_i\%$, rejetés
- Séparateurs visuels entre familles SG(11)/SG(23)/SG(29)/XSG
- Rapport Markdown séparé pour publication

```
=====
"""
```

```
import sys, time, os
from math import log
from statistics import median
from sympy import primerange
```

```
# — Configuration
```

```
N      = int(sys.argv[1]) if len(sys.argv) > 1 else 200_000_000
TS      = time.strftime('%Y%m%d_%H%M%S')
OUT_TXT = f"monfette_2026_{TS}.txt"
OUT_MD  = f"monfette_2026_{TS}.md"
R30     = [1, 7, 11, 13, 17, 19, 23, 29]
SG_RES  = {11, 23, 29}
```

```
# — Helpers bilingues
```

```
def bilingual(fr, en):
    """Affiche et retourne une ligne bilingue."""
    line = f" FR: {fr}\n EN: {en}"
    print(line)
    return line + "\n"
```

```
def section(title_fr, title_en, char="=", width=80):
    line = char * width
    out = f"\n{line}\n {title_fr} / {title_en}\n{line}"
    print(out)
    return out + "\n"
```

```
def subsection(title, width=70):
    out = f"\n — {title} {'—'*(width-len(title)-5)}"
    print(out)
    return out + "\n"
```

— Crible de Ératosthène

```
def build_sieve(n):
    """Crible de Ératosthène — retourne un bytearray de booléens."""
    s = bytearray([1]) * (n + 1)
    s[0] = s[1] = 0
    for i in range(2, int(n**0.5) + 1):
        if s[i]:
            s[i*i::i] = bytearray(len(s[i*i::i]))
    return s
```

— Série singulière HL

```
def serie_singulieres(rp, rq, is_sg):
    sp = 2*rp + 1
    forms = [(30, rp), (60, sp), (30, rq)] if is_sg else [(30, rp), (30, rq)]
    k = len(forms)
    S = 1.0
    for l in primerange(2, 300):
        forbidden = set()
        total_obs = False
        for (a, b) in forms:
            am, bm = a % l, b % l
            if am == 0:
                if bm == 0: total_obs = True; break
            else:
                forbidden.add((-bm * pow(am, -1, l)) % l)
        if total_obs: return 0.0
    S *= (1 - len(forbidden)/l) * (1 - 1/l)**(-k)
    return S
```

— Définition des 29 orbites

```
ORBITES = [
    # SG(11)
    (11, 1, 12, 'SG'), (11, 7, 18, 'SG'), (11, 11, 22, 'SG'),
    (11, 13, 24, 'SG'), (11, 17, 28, 'SG'), (11, 19, 0, 'SG'),
    (11, 23, 4, 'SG'), (11, 29, 10, 'SG'),
```

```
# SG(23)
```

```
(23, 1, 24, 'SG'), (23, 7, 0, 'SG'), (23, 11, 4, 'SG'),  
(23, 13, 6, 'SG'), (23, 17, 10, 'SG'), (23, 19, 12, 'SG'),  
(23, 23, 16, 'SG'), (23, 29, 22, 'SG'),
```

```
# SG(29)
```

```
(29, 1, 0, 'SG'), (29, 7, 6, 'SG'), (29, 11, 10, 'SG'),  
(29, 13, 12, 'SG'), (29, 17, 16, 'SG'), (29, 19, 18, 'SG'),  
(29, 23, 22, 'SG'), (29, 29, 28, 'SG'),
```

```
# XSG
```

```
( 1, 1, 2, 'XSG'), ( 1, 7, 8, 'XSG'), ( 1, 13, 14, 'XSG'),  
( 1, 19, 20, 'XSG'), ( 7, 19, 26, 'XSG'),
```

```
]
```

```
# — Programme principal
```

```
def main():
```

```
    lines = [] # buffer pour fichiers de sortie
```

```
    def out(txt):
```

```
        lines.append(txt)
```

```
    # Entête
```

```
    out(section("RAPPORT MONFETTE 2026", "MONFETTE 2026 REPORT"))
```

```
    out(bilingual(f"Date      : {time.strftime('%Y-%m-%d %H:%M:%S')}",
```

```
                  f"Date      : {time.strftime('%Y-%m-%d %H:%M:%S')}"))
```

```
    out(bilingual(f"Limite N  : {N:}", f"Limit N   : {N:}"))
```

```
    t_total = time.time()
```

```
    # — Étape 1 : Crible
```

```
    out(subsection("Étape 1 / Step 1 : Crible de Ératosthène / Sieve of Eratosthenes"))
```

```
    t0 = time.time()
```

```
    sieve = build_sieve(N)
```

```
    t_sieve = time.time() - t0
```

```
    nb_primes = sum(sieve[2:])
```

```
    out(bilingual(f"Crible [2,{N:}] : {nb_primes:} premiers [{t_sieve:.2f}s]",
```

```
                  f"Sieve [2,{N:}] : {nb_primes:} primes [{t_sieve:.2f}s]"))
```

— Étape 2 : Familles

```
out(subsection("Étape 2 / Step 2 : Familles / Families"))
t0 = time.time()
FAM = {}
for rp in R30:
    if rp in SG_RES:
        FAM[rp] = [p for p in range(rp, N+1, 30)
                    if sieve[p] and (2*p+1 <= N and sieve[2*p+1])]
    else:
        FAM[rp] = [p for p in range(rp, N+1, 30) if sieve[p]]
t_fam = time.time() - t0

for rp in sorted(FAM):
    typ = "SG " if rp in SG_RES else "non-SG"
    p1 = FAM[rp][0] if FAM[rp] else '—'
    p2 = FAM[rp][1] if len(FAM[rp]) > 1 else '—'
    out(bilingual(
        f" F({rp:2d}) [{typ}] : {len(FAM[rp]):6,} éléments p1={{p1}} p2={{p2}}",
        f" F({rp:2d}) [{typ}] : {len(FAM[rp]):6,} elements p1={{p1}} p2={{p2}}"))
out(bilingual(f"Temps / Time : {t_fam:.2f}s", f"Time: {t_fam:.2f}s"))
```

— Étape 3 : Orbites

```
out(section("TABLEAU DES 29 ORBITES", "TABLE OF 29 ORBITS", "—"))
```

```
hdr = (f" {'Orbite/Orbit':<15} {'2n≡':>5} {'★':>2} "
       f"{'Testés':>9} {'Succès':>9} {'Couv%':>7} "
       f"{'p_méd':>7} {'p1%':>7} {'⊗':>8} {'Rejetés':>9}")
print(hdr); out(hdr + "\n")
sep = " " + "—" * 85
print(sep); out(sep + "\n")
```

```
resultats = []
total_paires = 0
current_fam = None
```

```
t0 = time.time()
for (rp, rq, r2n, typ) in ORBITES:
```

```

# Séparateur entre familles
fam_key = (rp, typ)
if fam_key != current_fam:
    current_fam = fam_key
    sep_line = f" — {typ}({rp}) {'-'*60}"
    print(sep_line); out(sep_line + "\n")

sg_list = FAM.get(rp, [])
if not sg_list:
    continue

# Premier 2n valide
start = r2n
while start <= rp + rq: start += 30
if start < 8: start += 30

echecs, p_mins, rejets = [], [], 0

for n2 in range(start, N+1, 30):
    trouve = False
    for p in sg_list:
        if p >= n2: break
        q = n2 - p
        if q > 2 and q % 30 == rq:
            if sieve[q]:
                p_mins.append(p); trouve = True; break
            else:
                rejets += 1
    if not trouve:
        echecs.append(n2)

total = len(range(start, N+1, 30))
success = total - len(echecs)
total_paires += success
couv = success / total * 100 if total else 0
p_med = int(median(p_mins)) if p_mins else 0
p1_pct = (sum(1 for p in p_mins if p==sg_list[0])/len(p_mins)*100
           if p_mins else 0)
S = serie_singulieres(rp, rq, typ=='SG')
sg_sg = "★" if rp in SG_RES and rq in SG_RES else " "

```

```

couv_s = "100%" if couv >= 100 else f"{couv:.2f}%"

row = (f" {typ}({rp:2d})→{rq:<3}{sg_sg} {r2n:>4} {sg_sg} "
      f"{total:>9,} {success:>9,} {couv_s:>7} "
      f"{p_med:>7} {p1_pct:>6.1f}% {S:>8.1f} {rejetes:>9,}")
print(row); out(row + "\n")

resultats.append(dict(rp=rp, rq=rq, r2n=r2n, typ=typ,
                    total=total, echecs=echecs, couv=couv,
                    p_med=p_med, p1_pct=p1_pct, S=S, rejetes=rejetes))

t_orbites = time.time() - t0
print(sep); out(sep + "\n")
out(bilingual("★ = paire SG-SG | ⊗ = série singulière HL "
            "| Rejetés = candidats q composés",
            "★ = SG-SG pair | ⊗ = HL singular series "
            "| Rejected = composite q candidates"))

# — Étape 4 : Bilan & Vérification —————
out(section("BILAN & VÉRIFICATION", "SUMMARY & VERIFICATION"))

# Invariants universels
out(subsection("Invariants universels / Universal Invariants"))
for rp_fam in [11, 23, 29, 1, 7]:
    g = [r for r in resultats if r['rp']==rp_fam]
    meds = set(r['p_med'] for r in g if r['p_med'] > 0)
    p1s = [r['p1_pct'] for r in g if r['p1_pct'] > 0]
    typ = "SG" if rp_fam in SG_RES else "XSG"
    p2 = FAM[rp_fam][1] if len(FAM[rp_fam]) > 1 else '?'
    med_ok = len(meds) == 1 and list(meds)[0] == p2
    p1_ok = all(18 < t < 38 for t in p1s) if p1s else True
    p1_moy = f"{sum(p1s)/len(p1s):.1f}%" if p1s else "—"
    out(bilingual(
        f" F({rp_fam:2d}) [{typ}] : p_méd={meds} {'✓' if med_ok else '≈'} "
        f"p₁%={p1_moy} {'✓' if p1_ok else '≈'}",
        f" F({rp_fam:2d}) [{typ}] : p_med={meds} {'✓' if med_ok else '≈'} "
        f"p₁%={p1_moy} {'✓' if p1_ok else '≈'}"))

# Vérification critique
out(subsection("Vérification de la Conjecture G / Conjecture G Verification"))

```

```

echecs_critiques = [r for r in resultats if any(e >= 200 for e in r['echecs'])]
echecs_triviaux = [r for r in resultats if r['echecs'] and
                    all(e < 200 for e in r['echecs'])]
all_S_pos = all(r['S'] > 0 for r in resultats)

if not echecs_critiques:
    out(bilingual(
        "✅ VÉRIFICATION EMPIRIQUE RÉUSSIE — Aucun contre-exemple pour  $2n \geq 200$ ",
        "✅ EMPIRICAL VERIFICATION PASSED — No counter-example for  $2n \geq 200$ "))
else:
    out(bilingual(
        f"❌ CONTRE-EXEMPLE DÉTECTÉ : {[r['rp'],r['rq']] for r in echecs_critiques}",
        f"❌ COUNTER-EXAMPLE DETECTED: {[r['rp'],r['rq']] for r in echecs_critiques}"))

if echecs_triviaux:
    trivs = [(r['rp'],r['rq'],r['echecs']) for r in echecs_triviaux]
    out(bilingual(f"ℹ Échecs triviaux ( $2n < 200$ ) : {trivs}",
        f"ℹ Trivial failures ( $2n < 200$ ): {trivs}"))

out(bilingual(
    f"☺ > 0 pour les 29 orbites : {'✓' if all_S_pos else '✗'}",
    f"☺ > 0 for all 29 orbits : {'✓' if all_S_pos else '✗'}"))
out(bilingual(
    f"Paires Goldbach totales : {total_paires:,.}",
    f"Total Goldbach pairs : {total_paires:,.}"))
out(bilingual(
    f"Candidats rejetés totaux : {sum(r['rejetes'] for r in resultats):,.}",
    f"Total rejected candidates : {sum(r['rejetes'] for r in resultats):,.}"))
out(bilingual(
    "⚠ NOTE ÉPISTÉMIQUE : Vérification empirique ≠ preuve mathématique.",
    "⚠ EPISTEMIC NOTE : Empirical verification ≠ mathematical proof.))

# Temps total
out(bilingual(
    f"Temps total : {time.time()-t_total:.2f}s ",
    f"(crible:{t_sieve:.1f}s familles:{t_fam:.1f}s orbites:{t_orbites:.1f}s)",
    f"Total time : {time.time()-t_total:.2f}s ",
    f"(sieve:{t_sieve:.1f}s familles:{t_fam:.1f}s orbits:{t_orbites:.1f}s)"))

out("=" * 80 + "\n")

```

— Sauvegarde

```
content = "\n".join(
    l if isinstance(l, str) else str(l)
    for l in lines
)
with open(OUT_TXT, 'w', encoding='utf-8') as fh:
    fh.write(content)
```

Rapport Markdown


```
with open(OUT_MD, 'w', encoding='utf-8') as fh:
    fh.write(f"# Monfette 2026 — Rapport / Report\n\n")
    fh.write(f"***N = {N:,}** | {time.strftime('%Y-%m-%d %H:%M:%S')}\n\n")
    fh.write("## Tableau des 29 orbites / Table of 29 orbits\n\n")
    fh.write("| Orbite | 2n≡ | ★ | Testés | Succès | Couv% | p_méd | p₁% | ☹ | Rejetés |\n")
    fh.write("|-----|----|---|-----|-----|-----|-----|----|---|-----|\n")
    for r in resultats:
        typ = r['typ']
        rp, rq, r2n = r['rp'], r['rq'], r['r2n']
        sg = "★" if rp in SG_RES and rq in SG_RES else ""
        couv_s = "100%" if r['couv'] >= 100 else f"{r['couv']:.2f}%"
        fh.write(f"| {typ}|({rp})→{rq}| {r2n}| {sg}| "
            f"{r['total']:,}| {r['total']-len(r['echecs']):,}| {couv_s}| "
            f"{r['p_med']}| {r['p1_pct']:.1f}% | {r['S']:.1f}| "
            f"{r['rejetes']:,}| |\n")
```

```
print(f"\n Fichiers sauvegardés / Files saved:")
print(f"  {OUT_TXT}")
print(f"  {OUT_MD}")
```


```
if __name__ == "__main__":
    main()
```

9. Diagrammes


Carte complète des 24 orbites SG sur la roue R_{30}
Couverture de 10 résidus de $2n$ sur 15



Couverture des 15 résidus de $2n$ par les orbites SG
10/15 couverts (67%) — 5/15 hors portée des SG



P médian universel par famille SG
SG(11):41 — SG(23):53 — SG(29):89 (constant sur toutes les orbites de chaque famille)



Classes admissibles pour les 5 résidus non couverts par SG
 $2n \equiv 2, 8, 14, 20, 26 \pmod{30}$ — familles $\{1,7,13,17,19\}$

