



ANSIBLE

ANSIBLE



TABLE OF CONTENT



- Adhoc Commands
- Ansible Modules
- Colour Pattern
- Ansible Playbook
- Ansible Tags
- Ansible Variables
- Static variables
- Dynamic variables
- Ansible Handlers
- Ansible Vault
- Ansible Roles
- Ansible Galaxy
- Debug Module
- Ansible LookUps
- Ansible Conditions
- Ansible Loops

What Is Ansible



- Ansible is an open-source automation tool used for configuration management, application deployment, and task automation.
- It is also called as configuration management tool.
- Invented by Micheal Dehaaan in 2012.
- Later it was taken by Redhat.
- It has both free and paid versions.
- It is platform Independent.
- Ansible works with YAML Language.

ANSIBLE ARCHITECTURE



- **Control Nodes:** It is used to communicate with worker nodes and install packages.
- **Worker Nodes:** They will take commands from the Ansible server and will work accordingly.
- **Playbook:** Playbook will contains the code which is used to perform actions.
- **Inventory File:** It will contains the information about the worker nodes.

ANSIBLE SETUP



A N S I B L E

- Create three servers, one is an Ansible server and the remaining are worker nodes.
- create ssh-keygen and share with the worker nodes.
- `yum -y install ansible-core` (to install package on ansible server only)
- `vi/etc/ssh/sshd_config` (38th line uncomment, 63rd line change into no to yes)
- `vim /etc/ansible/hosts` (to make inventory list)
- `<195.175.8.103>`
- `<195.175.8.102>` (mention ip of worker nodes in hosts file)
- `:wq` (save and quit hosts file)

ADHOC COMMANDS

- `ansible all -a "yum -y install git"`
- `ansible all -a "systemctl status git"`
- `ansible all -a "systemctl start httpd"`
- `ansible all -a "systemctl enable httpd"`
- `ansible all -a "touch file1"`
- `ansible all -a "mkdir dir1"`
- `ansible all -a "useradd harsha"`
- `ansible all -a "userdel harsh"`
- `ansible all -a "cat /etc/group"`



A N S I B L E

ANSIBLE MODULES



ANSIBLE

what is Module?

An Ansible module is a reusable, standalone script used to perform specific tasks in Ansible, such as managing files, installing packages, or configuring systems.

ANSIBLE MODULES



- `ansible all -m file -a "path=/root/file1 state=touch"`
- `ansible all -m file -a "path=/tmp/dir state=directory"`
- `ansible all -m user -a "name=Harsh state=present"`
- `ansible all -m user -a "name=Harsh state=absent"`
- `ansible all -m yum -a "name=httpd state=present"`
- `ansible all -m service -a "name=httpd state=started"`
- `ansible all -m setup -a | grep -i CPUS & mem`
- `ansible all -m service -a "name=httpd enabled=yes"`
- `ansible all -m copy -a "src=/root/file1 dest=/tmp"`
- `ansible all -m lineinfile -a "path=/etc/test1 line=anyline create=yes"`
- `ansible all -m lineinfile -a "path=/etc/test1 regexp=anyline state=absent"`

ANSIBLE PLAYBOOK



ANSIBLE

- Playbook is a collection of Modules.
- In Playbook, we can execute multiple commands at the same time.
- The playbook is written in YAML Language.
- YAML: Yet Another Markup Language.
- YAML is a human-readable language.
- YAML is syntax-based.

ANSIBLE PLAYBOOK



ANSIBLE

```
> vim harsha.yml
```

```
---
```

```
- hosts: all
```

```
  tasks:
```

```
    - name: installing httpd
```

```
      yum: name=httpd state=present
```

```
    - name: starting httpd
```

```
      service: name=httpd state=started
```

```
:wq
```

```
> ansible-playbook harsha.yml
```

ANSIBLE PLAYBOOK



ANSIBLE

```
> vim harsha.yml
```

```
---
```

```
- hosts: all
```

```
  tasks:
```

```
    - name: installing httpd
```

```
      yum: name=httpd state=absent
```

```
    - name: add user
```

```
      user: name=harsha state=absent
```

```
:wq (sed -i "s/present/absent/g" harsha.yml) it changes from present to  
absent
```

ANSIBLE TAGS



ANSIBLE

Ansible tags are used to execute a specific task, or they can be used to skip a specific task.

ANSIBLE TAGS TYPE:

- SINGLE TAGS
- SKIP-TAGS

ANSIBLE TAGS



ANSIBLE

```
> vim my-playbook.yml
```

```
---
```

```
- hosts: all
```

```
  tasks:
```

```
    - name: installing docker
```

```
      yum: name=docker state=present
```

```
      tags: a
```

```
    - name: installing docker
```

```
      yum: name=docker state=present
```

```
      tags: b
```

```
> ansible-playbook --tags a my-playbook.yml (only task a will execute)
```

```
> ansible-playbook --skip-tags b my-playbook.yml ( task b will skip)
```

ANSIBLE VARIABLES



ANSIBLE

Static Variables

Static variables are those that are defined in the playbook or inventory files and do not change during playbook execution.

Dynamic Variables:

Dynamic variables in Ansible are variables whose values are determined during the execution of a playbook, based on the current environment, context, or specific conditions.

ANSIBLE VARIABLES (STATIC)



ANSIBLE

```
> vim harsha.yml
```

```
---
```

```
- hosts: all
```

```
  vars:
```

```
    a: git
```

```
    b: maven
```

```
    c: docker
```

```
    d: httpd
```

```
  tasks:
```

```
    - name: installing git
```

```
      yum: name={{a}} state=present
```

```
    - name: installing maven
```

```
      yum: name={{b}} state=present
```

```
    - name: installing Docker
```

```
      yum: name={{c}} state=present
```

```
    - name: installing httpd
```

```
      yum: name={{d}} state=present
```

```
> ansible-playbook harsha.yml
```

ANSIBLE VARIABLES

(DYNAMIC)



```
> vim harsha.yml
---
- hosts: all
  vars:
    - name: adding user
      user: name={{a}} state=present

:wq
> ansible-playbook harsha.yml --extra-vars "a=git"
```


ANSIBLE HANDLERS



ANSIBLE

Ansible handlers are special tasks in Ansible that are triggered by other tasks using the notify directive. Handlers are used to perform actions only when a change occurs in the tasks that notify them. This is useful for tasks that should only run when something specific has changed, like restarting a service after a configuration file has been updated.

ANSIBLE HANDLERS



ANSIBLE

```
> vim harsha.yml
```

```
---
```

```
- hosts: all
```

```
  tasks:
```

```
    - name: installing httpd
```

```
      yum: name=httpd state=present
```

```
      notify: installing httpd
```

```
  handlers:
```

```
    - name: starting httpd
```

```
      service: name=httpd state=started
```

```
:wq
```

```
> ansible-playbook harsha.yml
```

ANSIBLE LOOPS



ANSIBLE

Ansible loops allow you to repeat a task multiple times with different inputs. This is useful when you want to perform the same action on multiple items without having to write the task multiple times.

ANSIBLE LOOPS



ANSIBLE

```
---
- hosts: all
  tasks:
    - name: adding users
      user: name={{items}} state=present
      with_items:
        - hardik
        - virat
        - rohit
        - dhoni
        - sky

:wq
> ansible all harsha.yml
```

ANSIBLE DEBUG MODULE



ANSIBLE

The debug module in Ansible is used to display information, variables, or messages during the execution of a playbook. It is a useful tool for troubleshooting, verifying data, and providing context or feedback within a playbook.

ANSIBLE DEBUG MODULE



ANSIBLE

- hosts: all

- tasks:

- name: printing worker node information

- debug:

- msg: "The worker node name is: {{ansible_hostname}} , The total
memory is: {{ansible_memtotal_mb}} , Free memory is:
{{ansible_memfree_mb}} , The flavour is: {{ansible_os_family}} , Total no. of
cpu's: {{ansible_processor_vcpus}}"

- :wq

- > ansible all my-playbook.yml

ANSIBLE VAULT



ANSIBLE

Ansible Vault is a feature within Ansible that allows you to securely store and manage sensitive data, such as passwords, API keys, and other confidential information, by encrypting files and variables. This ensures that sensitive information is not exposed in plain text within your playbooks or version control systems.

ANSIBLE VAULT



ANSIBLE

- > `ansible-vault create file.txt` (To create a Vault)
- > `ansible -vault edit file.txt` (To edit a Vault)
- > `ansible-vault encrypt file.txt` (To encrypt the Content)
- > `ansible-vault decrypt file.txt` (To decrypt the Content)
- > `ansible-vault rekey file.txt` (to change the password for a vault)
- > `ansible-vault view file.txt` (To show the content without decrypt the file)

ANSIBLE CONDITIONS



ANSIBLE

Ansible conditions allow you to control the execution of tasks based on specific criteria. By using conditions, you can make your playbooks more dynamic and flexible, ensuring that tasks are only executed when certain conditions are met.

ANSIBLE CONDITIONS



ANSIBLE

```
---  
- hosts: all  
  tasks:  
    - name: installing git on redhat  
      yum: name=git state=present  
      when: ansible_os_family == "RedHat"  
  
    - name: installing git on ubuntu  
      apt: name=git state=present  
      when: ansible_os_family == "Debian"  
  
:wq  
> ansible all my-playbook.yml
```

ANSIBLE GALAXY



ANSIBLE

Ansible Galaxy is a community hub for discovering, sharing, and downloading Ansible roles and collections. It serves as a central repository where users can find reusable Ansible content created by others, as well as share their own.

ANSIBLE GALAXY



ANSIBLE

- > ansible-galaxy (search on goggle)
- > ansible-galaxy search httpd (to search package from ansible galaxy)
- > ansible-galaxy install username-tomcat (to install role)
- > ansible-galaxy search --author <username> (to see all role by a specific user)

ANSIBLE ROLES



- Ansible roles are used to divide the playbook into directory structure.
- We can organize the playbook through roles.
- We can reduce the length of playbook using roles.
- We can encapsulate the data

ANSIBLE ROLES



ANSIBLE

```
> mkdir -p roles/one/tasks
> vim roles/one/tasks/main.yml
- name: adding user
  user: name=hardik state=present
:wq
> vim harsha.yml
- hosts: all
  roles:
    - one
:wq
> vim roles/two/tasks/main.yml
- name: installing pkg
  yum: name=httpd state=present
:wq
> vim harsha.yml
- hosts:
  roles:
    - one
    - two
```

ANSIBLE LOOKUPS



ANSIBLE

Ansible Lookups are a feature that allows you to retrieve data from external sources during the execution of a playbook. They are used to fetch information from files, databases, APIs, or other sources and make it available within your playbooks.

ANSIBLE LOOKUPS



ANSIBLE

```
> vim file.txt
```

```
Hello, My name is hardik.
```

```
> vim harsha.yml
```

```
---
```

```
- hosts: all
```

```
vars:
```

```
  a: "{{ lookup ( 'file' , '/root/file.txt' ) }}"
```

```
tasks:
```

```
  - debug:
```

```
    msg: "welcome all {{a}}"
```

```
> vim harsha.yml
```


