















Bill of Materials

Designator	Description	Value	Q
C1	Electrolytic capacitor 16v/50v	220µF	1
C2	Ceramic capacitor	100nF	1
P1	Pin Header, THT, pitch 2.54mm, Dual Row, Angled, 16p	16p	1
P2	Socket Header, THT, pitch 2.54mm, Dual Row, Angled, 10	16p	1
Р3	Pin Header, THT, pitch 2.54mm, Dual Row, Angled, 32p	32p	1
P4	Socket Header, THT, pitch 2.54mm, Dual Row, Angled, 32	32p	1
P5, P9	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical,	32p	2
P8, P12	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical,	16p	2
PWR_JACK1	DC Power Jack, 2 mm Center Pin, 3 Position, THT Right	Angle	1
RN1, RN2	Resistor array 8 elements,9 pins	1K	2
SW1	Mini slide switch 2 pos, 3 pins	3р	1
U1	5v/1-1.5A Voltage Regulator		1



Assembly List

Designator	Description	Value		
C1	Electrolytic capacitor 16v/50v	220µF		
C2	Ceramic capacitor	100nF		
P1	Pin Header, THT, pitch 2.54mm, Dual Row, Angled, 16p			
P2	Socket Header, THT, pitch 2.54mm, Dual Row, Angled, 16p	16p		
Р3	Pin Header, THT, pitch 2.54mm, Dual Row, Angled, 32p	32p		
P4	Socket Header, THT, pitch 2.54mm, Dual Row, Angled, 32p	32p		
P5	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 32x	32p		
P8	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 16p	16p		
P9	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 32x	32p		
P12	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 16p	16p		
PWR_JACK1	DC Power Jack, 2 mm Center Pin, 3 Position, THT Right Angl	е		
RN1	Resistor array 8 elements,9 pins	1K		
RN2	Resistor array 8 elements,9 pins	1K		
SW1	Mini slide switch 2 pos, 3 pins	3р		
U1	5v/1-1.5A Voltage Regulator			