















Bill of Materials

Designator	Description	Value	Q
C1	Electrolytic capacitor 16v/50v	0.47μF	1
C2	Ceramic capacitor	100nF	1
P1	Pin Header, THT, pitch 2.54mm, Dual Row, Angled, 16p	16p	1
P2	Socket Header, THT, pitch 2.54mm, Dual Row, Angled, 16	16p	1
Р3	Pin Header, THT, pitch 2.54mm, Dual Row, Angled, 32p	32p	1
P4	Socket Header, THT, pitch 2.54mm, Dual Row, Angled, 32	32p	1
P5, P9	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical,	32p	2
P8, P12	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical,	16p	2
PWR_JACK1	DC Power Jack, 2 mm Center Pin, 3 Position, THT Right	Angle	1
SW1	Mini slide switch 2 pos, 3 pins	3р	1
U1	5v/1-1.5A Voltage Regulator		1



Assembly List

Designator	Description	Value
C1	Electrolytic capacitor 16v/50v	0.47µF
C2	Ceramic capacitor	100nF
P1	Pin Header, THT, pitch 2.54mm, Dual Row, Angled, 16p	16p
P2	Socket Header, THT, pitch 2.54mm, Dual Row, Angled, 16p	16p
Р3	Pin Header, THT, pitch 2.54mm, Dual Row, Angled, 32p	32p
P4	Socket Header, THT, pitch 2.54mm, Dual Row, Angled, 32p	32p
P5	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 32r	32p
Р8	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 16r	16p
Р9	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 32r	32p
P12	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 16r	16p
PWR_JACK1	DC Power Jack, 2 mm Center Pin, 3 Position, THT Right Angl	е
SW1	Mini slide switch 2 pos, 3 pins	3р
U1	5v/1-1.5A Voltage Regulator	