




## **Bill of Materials**

Designator	Description	Value	Q
C1	Electrolytic capacitor 16v/50v	10µF	1
C2, C3, C4, C5	Ceramic or tantalum capacitor	100nF	4
IC1, IC2	4-bit D-Type Register with 3 state outputs	74LS173	2
IC3	2-Line to 1 Line data selector 4-Bits	74LS157	1
IC4	4-Bits 2-Line to 1 Line data selector	74LS157	1
P1	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 16p		1
P2	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 32p		1
P3	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 8p		1
P4	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 24p		1
R1	Resistor axial	330Ω	1
RN1, RN3	Resistor array 8 elements,9 pins	330Ω	2
SW1	DIP switch 8 positions		1
SW2	Mini slide switch 2 pos, 3 pins		1



## **Assembly List**

Desig.	Description	Value
C1	Electrolytic capacitor 16v/50v	10µF
C2	Ceramic or tantalum capacitor	100nF
C3	Ceramic or tantalum capacitor	100nF
C4	Ceramic or tantalum capacitor	100nF
C5	Ceramic or tantalum capacitor	100nF
IC1	4-bit D-Type Register with 3 state outputs	74LS173
IC2	4-bit D-Type Register with 3 state outputs	74LS173
IC3	2-Line to 1 Line data selector 4-Bits	74LS157
IC4	4-Bits 2-Line to 1 Line data selector	74LS157
P1	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 16p	
P2	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 32p	
P3	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 8p	
P4	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 24p	
R1	Resistor axial	330Ω
RN1	Resistor array 8 elements,9 pins	330Ω
RN3	Resistor array 8 elements,9 pins	330Ω
SW1	DIP switch 8 positions	
SW2	Mini slide switch 2 pos, 3 pins	