



P2


Pin	Signal
1	HLT
2	SU
3	EO
4	AI
5	AO
6	BI
7	BO
8	CI
9	CO
10	BI
11	IO
12	II
13	RST
14	FI
15	PO
16	PE
17	UN
18	OI
19	RO
20	RI
21	SO
22	SI
23	PI
24	MI
25	FC
26	FN
27	FV
28	FZ
29	CLK
30	
31	VCC
32	/CLK

VCC **GND**




△ Cascade goes from IC2 to IC3 through pin TC (Terminal Count Output) to pin CET/CEP (10) enabling a count step.

Count operation goes from QA to QD, A pin is less significant bit input.




Pin DIR to GND means data flow from B >> A when a low PO signal comes.




PE control signal is not related to /PE pin of the IC

PI is the control signal to load the current value from the DATABUS to the counters.



Decoupling Capacitors










Project: myCPU Program Counter 8b


Revision: 14


Date: 09/01/2023


Author: Rafa Hernández





myCPU Program Counter 8b. Rev: 14













Bill of Materials

Designator	Description	Value	Q
C1	Electrolytic capacitor 16v/50v	10μF	1
C3, C4, C5	Ceramic or tantalum capacitor	100nF	3
IC1	Non inverting bus transceiver	74LS245	1
IC2, IC3	4-Bit sync counter	74LS161	2
P1	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical	16p	1
P2	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical	32p	1
P3	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical	24p	1
RN1	Resistor array 8 elements, 9 pins	680Ω	1



Assembly List

Designator	Description	Value
C1	Electrolytic capacitor 16v/50v	10 μ F
C3	Ceramic or tantalum capacitor	100nF
C4	Ceramic or tantalum capacitor	100nF
C5	Ceramic or tantalum capacitor	100nF
IC1	Non inverting bus transceiver	74LS245
IC2	4-Bit sync counter	74LS161
IC3	4-Bit sync counter	74LS161
P1	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical	16p
P2	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical	32p
P3	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical	24p
RN1	Resistor array 8 elements, 9 pins	680 Ω