




Control BUS Connector




Data BUS Connector




Programming Mode Switch






Output Connector




Address OUTPUT Connector



A 4 bits MAR version uses only less significative 4 bits of the data exposed on the data BUS.



Decoupling Capacitors





Project: myCPU MAR Module 4 bits

Revision: 2

Date: 20/06/2022

Author: Rafa Hernández







Bill of Materials

Designator	Description	Value	Q
C1	Electrolytic capacitor 16v/50v	10 μ F	1
C2, C3	Ceramic or tantalum capacitor	100nF	2
IC2	4-bit D-Type Register with 3 state outputs	74LS173	1
IC4	4-Bits 2-Line to 1 Line data selector	74LS157	1
P1	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 16p	16p	1
P2	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 32p	32p	1
P3	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 8p	8p	1
P4	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 24p	24p	1
R1	Resistor axial	220 Ω	1
RN1	Resistor array 8 elements,9 pins	330 Ω	1
SW1	DIP switch 4 positions	4 pos	1
SW2	Mini slide switch 2 pos, 3 pins		1



Assembly List

Desig.	Description	Value
C1	Electrolytic capacitor 16v/50v	10 μ F
C2	Ceramic or tantalum capacitor	100nF
C3	Ceramic or tantalum capacitor	100nF
IC2	4-bit D-Type Register with 3 state outputs	74LS173
IC4	4-Bits 2-Line to 1 Line data selector	74LS157
P1	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 16p	16p
P2	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 32p	32p
P3	Pin Header, THT, pitch 2.54mm, Dual Row, Vertical, 8p	8p
P4	Socket Header, THT, pitch 2.54mm, Dual Row, Vertical, 24p	24p
R1	Resistor axial	220 Ω
RN1	Resistor array 8 elements,9 pins	330 Ω
SW1	DIP switch 4 positions	4 pos
SW2	Mini slide switch 2 pos, 3 pins	