

EasyPay API Integration Guide

Version: 1.0.2

Last Updated: January 16, 2026

API Provider: MyMoolah Treasury Platform

Integration Partner: EasyPay South Africa


Status:  Production Ready

Table of Contents

1. [Executive Summary](#)
 2. [Quick Start Guide](#)
 3. [Authentication & Security](#)
 4. [API Endpoints](#)
 5. [Data Models](#)
 6. [Error Handling](#)
 7. [Idempotency](#)
 8. [Testing Guide \(UAT\)](#)
 9. [Production Deployment](#)
 10. [Reconciliation](#)
 11. [Support & SLAs](#)
 12. [Appendices](#)
-

1. Executive Summary

1.1 Overview

MyMoolah Treasury Platform provides two core EasyPay integration services:

1. **Top-up @ EasyPay:** Enables MyMoolah users to deposit cash into their wallets at any EasyPay merchant location
2. **Cash-out @ EasyPay:** Enables MyMoolah users to withdraw cash from their wallets at any EasyPay merchant location

1.2 Integration Architecture

```
sequenceDiagram
    participant User as MyMoolah User
    participant App as MM Mobile App
    participant API as MM Backend API
    participant EP as EasyPay Terminal
    participant EPBackend as EasyPay Backend

    Note over User,EPBackend: Top-up @ EasyPay Flow
    User->>App: Request Top-up (R100)
    App->>API: POST /vouchers/easypay/topup/issue
    API-->>App: 14-digit PIN (9123412345678)
    App-->>User: Display PIN
    User->>EP: Present PIN + R100 cash
    EP->>EPBackend: Verify PIN
    EPBackend->>API: POST /vouchers/easypay/topup/settlement
    API-->>EPBackend: 200 OK (Settled)
    EPBackend-->>EP: Payment Confirmed
    EP-->>User: Receipt
    Note over User: Wallet credited instantly
```

1.3 Key Features

- **Banking-Grade Security:** API key authentication, IP whitelisting (infrastructure-level), TLS 1.3
- **Real-Time Settlement:** Instant wallet crediting upon payment confirmation
- **Comprehensive Audit Trail:** All transactions logged with full metadata
- **Idempotent Operations:** Safe retry mechanisms for network failures
- **Mojaloop Compliance:** Aligned with ISO 20022 and Mojaloop specifications
- **Structured Error Responses:** Banking-grade error format with codes, request IDs, and timestamps

2. Quick Start Guide

2.1 Prerequisites

- Valid EasyPay Merchant Agreement with MyMoolah
- UAT environment access credentials
- Technical contact designated for integration support
- Firewall rules configured for API access

2.2 Integration Checklist

- ☐ Obtain UAT API credentials (API key)
- ☐ Configure IP whitelist (if required)
- ☐ Implement authentication flow (X-API-Key header)
- ☐ Integrate settlement endpoints
- ☐ Implement idempotency (X-Idempotency-Key header)
- ☐ Test with UAT test users

- ☐ Complete reconciliation testing
- ☐ Request production credentials
- ☐ Deploy to production
- ☐ Monitor first 48 hours

2.3 5-Minute Quick Test

```
# 1. Test Top-up Settlement Endpoint
curl -X POST https://staging.mymoolah.africa/api/v1/vouchers/easypay/topup/settlement \
-H "Content-Type: application/json" \
-H "X-API-Key: your_uat_api_key_here" \
-H "X-Idempotency-Key: test-topup-$(date +%s)" \
-H "X-Request-ID: test-request-$(uuidgen)" \
-d '{
  "easypay_code": "9123412345678",
  "settlement_amount": 100.00,
  "merchant_id": "EP_TEST_MERCHANT_001",
  "transaction_id": "EP_TXN_20260116_001",
  "terminal_id": "EP_TERMINAL_001",
  "timestamp": "2026-01-16T13:40:33+02:00"
}'

# 2. Test Cash-out Settlement Endpoint
curl -X POST https://staging.mymoolah.africa/api/v1/vouchers/easypay/cashout/settlement \
-H "Content-Type: application/json" \
-H "X-API-Key: your_uat_api_key_here" \
-H "X-Idempotency-Key: test-cashout-$(date +%s)" \
-H "X-Request-ID: test-request-$(uuidgen)" \
-d '{
  "easypay_code": "9123498765432",
  "settlement_amount": 500.00,
  "merchant_id": "EP_TEST_MERCHANT_001",
  "transaction_id": "EP_TXN_20260116_002",
  "terminal_id": "EP_TERMINAL_002",
  "timestamp": "2026-01-16T14:00:00+02:00"
}'
```

3. Authentication & Security

3.1 Security Architecture

MyMoolah employs a **defense-in-depth** security model with multiple layers:

Layer	Mechanism	Description
Transport	TLS 1.3	All API calls must use HTTPS with TLS 1.3+
Authentication	API Key	X-API-Key header validation
Network	IP Whitelist	Source IP validation (infrastructure-level, optional)
Application	Request ID	X-Request-ID header for request tracking
Idempotency	Idempotency Keys	Prevent duplicate transactions

3.2 API Key Authentication

Required Header: X-API-Key

Format: Secure random string (minimum 32 characters, recommended 64+)

Example:

```
X-API-Key: a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6q7r8s9t0u1v2w3x4y5z6
```

Obtaining API Keys:

- **UAT:** Provided by MyMoolah Integration Team after UAT registration
- **Production:** Provided separately via secure channel after UAT sign-off

Security Best Practices:

1. **Credential Storage:** Store API keys in secure vaults (e.g., HashiCorp Vault, AWS Secrets Manager, Google Secret Manager)
2. **Key Rotation:** Rotate API keys periodically (recommended: every 90 days)
3. **TLS Pinning:** Optionally pin MyMoolah's TLS certificate
4. **Request Logging:** Log all API interactions (mask API key in logs)
5. **Error Handling:** Never expose API keys in error messages

3.3 Required Headers

All API requests must include:

```
X-API-Key: {API_KEY}
X-Idempotency-Key: {UNIQUE_REQUEST_ID}
Content-Type: application/json
X-Request-ID: {UUID} (optional but recommended)
```

Header Descriptions:

Header	Required	Description	Example
X-API-Key	Yes	API key for authentication	a1b2c3d4e5f6...
X-Idempotency-Key	Recommended	Unique key to prevent duplicate processing	EP_MERCHANT_12345_EP_TXN_20260116_001_1642334
Content-Type	Yes	Must be application/json	application/json
X-Request-ID	Optional	UUID for request tracking	550e8400-e29b-41d4-a716-446655440000

3.4 IP Whitelisting (Optional)

Infrastructure-Level: IP whitelisting is handled at the infrastructure level (Google Cloud Load Balancer). Contact MyMoolah Integration Team to register your IP addresses.

Format: IPv4 CIDR notation (e.g., 197.85.10.0/24)

UAT Allowed IPs: Contact MyMoolah Integration Team to register

Production Allowed IPs: Requires formal request with business justification

4. API Endpoints

4.1 Top-up @ EasyPay Settlement

Endpoint

```
POST /api/v1/vouchers/easypay/topup/settlement
```

Description

Called by EasyPay when a user presents a Top-up PIN at a cashier and pays cash. This endpoint credits the user's MyMoolah wallet with the settlement amount.

Request

Headers:

```
X-API-Key: {API_KEY}
X-Idempotency-Key: {UNIQUE_KEY}
Content-Type: application/json
X-Request-ID: {UUID} (optional)
```

Body:

```

{
  "easypay_code": "9123412345678",
  "settlement_amount": 100.00,
  "merchant_id": "EP_MERCHANT_12345",
  "transaction_id": "EP_TXN_20260116_123456",
  "terminal_id": "EP_TERMINAL_001",
  "cashier_id": "CASHIER_789",
  "timestamp": "2026-01-16T13:40:33+02:00",
  "metadata": {
    "merchant_name": "Pick n Pay - Sandton City",
    "receipt_number": "RCP-001234"
  }
}

```

Field Specifications:

Field	Type	Required	Description	Validation
easypay_code	String	Yes	14-digit EasyPay PIN	<code>/^9\d{13}\$/</code> (starts with 9, 14 digits total)
settlement_amount	Number	Yes	Amount in ZAR (Rands)	<code>50.00-4000.00</code> (R50-R4000)
merchant_id	String	Yes	EasyPay merchant identifier	Max 50 chars
transaction_id	String	Yes	Unique EasyPay transaction ID	Max 100 chars, alphanumeric
terminal_id	String	Yes	Terminal identifier	Max 50 chars
cashier_id	String	No	Cashier identifier	Max 50 chars
timestamp	String	No	ISO 8601 timestamp with timezone	Must be within 5 minutes of server time
metadata	Object	No	Additional transaction data	Max 1KB

Response

Success (200 OK):

```

{
  "success": true,
  "message": "EasyPay top-up settled successfully",
  "data": {
    "easypay_code": "9123412345678",
    "settlement_amount": 100.00,
    "status": "completed",
    "settlement_transaction_id": "STL-1642334433-abc123"
  }
}

```

Response Field Descriptions:

Field	Type	Description
<code>success</code>	Boolean	Always <code>true</code> for successful responses
<code>message</code>	String	Human-readable success message
<code>data.easypay_code</code>	String	The 14-digit EasyPay PIN that was settled
<code>data.settlement_amount</code>	Number	Amount paid at store and credited to wallet (Rands)
<code>data.status</code>	String	Settlement status (<code>completed</code>)
<code>data.settlement_transaction_id</code>	String	MyMoolah internal transaction ID

Error Responses: See [Error Handling](#) section

4.2 Cash-out @ EasyPay Settlement

Endpoint

```
POST /api/v1/vouchers/easypay/cashout/settlement
```

Description

Called by EasyPay when a user presents a Cash-out PIN at a cashier to withdraw cash. This endpoint marks the voucher as redeemed after cash has been dispensed. The user's wallet was already debited when the cash-out voucher was created.

Request

Headers:

```
X-API-Key: {API_KEY}
X-Idempotency-Key: {UNIQUE_KEY}
Content-Type: application/json
X-Request-ID: {UUID} (optional)
```

Body:

```
{
  "easypay_code": "9123498765432",
  "settlement_amount": 500.00,
  "merchant_id": "EP_MERCHANT_12345",
  "transaction_id": "EP_TXN_20260116_654321",
  "terminal_id": "EP_TERMINAL_002",
  "cashier_id": "CASHIER_456",
  "timestamp": "2026-01-16T14:00:00+02:00",
  "metadata": {
    "merchant_name": "Checkers - Rosebank",
    "receipt_number": "RCP-567890"
  }
}
```

Field Specifications:

Field	Type	Required	Description	Validation
easypay_code	String	Yes	14-digit EasyPay PIN	<code>/^9\d{13}\$/</code>
settlement_amount	Number	Yes	Amount dispensed in ZAR (Rands)	<code>50.00-3000.00</code> (R50-R3000), must match voucher amount
merchant_id	String	Yes	EasyPay merchant identifier	Max 50 chars
transaction_id	String	Yes	Unique EasyPay transaction ID	Max 100 chars
terminal_id	String	Yes	Terminal identifier	Max 50 chars
cashier_id	String	No	Cashier identifier	Max 50 chars
timestamp	String	No	ISO 8601 timestamp	Within 5 minutes of server time
metadata	Object	No	Additional data	Max 1KB

Response

Success (200 OK):

```
{
  "success": true,
  "message": "EasyPay cash-out settled successfully",
  "data": {
    "easypay_code": "9123498765432",
    "voucher_amount": 500.00,
    "status": "completed",
    "settlement_transaction_id": "CASHOUT-STL-1642338000-xyz789"
  }
}
```

Response Field Descriptions:

Field	Type	Description
<code>success</code>	Boolean	Always <code>true</code> for successful responses
<code>message</code>	String	Human-readable success message
<code>data.easypay_code</code>	String	The 14-digit EasyPay PIN that was settled
<code>data.voucher_amount</code>	Number	Cash-out voucher amount (Rands)
<code>data.status</code>	String	Settlement status (<code>completed</code>)
<code>data.settlement_transaction_id</code>	String	MyMoolah internal transaction ID

Error Responses: See [Error Handling](#) section

5. Data Models

5.1 Top-up Voucher Lifecycle

```
stateDiagram-v2
    [*] --> Pending: User creates top-up
    Pending --> Settled: EasyPay settlement callback
    Pending --> Expired: 96 hours elapsed
    Settled --> [*]
    Expired --> [*]: Wallet not credited
```

States:

- `pending_payment` : Voucher created, waiting for payment at store
- `redeemed` : Payment received, wallet credited
- `expired` : Voucher expired (96 hours), no wallet credit

5.2 Cash-out Voucher Lifecycle

```
stateDiagram-v2
    [*] --> Pending: User creates cash-out<br/>(wallet debited)
    Pending --> Redeemed: EasyPay settlement callback
    Pending --> Cancelled: User cancels<br/>(wallet refunded)
    Pending --> Expired: 96 hours elapsed<br/>(wallet refunded)
    Redeemed --> [*]
    Cancelled --> [*]
    Expired --> [*]
```

States:

- `pending_payment` : Voucher created, wallet debited, waiting for cash-out at store
- `redeemed` : Cash dispensed, voucher consumed
- `cancelled` : User cancelled, wallet refunded
- `expired` : Voucher expired, wallet refunded

5.3 Settlement Request Schema

Top-up Settlement Request:

```
{
  "easypay_code": "string (14 digits, starts with 9)",
  "settlement_amount": "number (50.00-4000.00)",
  "merchant_id": "string (max 50 chars)",
  "transaction_id": "string (max 100 chars, alphanumeric)",
  "terminal_id": "string (max 50 chars)",
  "cashier_id": "string (max 50 chars, optional)",
  "timestamp": "string (ISO 8601, optional)",
  "metadata": "object (max 1KB, optional)"
}
```

Cash-out Settlement Request:

```
{
  "easypay_code": "string (14 digits, starts with 9)",
  "settlement_amount": "number (50.00-3000.00)",
  "merchant_id": "string (max 50 chars)",
  "transaction_id": "string (max 100 chars)",
  "terminal_id": "string (max 50 chars)",
  "cashier_id": "string (max 50 chars, optional)",
  "timestamp": "string (ISO 8601, optional)",
  "metadata": "object (max 1KB, optional)"
}
```

6. Error Handling

6.1 Error Response Format

All error responses follow this structured format:

```
{
  "success": false,
  "error": {
    "code": "ERROR_CODE",
    "message": "Human-readable error message",
    "details": "Additional context or resolution steps",
    "request_id": "uuid-1234-5678-90ab",
    "timestamp": "2026-01-16T14:05:00.000Z"
  }
}
```

6.2 Error Codes

Code	HTTP Status	Category	Description	Resolution
INVALID_PIN	400	Validation	PIN format incorrect	Check PIN is 14 digits starting with '9'
PIN_NOT_FOUND	404	Not Found	PIN doesn't exist or already settled	Verify PIN with user, check settlement status
AMOUNT_MISMATCH	400	Validation	Settlement amount doesn't match voucher	Verify expected amount with user
PIN_EXPIRED	400	Business Logic	PIN >96 hours old	User must create new top-up/cash-out request
ALREADY_SETTLED	409	Idempotency	Duplicate request (idempotency)	Return original response (idempotent)
DUPLICATE_REQUEST	409	Conflict	Idempotency key used with different request	Use unique idempotency key for each request
MISSING_API_KEY	401	Security	X-API-Key header missing	Include X-API-Key header
INVALID_API_KEY	401	Security	Invalid API key	Verify API key with MyMoolah
MISSING_REQUIRED_FIELD	400	Validation	Required field missing	Check request body for all required fields
INVALID_AMOUNT	400	Validation	Amount out of range	Top-up: R50-R4000, Cash-out: R50-R3000
INVALID_FORMAT	400	Validation	Invalid request format	Verify JSON structure and field types
WALLET_NOT_FOUND	404	Not Found	User wallet not found	Contact MyMoolah support
RATE_LIMIT_EXCEEDED	429	Rate Limiting	Too many requests	Implement exponential backoff
INTERNAL_ERROR	500	Server	Unexpected server error	Contact MyMoolah support with request_id

6.3 HTTP Status Codes

Code	Category	Usage
200	Success	Request completed successfully
400	Client Error	Invalid request (validation failed)
401	Auth Error	Authentication failed (missing/invalid API key)
404	Client Error	Resource not found (PIN, voucher, wallet)
409	Conflict	Idempotency conflict or already processed
429	Rate Limit	Too many requests
500	Server Error	Internal server error
502	Server Error	Bad gateway
503	Server Error	Service unavailable
504	Server Error	Gateway timeout

6.4 Retry Logic

Recommended Retry Strategy:

1. **Idempotent Requests:** Safe to retry with same idempotency key
2. **Exponential Backoff:** Base delay 1s, max 32s
3. **Retry Conditions:**
 - Network errors
 - HTTP 500, 502, 503, 504
 - Timeouts
4. **Do NOT Retry:**
 - HTTP 400, 401, 404 (fix request first)
 - HTTP 409 (already processed - use original response)

Example Retry Implementation:

```

async function settlementWithRetry(payload, maxRetries = 3) {
  const idempotencyKey = generateIdempotencyKey(payload);

  for (let attempt = 1; attempt <= maxRetries; attempt++) {
    try {
      return await callSettlementAPI(payload, idempotencyKey);
    } catch (error) {
      if (isRetryable(error) && attempt < maxRetries) {
        const delay = Math.min(1000 * Math.pow(2, attempt - 1), 32000);
        await sleep(delay);
        continue;
      }
      throw error;
    }
  }
}

function isRetryable(error) {
  const retryableStatuses = [500, 502, 503, 504];
  return retryableStatuses.includes(error.status) || error.code === 'ECONNRESET';
}

```

7. Idempotency

7.1 Overview

Idempotency ensures that making the same request multiple times has the same effect as making it once. This is **critical for financial APIs** to prevent duplicate processing if network errors cause retries.

7.2 Implementation

Header: `X-Idempotency-Key`

Format: Unique string per request (recommended:

```
{merchant_id}_{terminal_id}_{transaction_id}_{timestamp} )
```

Example:

```
X-Idempotency-Key: EP_MERCHANT_12345_EP_TERMINAL_001_EP_TXN_20260116_123456_1642334433
```

7.3 How It Works

1. **First Request:** Process normally, store response with idempotency key (24-hour TTL)
2. **Duplicate Request** (same key, same request body): Return cached response (HTTP 200)
3. **Different Request** (same key, different body): Return HTTP 409 CONFLICT

7.4 Best Practices

1. **Generate Unique Keys:** Use a combination of merchant_id, terminal_id, transaction_id, and timestamp
2. **Store Keys:** Keep idempotency keys for at least 24 hours (for retries)

3. **Handle 409 Responses:** If you receive HTTP 409, use a new idempotency key or verify the request body matches
4. **Never Reuse Keys:** Each unique request must have a unique idempotency key

7.5 Example

```
// Generate idempotency key
const idempotencyKey = `${merchantId}_${terminalId}_${transactionId}_${Date.now()}`;

// First request
const response1 = await fetch(settlementUrl, {
  method: 'POST',
  headers: {
    'X-API-Key': apiKey,
    'X-Idempotency-Key': idempotencyKey,
    'Content-Type': 'application/json'
  },
  body: JSON.stringify(payload)
});

// If network error, retry with SAME idempotency key
// Second request (retry) - returns cached response from first request
const response2 = await fetch(settlementUrl, {
  method: 'POST',
  headers: {
    'X-API-Key': apiKey,
    'X-Idempotency-Key': idempotencyKey, // SAME key
    'Content-Type': 'application/json'
  },
  body: JSON.stringify(payload) // SAME payload
});
// response2 === response1 (cached)
```

8. Testing Guide (UAT)

8.1 Environment Endpoints & API Keys

MyMoolah provides three environments for EasyPay integration:

Environment 1: QA/Test (Development)

Base URL: `https://staging.mymoolah.africa`

API Base: `https://staging.mymoolah.africa/api/v1`

Status:  Active

Purpose: Initial development and integration testing

Settlement Endpoints:

- **Top-up:** POST `https://staging.mymoolah.africa/api/v1/vouchers/easypay/topup/settlement`
- **Cash-out:** POST `https://staging.mymoolah.africa/api/v1/vouchers/easypay/cashout/settlement`

API Key: `EASYPAY_API_KEY_QA` (provided separately via secure channel)

Configuration: Stored in local `.env` file (not Secret Manager)

IP Whitelisting: Required - Contact MyMoolah Integration Team

Environment 2: Pre-Production/Staging

Base URL: `https://staging.mymoolah.africa`

API Base: `https://staging.mymoolah.africa/api/v1`

Status:  Active

Purpose: Pre-production testing and UAT sign-off

Settlement Endpoints:

- **Top-up:** POST `https://staging.mymoolah.africa/api/v1/vouchers/easypay/topup/settlement`
- **Cash-out:** POST `https://staging.mymoolah.africa/api/v1/vouchers/easypay/cashout/settlement`

API Key: `EASYPAY_API_KEY_STAGING` (provided separately via secure channel)

Configuration: Stored in Google Secret Manager (`easypay-api-key-staging`)

IP Whitelisting: Required - Contact MyMoolah Integration Team

Environment 3: Production

Base URL: `https://api.mymoolah.africa` (when available)

API Base: `https://api.mymoolah.africa/api/v1`

Status:  Planned (not yet deployed)

Purpose: Live production traffic

Settlement Endpoints (when production is live):

- **Top-up:** POST `https://api.mymoolah.africa/api/v1/vouchers/easypay/topup/settlement`
- **Cash-out:** POST `https://api.mymoolah.africa/api/v1/vouchers/easypay/cashout/settlement`

API Key: `EASYPAY_API_KEY_PROD` (provided separately via secure channel after UAT sign-off)

Configuration: Stored in Google Secret Manager (`easypay-api-key-production`)

IP Whitelisting: Required - Contact MyMoolah Integration Team

8.2 API Key Management

Security: API keys are generated using cryptographically secure random generation (minimum 64 characters).

Delivery Method: API keys are delivered via **separate secure channel** (not in documentation) to:

- EasyPay Technical Contact
- EasyPay Integration Team Lead

Storage by Environment:

- **QA/Test (UAT):** Stored in local `.env` file (not in Secret Manager)

- Add to `.env` : `EASYPAY_API_KEY=your_qa_api_key_here`
- Used for local development and Codespaces testing
- **Staging:** Stored in Google Secret Manager (`easypay-api-key-staging`)
 - Automatically loaded by Cloud Run deployment
 - Managed via `scripts/generate-easypay-api-keys.sh`
- **Production:** Stored in Google Secret Manager (`easypay-api-key-production`)
 - Automatically loaded by Cloud Run deployment
 - Managed via `scripts/generate-easypay-api-keys.sh`

Storage Requirements:

- **QA/Test:** Store in `.env` file (never commit to git - `.env` is in `.gitignore`)
- **Staging/Production:** Managed via Google Secret Manager (automated)
- Never commit API keys to version control
- Rotate API keys periodically (recommended: every 90 days)
- Use different API keys for each environment

Request API Keys: Contact `integrations@mymoolah.africa` with:

1. Environment(s) required (QA/Test, Staging, Production)
2. Technical contact information
3. IP addresses for whitelisting (see Section 8.3)

8.3 IP Whitelisting

Infrastructure-Level: IP whitelisting is configured at the Google Cloud Load Balancer level.

Required Information:

- **IP Address(es):** Provide in CIDR notation (e.g., `20.164.206.68/32` for single IP, `20.164.206.0/24` for subnet)
- **Environment:** Specify which environment(s) require whitelisting
- **Technical Contact:** Name, email, phone for coordination

EasyPay Azure IP (provided):

- **IP Address:** `20.164.206.68`
- **CIDR Notation:** `20.164.206.68/32`

Setup Process:

1. EasyPay provides IP addresses to MyMoolah Integration Team
2. MyMoolah configures whitelist at infrastructure level
3. MyMoolah confirms whitelist activation (typically within 24 hours)
4. EasyPay tests connectivity

Contact: `integrations@mymoolah.africa` for IP whitelisting requests

EasyPay IP Address (provided):

- **IP:** 20.164.206.68
 - **CIDR:** 20.164.206.68/32
 - **Environment:** All environments (QA, Staging, Production)
-

8.4 Test Data & Scenarios

Test Data

Test Users: MyMoolah will provide test user accounts for EasyPay testing:

- Test user phone numbers (for creating top-up/cash-out vouchers)
- Test wallet balances (pre-funded for testing)

Test PINs: EasyPay should use PINs generated by MyMoolah test users via the mobile app. Test PINs follow the same format as production PINs (14 digits, starting with '9', Luhn-validated).

Test Amounts:

- **Top-up:** R50.00 - R4000.00 (test with various amounts)
- **Cash-out:** R50.00 - R3000.00 (test with various amounts)

Test Merchant IDs (for settlement requests):

- QA/Test: EP_TEST_MERCHANT_001
 - Staging: EP_STAGING_MERCHANT_001
 - Production: EP_PROD_MERCHANT_001 (when available)
-

8.5 Test Scenarios

Scenario 1: Successful Top-up

1. Create top-up voucher via MM app (User, R100)
2. Note 14-digit PIN generated
3. Call settlement API with correct details
4. Verify wallet credited with settlement amount

Expected Response: HTTP 200, `status: "completed"`, `settlement_amount: 100.00`

Scenario 2: Invalid PIN

1. Call settlement API with non-existent PIN `99999999999999`
2. Verify proper error response

Expected Response: HTTP 404, `error.code: "PIN_NOT_FOUND"`

Scenario 3: Amount Mismatch

1. Create R100 top-up
2. Call settlement with R150 amount
3. Verify rejection

Expected Response: HTTP 400, `error.code: "AMOUNT_MISMATCH"`

Scenario 4: Idempotency

1. Call settlement API
2. Immediately retry with same idempotency key
3. Verify identical response (no double credit)

Expected Response: HTTP 200 (both times), same settlement_transaction_id

Scenario 5: Expired PIN

1. Use pre-expired test PIN (expired 100 hours ago)
2. Attempt settlement
3. Verify rejection

Expected Response: HTTP 400, `error.code: "PIN_EXPIRED"`

Scenario 6: Missing API Key

1. Call settlement API without X-API-Key header
2. Verify authentication error

Expected Response: HTTP 401, `error.code: "MISSING_API_KEY"`

Scenario 7: Invalid API Key

1. Call settlement API with incorrect API key
2. Verify authentication error

Expected Response: HTTP 401, `error.code: "INVALID_API_KEY"`

8.3 UAT Sign-off Checklist

Before requesting production credentials:

- ☐ Successfully completed all 7 test scenarios
- ☐ Tested with multiple test users
- ☐ Verified idempotency handling
- ☐ Tested retry logic
- ☐ Verified error handling (all error codes)
- ☐ Completed reconciliation test
- ☐ Documented integration in internal wiki
- ☐ Security review passed
- ☐ Load testing completed (100 TPS)

9. Production Deployment

9.1 Production Credentials Request

To obtain production credentials, submit the following to `integrations@mymoolah.africa` :

1. **UAT Sign-off Report** (proof of successful testing)
2. **Production IP Addresses** (CIDR notation, if IP whitelisting required)
3. **Expected Transaction Volume** (daily/monthly)
4. **Business Contact** (name, email, phone)
5. **Technical Contact** (name, email, phone, 24/7 on-call number)
6. **Go-Live Date** (proposed)

SLA: 5 business days for credential provisioning

9.2 Production Environment

Base URL: `https://api.mymoolah.africa` (when available)

API Base: `https://api.mymoolah.africa/api/v1`

Credentials: Delivered via secure channel after approval

Note: Production environment is planned but not yet deployed. Staging environment should be used for production readiness testing.

9.3 Go-Live Checklist

- ☐ Production credentials received and stored securely
- ☐ IP whitelist configured (if required)
- ☐ Production code deployed
- ☐ Monitoring & alerting configured
- ☐ Incident response plan documented
- ☐ MyMoolah support contacts saved
- ☐ First transaction test completed
- ☐ Reconciliation process automated
- ☐ Disaster recovery plan tested

9.4 Production Best Practices

1. **Monitoring:** Set up real-time monitoring for:

- API response times (target: <500ms p95)
- Error rates (target: <0.1%)
- Settlement success rate (target: >99.9%)

2. **Alerting:** Configure alerts for:

- Authentication failures
- Consecutive API errors
- Unusual transaction patterns

3. **Logging:** Log all API interactions with:

- Request/Response payloads (mask API key)
- Timestamps
- Response times
- Error stack traces

4. Capacity Planning: MyMoolah API can handle:

- 1,000 requests per second
- 10,000 concurrent connections
- 99.95% uptime SLA

10. Reconciliation

10.1 SFTP-Based Reconciliation (Primary Method)

MyMoolah operates a **secure SFTP server** for automated daily reconciliation file exchange. This is the **recommended** reconciliation method for production environments.

10.1.1 SFTP Connection Details

Production SFTP Server:

```
Host: 34.35.137.166
Port: 22
Username: easypay
Authentication: SSH public key only (no password authentication)
Home Directory: /home/easypay (mapped to gs://mymoolah-sftp-inbound/easypay/)
```

Security Requirements:

- SSH key-based authentication (RSA 4096-bit or ED25519 recommended)
- Source IP whitelisting (provide your CIDR ranges)
- TLS 1.3 for file transfer encryption

10.1.2 SFTP Setup Process

Step 1: Generate SSH Key Pair (if not already available)

```
# Generate ED25519 key (recommended)
ssh-keygen -t ed25519 -C "easypay-reconciliation@easypay.co.za"

# Or generate RSA 4096-bit key
ssh-keygen -t rsa -b 4096 -C "easypay-reconciliation@easypay.co.za"
```

Step 2: Provide MyMoolah with the Following

Email to: `integrations@mymoolah.africa`

Subject: `EasyPay SFTP Reconciliation Setup - [Your Company Name]`

Body:

- ```
1. SSH Public Key: [Paste contents of id_ed25519.pub or id_rsa.pub]
2. Source IP/CIDR Ranges: [e.g., 197.85.10.0/24, 41.203.45.100/32]
3. Technical Contact: [Name, Email, Phone]
4. Expected Go-Live Date: [YYYY-MM-DD]
```

### Step 3: Test Connection (after MyMoolah confirms setup)

```
sftp -P 22 easypay@34.35.137.166

You should see:
Connected to 34.35.137.166
sftp>
```

#### 10.1.3 File Upload Requirements

##### File Naming Convention:

```
easypay_recon_YYYYMMDD.csv
```

##### Examples:

- `easypay_recon_20260116.csv` (daily file for January 16, 2026)
- `easypay_recon_20260117.csv` (daily file for January 17, 2026)

##### Upload Schedule:

- **Frequency:** Daily
- **Cutoff Time:** 23:59:59 SAST
- **Upload Window:** 00:00 - 06:00 SAST (next day)
- **Example:** Transactions from Jan 16 (00:00 - 23:59) should be uploaded as `easypay_recon_20260116.csv` between Jan 17 00:00 - 06:00

##### Upload Command:

```
Upload reconciliation file
sftp easypay@34.35.137.166 << EOF
cd /home/easypay
put easypay_recon_20260116.csv
bye
EOF
```

#### 10.1.4 CSV File Format Specification

**File Encoding:** UTF-8

**Delimiter:** Comma ( , )

**Line Ending:** LF ( \n ) or CRLF ( \r\n )

**Quote Character:** Double quote ( " ) for fields containing commas

**Header Row:** Required (first line)

**CSV Schema:**

| Column                | Type    | Required | Description               | Format/Rules                                                      |
|-----------------------|---------|----------|---------------------------|-------------------------------------------------------------------|
| transaction_id        | String  | Yes      | EasyPay transaction ID    | Max 100 chars, alphanumeric + <code>-_</code>                     |
| easypay_code          | String  | Yes      | 14-digit PIN              | <code>/^9\d{13}\$/</code>                                         |
| transaction_type      | String  | Yes      | Transaction type          | <code>topup</code> or <code>cashout</code>                        |
| merchant_id           | String  | Yes      | Merchant identifier       | Max 50 chars                                                      |
| terminal_id           | String  | Yes      | Terminal identifier       | Max 50 chars                                                      |
| cashier_id            | String  | No       | Cashier identifier        | Max 50 chars, empty if N/A                                        |
| transaction_timestamp | String  | Yes      | Transaction date/time     | ISO 8601: <code>YYYY-MM-DDTHH:MM:SS+02:00</code>                  |
| gross_amount          | Decimal | Yes      | Amount in ZAR             | Format: <code>0.00</code> , 2 decimal places                      |
| settlement_status     | String  | Yes      | EasyPay settlement status | <code>settled</code> , <code>pending</code> , <code>failed</code> |
| merchant_name         | String  | No       | Merchant location name    | Max 100 chars                                                     |
| receipt_number        | String  | No       | Receipt number            | Max 50 chars                                                      |

#### Example CSV:

```
transaction_id,easypay_code,transaction_type,merchant_id,terminal_id,cashier_id,transaction
EP_TXN_20260116_001,9123412345678,topup,EP_MERCHANT_12345,EP_TERMINAL_001,CASHIER_789,2026-
EP_TXN_20260116_002,9123498765432,cashout,EP_MERCHANT_12345,EP_TERMINAL_002,CASHIER_456,202
EP_TXN_20260116_003,9123400000003,topup,EP_MERCHANT_67890,EP_TERMINAL_005,,2026-01-16T15:30
```

#### CSV Validation Rules:

- File size: Max 100MB (contact support if larger)
- Row limit: Max 100,000 transactions per file
- All required fields must be non-empty
- `gross_amount` must match the amount in MyMoolah's records (±R0.01 tolerance)
- `transaction_timestamp` must be within the date range of the filename

#### 10.1.5 Automated Reconciliation Process

MyMoolah's **automated reconciliation service** monitors the SFTP server and processes files as follows:

```
flowchart TD
 A[EasyPay uploads CSV] --> B[SFTP Server: easypay_recon_20260116.csv]
 B --> C{File detected
within 5 minutes}
 C -->|Yes| D[Download & Parse CSV]
 C -->|No| E[Alert: File not received]
 D --> F{CSV Valid?}
 F -->|No| G[Alert: CSV validation failed]
 F -->|Yes| H[Match against MyMoolah transactions]
 H --> I{All transactions match?}
 I -->|Yes| J[Reconciliation: SUCCESS]
 I -->|No| K[Generate discrepancy report]
 K --> L[Email finance team + EasyPay contact]
 J --> M[Move file to /processed/]
 G --> N[Move file to /error/]
 E --> O[Email alert to EasyPay contact]
```

**Processing Timeline:**

- 1. **File Upload:** 00:00 - 06:00 SAST
- 2. **Auto-Detection:** Within 5 minutes of upload
- 3. **Validation:** ~1 minute
- 4. **Reconciliation:** ~5 minutes (for 10,000 transactions)
- 5. **Notification:** Immediate (success or failure)

**Reconciliation Results:**

| Result              | Action                        | Notification                              |
|---------------------|-------------------------------|-------------------------------------------|
| 100% Match          | File moved to /processed/     | Email: "Reconciliation successful"        |
| Discrepancies Found | File moved to /discrepancies/ | Email with discrepancy report             |
| CSV Invalid         | File moved to /error/         | Email with validation errors              |
| File Missing        | No file detected by 07:00     | Email: "Reconciliation file not received" |

**Discrepancy Handling:**

If discrepancies are found, MyMoolah generates a report with details. Contact `finance@mymoolah.africa` for resolution.

**10.1.6 SFTP Best Practices**

- 1. **Automate Uploads:** Use cron jobs or scheduled tasks
- 2. **Verify File Integrity:** Calculate MD5 checksum before upload
- 3. **Log All Transfers:** Maintain audit log of uploaded files
- 4. **Monitor Notifications:** Set up email alerts for reconciliation results
- 5. **Backup Files:** Keep local copies for 90 days minimum

**Example Automated Upload Script** (Linux/macOS):

```
#!/bin/bash
Daily EasyPay Reconciliation Upload
Schedule with cron: 0 2 * * * /path/to/upload_recon.sh

DATE=$(date -d "yesterday" +%Y%m%d)
FILE="easypay_recon_${DATE}.csv"
LOCAL_PATH="/opt/easypay/recon/${FILE}"
SFTP_HOST="34.35.137.166"
SFTP_USER="easypay"

Generate reconciliation file (your internal process)
/opt/easypay/scripts/generate_recon.sh $DATE

Verify file exists and is not empty
if [! -s "$LOCAL_PATH"]; then
 echo "ERROR: Reconciliation file missing or empty" | mail -s "EasyPay Recon Upload Fail" ops@easypay.co
 exit 1
fi

Upload to MyMoolah SFTP
sftp ${SFTP_USER}@${SFTP_HOST} << EOF
cd /home/easypay
put ${LOCAL_PATH}
bye
EOF

if [$? -eq 0]; then
 echo "SUCCESS: Uploaded ${FILE}" | mail -s "EasyPay Recon Upload Successful" ops@easypay.co
else
 echo "ERROR: SFTP upload failed" | mail -s "EasyPay Recon Upload Failed" ops@easypay.co
 exit 1
fi
```

## 10.2 Alternative: REST API Reconciliation

For partners who cannot use SFTP, MyMoolah provides a REST API endpoint for downloading reconciliation data.

### Endpoint:

```
GET /api/v1/reconciliation/easypay/daily/{date}
```

### Parameters:

- `date` : YYYY-MM-DD format (e.g., `2026-01-16` )

**Response:** Same CSV format as SFTP (see Section 10.1.4)

**Authentication:** Requires X-API-Key header

### Example:

```
curl -X GET https://staging.mymoolah.africa/api/v1/reconciliation/easypay/daily/2026-01-16 \
-H "X-API-Key: {API_KEY}" \
--output easypay_recon_20260116.csv
```



**Note:** SFTP method is **strongly preferred** for production as it provides automated reconciliation processing. REST API requires manual processing on EasyPay's side.

## 11. Support & SLAs

### 11.1 Support Channels

| Channel           | Availability     | Response Time | Use Case           |
|-------------------|------------------|---------------|--------------------|
| Email             | 24/7             | 4 hours       | Non-urgent queries |
| Phone             | 08:00-17:00 SAST | Immediate     | Production issues  |
| Emergency Hotline | 24/7             | 15 minutes    | Critical outages   |

**Contact Details:**

- Email: `support@mymoolah.africa`
- Integration Support: `integrations@mymoolah.africa`
- Phone: `+27 21 140 7030`
- Emergency: `+27 82 557 1055`

### 11.2 Service Level Agreements

| Metric                          | Target      | Measurement                    |
|---------------------------------|-------------|--------------------------------|
| API Availability                | 99.95%      | Monthly uptime                 |
| API Response Time (p95)         | <500ms      | 95th percentile                |
| Settlement Processing Time      | <5 seconds  | From API call to wallet credit |
| Support Response (Critical)     | <15 minutes | Phone/emergency hotline        |
| Support Response (Non-Critical) | <4 hours    | Email                          |

### 11.3 Incident Response

In case of production issues:

1. **Immediate:** Call emergency hotline
2. **Provide:** Request ID from error response ( `X-Request-ID` header or `error.request_id` in response)
3. **Escalation:** Automatic escalation after 30 minutes
4. **Status Updates:** Posted to status.mymoolah.africa (when available)

## 12. Appendices

---

### Appendix A: Sequence Diagrams

#### Top-up Flow (Detailed)

```
sequenceDiagram
 autonumber
 participant U as User
 participant App as MM App
 participant API as MM API
 participant DB as Database
 participant EPTerm as EP Terminal
 participant EPBack as EP Backend

 U->>App: Tap "Top-up @ EasyPay"
 App->>U: Enter amount (R50-R4000)
 U->>App: Submit R100
 App->>API: POST /vouchers/easypay/topup/issue
 API->>DB: Create Voucher (status: pending)
 DB-->>API: Voucher ID + PIN
 API-->>App: 14-digit PIN
 App-->>U: Display PIN+QR code

 Note over U,EPTerm: User goes to EasyPay store
 U->>EPTerm: Present PIN + R100 cash
 EPTerm->>EPBack: Validate PIN
 EPBack->>API: POST /vouchers/easypay/topup/settlement
(X-API-Key, X-Idempotency-Key)
 API->>DB: Update voucher (status: redeemed)
 API->>DB: Credit wallet (settlement amount)
 API->>DB: Create transaction record
 API-->>EPBack: 200 OK (settled)
 EPBack-->>EPTerm: Confirmed
 EPTerm-->>U: Receipt

 Note over U: Wallet credited instantly
```

## Cash-out Flow (Detailed)

```
sequenceDiagram
 autonumber
 participant U as User
 participant App as MM App
 participant API as MM API
 participant DB as Database
 participant EPTerm as EP Terminal
 participant EPBack as EP Backend

 U->>App: Tap "Cash-out @ EasyPay"
 App->>U: Enter amount (R50-R3000)
 U->>App: Submit R500
 App->>API: POST /vouchers/easypay/cashout/issue
 API->>DB: Check wallet balance
 API->>DB: Debit wallet (voucher amount + transaction fee)
 API->>DB: Create Voucher (status: pending)
 DB-->>API: Voucher ID + PIN
 API-->>App: 14-digit PIN
 App-->>U: Display PIN

 Note over U,EPTerm: User goes to EasyPay store
 U->>EPTerm: Present PIN
 EPTerm->>EPBack: Validate PIN
 EPBack->>API: POST /vouchers/easypay/cashout/settlement
(X-API-Key, X-Idempotency-K
 API->>DB: Update voucher (status: redeemed)
 API-->>EPBack: 200 OK (settled)
 EPBack-->>EPTerm: Confirmed
 EPTerm->>U: Dispense R500 cash
 EPTerm-->>U: Receipt
```

Appendix B: Error Code Reference

| Code                   | HTTP | Category       | Description                     | Action                |
|------------------------|------|----------------|---------------------------------|-----------------------|
| INVALID_PIN            | 400  | Validation     | PIN format incorrect            | Fix PIN format        |
| PIN_NOT_FOUND          | 404  | Not Found      | PIN doesn't exist               | Verify with user      |
| AMOUNT_MISMATCH        | 400  | Validation     | Amount $\neq$ expected          | Verify amount         |
| PIN_EXPIRED            | 400  | Business Logic | PIN >96 hours old               | User creates new PIN  |
| ALREADY_SETTLED        | 409  | Idempotency    | Duplicate request               | Use original response |
| DUPLICATE_REQUEST      | 409  | Conflict       | Key used with different request | Use unique key        |
| MISSING_API_KEY        | 401  | Security       | X-API-Key missing               | Include header        |
| INVALID_API_KEY        | 401  | Security       | Invalid API key                 | Verify key            |
| MISSING_REQUIRED_FIELD | 400  | Validation     | Required field missing          | Check request body    |
| INVALID_AMOUNT         | 400  | Validation     | Amount out of range             | Check limits          |
| INVALID_FORMAT         | 400  | Validation     | Invalid format                  | Verify JSON structure |
| WALLET_NOT_FOUND       | 404  | Not Found      | User wallet not found           | Contact support       |
| RATE_LIMIT_EXCEEDED    | 429  | Rate Limiting  | Too many requests               | Backoff and retry     |
| INTERNAL_ERROR         | 500  | Server         | Unexpected error                | Contact support       |

Appendix C: Glossary

| Term              | Definition                                                       |
|-------------------|------------------------------------------------------------------|
| EasyPay Code      | 14-digit PIN starting with '9' using Luhn algorithm              |
| Settlement        | Process of confirming payment and updating wallet                |
| Settlement Amount | Amount paid/withdrawn by user and processed                      |
| Idempotency Key   | Unique identifier preventing duplicate processing                |
| Voucher Lifecycle | States: pending $\rightarrow$ settled/redeemed/expired/cancelled |
| Request ID        | UUID for tracking requests in logs and support                   |

## Appendix D: Change Log

| Version | Date       | Changes                                                                                                                                                     |
|---------|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.0.2   | 2026-01-16 | Added comprehensive environment endpoints (QA/Test, Staging, Production), API key management section, IP whitelisting instructions, and test data scenarios |
| 1.0.1   | 2026-01-16 | Removed fee and margin references (commercial agreement pending)                                                                                            |
| 1.0.0   | 2026-01-16 | Initial release - Banking-grade API documentation                                                                                                           |

---

## Need Help?

### Integration Support Team

Email: [support@mymoolah.africa](mailto:support@mymoolah.africa)

Phone: +27 21 140 7030

Emergency: +27 82 557 1055

### General Support

Email: [support@mymoolah.africa](mailto:support@mymoolah.africa)

### Documentation Feedback

If you find any issues or have suggestions for improving this documentation, please email:

[andre@mymoolah.africa](mailto:andre@mymoolah.africa)

---

### MyMoolah Treasury Platform

*Powering Africa's Financial Inclusion*

© 2026 MyMoolah (Pty) Ltd. All rights reserved.