



Joint Face Alignment and 3D Face Reconstruction




Feng Liu¹, Dan Zeng¹, Qijun Zhao¹ and Xiaoming Liu²

¹ College of Computer Science, Sichuan University, Chengdu, China

² Department of Computer Science and Engineering, Michigan State University, East Lansing, MI, USA

1. Introduction


- Existing studies tackle the problems of face alignment and 3D face reconstruction *separately*.
 - Face alignment methods mostly do not consider the visibility of landmarks. Consequently, their performance degrades for large pose face images.
 - 3D face reconstruction methods suffer from the invisible landmarks, and do not generate normalized 3D face for face recognition purpose.



Objectives

- To propose an effective cascaded coupled-regressor based method to jointly solve the two problems of face alignment and 3D face reconstruction in one unified framework.
- To reconstruct pose-expression-normalized (PEN) 3D faces which are believed to be useful for face recognition.

2. Proposed Algorithm



Notations: 3D shape S , 2D landmarks U , SIFT descriptors h , Ground truth training data $\{S^*, U^*\}$, shape and landmark regressors $\{R_S^k, R_U^k\}_{k=1}^K$.

- The coupled process in each iteration
 - Step1:** Updating landmarks. The adjustment to the landmarks' locations is determined by the local texture features via a *landmark regressor*.
 - Step2:** Updating 3D shape. The above-obtained landmark location adjustment is used to estimate the adjustment of the 3D shape via a *shape regressor*.
 - Step3:** Refining landmarks. Once the 3D shape is updated, the landmarks with visibility can be further refined with a 3D-to-2D mapping matrix.

Cascaded coupled-regressor learning

- Landmark regressors:** We employ linear regressors as the landmark regressors:

$$R_U^k = \arg \min_{R_U^k} \sum_{i=1}^N \left\| (U_i^* - U_i^k) - R_U^k(h(I_i, U_i^{k-1})) \right\|_2^2$$

- Shape regressors:** Using similar linear regressors in shape space [1]:


$$R_S^k = \arg \min_{R_S^k} \sum_{i=1}^N \left\| (S_i^* - S_i^k) - R_S^k(\Delta U_i^k) \right\|_2^2$$

3D-to-2D mapping and landmark visibility

- We assume that the expression and pose induced deformation can be approximated by a linear transform. The visibility of landmarks are computed based on the surface normal and the camera rotation matrix [2].

3. Training Data


- Two different models are trained using two training sets.



- 3D shapes in BU3DFE have been established dense correspondence by [3].
- The 68 2D landmarks of LFW images are provided by the work of [4].
- The 3D neutral shapes of LFW are obtained by [1].

4. Experimental Results


- 3D Face reconstruction accuracy on BU3DFE dataset



- Face alignment accuracy on AFW dataset

Method	CDM [5]	PIFA [2]	The proposed method
NME	7.52%	5.60%	3.15%

- Application to face recognition on BU3DFE dataset



- The effect of the reconstructed PEN 3D face shapes on face recognition is evaluated by performing direct 3D-to-3D matching and fusion with conventional 2D face recognition.

Computational efficiency

- The Matlab implementation on a PC with i7-4710 CPU runs at ~26 FPS.

5. Summary

- By alternately applying cascaded landmark regressors and 3D shape regressors, the proposed method can effectively accomplish the two tasks of face alignment and 3D face reconstruction simultaneously in real time.
- Extensive experiments with comparison to state-of-the-art methods demonstrate the effectiveness of the proposed method in both face alignment and 3D face shape reconstruction, and in facilitating face recognition as well.

[1] Liu, F., Zeng, D., Li, J., Zhao, Q.: Cascaded regressor based 3D face reconstruction from a single arbitrary view image. arXiv preprint arXiv:1509.06161 (2015)

[2] Jourabloo, A., Liu, X.: Pose-invariant 3D face alignment. In: ICCV. pp. 3694–3702 (2015)

[3] Zhu, X., Lei, Z., Liu, X., Shi, H., Li, S.Z.: Face alignment across large poses: A 3D solution. In: CVPR (June 2016)

[4] Gong, X., Wang, G.: An automatic approach for pixel-wise correspondence between 3D faces. In: Hybrid Information Technology. vol. 2, pp. 198/205 (2006)

[5] Yu, X., Huang, J., Zhang, S., Yan, W., Metaxas, D.N.: Pose-free facial landmark fitting via optimized part mixtures and cascaded deformable shape model. In: ICCV. pp. 1944–1951. IEEE (2013)