CSC3002
C/C++ Programming

Stream


Prof. Dr. Ruizhi Chen, SDS
Office: TxC 717
E-mail: chenruizhi@cuhk.edu.cn

1 Formatted output
2 Formatted input
3 Data files
4 String Streams

Introduction to the C++ Standard Libraries

- A collection of classes and functions, which are written in the core language and part of the C++ ISO Standard itself. Features of the C++ Standard Library are declared within the std namespace
  - Containers: vector, queue, stack, map, set, etc.
  - General: algorithm, functional, iterator, memory, etc.
  - Strings
  - Streams and Input/Output: iostream, fstream, sstream, etc.
  - Localization
  - Language support
  - Thread support library
  - Numerics library
  - C standard library: cmath, cctype, cstring, cstdio, cstdlib, etc.

Streams


Keyboard
File
String
H
L
E
O
L
Input stream
Y
Variable/
Memory
output stream
Console
File
String
HELLO
source
destination

```cpp
#include <iostream>
#include <string>
using namespace std;

int main()
{
    string name;
    string tmp = "Enter a name:";
    cout << tmp << endl;
    cin >> name;
    cout << "The name you entered:" << name << endl;
}
```

output the variable "*tmp*" to console

get the value of "*name*" from keyboard

output the variable "*name*" to console

Using <cstdio> (stdio.h) Interface

File access:

fclose	Close file (function)
fflush	Flush stream (function)
fopen	Open file (function)
freopen	Reopen stream with different file or mode (function)
setbuf	Set stream buffer (function)
setvbuf	Change stream buffering (function)

Formatted input/output:

fprintf	Write formatted data to stream (function)
fscanf	Read formatted data from stream (function)
printf	Print formatted data to stdout (function)
scanf	Read formatted data from stdin (function)
snprintf C++11	Write formatted output to sized buffer (function)
sprintf	Write formatted data to string (function)
sscanf	Read formatted data from string (function)
vfprintf	Write formatted data from variable argument list to stream (function)
vfscanf C++11	Read formatted data from stream into variable argument list (function)
vprintf	Print formatted data from variable argument list to stdout (function)
vscanf C++11	Read formatted data into variable argument list (function)
vsnprintf C++11	Write formatted data from variable argument list to sized buffer (function)
vsprintf	Write formatted data from variable argument list to string (function)
vsscanf C++11	Read formatted data from string into variable argument list (function)

Using printf from <cstdio> (stdio.h)

```
#include <cstdio>
#include <iostream>
#include <iomanip>
using namespace std;

int main()
{
    char c = 'a';
    int i = 1;
    double d = 3.14159265358979323846;
    // C style, acceptable in C++
    printf("This is a character: %c\n", c);
    printf("This is an integer: %d\n", i);
    printf("This is a double: %.2f\n", d);
    // C++ style
    cout << "This is a character: " << c << endl;
    cout << "This is an integer: " << i << endl;
    cout << "This is a double: " << fixed
         << setprecision(2) << d << endl;
    return 0;
}
```



```
This is a character: a
This is an integer: 1
This is a double: 3.14
```



```
This is a character: a
This is an integer: 1
This is a double: 3.14
```

Using printf from <cstdio> (stdio.h)

specifier	Output	Example
d *or* i	Signed decimal integer	392
u	Unsigned decimal integer	7235
o	Unsigned octal	610
x	Unsigned hexadecimal integer	7fa
X	Unsigned hexadecimal integer (uppercase)	7FA
f	Decimal floating point, lowercase	392.65, inf
F	Decimal floating point, uppercase	392.65, INF
e	Scientific notation (mantissa/exponent), lowercase	3.9265e+2
E	Scientific notation (mantissa/exponent), uppercase	3.9265E+2
g	Use the shortest representation: %e or %f	392.65
G	Use the shortest representation: %E or %F	392.65
a	Hexadecimal floating point, lowercase	-0xc.90fep-2
A	Hexadecimal floating point, uppercase	-0XC.90FEP-2
c	Character	a
s	String of characters	sample
p	Pointer address	b8000000
n	Nothing printed. The corresponding argument must be a pointer to a signed int. The number of characters written so far is stored in the pointed location.	
%	A % followed by another % character will write a single % to the stream.	%

No difference for normal numbers, make sense only for special value (like infinity (inf) or (NaN)

Int count =0;
printf("Hello%n, World", &count);

"count" will be 5.

C++ Streams

- Ever since the very first program in the text, which displayed the message "hello, world" on the screen, the programs in this text have made use of an important object called a stream, which C++ uses to manage the flow of information to or from some data source.
- In the earlier chapters, you have used the << and >> operators and have already had occasion to use the three standard streams exported by the <iostream> library: cin, cout, and cerr.
- Later, to implement file-processing applications, we will learn the notion of data files.
- Finally, we explore the structure of the C++ stream classes as a representative example of inheritance hierarchies in an object-oriented language.

C++ Streams

- A stream is an abstraction (object) that represents an input source or output destination of characters of indefinite length, on which input and ouput operations can be performed.

- Streams are often associated to a physical source or destination of characters, like a disk file (file streams), the keyboard (standard input stream cin), or the console (standard output stream cout), so the characters gotten from or written to our abstraction called stream are physically input from or output to the corresponding physical device.

- For example, file streams are C++ objects to manipulate and interact with files. Once a file stream is used to open a file, any input or output operation performed on that stream is physically reflected in the file.

Standard Output Stream **cout** and the Insertion Operator **<<**

- The standard technique to specify formatted output in C++ uses the insertion operator, which is written as <<. This operator takes an output stream on the left and an expression of any type on its right. The effect is to write the value of the expression to the output stream using the current format settings.
- The insertion operator returns the output stream as its result. The advantage of this interpretation is that output operations can be chained together, as in the following statement:

```
cout << "The total is " << total << endl;
```

```
<<(<<(<<(cout, "The total is "), total), endl);
```



- C++ allows you to control the output by including items in the output chain called manipulators (<iomanip>), which affect the way how subsequent values are formatted. A list of the most common output manipulators appears on the next slide.

Output Manipulators

`endl`	Moves cursor to the next line.
`setw(`*n*`)`**	Sets the width of the next value to *n* characters.
`setprecision(`*digits*`)`**	Sets how many digits should appear.
`setfill(`*ch*`)`**	Sets the fill character used to pad values.
`left`	Aligns the value at the left edge of the field.
`right`	Aligns the value at the right edge of the field.
`fixed`	Sets fixed-point output (no scientific notation).
`scientific`	Sets scientific-notation output.
`showpoint/noshowpoint`	Controls whether a decimal point must appear.
`showpos/noshowpos`	Controls appearance of a plus sign.
`uppercase/nouppercase`	Controls whether uppercase is used in hex.
`boolalpha/noboolalpha`	Controls whether **`bool`**s appear as **`true`**/**`false`**.

Formatting output

```
#include <iostream>
#include <iomanip>
using namespace std;

const double PI = 314.15926535897932384650;

int main() {
   cout << fixed << setprecision(20) << PI << endl;
   cout << fixed << setprecision(6) << PI << endl;
   cout << scientific << setprecision(15) << PI << endl;
   cout << uppercase << scientific << setprecision(6) << PI << endl;
   cout << fixed << setw(16) << setprecision(9) << PI << endl;
   cout << fixed << setfill('0') << setw(10) << setprecision(4) << PI << endl;
   cout << fixed << setfill('0') << setw(10) << setprecision(4) << left << PI << endl;
   return 0;
}
```

The closest floating-point number with the specified precision.

```
314.15926535897932384650
314.159265
3.141592653589793e+02
3.141593E+02
   314.159265359
00314.1593
314.159300
```

You might see `002` *in the exponent in some compilers/systems.*


Precision Example

```
const double PI = 3.14159265358979323846;
const double SPEED_OF_LIGHT = 2.99792458E+8;
const double FINE_STRUCTURE = 7.2573525E-3;

int main() {
   cout << uppercase << right;
   cout << "Default format:" << endl << endl;
   printPrecisionTable();
   cout << endl << "Fixed format:" << fixed << endl << endl;
   printPrecisionTable();
   cout << endl << "Scientific format:" << scientific << endl << endl;
   printPrecisionTable();
   return 0;
}

void printPrecisionTable() {
   cout << " prec |      pi        |  speed of light  | fine structure" << endl;
   cout << "------+----------------+------------------+----------------" << endl;
   for (int prec = 0; prec <= 6; prec += 2) {
      cout << setw(4) << prec << "  |";
      cout << " " << setw(13) << setprecision(prec) << PI << " |";
      cout << " " << setw(16) << setprecision(prec) << SPEED_OF_LIGHT << " |";
      cout << " " << setw(14) << setprecision(prec) << FINE_STRUCTURE << endl;
   }
}
```

Precision Example



Standard Input Stream cin and the Extraction Operator >>

- For input, C++ includes the >> operator, which is called the extraction operator. The >> operator is symmetrical to the << operator and reads formatted data from the stream on the left into the variables that appear on the right.
- Up to now, you have used the >> operator to request input values from the console (PowerOfTwo):

```
int limit;
cout << "Enter exponent limit: ";
cin >> limit;
```

- Similar to the << operator, you can use manipulators to affect the way how subsequent values are formatted:

```
char ch;
cout << "Enter a single character: ";
cin >> noskipws >> ch;
```

Overload the operators >> and << for user-defined data type.

```
class Point{
public:
        int x;
        int y;

        Point(int xx = 0, int yy = 0) : x(xx), y(yy) {};
        void Set(int x, int y);
        friend std::ostream &operator<<(std::ostream &os, const Point &pt);
        friend std::istream &operator>>(std::istream &is, Point &pt);
};
```

```
std::ostream &operator<<(std::ostream &os, const Point &pt)
{
    os << "x=" << pt.x << " y=" << pt.y << std::endl;
    return os;
}

std::istream &operator>>(std::istream &is, Point &pt)
{
    std::cout << "Please enter two integers x, y" << std::endl;
    is >> pt.x >> pt.y;
    return is;
}
```

Input Manipulators

TABLE 4-2 **Input manipulators**

skipws **noskipws**	These manipulators control whether the extraction operator skips over whitespace characters before reading a value. If you specify **noskipws**, the extraction operator treats all characters (including whitespace characters) as part of the input field. You can later use **skipws** to restore the default behavior. This property is persistent.
ws	Reads characters from the input stream until some character appears that is not in the whitespace category. The effect of this manipulator is therefore to skip over any spaces, tabs, and newlines in the input. Unlike **skipws** and **noskipws**, which change the behavior of the stream for subsequent input operations, the **ws** manipulator takes effect immediately. **Take effect only once。**

- Exercise: type in `' '' ''A'' ''B'`, and what is the output?

```
char a, b, c;
cout << "Enter at least 3 character: ";
cin >> noskipws >> a >> ws >> b >> skipws >> c;
cout << a << b << c << endl;
```

Using <cstdio> (stdio.h) Interface

File access:

fclose	Close file (function)
fflush	Flush stream (function)
fopen	Open file (function)
freopen	Reopen stream with different file or mode (function)
setbuf	Set stream buffer (function)
setvbuf	Change stream buffering (function)

Formatted input/output:

fprintf	
fscanf	
printf	
scanf	
snprintf C++11	Write formatted output to sized buffer (function)
sprintf	Write formatted data to string (function)
sscanf	Read formatted data from string (function)
vfprintf	Write formatted data from variable argument list to stream (function)
vfscanf C++11	Read formatted data from stream into variable argument list (function)
vprintf	Print formatted data from variable argument list to stdout (function)
vscanf C++11	Read formatted data into variable argument list (function)
vsnprintf C++11	Write formatted data from variable argument list to sized buffer (function)
vsprintf	Write formatted data from variable argument list to string (function)
vsscanf C++11	Read formatted data from string into variable argument list (function)

Like the relationship between **`cout`** *and* **`<<`** *and* **`printf`**, *you are encouraged to use* **`cin`** *and* **`>>`** *in C++, but should know about* **`scanf`** *in C.*

Data Files

- A file is the generic name for any named collection of data maintained on the various types of permanent storage media attached to a computer. In most cases, a file is stored on a hard disk, but it can also be stored on removable medium, such as a CD or flash memory drive.

- Files can contain information of many different types. When you compile a C++ program, for example, the compiler stores its output in an object file containing the binary representation of the program. The most common type of file, however, is probably a text file, which contains character data of the sort you find in a string.

- Files can be both a source associated to an input stream and a destination associated to an output stream.

Using Text Files

- When you want to read data from a text file as part of a C++ program, you need to take the following steps:
  1. Construct a new ifstream (i.e., input file stream) object that is tied to the data in the file by declaring a stream variable to refer to the file.
  2. Call the open method for the stream. This phase of the process is called opening the file. For historical reasons, the argument to open is a C string literal rather than a C++ string object.
  3. Call the methods provided by the ifstream class to read data from the file in sequential order. The text of the file can be read in several ways, including character by character or line by line.
  4. Break the association between the reader and the file by calling the stream's close method, which is called closing the file. This is important because before you close the file, no one else can use the file.

Using Text Files

- Question: Why does it seem so complicated to process a file?

  Files live in the external storage, and are exposed to all programs. You have to open (associate a stream living in your program to) a file before you can use it. While you are accessing a file through a stream, other programs might not be allowed to access the file to avoid conflicts. You have to close (untie the stream to) a file after you use it so that it can be used by others.

- Question: How to write data to a text file?

Using Text Files

Methods supported by all streams

stream`.fail()`	Returns **`true`** if the stream is in a failure state. This condition usually occurs when you try to read data past the end of the file, but may also indicate an integrity error in the data.
stream`.eof()`	Returns **`true`** if the stream is positioned at the end of the file. Given the semantics of the C++ stream library, the **`eof`** method is useful *only* after a call to **`fail`**. At that point, calling **`eof`** allows you to test whether the failure indication was caused by the end of file or some other data error.
stream`.clear()`	Resets the status bits associated with the stream. You need to call this method whenever you need to reuse a stream after a failure has occurred.
`if` `(`*stream*`)` . . .	If you use a stream in a conditional context, C++ interprets it as a test of whether the stream is valid. For the most part, this test has the same effect as calling **`if (!`***stream*`.fail())`**.

Methods supported by all file streams

stream`.open(`*filename*`)`	Attempts to open the named file and attach it to the stream. The direction is determined by the stream type: input streams are opened for input, output streams are opened for output. The *filename* parameter is a C-style string, which means that you will need to call **`c_str`** on any C++ string. You can check whether the **`open`** method fails by calling **`fail`**.
stream`.close()`	Closes the file attached to the stream.

Using Text Files

Methods supported by all input streams

stream **>>** *variable*	Reads formatted data into a variable. The data format is controlled by the variable type and whatever input manipulators are in effect.
stream`.`**`get`**`(`*var*`)`	Reads the next character into the character variable *var,* which is passed by reference. The return value is the stream itself, with the **`fail`** flag set if there are no more characters.
stream`.`**`get`**`()`	Returns the next character in the stream. The return value is an integer, which makes it possible to identify the end-of-file character, which is represented by the constant **`EOF`**.
stream`.`**`unget`**`()`	Backs up the internal pointer of the stream so that the last character read will be read again by the next call to **`get`**.
`getline``(`*stream*`,` *str*`)`	Reads the next line of input from *stream* into the string *str*. The **`getline`** function returns the stream, which simplifies the end-of-file test.

a free function belonging to <string>

Methods supported by all output stre

stream **<<** *expression*	Writes formatted data to an output stream. The data format is controlled by the expression type and whatever output manipulators are in effect.
stream`.`**`put`**`(`*ch*`)`	Writes the character *ch* to the output stream.

Using Text Files

```
#include <iostream>
#include <fstream>
#include <string>
#include <cctype>
using namespace std;

int main()
{
        ifstream ifile;
        ofstream ofile;
        string instr;
        ifile.open("MyFile.txt"); // open the input filestream
        ofile.open("Output.txt", std::ios::out | std::ios::app);
        while (!ifile.eof())
        {
        getline(ifile, instr); // read a line from input file.
        cout << instr << endl;
        ofile << instr << endl; // write a line to output file
        }
        ifile.close();
        ofile.close();
        return 0;
}
```

Reading Characters

- You can read characters from an input stream by calling the get method, which comes in two forms:
  - If you supply no arguments, get() reads and returns the next character value as an int, which is EOF at the end of the file.
  - If you instead pass a character variable by reference, get(ch) reads the next character into that variable. This form of get returns a value that acts like false at the end of the file.

```
int ch;                                          // int get();
while ( ch != EOF) {
    . . . Perform the necessary operations using the character . . .
}
```

```
char ch;                                  // istream& get(char& c);
while (infile.get(ch)) {
    . . . Perform the necessary operations using the char
}
```


Type casting a stream to bool using a bool operator of itself

- The second is less conventional but typically more convenient.

The conversion function operator bool()

```
struct INT
{
        int i;
        INT(int k = 0) : i(k) {};
        INT &operator=(const INT &src);
        explicit operator bool() const { return i > 5; };
        friend INT operator++(INT &m); // pre-increment operator
        friend INT operator++(INT &m, int); // post-increment operator
        friend INT operator+(const INT m, const INT n);
        friend INT operator-(const INT m, const INT n);
        friend INT operator*(const INT m, const INT n);
        friend INT operator/(const INT m, const INT n);
        friend std::ostream &operator<<(std::ostream &os, INT k);
};
```

When i > 5, return true, otherwise return false



```
int main()
        {
        INT I = 10;
        INT J = 5;

        if (I) cout << "I is true" << endl;
        else cout << "I is false" << endl;

        if (J) cout << "J is true" << endl;
        else cout << "J is false" << endl;
}
```

Call the bool operator of the data type INT to convert(cast) I to bool





```
I is true
J is false
```

Reading a File Character by Character

```
/*
 * File: ShowFileContents.cpp
 * --------------------------
 * This program displays the contents of a file chosen by the user.
 */

#include <iostream>
#include <fstream>
#include <string>
#include "filelib.h"
using namespace std;

int main() {
   ifstream infile;
   promptUserForFile(infile, "Input file: ");
   int ch;
   while ((ch = infile.get()) != EOF) {
      cout.put(ch);
   }
   infile.close();
   return 0;
}
```

comes from the Stanford C++ Library

Reading a File Character by Character

```
/*
 * File: ShowFileContents.cpp
 * --------------------------
 * This program displays the contents of a file chosen by the user.
 */

#include <iostream>
#include <fstream>
#include <string>
#include "filelib.h"
using namespace std;

int main() {
   ifstream infile;
   promptUserForFile(infile, "Input file: ");
   char ch;
   while (infile.get(ch)) {
      cout.put(ch);
   }
   infile.close();
   return 0;
}
```

Reading Lines from a File

- You can also read lines from a text file by calling the free function (unlike a method, a free function is not bound to a particular class) getline, which takes an ifstream and a string as reference parameters.
- The effect of getline is to store the next line of data from the file into the string variable after discarding the end-of-line character.
- If you try to read past the end of the data, getline sets the fail indicator for the stream, which is then interpreted as false.
- The following code fragment uses the getline method to…?

```
...
int max = 0;
string line;
while (getline(infile, line)) {
   if (line.length() > max) max = line.length();
}
```

determine the length of the longest line in the stream infile.

Reading a File Line by Line

```
#include <iostream>
#include <fstream>
#include <string>
using namespace std;

int main()
{
    ifstream ifile;
    ofstream ofile;
    string line;

    ifile.open("MyFile.txt"); // open the input filestream
    // open output file stream
    ofile.open("Output.txt", std::ios::out | std::ios::app);
    while (getline(ifile, line)) // read a line from input file
    {
        cout << line << endl;
        ofile << line << endl; // write a line to output file
    }

    ifile.close();
    ofile.close();
    return 0;
}
```

getline

- The free function std::getline is defined in <string>, and not only works on input file stream but other input streams:

```
istream& getline(istream& is, string& str, char delim);
istream& getline(istream& is, string& str);
```

- There are actually another overloaded version of getline in C++. It is the member method of the istream class, i.e., std::istream::getline


```
istream& getline(char* s, streamsize n);
istream& getline(char* s, streamsize n, char delim);
```

- Question: Why is there istream in the parameter list of the first version of getline but not in the second version?

Text Files vs. Strings

- Although text files and strings both contain character data, it is important to keep in mind the following important differences between text files and strings:
  - The information stored in a file is permanent. Information stored in a file exists in the external storage until the file is deleted. Strings only live in a certain program while files are exposed to all programs. The value of a string variable persists only as long as the variable does. Local variables disappear when the method returns, and instance variables disappear when the object goes away.
  - Data in files are usually accessed sequentially. When you read data from a file, you usually start at the beginning and read the characters in order, either individually or in groups that are most commonly individual lines. Once you have read one set of characters, you then move on to the next set of characters until you reach the end of the file.

RAM *vs.* Storage





String Streams

- Given that files and strings are both sequences of characters, C++ allows you to treat them symmetrically.
- C++ provides that capability through the <sstream> library, which exports several classes that allow you to associate a stream with a string value in much the same way that the <fstream> library allows you to associate a stream with a file.
- The istringstream class is the counterpart of ifstream and makes it possible to use stream operators to read data from a string.
- For output, the ostringstream class works very much like ofstream except that the output is directed to a string rather than a file.
- A string is a collection of characters, a stream is an object to manipulate a flow of data (e.g., characters), and a string stream is a special stream object that lets you use a string as the source and destination of the flow of data.

String Streams

FIGURE 4-4 Function to read an integer from the console

```
/*
 * Function: getInteger
 * Usage: int n = getInteger(prompt);
 * ----------------------------------
 * Requests an integer value from the user.  The function begins by
 * printing the prompt string on the console and then waits for the
 * user to enter a line of input data.  If that line contains a
 * single integer, the function returns the corresponding integer
 * value.  If the input is not a legal integer or if extraneous
 * characters (other than whitespace) appear on the input line,
 * the implementation gives the user a chance to reenter the value.
 */

int getInteger(string prompt) {
   int value;
   string line;
   while (true) {
      cout << prompt;
      getline(cin, line);
      istringstream stream(line);
      stream >> value >> ws;
      if (!stream.fail() && stream.eof()) break;
      cout << "Illegal integer format. Try again." << endl;
   }
   return value;
}
```

String Streams

```
#include <iostream>
#include <string>
#include <sstream>
using namespace std;

int main()
{
    int i;
    cin >> i;
    cout << "My favorite number is: " << i << endl;
    string s = "My favorite number is: " + to_string(i);
    cout << s << endl;
    stringstream ss;
    ss << "My favorite number is: " << i;
    s = ss.str();
    cout << s << endl;
}
```


Only available since C++ 11.

Input Streams ---------- Output Stream









A B C D E F G H I J …

A B C D E F G H I J …

Standard Input/Output Streams
String Streams
File Streams

```
int main()
{
	ifstream ifile; // file stream objects
	ofstream ofile;
	string ifstr; // string stream objects
	string ofstr;

	string line;
	string name;
	char sex;
	long ID;

	cout << "Enter the input and output file names:" << endl; // system output
	cin >> skipws >> ifstr >> ofstr; // system input

	ifile.open(ifstr.c_str()); // open the input filestream
	ofile.open(ofstr.c_str(), std::ios::out | std::ios::app); // open output file stream
	while (getline(ifile, line)) // read a line from input file
	{
		istringstream iss(line); // create an input string stream using line
		ostringstream oss; // create an output string stream using line
		iss >> skipws >> name >> sex >> ID; // read a string, a char and a long variable from stringstream
		oss << name << "\t" << sex << "\t" << ID << endl; // write this variable to a output stringstream
		ofile << oss.str(); // write the string to an output file
		cout << oss.str(); // we can also output the same thing to system output
	} // Complete the task of reading all lines in the input file。
	ifile.close(); // close the file for other user。
	ofile.close();

	return 0;
}
```

End