


50Ω Wideband 10 MHz to 12 GHz



CASE STYLE: GU1414

The Big Deal

- Extremely Wideband, 10 MHz to 12 GHz
- Very low insertion loss, 0.5 dB
- Excellent VSWR, 1.25:1
- Tiny size, 0.15 x 0.15 x 0.14"

Product Overview

Mini-Circuits' TCBT-123+ is an ultra-wideband surface-mount bias tee covering applications from 10 MHz to 12 GHz with low insertion loss, excellent VSWR, and high DC-RF isolation over its entire frequency range. This model is capable of handling up to +30 dBm (1W) RF input power and DC input current up to 200mA. The unit comes housed in a miniature, shielded package (0.15 x 0.15 x 0.14") with wraparound terminations for excellent solderability.

Key Features

Feature	Advantages
Ultra-wideband, 10 MHz to 12 GHz	Supports a wide range of applications with a single device, including biasing broadband amplifiers, laser diodes, active antennas and more.
Low insertion loss, 0.5 dB	Preserves signal strength from input to output and minimizes overall system loss
Excellent VSWR, 1.25:1	Provides excellent matching for 50Ω systems with minimal signal reflection.
RF power handling up to 1W	This model supports applications with a variety of power requirements.
Excellent DC-RF isolation <ul style="list-style-type: none"> • 55 dB, 10 to 100 MHz • 33 dB, 100 to 6000 MHz • 22 dB, 6000 to 12000 MHz 	Minimizes RF leakage and interference with other elements in the system.
Miniature size, 0.15 x 0.15 x 0.14"	Small footprint makes the TCBT-123+ a space-saver in dense PCB-layouts.

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Surface Mount Bias-Tee

50Ω Wideband 10 MHz to 12 GHz

TCBT-123+


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	30dBm max.
Voltage at DC port	25V max.
Input Current	200mA
Permanent damage may occur if any of these limits are exceeded.	


Pad Terminations

RF	2
RF&DC	1
DC	3
NOT USED	4

Outline Drawing



PCB Land Pattern




Suggested Layout,
Tolerance to be within ±.002

Outline Dimensions (inch)

A	B	C	D	E	F	G	H	J
.150	.150	.14	.025	.100	.043	.030	.050	.087
3.81	3.81	3.56	0.64	2.54	1.09	0.76	1.27	2.21
K	L	M	N	P	Q	R	wt	
.193	.066	0.031	.081	.083	.027	0.013	grams	
4.90	1.68	0.79	2.06	2.11	0.69	0.33		0.06

Demo Board MCL P/N: TB-879+ Suggested PCB Layout (PL-481)



- NOTES:
- COPLANAR WAVEGUIDE PARAMETERS ARE SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .020" ± .0015", COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
 - FOOTPRINT OF C1 IS SHOWN FOR REFERENCE.
 - BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Notes


- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp

Features

- wideband, 10 to 12000 MHz
- low insertion loss, 0.5 dB typ.
- excellent VSWR, 1.25:1 typ.
- miniature surface mount 0.15"x0.15"
- aqueous washable
- protected by US Patent 8,644,029

Applications

- biasing amplifiers
- biasing of laser diodes
- biasing of active antennas



CASE STYLE: GU1414

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Reel Size	Available Tape and Reel at no extra cost
7"	Devices/Reel
13"	10, 20, 50, 100, 200, 500
	1000


Electrical Specifications at 25°C

Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Frequency Range		10		12000	MHz
Insertion Loss	10-100 100-6000 6000-12000	— — —	0.1 0.3 0.8	0.5 0.8 1.6	dB
Isolation	10-100 100-6000 6000-12000	30 18 15	55 33 22	— — —	dB
VSWR	10-100 100-6000 6000-12000		1.05 1.2 1.3	1.3 1.5 1.7	:1

Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB) with current RF & DC-RF	VSWR (:1) with current RF-DC	ISOLATION (dB) 0mA RF & DC - DC
10	0.17	1.25	36.31
100	0.04	1.03	69.24
500	0.06	1.01	59.14
1000	0.09	1.02	52.98
1500	0.09	1.04	46.74
2000	0.11	1.09	42.79
2500	0.10	1.12	39.96
3000	0.10	1.16	36.36
4000	0.12	1.16	31.23
5000	0.17	1.06	29.13
6000	0.23	1.03	27.37
7000	0.36	1.07	23.78
8000	0.28	1.11	22.78
10000	0.26	1.20	23.54
12000	0.75	1.36	20.82




Functional Schematic



Mini-Circuits®

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. OR
M154049
TCBT-123+
ED-15081705
DJ/CP/AM
160324
Page 2 of 3



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

