

Ismod.c File Reference

[Go to the source code of this file.](#)

Kconfigs

ENABLE_FEATURE_2_4_MODULES

ENABLE_FEATURE_CHECK_TAINTED_MODULE

ENABLE_FEATURE_CLEAN_UP

ENABLE_FEATURE_LSMOD_PRETTY_2_6_OUTPUT

ENABLE_UNICODE_SUPPORT

Enumerations

```
enum { TAIN_TPROPRIETARY_MODULE = (1 << 0), TAIN_FORCED_MODULE = (1 << 1), TAIN_UNSAFE_SMP = (1 << 2) }
```

Functions

```
static void check_tainted (void)
```

```
int lsmod_main(int argc, char **argv) MAIN_EXTERNALLY_VISIBLE
```

```
int lsmmod_main (int argc UNUSED_PARAM, char **argv UNUSED_PARAM)
```

Kconfig Documentation

- ◆ `ENABLE_FEATURE_2_4_MODULES`

Name: FEATURE_2_4_MODULES

Type: bool

Default: 0 if (INSMOD || RMMOD || LSMOD)

- archival
- console-tools
- coreutils
- debianutils
- e2fsprogs
- editors
- findutils
- include
- init
- libbb
- libpwdgrp
- loginutils
- mailutils
- miscutils
- ▼ modutils
 - depmod.c
 - insmod.c
 - **lsmod.c**
 - modinfo.c
 - modprobe-small.c
 - modprobe.c
 - modutils-24.c
 - modutils.c
 - modutils.h
 - rmmod.c
- networking
- printutils
- procps
- runit
- scripts
- selinux
- shell
- sysklogd
- util-linux