

File List

- ▶ applets
- ▶ archival
- ▶ console-tools
- ▶ coreutils
- ▶ debianutils
- ▶ e2fsprogs
- ▶ editors
- ▶ findutils
- ▶ include
- ▶ init
- ▶ libbb
- ▶ libpwdgrp
- ▶ loginutils
- ▶ mailutils
- ▶ miscutils
- ▼ modutils
- ▶ depmod.c
- ▶ insmod.c
- ▶ **lsmod.c**
- ▶ modprobe-small.c
- ▶ modprobe.c
- ▶ modutils-24.c
- ▶ modutils.c
- ▶ modutils.h
- ▶ rmmod.c
- ▶ networking
- ▶ printutils
- ▶ procps
- ▶ runit
- ▶ scripts
- ▶ selinux

lsmod.c File Reference

Go to the source code of this file.

Kconfigs

- ENABLE_FEATURE_2_4_MODULES
- ENABLE_FEATURE_ASSUME_UNICODE
- ENABLE_FEATURE_CHECK_TAINTED_MODULE
- ENABLE_FEATURE_CLEAN_UP
- ENABLE_FEATURE_LSMOD_PRETTY_2_6_OUTPUT

Enumerations

```
enum { Taint_Proprietary_Module = (1 << 0) , Taint_Forced_Module = (1 << 1) ,
       Taint_Unsafe_Smp = (1 << 2) }
```

Functions

```
static void check_tainted(void)
int lsmod_main(int argc, char **argv) MAIN_EXTERNALLY_VISIBLE
int lsmod_main(int argc UNUSED_PARAM, char **argv UNUSED_PARAM)
```

Kconfig Documentation

- ◆ ENABLE_FEATURE_2_4_MODULES

▼ File List

- ▶ applets
- ▶ archival
- ▶ console-tools
- ▶ coreutils
- ▶ debianutils
- ▶ e2fsprogs
- ▶ editors
- ▶ findutils
- ▶ include
- ▶ init
- ▶ libbb
- ▶ libpwdgrp
- ▶ loginutils
- ▶ mailutils
- ▶ miscutils
- ▼ modutils
 - ▶ depmod.c
 - ▶ insmod.c
 - ▶ **lsmod.c**
 - ▶ modprobe-small.c
 - ▶ modprobe.c
 - ▶ modutils-24.c
 - ▶ modutils.c
 - ▶ modutils.h
 - ▶ rmmod.c
- ▶ networking
- ▶ printutils
- ▶ procps
- ▶ runit
- ▶ scripts
- ▶ selinux
- ▶ shell
- ▶ sysklogd
- ▶ util-linux
- ▶ File Members



◆ ENABLE_FEATURE_2_4_MODULES

Name: FEATURE_2_4_MODULES

Type: bool

Default: 0 if (INSMOD || RMMOD || LSMOD)

Prompt: "Support version 2.2/2.4 Linux kernels" if (INSMOD || RMMOD || LSMOD)

Depends on: (INSMOD || RMMOD || LSMOD)

Help:

Support module loading for 2.2.x and 2.4.x Linux kernels.
This increases size considerably. Say N unless you plan
to run ancient kernels.

Defined at line 115 of file modutils/Config.in.

Used at line **57** of file **modutils/lsmod.c**.

◆ ENABLE_FEATURE_ASSUME_UNICODE

Name: FEATURE_ASSUME_UNICODE

Type: bool

Default: 0

Prompt: "Support Unicode"

Help:

This makes various applets aware that one byte is not
one character on screen.

Busybox aims to eventually work correctly with Unicode displays.
Any older encodings are not guaranteed to work.
Probably by the time when busybox will be fully Unicode-clean,
other encodings will be mainly of historic interest.

Defined at line 122 of file Config.in.

- ▶ findutils
- ▶ include
- ▶ init
- ▶ libbb
- ▶ libpwdgrp
- ▶ loginutils
- ▶ mailutils
- ▶ miscutils
- ▼ modutils
 - ▶ depmod.c
 - ▶ insmod.c
 - ▶ lsmod.c
 - ▶ modprobe-small.c
 - ▶ modprobe.c
 - ▶ modutils-24.c
 - ▶ modutils.c
 - ▶ modutils.h
 - ▶ rmmod.c
- ▶ networking
- ▶ printutils
- ▶ procps
- ▶ runit
- ▶ scripts
- ▶ selinux
- ▶ shell
- ▶ sysklogd
- ▶ util-linux
- ▶ File Members

other encodings will be mainly of historic interest.

Defined at line 122 of file Config.in.

Used at lines **49**, **66** and **80** of file **modutils/lsmod.c**.

◆ ENABLE_FEATURE_CHECK_TAINTED_MODULE

Name: FEATURE_CHECK_TAINTED_MODULE

Type: bool

Default: 1 if ((LSMOD || FEATURE_2_4_MODULES) && !MODPROBE_SMALL)

Prompt: "Support tainted module checking with new kernels" if ((LSMOD || FEATURE_2_4_MODULES) && !MODPROBE_SMALL)

Depends on: ((LSMOD || FEATURE_2_4_MODULES) && !MODPROBE_SMALL)

Help:

Support checking for tainted modules. These are usually binary only modules that will make the linux-kernel list ignore your support request.

This option is required to support GPLONLY modules.

Defined at line 189 of file modutils/Config.in.

Used at line **13** of file **modutils/lsmod.c**.

◆ ENABLE_FEATURE_CLEAN_UP

- File List
- ▶ applets
 - ▶ archival
 - ▶ console-tools
 - ▶ coreutils
 - ▶ debianutils
 - ▶ e2fsprogs
 - ▶ editors
 - ▶ findutils
 - ▶ include
 - ▶ init
 - ▶ libbb
 - ▶ libpwdgrp
 - ▶ loginutils
 - ▶ mailutils
 - ▶ miscutils
 - ▼ modutils
 - ▶ depmod.c
 - ▶ insmod.c
 - ▶ lsmod.c
 - ▶ modprobe-small.c
 - ▶ modprobe.c
 - ▶ modutils-24.c
 - ▶ modutils.c
 - ▶ modutils.h
 - ▶ rmmod.c
 - ▶ networking
 - ▶ printutils
 - ▶ procs
 - ▶ runit
 - ▶ scripts
 - ▶ selinux
 - ▶ shell
 - ▶ sysklogd
 - ▶ util-linux

◆ ENABLE_FEATURE_CLEAN_UP

Name: FEATURE_CLEAN_UP

Type: bool

Default: 0

Prompt: "Clean up all memory before exiting (usually not needed)"

Help:

As a size optimization, busybox normally exits without explicitly freeing dynamically allocated memory or closing files. This saves space since the OS will clean up for us, but it can confuse debuggers like valgrind, which report tons of memory and resource leaks.

Don't enable this unless you have a really good reason to clean things up manually.

Defined at line 161 of file Config.in.

Used at lines **26** and **89** of file **modutils/lsmod.c**.

◆ ENABLE_FEATURE_LSMOD_PRETTY_2_6_OUTPUT

Name: FEATURE_LSMOD_PRETTY_2_6_OUTPUT

Type: bool

Default: 0 if (LSMOD)

Prompt: "Pretty output" if (LSMOD)

Depends on: (LSMOD)

Help:

This option makes output format of lsmod adjusted to the format of module-init-tools for Linux kernel 2.6.
Increases size somewhat.

- ▶ editors
- ▶ findutils
- ▶ include
- ▶ init
- ▶ libbb
- ▶ libpwdgrp
- ▶ loginutils
- ▶ mailutils
- ▶ miscutils
- ▼ modutils
 - ▶ depmod.c
 - ▶ insmod.c
 - ▶ **lsmod.c**
 - ▶ modprobe-small.c
 - ▶ modprobe.c
 - ▶ modutils-24.c
 - ▶ modutils.c
 - ▶ modutils.h
 - ▶ rmmod.c
- ▶ networking
- ▶ printutils
- ▶ procps
- ▶ runit
- ▶ scripts
- ▶ selinux
- ▶ shell
- ▶ sysklogd
- ▶ util-linux

This option makes output format of lsmod adjusted to the format of module-init-tools for Linux kernel 2.6.
Increases size somewhat.

Defined at line 76 of file modutils/Config.in.

Used at line 46 of file **modutils/lsmod.c**.

Enumeration Type Documentation

◆ anonymous enum

anonymous enum

Enumerator

TAINT_PROPRIETARY_MODULE

TAINT_FORCED_MODULE

TAINT_UNSAFE_SMP

Definition at line 14 of file **lsmod.c**.

Function Documentation

- ▶ findutils
- ▶ include
- ▶ init
- ▶ libbb
- ▶ libpwdgrp
- ▶ loginutils
- ▶ mailutils
- ▶ miscutils
- ▼ modutils
 - ▶ depmod.c
 - ▶ insmod.c
 - ▶ **lsmod.c**
 - ▶ modprobe-small.c
 - ▶ modprobe.c
 - ▶ modutils-24.c
 - ▶ modutils.c
 - ▶ modutils.h
 - ▶ rmmod.c
- ▶ networking
- ▶ printutils
- ▶ procps
- ▶ runit
- ▶ scripts
- ▶ selinux
- ▶ shell
- ▶ syslogd
- ▶ util-linux
- ▶ File Members

Function Documentation

◆ check_tainted()

```
static void check_tainted ( void  )
```

static

Definition at line **20** of file **lsmod.c**.

◆ lsmod_main() [1/2]

```
int lsmod_main ( int argc    UNUSED_PARAM,  
                char **argv UNUSED_PARAM  
                )
```

Definition at line **44** of file **lsmod.c**.

◆ lsmod_main() [2/2]

```
int lsmod_main ( int    argc,  
                char ** argv  
                )
```