



Compiler construction

Lecture 4: Code generation for LLVM

Alex Gerdes

Vårtermin 2016

Chalmers University of Technology — Gothenburg University

LLVM modules



A LLVM compilation unit (a module) consists of a sequence of:

- type definitions
- global variable definitions
- function definitions
- (external) function declarations

Also global variables may be declared, rather than defined.

This is not necessary for JAVALETTE; the only use of global variables is for naming string literals (as arguments to `@printfString`).

Basic blocks in LLVM



Recall

A basic block starts with a label and ends with a terminating instruction (`ret` or `br`).

Thus one cannot 'fall through' the end of a block into the next; an explicit branch to (the label of) the next instruction is necessary.

Basic blocks in LLVM




Recall

A basic block starts with a label and ends with a terminating instruction (`ret` or `br`).

Thus one cannot 'fall through' the end of a block into the next; an explicit branch to (the label of) the next instruction is necessary.

Consequence

The basic blocks of a LLVM function definition can be reordered arbitrarily; a function body is a graph of basic blocks (the control flow graph).



Compilation to LLVM



General observations

- Compilation schemes described for JVM (in the PLT course) often easily modified
- Local variables and parameters should be treated as memory locations (`alloca/load/store` instructions)
- These will be removed by `opt` (and new memory references maybe introduced during register allocation)


Code generation for variables, 1



There are no nested scopes in LLVM. Thus JAVALETTE variables may need to be renamed.

Example

```
int main () {
    int x = 5;
    int y = 3;
    while (x > 0) {
        int y = x;
        printInt(y);
        x--;
    }
    printInt(y);
    return 0;
}
```



Optimizing code from previous slide



```
> opt -std-compile-opts a.ll | llvmdisasm

; ModuleID = '<stdin>'
declare void @printInt(i32)

define i32 @main() {
entry:
  tail call void @printInt(i32 5)
  tail call void @printInt(i32 4)
  tail call void @printInt(i32 3)
  tail call void @printInt(i32 2)
  tail call void @printInt(i32 1)
  tail call void @printInt(i32 3)
  ret i32 0
}
```

Code generation for variables, 2



- When a variable declaration is seen:
 - generate a (possibly) new name
 - generate `alloca` instruction
 - save (JAVALETTE name, LLVM name) pair in lookup table in the code generator
- Keep track of scope in lookup table
- In assignment statement, `store` value of RHS using the LLVM name
- When a variable is seen (in an expression), `load` from memory using the LLVM name
- Similar considerations for parameters

Code generation for variables, alternative



Use α -renaming to convert each variable to a fresh variable. Some compilers include an α -renaming phase to rename all program variables such that variable names become unique. (This may simplify subsequent compiler phases.)

Before

```
int main () {
  int x = 5;
  int y = 3;
  while (x > 0) {
    int y = x;
    printInt(y);
    x--;
  }
  printInt(y);
  return 0;
}
```

After

```
int main () {
  int v1 = 5;
  int v2 = 3;
  while (v1 > 0) {
    int v3 = v1;
    printInt(v3);
    v1--;
  }
  printInt(v2);
  return 0;
}
```

Types of local and global variables



Local variables

The instruction

```
%x = alloca i32
```

introduces a new variable `%x` of type `i32*`

`%x` is a pointer to a newly allocated memory location on the stack.

Types of local and global variables



Local variables

The instruction

```
%x = alloca i32
```

introduces a new variable `%x` of type `i32*`

`%x` is a pointer to a newly allocated memory location on the stack.

Global variables

The instruction

```
@hw = global [13 x i8] c"hello world\0A\00"
```

introduces a global name `@hw` of type `[13 x i8]*`

`@hw` is a pointer to a byte array.

Treatment of labels



Labels are not instructions in LLVM

But it may be convenient for you to treat them as if they were!

Basic blocks without instructions are illegal

Depending on your compilation schemes, you may find yourself in the situation that a label has just been emitted and the function ends without further instructions.

Treatment of labels



Labels are not instructions in LLVM

But it may be convenient for you to treat them as if they were!

Basic blocks without instructions are illegal

Depending on your compilation schemes, you may find yourself in the situation that a label has just been emitted and the function ends without further instructions.

The situation can then be saved by emitting the terminator instruction `unreachable`.

The `getelementptr` instruction



From reference manual

The `getelementptr` instruction is used to get the address of a subelement of an aggregate data structure. It performs address calculation only and does not access memory.

Instruction arguments

First argument is always a pointer to the beginning of the structure; the following are integers specifying the subelement.

Example type

```
%T = type
{ i32,
  [4 x i32],
  [8 x i32]
}*
```

Example use

```
define i32 @f (%T %x) {
  %p = getelementptr %T %x,
    i32 0, i32 1, i32 1, i32 7
  %res = load i32* %p
  ret i32 %res
}
```

Another `getelementptr` example



```
@mat = global [3 x [4 x i32]]
        [[4 x i32] [i32 1, i32 2, i32 3, i32 4],
         [4 x i32] [i32 5, i32 6, i32 7, i32 8],
         [4 x i32] [i32 9, i32 10, i32 11, i32 12]]

declare void @printInt(i32)

define i32 @main () {
  %t1 = getelementptr [3 x [4 x i32]]* @mat,
    i32 0, i32 1, i32 2
  %t2 = load i32* %t1
  call void @printInt(i32 %t2)
  ret i32 0
}
```

Executing this program prints 7. Note type of `@mat`.

Yet another `getelementptr` example



```
%T1 = type {i32, {[4 x i32]*, [8 x i32]*}}*

define i32 @g (%T1 %x) {
  %p = getelementptr %T1 %x, i32 0, i32 1, i32 1
  %p1 = load [ 8 x i32 ]** %p
  %p2 = getelementptr [ 8 x i32 ]* %p1, i32 0, i32 7
  %res = load i32* %p2
  ret i32 %res
}
```

`@g` returns the last element of the 8-element array in `%x`.

We can not do this with just one `getelementptr` instruction; we need to access memory to get the pointer to the array.

Why the first 0?



```
struct Pair {
  int x, y;
};

int f(struct Pair *p) {
  return p[0].y + p[1].x;
}
```

Why the first 0?



```
struct Pair {
  int x, y;
};

int f(struct Pair *p) {
  return p[0].y + p[1].x;
}

%Pair = type { i32, i32 }
define i32 @f(%Pair* %p) {
entry: %t1 = getelementptr %Pair* %p, i32 0, i32 1
       %t2 = load i32* %t1
       %t3 = getelementptr %Pair* %p, i32 1, i32 0
       %t4 = load i32* %t3
       %t5 = add i32 %t2, %t4
       ret i32 %t5
}
```

Computing the size of a type



Size of a variable

With the size of a type `%T`, we mean the size (in bytes) of a variable of type `%T`. For a given LLVM type `%T`, this size can vary between target architectures (e.g. pointer types differ in size). So, how does one write portable code?

LLVM does not have a correspondence to C's `sizeof` macro.

Computing the size of a type



Size of a variable

With the size of a type `%T`, we mean the size (in bytes) of a variable of type `%T`. For a given LLVM type `%T`, this size can vary between target architectures (e.g. pointer types differ in size). So, how does one write portable code?

LLVM does not have a correspondence to C's `sizeof` macro.

The trick

We use the `getelementptr` instruction:

```
%p = getelementptr %T* null, i32 1
%s = ptrtoint %T* %p to i32
```

Now, `%s` holds the size of `%T`. Why?

Treatment of string literals



- String literals occur in JAVALETTE only as argument to `@printString`
- When you encounter such a string you must introduce a definition that gives the string literal a global name
- Such a definition must not appear in the middle of the current function (recall the 'hello world' program)
- The type of a global variable is `[n x i8]*`, where `n` is the length of the string (after padding at the end)
- `@printString` is called with a global variable as argument

Quiz

What is the type of the parameter to `@printString`?

```
declare void @printString( ? )
```

String literals, 2



Answer

- We cannot let the parameter type be `[n x i8]*`, since `n` varies
- Let instead the parameter type be `i8*`, a pointer to the first byte
- How can we then call `@printString` in a type-correct way?

String literals, 2



Answer

- We cannot let the parameter type be `[n x i8]*`, since `n` varies
- Let instead the parameter type be `i8*`, a pointer to the first byte
- How can we then call `@printString` in a type-correct way?

We use `getelementptr` to get a pointer to the first byte of the string (i.e. to the same address, but the type will change).

```
@hw = internal constant [13 x i8] c"hello world\0A\00"
declare void @printString(i8*)

define i32 @main () {
entry: %t1 = getelementptr [13 x i8]* @hw, i32 0, i32 0
call void @printString(i8* %t1)
ret i32 0
}
```

State during code generation



We need to keep some state information during code generation. This includes at least:

- next number for generating register names (and labels)
- definitions of global names for string literals
- lookup table to find LLVM name for JAVALETTE variable name
- lookup table to find type of function

Further properties of functions



In function definitions

- Linkage type, for example: `private`, `internal`
- Attributes, for example: `readnone`, `readonly`, `nounwind`
- Calling convention, for example: `ccc`, `fastcc`

In function calls

- Tail call indication
- Attributes
- Calling convention

Final example



JAVALETTE code

```
boolean even(int n) {  
    if (n == 0)  
        return true;  
    else  
        return odd (n - 1);  
}  
boolean odd(int n) {  
    if (n == 0)  
        return false;  
    else  
        return even (n - 1);  
}
```

JAVALETTE code

```
int main () {  
    if (even (20))  
        printString("Even!");  
    else  
        printString("Odd!");  
    return 0;  
}
```

To be done in class

- Write naive LLVM code
- Send it through `opt` to get better code