

MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

Maximum Relevancy, Minimum Redundancy

Michael Matějů

AI Squad

July 28, 2023



Outline

MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

Motivation

2 Introduction

MRMR Explained



Motivation

MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

- Mirek Pavelka point this algorithm to me
- Recent popularity of the algorithm due to UBER's paper (2019).



Motivation

MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

- Mirek Pavelka point this algorithm to me
- Recent popularity of the algorithm due to UBER's paper (2019).



MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained End of Story

MRMR

- Filter Methods: Feature selection is made as part of the pre-processing, that is, before we train a model. We filter out features that perform poorly based on some criteria (e.g. correlation).
- Wrapper Methods: Iteratively choose a subset of features, train your model, and choose the best combination. Very time consuming.
- Embedded Methods: Embedded methods take advantage of the feature importance estimations which are embedded in the algorithm. E.g. Random Forest.



MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

- Filter Methods: Feature selection is made as part of the pre-processing, that is, before we train a model. We filter out features that perform poorly based on some criteria (e.g. correlation).
- Wrapper Methods: Iteratively choose a subset of features, train your model, and choose the best combination. Very time consuming.
- Embedded Methods: Embedded methods take advantage of the feature importance estimations which are embedded in the algorithm. E.g. Random Forest.



MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained End of Story

- Filter Methods: Feature selection is made as part of the pre-processing, that is, before we train a model. We filter out features that perform poorly based on some criteria (e.g. correlation).
- Wrapper Methods: Iteratively choose a subset of features, train your model, and choose the best combination. Very time consuming.
- Embedded Methods: Embedded methods take advantage



MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained End of Story

- Filter Methods: Feature selection is made as part of the pre-processing, that is, before we train a model. We filter out features that perform poorly based on some criteria (e.g. correlation).
- Wrapper Methods: Iteratively choose a subset of features, train your model, and choose the best combination. Very time consuming.
- Embedded Methods: Embedded methods take advantage of the feature importance estimations which are embedded in the algorithm. E.g. Random Forest.



Cheat Sheet


MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained





MRMR

MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

MRMR works iteratively. At each iteration, it identifies the best feature (according to a rule) and adds it to the basket of selected features. Once a feature goes into the bucket, it cannot ever come out.

In each iteration i a score is computed for each feature f according to formula:

$$score_i(f) = \frac{relevance(f|target)}{redundancy(f|features selected until (i-1))}$$

where we have to specify the relevancy and redundancy functions.



MRMR

MRMR

Michael Matějů

 ${\sf Motivation}$

Introduction

MRMR Explained

End of Story

MRMR works iteratively. At each iteration, it identifies the best feature (according to a rule) and adds it to the basket of selected features. Once a feature goes into the bucket, it cannot ever come out.

In each iteration i a score is computed for each feature f according to formula:

$$score_i(f) = \frac{relevance(f|target)}{redundancy(f| \text{features selected until } (i-1))}$$

where we have to specify the relevancy and redundancy functions.



MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

There are couple of variants to calculate the feature importance from the original UBER paper. For discrete features:

Mutual Information Difference (MID):

$$f^{MID}(X_i) = I(Y, X_i) - \frac{1}{|S|} \sum_{X_s \in S} I(X_s, X_i)$$

Mutual Information Quotient (MIQ):

$$f^{MID}(X_i) = I(Y, X_i) / \left(\frac{1}{|S|} \sum_{X_s \in S} I(X_s, X_i)\right]$$



MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

There are couple of variants to calculate the feature importance from the original UBER paper. For discrete features:

Mutual Information Difference (MID):

$$f^{MID}(X_i) = I(Y, X_i) - \frac{1}{|S|} \sum_{X_s \in S} I(X_s, X_i)$$

Mutual Information Quotient (MIQ):

$$f^{MID}(X_i) = I(Y, X_i) / \left(\frac{1}{|S|} \sum_{X_s \in S} I(X_s, X_i)\right)$$



MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

For continues features:

F-test Correlation Difference (FCD):

$$f^{MID}(X_i) = F(Y, X_i) - \frac{1}{|S|} \sum_{X_s \in S} \rho(X_s, X_i)$$

• F-test Correlation Quotient (FCQ):

$$f^{MID}(X_i) = F(Y, X_i) / \left(\frac{1}{|S|} \sum_{X_s \in S} \rho(X_s, X_i)\right]$$

where ρ is Pearson correlation.



MRMR

Michael Matějů

 ${\sf Motivation}$

Introduction

MRMR Explained

End of Story

For continues features:

• F-test Correlation Difference (FCD):

$$f^{MID}(X_i) = F(Y, X_i) - \frac{1}{|S|} \sum_{X_s \in S} \rho(X_s, X_i)$$

F-test Correlation Quotient (FCQ):

$$f^{MID}(X_i) = F(Y, X_i) / \left(\frac{1}{|S|} \sum_{X_s \in S} \rho(X_s, X_i)\right]$$

where ρ is Pearson correlation.



MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

Another extensions:

- RDC algorithm for redundancy function (The randomized dependence coefficient)
- Model-based Feature importance for relevance:
 - Random Forest Correlation Quotient
 - Random Forest RDC Quotient
 - Pure Random Forest

From benchmarks, RF variances are good if down-stream model is Random Forest. FCQ is pretty close and works on more models.



MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

Another extensions:

- RDC algorithm for redundancy function (The randomized dependence coefficient)
- Model-based Feature importance for relevance:
 - Random Forest Correlation Quotient
 - Random Forest RDC Quotient
 - Pure Random Forest

From benchmarks, RF variances are good if down-stream model is Random Forest. FCQ is pretty close and works on more models.



MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

Another extensions:

- RDC algorithm for redundancy function (The randomized dependence coefficient)
- Model-based Feature importance for relevance:
 - Random Forest Correlation Quotient
 - Random Forest RDC Quotient
 - Pure Random Forest

From benchmarks, RF variances are good if down-stream model is Random Forest. FCQ is pretty close and works on more models.



Example

MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story




Illustration of what happens at iteration 3. [Figure by Author]



The End

MRMR

Michael Matějů

Motivation

Introduction

MRMR Explained

End of Story

Thank you for your attention and patience.