```
Last login: Fri Oct 16 15:45:20 on ttys013
nisha.singh@WPNWCC6CWQ backend % cd ..
nisha.singh@WPNWCC6CWQ services % cd ..
nisha.singh@WPNWCC6CWQ trustbank-ai % node --version
v20.15.1
nisha.singh@WPNWCC6CWQ trustbank-ai % nvm use 22.22.3
Now using node v22.22.3 (npm v10.9.8)
nisha.singh@WPNWCC6CWQ trustbank-ai % cd apps/banking-web
nisha.singh@WPNWCC6CWQ banking-web % npm ci

added 284 packages, and audited 285 packages in 9s

84 packages are looking for funding
  run `npm fund` for details

found 0 vulnerabilities
nisha.singh@WPNWCC6CWQ banking-web % npm run build

> banking-web@0.0.0 build
> ng build

Initial chunk files | Names                |  Raw size | Estimated transfer size
main-ECT7WOPT.js    | main                 | 276.93 kB |                76.52 kB
styles-RJOX3PSV.css | styles               |   5.99 kB |                 1.70 kB

                    | Initial total        | 282.92 kB |                78.22 kB

Lazy chunk files    | Names                |  Raw size | Estimated transfer size
chunk-ebINjTTC.js   | transaction-page     | 498.24 kB |               133.27 kB
chunk-BbdDm0g7.js   | pay-status           |  22.23 kB |                 6.34 kB
chunk-9bES4dir.js   | pay-form             |   8.96 kB |                 2.90 kB
chunk-Cjjpv1Pd.js   | landing              |   5.72 kB |                 2.20 kB
chunk-BIr7Xkh6.js   | -                    |   4.59 kB |                 1.97 kB
chunk-CiiSSKt1.js   | investigation-shell  |   4.56 kB |                 1.61 kB
chunk-KklfS0wT.js   | entry                |   4.09 kB |                 1.64 kB
chunk-DlsZz8ED.js   | -                    |   3.70 kB |                 1.49 kB
chunk-COWvy8t8.js   | home                 |   2.58 kB |                 1.21 kB
chunk-CSS7m9D1.js   | customer-routes      |   1.83 kB |               862 bytes
chunk-CvAOvdUQ.js   | investigation-routes |   1.52 kB |               704 bytes
chunk-4u2CYD7O.js   | -                    | 831 bytes |               831 bytes
chunk-B0_8tRTG.js   | -                    | 682 bytes |               682 bytes

Application bundle generation complete. [3.386 seconds] - 2026-10-16T12:28:03.563Z

Output location: /Users/nisha.singh/dev/trustbank-ai/apps/banking-web/dist/banking-web

nisha.singh@WPNWCC6CWQ banking-web % cd ../..
nisha.singh@WPNWCC6CWQ trustbank-ai % firebase hosting:channel:deploy preview --expires 7d
zsh: command not found: firebase
nisha.singh@WPNWCC6CWQ trustbank-ai % npm install -g firebase-tools
npm warn deprecated node-domexception@1.0.0: Use your platform's native DOMException instead
npm warn deprecated json-ptr@3.1.1: Package no longer supported. Contact Support at https://www.npmjs.com/support for more info.
npm warn deprecated uuid@9.0.1: uuid@10 and below is no longer supported.  For ESM codebases, update to uuid@latest.  For CommonJS codebases, use uuid@11 (but be aware this version wil
l likely be deprecated in 2028).
npm warn deprecated glob@10.5.0: Old versions of glob are not supported, and contain widely publicized security vulnerabilities, which have been fixed in the current version. Please up
date. Support for old versions may be purchased (at exorbitant rates) by contacting i@izs.me

added 632 packages in 18s

99 packages are looking for funding
  run `npm fund` for details
nisha.singh@WPNWCC6CWQ trustbank-ai % firebase login
Already logged in as nisha.singh@apree.health
nisha.singh@WPNWCC6CWQ trustbank-ai % firebase logout
✔  Logged out from nisha.singh@apree.health
nisha.singh@WPNWCC6CWQ trustbank-ai % firebase login
i  The Firebase CLI's MCP server feature can optionally make use of Gemini in Firebase. Learn more about Gemini in Firebase and how it uses your data: https://firebase.google.com/docs/
gemini-in-firebase#how-gemini-in-firebase-uses-your-data
✔ Enable Gemini in Firebase features? Yes

i  Firebase optionally collects CLI and Emulator Suite usage and error reporting information to help improve our products. Data is collected in accordance with Google's privacy policy
(https://policies.google.com/privacy) and is not used to identify you.
✔ Allow Firebase to collect CLI and Emulator Suite usage and error reporting information? Yes

i  To change your preferences at any time, run `firebase logout` and `firebase login` again.

Visit this URL on this device to log in:
https://accounts.google.com/o/oauth2/auth?client_id=563584335869-fgrhgmd47bqnekij5i8b5pr03ho849e6.apps.googleusercontent.com&scope=email%20openid%20https%3A%2F%2Fwww.googleapis.com%2Fa
uth%2Fcloudplatformprojects.readonly%20https%3A%2F%2Fwww.googleapis.com%2Fauth%2Ffirebase%20https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fcloud-platform&response_type=code&state=67344998&r
edirect_uri=http%3A%2F%2Flocalhost%3A9005

Waiting for authentication...

✔  Success! Logged in as teamdynaminds3@gmail.com
nisha.singh@WPNWCC6CWQ trustbank-ai % firebase hosting:channel:deploy preview --expires 7d
✔  hosting:channel: Channel preview has been created on site trustbank-pausepay.

=== Deploying to 'project-b63ed173-f777-4777-81a'...

i  deploying hosting
i  hosting[trustbank-pausepay]: beginning deploy...
i  hosting[trustbank-pausepay]: found 17 files in apps/banking-web/dist/banking-web/browser
✔  hosting[trustbank-pausepay]: file upload complete
i  hosting[trustbank-pausepay]: finalizing version...
✔  hosting[trustbank-pausepay]: version finalized
i  hosting[trustbank-pausepay]: releasing new version...
✔  hosting[trustbank-pausepay]: release complete

✔  Deploy complete!

Project Console: https://console.firebase.google.com/project/project-b63ed173-f777-4777-81a/overview
Hosting URL: https://trustbank-pausepay.web.app
⚠  hosting:channel: Unable to add channel domain to Firebase Auth. Visit the Firebase Console at https://console.firebase.google.com/project/project-b63ed173-f777-4777-81a/authenticati
on/providers


⚠  hosting:channel: Unable to sync Firebase Auth state.

✔  hosting:channel: Channel URL (trustbank-pausepay): https://trustbank-pausepay--preview-81mo86wa.web.app [expires 2026-10-23 18:01:52] [version 430d1e9ef62744ad]
nisha.singh@WPNWCC6CWQ trustbank-ai % firebase deploy --only hosting

=== Deploying to 'project-b63ed173-f777-4777-81a'...

i  deploying hosting
i  hosting[trustbank-pausepay]: beginning deploy...
i  hosting[trustbank-pausepay]: found 17 files in apps/banking-web/dist/banking-web/browser
✔  hosting[trustbank-pausepay]: file upload complete
i  hosting[trustbank-pausepay]: finalizing version...
✔  hosting[trustbank-pausepay]: version finalized
i  hosting[trustbank-pausepay]: releasing new version...
✔  hosting[trustbank-pausepay]: release complete

✔  Deploy complete!

Project Console: https://console.firebase.google.com/project/project-b63ed173-f777-4777-81a/overview
Hosting URL: https://trustbank-pausepay.web.app
nisha.singh@WPNWCC6CWQ trustbank-ai % cd /Users/nisha.singh/dev/trustbank-ai/services/backend
```

```
.venv/bin/ruff check .
.venv/bin/mypy src tests
.venv/bin/pytest -q
F401 [*] `typing.Self` imported but unused
 --> src/trustbank/config.py:2:20
  |
1 | from functools import lru_cache
2 | from typing import Self
  |                    ^^^^
3 |
4 | from pydantic import Field, SecretStr, model_validator
  |
help: Remove unused import: `typing.Self`
  |
1 | from functools import lru_cache
  - from typing import Self
2 |
  |

Found 1 error.
[*] 1 fixable with `--fix`.
src/trustbank/config.py:78: error: "tuple[str, ...]" has no attribute "split"  [attr-defined]
src/trustbank/api/security.py:10: error: Cannot find implementation or library stub for module named "jwt"  [import-not-found]
src/trustbank/api/security.py:10: note: See https://mypy.readthedocs.io/en/stable/running_mypy.html#missing-imports
src/trustbank/api/security.py:28: error: "Settings" has no attribute "customer_token_hours"  [attr-defined]
src/trustbank/api/security.py:30: error: "Settings" has no attribute "investigator_token_minutes"; maybe "investigator_rate_limit"?  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "ComponentStatus"  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "CustomerAuthIn"  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "HealthOut"; maybe "Health"?  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "InvestigatorAuthIn"  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "InvestigatorSessionOut"; maybe "InvestigatorSession"?  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "MeOut"  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "PersonaOut"; maybe "Persona"?  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "RecipientLookupOut"; maybe "RecipientLookup"?  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "RecipientOut"  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "TokenOut"  [attr-defined]
src/trustbank/api/routes.py:10: error: Module "trustbank.api.schemas" has no attribute "TransactionOut"  [attr-defined]
src/trustbank/api/routes.py:53: error: "DatasetRepository" has no attribute "ping"  [attr-defined]
src/trustbank/api/routes.py:79: error: "DatasetRepository" has no attribute "list_demo_personas"; maybe "demo_personas"?  [attr-defined]
src/trustbank/api/routes.py:158: error: "DatasetRepository" has no attribute "find_beneficiary_by_handle"; maybe "beneficiary_by_handle"?  [attr-defined]
src/trustbank/api/routes.py:160: error: "DatasetRepository" has no attribute "find_beneficiary_by_account_number"  [attr-defined]
src/trustbank/ingest.py:6: error: Module "trustbank.graph" has no attribute "GraphStore"  [attr-defined]
src/trustbank/ingest.py:6: error: Module "trustbank.graph" has no attribute "create_driver"  [attr-defined]
tests/test_anomaly.py:140: error: Missing named argument "account_number" for "Account"  [call-arg]
Found 22 errors in 5 files (checked 71 source files)
.............................FFF.....................................................................................................................................................  [ 84%]
.........................                                                                                                                                                 [100%]
================================================================================ FAILURES =================================================================================
_____________________________________________ test_detector_failure_is_recorded_and_the_other_detector_still_reports _____________________________________________

    def test_detector_failure_is_recorded_and_the_other_detector_still_reports() -> None:
        result, sink = run(_Reader(history([1000] * 6), fail=True))
>       assert result.anomaly.status == "FAILED" and "ConnectionError" in (result.anomaly.error or "")
E       AssertionError: assert ('FAILED' == 'FAILED'
E
E           FAILED and 'ConnectionError' in (('ValidationError: 1 validation error for Account')))
E         +  where 'ValidationError: 1 validation error for Account' = AgentFinding(agent_id='anomaly', status='FAILED', score=0, confidence=0.0, evidence=[], error='ValidationError: 1
validation error for Account').error
E         +    where AgentFinding(agent_id='anomaly', status='FAILED', score=0, confidence=0.0, evidence=[], error='ValidationError: 1 validation error for Account') = DetectorResult(an
omaly=AgentFinding(agent_id='anomaly', status='FAILED', score=0, confidence=0.0, evidence=[], error='...nError', started_at=datetime.datetime(2026, 10, 16, 12, 41, 34, 991882, tzinfo=d
atetime.timezone.utc), duration_ms=0)]).anomaly

tests/test_anomaly.py:179: AssertionError
_____________________________________________ test_detector_timeout_is_recorded _____________________________________________

    def test_detector_timeout_is_recorded() -> None:
        orch = AdkOrchestrator(
            model=scripted(),
            graph=cast(GraphService, _Graph()),
            history=_Reader(history([1000] * 6), delay=1.0),
            detector_timeout=0.1,
        )
        ctx = PaymentContext(payment_id="p", customer_id="c", beneficiary_id="b", amount=900, now=NOW)

        async def timed() -> tuple[Any, float]:
            started = time.perf_counter()
            result = await orch.run_detectors(ctx, Sink())
            return result, time.perf_counter() - started

        result, elapsed = asyncio.run(timed())
        assert elapsed < 0.9
>       assert result.anomaly.status == "TIMEOUT" and result.anomaly.score == 0
E       AssertionError: assert ('FAILED' == 'TIMEOUT'
E
E         - TIMEOUT
E         + FAILED)

tests/test_anomaly.py:201: AssertionError
_____________________________________________ test_successful_run_records_tool_calls _____________________________________________

    def test_successful_run_records_tool_calls() -> None:
        result, sink = run(_Reader(history([1000] * 6)))
        tools = [c.tool for c in result.tool_calls if c.agent_id == "anomaly"]
>       assert tools == [
            "load_customer", "load_account", "load_history", "amount_deviation",
            "recipient_familiarity", "frequency_burst", "time_of_day_shift",
        ]  # fmt: skip
E       AssertionError: assert ['load_custom...load_account'] == ['load_custom...y_burst', ...]
E
E         Right contains 5 more items, first extra item: 'load_history'
E         Use -v to get more diff

tests/test_anomaly.py:208: AssertionError
============================================================================== warnings summary ===============================================================================
.venv/lib/python3.12/site-packages/fastapi/testclient.py:1
  /Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/fastapi/testclient.py:1: StarletteDeprecationWarning: Using `httpx` with `starlette.testclient
` is deprecated; install `httpx2` instead.
    from starlette.testclient import TestClient as TestClient  # noqa

tests/test_investigation.py::test_assessments_are_immutable
  /Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/cloud/firestore_v1/base_collection.py:317: UserWarning: Detected filter using positiona
l arguments. Prefer using the 'filter' keyword argument instead.
    return query.where(field_path, op_string, value)

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
========================================================================== short test summary info ============================================================================
FAILED tests/test_anomaly.py::test_detector_failure_is_recorded_and_the_other_detector_still_reports - AssertionError: assert ('FAILED' == 'FAILED'
FAILED tests/test_anomaly.py::test_detector_timeout_is_recorded - AssertionError: assert ('FAILED' == 'TIMEOUT'
FAILED tests/test_anomaly.py::test_successful_run_records_tool_calls - AssertionError: assert ['load_custom...load_account'] == ['load_custom...y_burst', ...]
3 failed, 205 passed, 1 deselected, 2 warnings in 7.73s
nisha.singh@WPNWCC6CWQ backend % export PROJECT_ID=project-b63ed173-f777-4777-81a
export REGION=asia-southeast1
export SERVICE=trustbank-api
export REPOSITORY=trustbank
nisha.singh@WPNWCC6CWQ backend % gcloud auth login
Your browser has been opened to visit:
```

```
    https://accounts.google.com/o/oauth2/auth?response_type=code&client_id=32555940559.apps.googleusercontent.com&redirect_uri=http%3A%2F%2Flocalhost%3A8086%2F&scope=openid+https%3A%2F
%2Fwww.googleapis.com%2Fauth%2Fuserinfo.email+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fcloud-platform+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fappengine.admin+https%3A%2F%2Fwww.googl
eapis.com%2Fauth%2Fsqlservice.login+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fcompute+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Faccounts.reauth&state=IB9KbMU72AyGr5sFpT8UoKrySIXLub&acc
ess_type=offline&code_challenge=iNFIF8I5oubqUSq7HhIWtNyZHg8fuUHRUIQGLrSNaYk&code_challenge_method=S256

^C

Command killed by keyboard interrupt


nisha.singh@WPNWCC6CWQ backend % gcloud auth login
Your browser has been opened to visit:

    https://accounts.google.com/o/oauth2/auth?response_type=code&client_id=32555940559.apps.googleusercontent.com&redirect_uri=http%3A%2F%2Flocalhost%3A8086%2F&scope=openid+https%3A%2F
%2Fwww.googleapis.com%2Fauth%2Fuserinfo.email+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fcloud-platform+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fappengine.admin+https%3A%2F%2Fwww.googl
eapis.com%2Fauth%2Fsqlservice.login+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fcompute+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Faccounts.reauth&state=bmK5gghdYRhoeFSKNdMTeeP2hA35OB&acc
ess_type=offline&code_challenge=fUDOV0-PEw4nBZxPWMWVvBK7_X2gdAmSkeEmZw-mYNs&code_challenge_method=S256


You are now logged in as [teamdynaminds3@gmail.com].
Your current project is [prj-eng-p-env-prod-ops-15bc].  You can change this setting by running:
  $ gcloud config set project PROJECT_ID


Updates are available for some Google Cloud CLI components.  To install them,
please run:
  $ gcloud components update

nisha.singh@WPNWCC6CWQ backend % gcloud auth application-default login
Your browser has been opened to visit:

    https://accounts.google.com/o/oauth2/auth?response_type=code&client_id=764086051850-6qr4p6gpi6hn506pt8ejuq83di341hur.apps.googleusercontent.com&redirect_uri=http%3A%2F%2Flocalhost%
3A8086%2F&scope=openid+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fuserinfo.email+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fcloud-platform+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fsqlse
rvice.login&state=g0M3gRVB8TsoHq9wASCBmCONrFlNbB&access_type=offline&code_challenge=gvjumLechn8GTFTdHEXPgSZA_NvJEsr6iwCmuI4BtxU&code_challenge_method=S256


Credentials saved to file: [/Users/nisha.singh/.config/gcloud/application_default_credentials.json]

These credentials will be used by any library that requests Application Default Credentials (ADC).
WARNING:
Cannot add the project "prj-eng-p-env-prod-ops-15bc" to ADC as the quota project because the account in ADC does not have the "serviceusage.services.use" permission on this project. Yo
u might receive a "quota_exceeded" or "API not enabled" error. Run $ gcloud auth application-default set-quota-project to add a quota project.
nisha.singh@WPNWCC6CWQ backend % gcloud config set project "$PROJECT_ID"
WARNING: Your active project does not match the quota project in your local Application Default Credentials file. This might result in unexpected quota issues.

To update your Application Default Credentials quota project, use the `gcloud auth application-default set-quota-project` command.
Updated property [core/project].
nisha.singh@WPNWCC6CWQ backend % gcloud projects describe "$PROJECT_ID" --format='value(projectNumber,projectId)'
767440027550    project-b63ed173-f777-4777-81a
nisha.singh@WPNWCC6CWQ backend % gcloud auth list
     Credentialed Accounts
ACTIVE  ACCOUNT
        nisha.singh@apree.health
*       teamdynaminds3@gmail.com

To set the active account, run:
    $ gcloud config set account `ACCOUNT`

nisha.singh@WPNWCC6CWQ backend % firebase use "$PROJECT_ID"
Now using project project-b63ed173-f777-4777-81a
nisha.singh@WPNWCC6CWQ backend % gcloud services enable \
  artifactregistry.googleapis.com \
  cloudbuild.googleapis.com \
  run.googleapis.com \
  secretmanager.googleapis.com \
  vpcaccess.googleapis.com \
  aiplatform.googleapis.com \
  firestore.googleapis.com
Operation "operations/acf.p2-767440027550-f403f28d-0047-438f-9d53-2b385f56b08f" finished successfully.
nisha.singh@WPNWCC6CWQ backend % gcloud services list --enabled \
  --filter='config.name:(artifactregistry.googleapis.com cloudbuild.googleapis.com run.googleapis.com secretmanager.googleapis.com vpcaccess.googleapis.com aiplatform.googleapis.com fi
restore.googleapis.com)' \
  --format='value(config.name)'
aiplatform.googleapis.com
artifactregistry.googleapis.com
cloudbuild.googleapis.com
firestore.googleapis.com
run.googleapis.com
secretmanager.googleapis.com
vpcaccess.googleapis.com
nisha.singh@WPNWCC6CWQ backend % gcloud artifacts repositories describe "$REPOSITORY" \
  --location="$REGION" \
  || gcloud artifacts repositories create "$REPOSITORY" \
       --repository-format=docker \
       --location="$REGION" \
       --description='TrustBank container images'
ERROR: (gcloud.artifacts.repositories.describe) NOT_FOUND: Requested entity was not found. This command is authenticated as teamdynaminds3@gmail.com which is the active account specifi
ed by the [core/account] property.
Create request issued for: [trustbank]
Waiting for operation [projects/project-b63ed173-f777-4777-81a/locations/asia-southeast1/operations/b30b4494-2c69-45df-bcdf-c35126e73f84] to complete...done.
Created repository [trustbank].
nisha.singh@WPNWCC6CWQ backend % gcloud artifacts repositories describe "$REPOSITORY" \
  --location="$REGION" \
  --format='value(name,format)'
Encryption: Google-managed key
Registry URL: asia-southeast1-docker.pkg.dev/project-b63ed173-f777-4777-81a/trustbank
Repository Size: 0.000MB
projects/project-b63ed173-f777-4777-81a/locations/asia-southeast1/repositories/trustbank        DOCKER
nisha.singh@WPNWCC6CWQ backend % export RUNTIME_SA=trustbank-api-runtime
export RUNTIME_SA_EMAIL="${RUNTIME_SA}@${PROJECT_ID}.iam.gserviceaccount.com"
nisha.singh@WPNWCC6CWQ backend % gcloud iam service-accounts describe "$RUNTIME_SA_EMAIL" \
  || gcloud iam service-accounts create "$RUNTIME_SA" \
       --display-name='TrustBank API runtime'
ERROR: (gcloud.iam.service-accounts.describe) NOT_FOUND: Unknown service account. This command is authenticated as teamdynaminds3@gmail.com which is the active account specified by the
 [core/account] property
Created service account [trustbank-api-runtime].
nisha.singh@WPNWCC6CWQ backend % gcloud projects add-iam-policy-binding "$PROJECT_ID" \
  --member="serviceAccount:${RUNTIME_SA_EMAIL}" \
  --role='roles/datastore.user'
Updated IAM policy for project [project-b63ed173-f777-4777-81a].
bindings:
- members:
  - serviceAccount:service-767440027550@gcp-sa-aiplatform.iam.gserviceaccount.com
  role: roles/aiplatform.serviceAgent
- members:
  - serviceAccount:767440027550-compute@developer.gserviceaccount.com
  role: roles/aiplatform.user
- members:
  - serviceAccount:service-767440027550@gcp-sa-artifactregistry.iam.gserviceaccount.com
  role: roles/artifactregistry.serviceAgent
- members:
  - serviceAccount:767440027550-compute@developer.gserviceaccount.com
  role: roles/artifactregistry.writer
- members:
  - serviceAccount:767440027550-compute@developer.gserviceaccount.com
  - serviceAccount:767440027550@cloudbuild.gserviceaccount.com
```

```
  role: roles/cloudbuild.builds.builder
- members:
  - serviceAccount:service-767440027550@gcp-sa-cloudbuild.iam.gserviceaccount.com
  role: roles/cloudbuild.serviceAgent
- members:
  - serviceAccount:767440027550@cloudservices.gserviceaccount.com
  role: roles/compute.instanceGroupManagerServiceAgent
- members:
  - serviceAccount:service-767440027550@compute-system.iam.gserviceaccount.com
  role: roles/compute.serviceAgent
- members:
  - serviceAccount:service-767440027550@containerregistry.iam.gserviceaccount.com
  role: roles/containerregistry.ServiceAgent
- members:
  - serviceAccount:trustbank-api-runtime@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/datastore.user
- members:
  - serviceAccount:767440027550@cloudservices.gserviceaccount.com
  role: roles/editor
- members:
  - serviceAccount:service-767440027550@gcp-sa-firebase.iam.gserviceaccount.com
  role: roles/firebase.managementServiceAgent
- members:
  - serviceAccount:firebase-adminsdk-fbsvc@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/firebase.sdkAdminServiceAgent
- members:
  - serviceAccount:service-767440027550@firebase-rules.iam.gserviceaccount.com
  role: roles/firebaserules.system
- members:
  - serviceAccount:service-767440027550@gcp-sa-firestore.iam.gserviceaccount.com
  role: roles/firestore.serviceAgent
- members:
  - serviceAccount:firebase-adminsdk-fbsvc@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/iam.serviceAccountTokenCreator
- members:
  - serviceAccount:767440027550-compute@developer.gserviceaccount.com
  role: roles/logging.logWriter
- members:
  - serviceAccount:service-767440027550@gcp-sa-notebooks.iam.gserviceaccount.com
  role: roles/notebooks.serviceAgent
- members:
  - user:teamdynaminds3@gmail.com
  role: roles/owner
- members:
  - serviceAccount:service-767440027550@gcp-sa-pubsub.iam.gserviceaccount.com
  role: roles/pubsub.serviceAgent
- members:
  - serviceAccount:service-767440027550@serverless-robot-prod.iam.gserviceaccount.com
  role: roles/run.serviceAgent
- members:
  - serviceAccount:767440027550-compute@developer.gserviceaccount.com
  role: roles/storage.objectViewer
- members:
  - serviceAccount:service-767440027550@gcp-sa-vpcaccess.iam.gserviceaccount.com
  role: roles/vpcaccess.serviceAgent
etag: BwZd9JbE6-0=
version: 1
nisha.singh@WPNWCC6CWQ backend % gcloud projects add-iam-policy-binding "$PROJECT_ID" \
  --member="serviceAccount:${RUNTIME_SA_EMAIL}" \
  --role='roles/aiplatform.user'
Updated IAM policy for project [project-b63ed173-f777-4777-81a].
bindings:
- members:
  - serviceAccount:service-767440027550@gcp-sa-aiplatform.iam.gserviceaccount.com
  role: roles/aiplatform.serviceAgent
- members:
  - serviceAccount:767440027550-compute@developer.gserviceaccount.com
  - serviceAccount:trustbank-api-runtime@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/aiplatform.user
- members:
  - serviceAccount:service-767440027550@gcp-sa-artifactregistry.iam.gserviceaccount.com
  role: roles/artifactregistry.serviceAgent
- members:
  - serviceAccount:767440027550-compute@developer.gserviceaccount.com
  role: roles/artifactregistry.writer
- members:
  - serviceAccount:767440027550-compute@developer.gserviceaccount.com
  - serviceAccount:767440027550@cloudbuild.gserviceaccount.com
  role: roles/cloudbuild.builds.builder
- members:
  - serviceAccount:service-767440027550@gcp-sa-cloudbuild.iam.gserviceaccount.com
  role: roles/cloudbuild.serviceAgent
- members:
  - serviceAccount:767440027550@cloudservices.gserviceaccount.com
  role: roles/compute.instanceGroupManagerServiceAgent
- members:
  - serviceAccount:service-767440027550@compute-system.iam.gserviceaccount.com
  role: roles/compute.serviceAgent
- members:
  - serviceAccount:service-767440027550@containerregistry.iam.gserviceaccount.com
  role: roles/containerregistry.ServiceAgent
- members:
  - serviceAccount:trustbank-api-runtime@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/datastore.user
- members:
  - serviceAccount:767440027550@cloudservices.gserviceaccount.com
  role: roles/editor
- members:
  - serviceAccount:service-767440027550@gcp-sa-firebase.iam.gserviceaccount.com
  role: roles/firebase.managementServiceAgent
- members:
  - serviceAccount:firebase-adminsdk-fbsvc@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/firebase.sdkAdminServiceAgent
- members:
  - serviceAccount:service-767440027550@firebase-rules.iam.gserviceaccount.com
  role: roles/firebaserules.system
- members:
  - serviceAccount:service-767440027550@gcp-sa-firestore.iam.gserviceaccount.com
  role: roles/firestore.serviceAgent
- members:
  - serviceAccount:firebase-adminsdk-fbsvc@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/iam.serviceAccountTokenCreator
- members:
  - serviceAccount:767440027550-compute@developer.gserviceaccount.com
  role: roles/logging.logWriter
- members:
  - serviceAccount:service-767440027550@gcp-sa-notebooks.iam.gserviceaccount.com
  role: roles/notebooks.serviceAgent
- members:
  - user:teamdynaminds3@gmail.com
  role: roles/owner
- members:
  - serviceAccount:service-767440027550@gcp-sa-pubsub.iam.gserviceaccount.com
  role: roles/pubsub.serviceAgent
- members:
  - serviceAccount:service-767440027550@serverless-robot-prod.iam.gserviceaccount.com
  role: roles/run.serviceAgent
```

```
- members:
  - serviceAccount:767440027550-compute@developer.gserviceaccount.com
  role: roles/storage.objectViewer
- members:
  - serviceAccount:service-767440027550@gcp-sa-vpcaccess.iam.gserviceaccount.com
  role: roles/vpcaccess.serviceAgent
etag: BwZd9JeiZkE=
version: 1
nisha.singh@WPNWCC6CWQ backend % export TOKEN_SECRET="$(openssl rand -base64 48)"
read -rsp 'Investigator demo access code: ' INVESTIGATOR_CODE; echo
read -rsp 'Neo4j password: ' NEO4J_PASSWORD; echo

printf '%s' "$TOKEN_SECRET" | gcloud secrets create trustbank-token-secret \
  --replication-policy=automatic --data-file=- \
  || printf '%s' "$TOKEN_SECRET" | gcloud secrets versions add trustbank-token-secret --data-file=-

printf '%s' "$INVESTIGATOR_CODE" | gcloud secrets create trustbank-investigator-code \
  --replication-policy=automatic --data-file=- \
  || printf '%s' "$INVESTIGATOR_CODE" | gcloud secrets versions add trustbank-investigator-code --data-file=-

printf '%s' "$NEO4J_PASSWORD" | gcloud secrets create trustbank-neo4j-password \
  --replication-policy=automatic --data-file=- \
  || printf '%s' "$NEO4J_PASSWORD" | gcloud secrets versions add trustbank-neo4j-password --data-file=-

unset TOKEN_SECRET INVESTIGATOR_CODE NEO4J_PASSWORD
read: -p: no coprocess

read: -p: no coprocess

Created version [1] of the secret [trustbank-token-secret].
Created secret [trustbank-investigator-code].
Created secret [trustbank-neo4j-password].
nisha.singh@WPNWCC6CWQ backend % for SECRET in trustbank-token-secret trustbank-investigator-code trustbank-neo4j-password; do
  gcloud secrets add-iam-policy-binding "$SECRET" \
    --member="serviceAccount:${RUNTIME_SA_EMAIL}" \
    --role='roles/secretmanager.secretAccessor'
done
Updated IAM policy for secret [trustbank-token-secret].
bindings:
- members:
  - serviceAccount:trustbank-api-runtime@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/secretmanager.secretAccessor
etag: BwZd9JoFCsU=
version: 1
Updated IAM policy for secret [trustbank-investigator-code].
bindings:
- members:
  - serviceAccount:trustbank-api-runtime@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/secretmanager.secretAccessor
etag: BwZd9JomB_c=
version: 1
Updated IAM policy for secret [trustbank-neo4j-password].
bindings:
- members:
  - serviceAccount:trustbank-api-runtime@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/secretmanager.secretAccessor
etag: BwZd9JpJ424=
version: 1
nisha.singh@WPNWCC6CWQ backend % gcloud secrets list --filter='name:trustbank-' --format='table(name)'
NAME
trustbank-investigator-code
trustbank-neo4j-password
trustbank-token-secret
nisha.singh@WPNWCC6CWQ backend % export VPC_NETWORK=default
export CONNECTOR=trustbank-run-egress
export CONNECTOR_RANGE=10.8.0.0/28
nisha.singh@WPNWCC6CWQ backend % gcloud compute networks vpc-access connectors describe "$CONNECTOR" \
  --region="$REGION" \
  || gcloud compute networks vpc-access connectors create "$CONNECTOR" \
       --region="$REGION" \
       --network="$VPC_NETWORK" \
       --range="$CONNECTOR_RANGE" \
       --min-instances=2 \
       --max-instances=3
ERROR: (gcloud.compute.networks.vpc-access.connectors.describe) NOT_FOUND: The connector is not found. This command is authenticated as teamdynaminds3@gmail.com which is the active acc
ount specified by the [core/account] property.
Create request issued for: [trustbank-run-egress]
Waiting for operation [projects/project-b63ed173-f777-4777-81a/locations/asia-southeast1/operations/c186073e-4f31-434a-8708-e52990547a2d] to complete...done.
Created connector [trustbank-run-egress].
nisha.singh@WPNWCC6CWQ backend % gcloud compute networks vpc-access connectors describe "$CONNECTOR" \
  --region="$REGION" \
  --format='value(state)'
READY
nisha.singh@WPNWCC6CWQ backend % gcloud compute instances add-tags trustbank-neo4j \
  --zone=asia-southeast1-b \
  --tags=trustbank-neo4j
Updated [https://www.googleapis.com/compute/v1/projects/project-b63ed173-f777-4777-81a/zones/asia-southeast1-b/instances/trustbank-neo4j].
nisha.singh@WPNWCC6CWQ backend % export IMAGE="${REGION}-docker.pkg.dev/${PROJECT_ID}/${REPOSITORY}/trustbank-api:$(git rev-parse --short HEAD)"

gcloud builds submit services/backend --tag="$IMAGE"
gcloud artifacts docker images describe "$IMAGE"
ERROR: (gcloud.builds.submit) could not find source [services/backend]
ERROR: (gcloud.artifacts.docker.images.describe) Image not found.

A valid container image can be referenced by tag or digest, has the format of
  LOCATION-docker.DOMAIN/PROJECT-ID/REPOSITORY-ID/IMAGE:tag
  LOCATION-docker.DOMAIN/PROJECT-ID/REPOSITORY-ID/IMAGE@sha256:digest

nisha.singh@WPNWCC6CWQ backend % gcloud builds submit . --tag="$IMAGE"
Creating temporary archive of 79 file(s) totalling 478.0 KiB before compression.
Some files were not included in the source upload.

Check the gcloud log [/Users/nisha.singh/.config/gcloud/logs/2026.10.16/18.27.20.401060.log] to see which files and the contents of the
default gcloudignore file used (see `$ gcloud topic gcloudignore` to learn
more).

Uploading tarball of [.] to [gs://project-b63ed173-f777-4777-81a_cloudbuild/source/1792155440.519811-953ab2c8668b41e0b43a59756daf6dee.tgz]
Created [https://cloudbuild.googleapis.com/v1/projects/project-b63ed173-f777-4777-81a/locations/global/builds/4fd26b60-ed70-4d3b-bca0-3aefdc5d3a71].
Logs are available at [ https://console.cloud.google.com/cloud-build/builds/4fd26b60-ed70-4d3b-bca0-3aefdc5d3a71?project=767440027550 ].
Waiting for build to complete. Polling interval: 1 second(s).
------------------------------------------------------------------------ REMOTE BUILD OUTPUT ------------------------------------------------------------------------
starting build "4fd26b60-ed70-4d3b-bca0-3aefdc5d3a71" using release legacy

FETCHSOURCE
Fetching storage object: gs://project-b63ed173-f777-4777-81a_cloudbuild/source/1792155440.519811-953ab2c8668b41e0b43a59756daf6dee.tgz#1792155442547409
Copying gs://project-b63ed173-f777-4777-81a_cloudbuild/source/1792155440.519811-953ab2c8668b41e0b43a59756daf6dee.tgz#1792155442547409...
/ [1 files][110.6 KiB/110.6 KiB]
Operation completed over 1 objects/110.6 KiB.
BUILD
Already have image (with digest): gcr.io/cloud-builders/docker
Sending build context to Docker daemon  327.7kB
Step 1/10 : FROM python:3.12-slim
3.12-slim: Pulling from library/python
ecc510c1e359: Already exists
75b6a36c64a1: Pulling fs layer
6912e23eb445: Pulling fs layer
bbc5a1223747: Pulling fs layer
```

```
bbc5a1223747: Verifying Checksum
bbc5a1223747: Download complete
75b6a36c64a1: Verifying Checksum
75b6a36c64a1: Download complete
6912e23eb445: Verifying Checksum
6912e23eb445: Download complete
75b6a36c64a1: Pull complete
6912e23eb445: Pull complete
bbc5a1223747: Pull complete
Digest: sha256:a6e34c598f2467ed0e9a8d349809fcd8b5c603269512df273a0bb1784edc11b1
Status: Downloaded newer image for python:3.12-slim
 ---> df18428df8a0
Step 2/10 : ENV PYTHONDONTWRITEBYTECODE=1     PYTHONUNBUFFERED=1     PIP_NO_CACHE_DIR=1
 ---> Running in b0c153e4ac07
Removing intermediate container b0c153e4ac07
 ---> e1093de2d6ac
Step 3/10 : WORKDIR /app
 ---> Running in 587e3f7888f0
Removing intermediate container 587e3f7888f0
 ---> a6b52ab7a5cd
Step 4/10 : COPY pyproject.toml ./
 ---> 85128c4dbc17
Step 5/10 : COPY src ./src
 ---> 0e03c409aa55
Step 6/10 : RUN pip install --upgrade pip && pip install .
 ---> Running in 02ad1adbc1e1
Requirement already satisfied: pip in /usr/local/lib/python3.12/site-packages (25.0.1)
Collecting pip
  Downloading pip-26.2.1-py3-none-any.whl.metadata (4.6 kB)
Downloading pip-26.2.1-py3-none-any.whl (1.8 MB)
   ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 1.8/1.8 MB 79.9 MB/s eta 0:00:00
Installing collected packages: pip
  Attempting uninstall: pip
    Found existing installation: pip 25.0.1
    Uninstalling pip-25.0.1:
      Successfully uninstalled pip-25.0.1
Successfully installed pip-26.2.1
WARNING: Running pip as the 'root' user can result in broken permissions and conflicting behaviour with the system package manager, possibly rendering your system unusable. It is recom
mended to use a virtual environment instead: https://pip.pypa.io/warnings/venv. Use the --root-user-action option if you know what you are doing and want to suppress this warning.
Processing ./.
  Installing build dependencies: started
  Installing build dependencies: finished with status 'done'
  Getting requirements to build wheel: started
  Getting requirements to build wheel: finished with status 'done'
  Preparing metadata (pyproject.toml): started
  Preparing metadata (pyproject.toml): finished with status 'done'
Collecting fastapi>=0.115 (from trustbank-backend==0.1.0)
  Downloading fastapi-0.143.2-py3-none-any.whl.metadata (26 kB)
Collecting uvicorn>=0.30 (from uvicorn[standard]>=0.30->trustbank-backend==0.1.0)
  Downloading uvicorn-0.54.0-py3-none-any.whl.metadata (6.6 kB)
Collecting pydantic>=2.8 (from trustbank-backend==0.1.0)
  Downloading pydantic-2.14.1-py3-none-any.whl.metadata (133 kB)
Collecting pydantic-settings>=2.4 (from trustbank-backend==0.1.0)
  Downloading pydantic_settings-2.16.0-py3-none-any.whl.metadata (4.0 kB)
Collecting google-cloud-firestore>=2.19 (from trustbank-backend==0.1.0)
  Downloading google_cloud_firestore-2.34.1-py3-none-any.whl.metadata (9.5 kB)
Collecting neo4j>=5.20 (from trustbank-backend==0.1.0)
  Downloading neo4j-6.4.1-py3-none-any.whl.metadata (5.5 kB)
Collecting google-genai>=1.0 (from trustbank-backend==0.1.0)
  Downloading google_genai-2.31.0-py3-none-any.whl.metadata (58 kB)
Collecting pyjwt>=2.8 (from trustbank-backend==0.1.0)
  Downloading pyjwt-2.15.1-py3-none-any.whl.metadata (3.5 kB)
Collecting google-adk>=2.12 (from trustbank-backend==0.1.0)
  Downloading google_adk-2.12.0-py3-none-any.whl.metadata (26 kB)
Collecting starlette>=0.46.0 (from fastapi>=0.115->trustbank-backend==0.1.0)
  Downloading starlette-1.8.0-py3-none-any.whl.metadata (6.6 kB)
Collecting typing-extensions>=4.8.0 (from fastapi>=0.115->trustbank-backend==0.1.0)
  Downloading typing_extensions-4.16.0-py3-none-any.whl.metadata (3.3 kB)
Collecting typing-inspection>=0.4.2 (from fastapi>=0.115->trustbank-backend==0.1.0)
  Downloading typing_inspection-0.4.4-py3-none-any.whl.metadata (2.6 kB)
Collecting annotated-doc>=0.0.2 (from fastapi>=0.115->trustbank-backend==0.1.0)
  Downloading annotated_doc-0.0.5-py3-none-any.whl.metadata (6.5 kB)
Collecting opentelemetry-api>=1.44.0 (from fastapi>=0.115->trustbank-backend==0.1.0)
  Downloading opentelemetry_api-1.45.1-py3-none-any.whl.metadata (1.4 kB)
Collecting aiosqlite>=0.21 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading aiosqlite-0.22.1-py3-none-any.whl.metadata (4.3 kB)
Collecting authlib<2,>=1.6.6 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading authlib-1.9.1-py2.py3-none-any.whl.metadata (10 kB)
Collecting click<9,>=8.1.8 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading click-8.5.0-py3-none-any.whl.metadata (2.6 kB)
Collecting cryptography>=42 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading cryptography-50.0.2-cp311-abi3-manylinux_2_34_x86_64.whl.metadata (4.4 kB)
Collecting google-auth>=2.47 (from google-auth[pyopenssl]>=2.47->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading google_auth-2.62.0-py3-none-any.whl.metadata (6.0 kB)
Collecting graphviz<1,>=0.20.2 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading graphviz-0.21-py3-none-any.whl.metadata (12 kB)
Collecting httpx<1,>=0.27 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading httpx-0.28.1-py3-none-any.whl.metadata (7.1 kB)
Collecting jsonschema<5,>=4.23 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading jsonschema-4.26.0-py3-none-any.whl.metadata (7.6 kB)
INFO: pip is looking at multiple versions of google-adk to determine which version is compatible with other requirements. This could take a while.
Collecting fastapi>=0.115 (from trustbank-backend==0.1.0)
  Downloading fastapi-0.143.1-py3-none-any.whl.metadata (26 kB)
  Downloading fastapi-0.143.0-py3-none-any.whl.metadata (26 kB)
  Downloading fastapi-0.142.4-py3-none-any.whl.metadata (26 kB)
Collecting opentelemetry-api<=1.42.1,>=1.39 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading opentelemetry_api-1.42.1-py3-none-any.whl.metadata (1.4 kB)
Collecting opentelemetry-sdk<=1.42.1,>=1.39 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading opentelemetry_sdk-1.42.1-py3-none-any.whl.metadata (1.7 kB)
Collecting packaging>=21 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading packaging-26.3-py3-none-any.whl.metadata (3.5 kB)
Collecting python-dotenv<2,>=1 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading python_dotenv-1.2.4-py3-none-any.whl.metadata (29 kB)
Collecting python-multipart<1,>=0.0.9 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading python_multipart-0.0.32-py3-none-any.whl.metadata (2.1 kB)
Collecting pyyaml<7,>=6.0.2 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading pyyaml-6.0.3-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl.metadata (2.4 kB)
Collecting requests<3,>=2.32.4 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading requests-2.34.2-py3-none-any.whl.metadata (4.8 kB)
Collecting tenacity<10,>=9 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading tenacity-9.2.1-py3-none-any.whl.metadata (1.4 kB)
Collecting watchdog<7,>=6 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading watchdog-6.0.0-py3-none-manylinux2014_x86_64.whl.metadata (44 kB)
Collecting websockets<16,>=15.0.1 (from google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading websockets-15.0.1-cp312-cp312-manylinux_2_5_x86_64.manylinux1_x86_64.manylinux_2_17_x86_64.manylinux2014_x86_64.whl.metadata (6.8 kB)
INFO: pip is looking at multiple versions of fastapi to determine which version is compatible with other requirements. This could take a while.
Collecting fastapi>=0.115 (from trustbank-backend==0.1.0)
  Downloading fastapi-0.142.3-py3-none-any.whl.metadata (26 kB)
  Downloading fastapi-0.142.2-py3-none-any.whl.metadata (27 kB)
  Downloading fastapi-0.142.1-py3-none-any.whl.metadata (27 kB)
  Downloading fastapi-0.142.0-py3-none-any.whl.metadata (27 kB)
  Downloading fastapi-0.141.1-py3-none-any.whl.metadata (27 kB)
Collecting joserfc>=1.6.8 (from authlib<2,>=1.6.6->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading joserfc-1.7.5-py3-none-any.whl.metadata (3.1 kB)
Collecting anyio<5.0.0,>=4.8.0 (from google-genai>=1.0->trustbank-backend==0.1.0)
  Downloading anyio-4.15.1-py3-none-any.whl.metadata (4.7 kB)
Collecting tenacity<10,>=9 (from google-adk>=2.12->trustbank-backend==0.1.0)
```

```
  Downloading tenacity-9.1.4-py3-none-any.whl.metadata (1.2 kB)
Collecting distro<2,>=1.7.0 (from google-genai>=1.0->trustbank-backend==0.1.0)
  Downloading distro-1.9.0-py3-none-any.whl.metadata (6.8 kB)
Collecting sniffio (from google-genai>=1.0->trustbank-backend==0.1.0)
  Downloading sniffio-1.3.1-py3-none-any.whl.metadata (3.9 kB)
Collecting idna>=2.8 (from anyio<5.0.0,>=4.8.0->google-genai>=1.0->trustbank-backend==0.1.0)
  Downloading idna-3.20-py3-none-any.whl.metadata (7.2 kB)
Collecting pyasn1-modules>=0.2.1 (from google-auth>=2.47->google-auth[pyopenssl]>=2.47->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading pyasn1_modules-0.4.2-py3-none-any.whl.metadata (3.5 kB)
Collecting certifi (from httpx<1,>=0.27->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading certifi-2026.7.22-py3-none-any.whl.metadata (2.5 kB)
Collecting httpcore==1.* (from httpx<1,>=0.27->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading httpcore-1.0.9-py3-none-any.whl.metadata (21 kB)
Collecting h11>=0.16 (from httpcore==1.*->httpx<1,>=0.27->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading h11-0.16.0-py3-none-any.whl.metadata (8.3 kB)
Collecting attrs>=22.2.0 (from jsonschema<5,>=4.23->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading attrs-26.1.0-py3-none-any.whl.metadata (8.8 kB)
Collecting jsonschema-specifications>=2023.03.6 (from jsonschema<5,>=4.23->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading jsonschema_specifications-2025.9.1-py3-none-any.whl.metadata (2.9 kB)
Collecting referencing>=0.28.4 (from jsonschema<5,>=4.23->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading referencing-0.37.0-py3-none-any.whl.metadata (2.8 kB)
Collecting rpds-py>=0.25.0 (from jsonschema<5,>=4.23->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading rpds_py-2026.9.1-cp312-cp312-manylinux_2_17_x86_64.manylinux2014_x86_64.whl.metadata (4.1 kB)
Collecting opentelemetry-semantic-conventions==0.63b1 (from opentelemetry-sdk<=1.42.1,>=1.39->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading opentelemetry_semantic_conventions-0.63b1-py3-none-any.whl.metadata (2.4 kB)
Collecting annotated-types>=0.6.0 (from pydantic>=2.8->trustbank-backend==0.1.0)
  Downloading annotated_types-0.8.0-py3-none-any.whl.metadata (15 kB)
Collecting pydantic-core==2.50.1 (from pydantic>=2.8->trustbank-backend==0.1.0)
  Downloading pydantic_core-2.50.1-cp312-cp312-manylinux_2_17_x86_64.manylinux2014_x86_64.whl.metadata (6.5 kB)
Collecting charset_normalizer<4,>=2 (from requests<3,>=2.32.4->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading charset_normalizer-3.5.2-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl.metadata (46 kB)
Collecting urllib3<3,>=1.26 (from requests<3,>=2.32.4->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading urllib3-2.8.0-py3-none-any.whl.metadata (7.4 kB)
Collecting cffi>=2.0.0 (from cryptography>=42->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading cffi-2.1.1-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.whl.metadata (2.5 kB)
Collecting pycparser (from cffi>=2.0.0->cryptography>=42->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading pycparser-3.11-py3-none-any.whl.metadata (8.2 kB)
Collecting google-api-core<3.0.0,>=2.28.0 (from google-api-core[grpc]<3.0.0,>=2.28.0->google-cloud-firestore>=2.19->trustbank-backend==0.1.0)
  Downloading google_api_core-2.42.0-py3-none-any.whl.metadata (3.2 kB)
Collecting google-cloud-core<3.0.0,>=2.0.0 (from google-cloud-firestore>=2.19->trustbank-backend==0.1.0)
  Downloading google_cloud_core-2.8.0-py3-none-any.whl.metadata (2.9 kB)
Collecting grpcio<2.0.0,>=1.59.0 (from google-cloud-firestore>=2.19->trustbank-backend==0.1.0)
  Downloading grpcio-1.84.0-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.whl.metadata (3.8 kB)
Collecting proto-plus<2.0.0,>=1.26.1 (from google-cloud-firestore>=2.19->trustbank-backend==0.1.0)
  Downloading proto_plus-1.29.0-py3-none-any.whl.metadata (2.2 kB)
Collecting protobuf<8.0.0,>=6.33.5 (from google-cloud-firestore>=2.19->trustbank-backend==0.1.0)
  Downloading protobuf-7.36.2-cp310-abi3-manylinux2014_x86_64.whl.metadata (595 bytes)
Collecting googleapis-common-protos<2.0.0,>=1.69.2 (from google-api-core<3.0.0,>=2.28.0->google-api-core[grpc]<3.0.0,>=2.28.0->google-cloud-firestore>=2.19->trustbank-backend==0.1.0)
  Downloading googleapis_common_protos-1.75.5-py3-none-any.whl.metadata (8.5 kB)
INFO: pip is looking at multiple versions of google-api-core to determine which version is compatible with other requirements. This could take a while.
Collecting google-api-core<3.0.0,>=2.28.0 (from google-api-core[grpc]<3.0.0,>=2.28.0->google-cloud-firestore>=2.19->trustbank-backend==0.1.0)
  Downloading google_api_core-2.41.0-py3-none-any.whl.metadata (3.2 kB)
  Downloading google_api_core-2.40.0-py3-none-any.whl.metadata (3.2 kB)
  Downloading google_api_core-2.39.0-py3-none-any.whl.metadata (3.2 kB)
  Downloading google_api_core-2.38.0-py3-none-any.whl.metadata (3.2 kB)
  Downloading google_api_core-2.37.0-py3-none-any.whl.metadata (3.2 kB)
  Downloading google_api_core-2.36.0-py3-none-any.whl.metadata (3.2 kB)
  Downloading google_api_core-2.34.0-py3-none-any.whl.metadata (2.9 kB)
INFO: pip is looking at multiple versions of google-api-core[grpc] to determine which version is compatible with other requirements. This could take a while.
Collecting grpcio-status<2.0.0,>=1.59.0 (from google-api-core[grpc]<3.0.0,>=2.28.0->google-cloud-firestore>=2.19->trustbank-backend==0.1.0)
  Downloading grpcio_status-1.84.0-py3-none-any.whl.metadata (1.3 kB)
Collecting pytz (from neo4j>=5.20->trustbank-backend==0.1.0)
  Downloading pytz-2026.5-py2.py3-none-any.whl.metadata (22 kB)
Collecting pyasn1<0.7.0,>=0.6.1 (from pyasn1-modules>=0.2.1->google-auth>=2.47->google-auth[pyopenssl]>=2.47->google-adk>=2.12->trustbank-backend==0.1.0)
  Downloading pyasn1-0.6.4-py3-none-any.whl.metadata (8.4 kB)
Collecting httptools>=0.8.0 (from uvicorn[standard]>=0.30->trustbank-backend==0.1.0)
  Downloading httptools-0.9.0-cp312-cp312-manylinux1_x86_64.manylinux_2_28_x86_64.manylinux_2_5_x86_64.whl.metadata (3.5 kB)
Collecting uvloop>=0.15.1 (from uvicorn[standard]>=0.30->trustbank-backend==0.1.0)
  Downloading uvloop-0.23.0-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl.metadata (5.1 kB)
Collecting watchfiles>=0.20 (from uvicorn[standard]>=0.30->trustbank-backend==0.1.0)
  Downloading watchfiles-1.3.0-cp310-abi3-manylinux_2_17_x86_64.manylinux2014_x86_64.whl.metadata (4.9 kB)
Downloading google_adk-2.12.0-py3-none-any.whl (5.0 MB)
   ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 5.0/5.0 MB 171.3 MB/s  0:00:00
Downloading opentelemetry_api-1.42.1-py3-none-any.whl (61 kB)
Downloading fastapi-0.141.1-py3-none-any.whl (131 kB)
Downloading authlib-1.9.1-py2.py3-none-any.whl (266 kB)
Downloading click-8.5.0-py3-none-any.whl (125 kB)
Downloading google_genai-2.31.0-py3-none-any.whl (1.2 MB)
   ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 1.2/1.2 MB 438.7 MB/s  0:00:00
Downloading anyio-4.15.1-py3-none-any.whl (132 kB)
Downloading distro-1.9.0-py3-none-any.whl (20 kB)
Downloading google_auth-2.62.0-py3-none-any.whl (267 kB)
Downloading graphviz-0.21-py3-none-any.whl (47 kB)
Downloading httpx-0.28.1-py3-none-any.whl (73 kB)
Downloading httpcore-1.0.9-py3-none-any.whl (78 kB)
Downloading jsonschema-4.26.0-py3-none-any.whl (90 kB)
Downloading opentelemetry_sdk-1.42.1-py3-none-any.whl (170 kB)
Downloading opentelemetry_semantic_conventions-0.63b1-py3-none-any.whl (203 kB)
Downloading pydantic-2.14.1-py3-none-any.whl (488 kB)
Downloading pydantic_core-2.50.1-cp312-cp312-manylinux_2_17_x86_64.manylinux2014_x86_64.whl (2.2 MB)
   ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 2.2/2.2 MB 249.2 MB/s  0:00:00
Downloading python_dotenv-1.2.4-py3-none-any.whl (23 kB)
Downloading python_multipart-0.0.32-py3-none-any.whl (30 kB)
Downloading pyyaml-6.0.3-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl (807 kB)
   ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 807.9/807.9 kB 435.9 MB/s  0:00:00
Downloading requests-2.34.2-py3-none-any.whl (73 kB)
Downloading charset_normalizer-3.5.2-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl (257 kB)
Downloading idna-3.20-py3-none-any.whl (69 kB)
Downloading starlette-1.8.0-py3-none-any.whl (79 kB)
Downloading tenacity-9.1.4-py3-none-any.whl (28 kB)
Downloading typing_extensions-4.16.0-py3-none-any.whl (45 kB)
Downloading urllib3-2.8.0-py3-none-any.whl (135 kB)
Downloading uvicorn-0.54.0-py3-none-any.whl (87 kB)
Downloading watchdog-6.0.0-py3-none-manylinux2014_x86_64.whl (79 kB)
Downloading websockets-15.0.1-cp312-cp312-manylinux_2_5_x86_64.manylinux1_x86_64.manylinux_2_17_x86_64.manylinux2014_x86_64.whl (182 kB)
Downloading aiosqlite-0.22.1-py3-none-any.whl (17 kB)
Downloading annotated_doc-0.0.5-py3-none-any.whl (5.3 kB)
Downloading annotated_types-0.8.0-py3-none-any.whl (13 kB)
Downloading attrs-26.1.0-py3-none-any.whl (67 kB)
Downloading certifi-2026.7.22-py3-none-any.whl (136 kB)
Downloading cryptography-50.0.2-cp311-abi3-manylinux_2_34_x86_64.whl (4.8 MB)
   ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 4.8/4.8 MB 345.6 MB/s  0:00:00
Downloading cffi-2.1.1-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.whl (221 kB)
Downloading google_cloud_firestore-2.34.1-py3-none-any.whl (443 kB)
Downloading google_api_core-2.34.0-py3-none-any.whl (180 kB)
Downloading google_cloud_core-2.8.0-py3-none-any.whl (31 kB)
Downloading googleapis_common_protos-1.75.5-py3-none-any.whl (307 kB)
Downloading grpcio-1.84.0-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.whl (7.2 MB)
   ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 7.2/7.2 MB 277.6 MB/s  0:00:00
Downloading grpcio_status-1.84.0-py3-none-any.whl (14 kB)
Downloading proto_plus-1.29.0-py3-none-any.whl (50 kB)
Downloading protobuf-7.36.2-cp310-abi3-manylinux2014_x86_64.whl (343 kB)
Downloading h11-0.16.0-py3-none-any.whl (37 kB)
Downloading joserfc-1.7.5-py3-none-any.whl (71 kB)
Downloading jsonschema_specifications-2025.9.1-py3-none-any.whl (18 kB)
Downloading neo4j-6.4.1-py3-none-any.whl (390 kB)
Downloading packaging-26.3-py3-none-any.whl (129 kB)
```

```
Downloading pyasn1_modules-0.4.2-py3-none-any.whl (181 kB)
Downloading pyasn1-0.6.4-py3-none-any.whl (84 kB)
Downloading pydantic_settings-2.16.0-py3-none-any.whl (80 kB)
Downloading pyjwt-2.15.1-py3-none-any.whl (33 kB)
Downloading referencing-0.37.0-py3-none-any.whl (26 kB)
Downloading rpds_py-2026.9.1-cp312-cp312-manylinux_2_17_x86_64.manylinux2014_x86_64.whl (371 kB)
Downloading typing_inspection-0.4.4-py3-none-any.whl (14 kB)
Downloading httptools-0.9.0-cp312-cp312-manylinux1_x86_64.manylinux_2_28_x86_64.manylinux_2_5_x86_64.whl (552 kB)
   ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 552.8/552.8 kB 419.9 MB/s  0:00:00
Downloading uvloop-0.23.0-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl (4.5 MB)
   ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 4.5/4.5 MB 334.7 MB/s  0:00:00
Downloading watchfiles-1.3.0-cp310-abi3-manylinux_2_17_x86_64.manylinux2014_x86_64.whl (458 kB)
Downloading pycparser-3.11-py3-none-any.whl (51 kB)
Downloading pytz-2026.5-py2.py3-none-any.whl (506 kB)
Downloading sniffio-1.3.1-py3-none-any.whl (10 kB)
Building wheels for collected packages: trustbank-backend
  Building wheel for trustbank-backend (pyproject.toml): started
  Building wheel for trustbank-backend (pyproject.toml): finished with status 'done'
  Created wheel for trustbank-backend: filename=trustbank_backend-0.1.0-py3-none-any.whl size=92831 sha256=4ad0a8e978faa5c9fac64aad19bdf9d110ee061f4c60f3f905073c41c6a5d0d6
  Stored in directory: /tmp/pip-ephem-wheel-cache-mwlc20wi/wheels/54/1b/b7/aa63e25c8f14f4f2ae7b04e6097bdecb770e455c5c1ee0a600
Successfully built trustbank-backend
Installing collected packages: pytz, websockets, watchdog, uvloop, urllib3, typing-extensions, tenacity, sniffio, rpds-py, pyyaml, python-multipart, python-dotenv, pyjwt, pycparser, py
asn1, protobuf, packaging, neo4j, idna, httptools, h11, graphviz, distro, click, charset_normalizer, certifi, attrs, annotated-types, annotated-doc, aiosqlite, uvicorn, typing-inspecti
on, requests, referencing, pydantic-core, pyasn1-modules, proto-plus, opentelemetry-api, httpcore, grpcio, googleapis-common-protos, cffi, anyio, watchfiles, starlette, pydantic, opent
elemetry-semantic-conventions, jsonschema-specifications, httpx, grpcio-status, cryptography, pydantic-settings, opentelemetry-sdk, jsonschema, joserfc, google-auth, fastapi, google-ap
i-core, authlib, google-genai, google-cloud-core, google-cloud-firestore, google-adk, trustbank-backend

Successfully installed aiosqlite-0.22.1 annotated-doc-0.0.5 annotated-types-0.8.0 anyio-4.15.1 attrs-26.1.0 authlib-1.9.1 certifi-2026.7.22 cffi-2.1.1 charset_normalizer-3.5.2 click-8.
5.0 cryptography-50.0.2 distro-1.9.0 fastapi-0.141.1 google-adk-2.12.0 google-api-core-2.34.0 google-auth-2.62.0 google-cloud-core-2.8.0 google-cloud-firestore-2.34.1 google-genai-2.31
.0 googleapis-common-protos-1.75.5 graphviz-0.21 grpcio-1.84.0 grpcio-status-1.84.0 h11-0.16.0 httpcore-1.0.9 httptools-0.9.0 httpx-0.28.1 idna-3.20 joserfc-1.7.5 jsonschema-4.26.0 jso
nschema-specifications-2025.9.1 neo4j-6.4.1 opentelemetry-api-1.42.1 opentelemetry-sdk-1.42.1 opentelemetry-semantic-conventions-0.63b1 packaging-26.3 proto-plus-1.29.0 protobuf-7.36.2
 pyasn1-0.6.4 pyasn1-modules-0.4.2 pycparser-3.11 pydantic-2.14.1 pydantic-core-2.50.1 pydantic-settings-2.16.0 pyjwt-2.15.1 python-dotenv-1.2.4 python-multipart-0.0.32 pytz-2026.5 pyy
aml-6.0.3 referencing-0.37.0 requests-2.34.2 rpds-py-2026.9.1 sniffio-1.3.1 starlette-1.8.0 tenacity-9.1.4 trustbank-backend-0.1.0 typing-extensions-4.16.0 typing-inspection-0.4.4 urll
ib3-2.8.0 uvicorn-0.54.0 uvloop-0.23.0 watchdog-6.0.0 watchfiles-1.3.0 websockets-15.0.1
WARNING: Running pip as the 'root' user can result in broken permissions and conflicting behaviour with the system package manager, possibly rendering your system unusable. It is recom
mended to use a virtual environment instead: https://pip.pypa.io/warnings/venv. Use the --root-user-action option if you know what you are doing and want to suppress this warning.
Removing intermediate container 02ad1adbc1e1
 ---> ad8b18e219ec
Step 7/10 : RUN useradd --create-home --uid 10001 appuser
 ---> Running in 870ec467a907
Removing intermediate container 870ec467a907
 ---> a6cf172997ea
Step 8/10 : USER appuser
 ---> Running in c5684a330e17
Removing intermediate container c5684a330e17
 ---> 61375a194836
Step 9/10 : EXPOSE 8080
 ---> Running in 000457a963fb
Removing intermediate container 000457a963fb
 ---> 65717fcc9126
Step 10/10 : CMD ["sh", "-c", "uvicorn trustbank.main:app --host 0.0.0.0 --port ${PORT:-8080}"]
 ---> Running in 2304b51ff6cd
Removing intermediate container 2304b51ff6cd
 ---> 9d301a73c0e8
Successfully built 9d301a73c0e8
Successfully tagged asia-southeast1-docker.pkg.dev/project-b63ed173-f777-4777-81a/trustbank/trustbank-api:56284dc
PUSH
Pushing asia-southeast1-docker.pkg.dev/project-b63ed173-f777-4777-81a/trustbank/trustbank-api:56284dc
The push refers to repository [asia-southeast1-docker.pkg.dev/project-b63ed173-f777-4777-81a/trustbank/trustbank-api]
05eed7b9b37f: Preparing
cf3b65f114f4: Preparing
df599d4fc6f4: Preparing
a6694ba8ad6a: Preparing
bee72ea1937e: Preparing
dca2a125b490: Preparing
b361fa3b9794: Preparing
e1fa2746ad6d: Preparing
15f1c8eb1ab1: Preparing
a6694ba8ad6a: Pushed
bee72ea1937e: Pushed
df599d4fc6f4: Pushed
dca2a125b490: Pushed
05eed7b9b37f: Pushed
e1fa2746ad6d: Pushed
b361fa3b9794: Pushed
15f1c8eb1ab1: Pushed
cf3b65f114f4: Pushed
56284dc: digest: sha256:4fd100e6b0383e6ed2376bfa6deb2754bb56d9621907c742870c73a032c21bc8 size: 2202
DONE
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------
ID                                    CREATE_TIME                DURATION  SOURCE                                                                                                 IMAGES                                                                                                 STATUS
4fd26b60-ed70-4d3b-bca0-3aefdc5d3a71  2026-10-16T12:57:24+00:00  1M24S     gs://project-b63ed173-f777-4777-81a_cloudbuild/source/1792155440.519811-953ab2c8668b41e0b43a59756daf6dee.tgz  asia-southeast1-docker.pkg.dev/project-b63ed173-f777-4777-81a/trustbank/trustbank-api:56284dc  SUCCESS
nisha.singh@WPNWCC6CWQ backend % gcloud artifacts docker images describe "$IMAGE"
image_summary:
  digest: sha256:4fd100e6b0383e6ed2376bfa6deb2754bb56d9621907c742870c73a032c21bc8
  fully_qualified_digest: asia-southeast1-docker.pkg.dev/project-b63ed173-f777-4777-81a/trustbank/trustbank-api@sha256:4fd100e6b0383e6ed2376bfa6deb2754bb56d9621907c742870c73a032c21bc8
  registry: asia-southeast1-docker.pkg.dev
  repository: trustbank
  slsa_build_level: unknown
nisha.singh@WPNWCC6CWQ backend % export VERTEX_LOCATION=global
nisha.singh@WPNWCC6CWQ backend % gcloud run deploy "$SERVICE" \
  --image="$IMAGE" \
  --region="$REGION" \
  --service-account="$RUNTIME_SA_EMAIL" \
  --allow-unauthenticated \
  --ingress=all \
  --vpc-connector="$CONNECTOR" \
  --vpc-egress=private-ranges-only \
  --min-instances=1 \
  --max-instances=1 \
  --cpu=1 \
  --memory=1Gi \
  --timeout=60 \
  --set-env-vars="TRUSTBANK_ENVIRONMENT=deployed,TRUSTBANK_GOOGLE_CLOUD_PROJECT=${PROJECT_ID},TRUSTBANK_NEO4J_URI=bolt://10.148.0.2:7687,TRUSTBANK_NEO4J_USER=neo4j,TRUSTBANK_MODEL_NAME
=gemini-2.5-flash,GOOGLE_GENAI_USE_VERTEXAI=TRUE,GOOGLE_CLOUD_PROJECT=${PROJECT_ID},GOOGLE_CLOUD_LOCATION=${VERTEX_LOCATION}" \
  --set-secrets="TRUSTBANK_TOKEN_SECRET=trustbank-token-secret:latest,TRUSTBANK_INVESTIGATOR_CODE=trustbank-investigator-code:latest,TRUSTBANK_NEO4J_PASSWORD=trustbank-neo4j-password:l
atest"

export API_URL="$(gcloud run services describe "$SERVICE" --region="$REGION" --format='value(status.url)')"
printf '%s\n' "$API_URL"
Deploying container to Cloud Run service [trustbank-api] in project [project-b63ed173-f777-4777-81a] region [asia-southeast1]
X Deploying new service...
  - Creating Revision...
  . Routing traffic...
  ✓ Setting IAM Policy...
Deployment failed
ERROR: (gcloud.run.deploy) spec.template.spec.containers[0].env[9].value_from.secret_key_ref.name: Secret projects/767440027550/secrets/trustbank-investigator-code/versions/latest was
not found
spec.template.spec.containers[0].env[10].value_from.secret_key_ref.name: Secret projects/767440027550/secrets/trustbank-neo4j-password/versions/latest was not found

nisha.singh@WPNWCC6CWQ backend % read -rsp 'Investigator demo access code: ' INVESTIGATOR_CODE; echo
printf '%s' "$INVESTIGATOR_CODE" | gcloud secrets create trustbank-investigator-code \
  --replication-policy=automatic \
  --data-file=-
unset INVESTIGATOR_CODE
```

```
read -rsp 'Neo4j VM password: ' NEO4J_PASSWORD; echo
printf '%s' "$NEO4J_PASSWORD" | gcloud secrets create trustbank-neo4j-password \
  --replication-policy=automatic \
  --data-file=-
unset NEO4J_PASSWORD

Grant Cloud Run runtime identity permission:

for SECRET in trustbank-investigator-code trustbank-neo4j-password; do
  gcloud secrets add-iam-policy-binding "$SECRET" \
    --member="serviceAccount:${RUNTIME_SA_EMAIL}" \
    --role="roles/secretmanager.secretAccessor"
done

Verify only secret names, never values:

gcloud secrets list \
  --filter='name:(trustbank-token-secret trustbank-investigator-code trustbank-neo4j-password)' \
  --format='table(name)'
read: -p: no coprocess

ERROR: (gcloud.secrets.create) Resource in projects [project-b63ed173-f777-4777-81a] is the subject of a conflict: Secret [projects/767440027550/secrets/trustbank-investigator-code] al
ready exists.
read: -p: no coprocess

ERROR: (gcloud.secrets.create) Resource in projects [project-b63ed173-f777-4777-81a] is the subject of a conflict: Secret [projects/767440027550/secrets/trustbank-neo4j-password] alrea
dy exists.
zsh: command not found: Grant
Updated IAM policy for secret [trustbank-investigator-code].
bindings:
- members:
  - serviceAccount:trustbank-api-runtime@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/secretmanager.secretAccessor
etag: BwZd9MIBb1M=
version: 1
Updated IAM policy for secret [trustbank-neo4j-password].
bindings:
- members:
  - serviceAccount:trustbank-api-runtime@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/secretmanager.secretAccessor
etag: BwZd9MImJ3M=
version: 1
zsh: command not found: Verify
ERROR: (gcloud.secrets.list) INVALID_ARGUMENT: syntax error at line 1, column 29, token ','
nisha.singh@WPNWCC6CWQ backend % read -rsp 'Investigator demo access code: ' INVESTIGATOR_CODE; echo
printf '%s' "$INVESTIGATOR_CODE" | gcloud secrets create trustbank-investigator-code \
  --replication-policy=automatic \
  --data-file=-
unset INVESTIGATOR_CODE

read -rsp 'Neo4j VM password: ' NEO4J_PASSWORD; echo
printf '%s' "$NEO4J_PASSWORD" | gcloud secrets create trustbank-neo4j-password \
  --replication-policy=automatic \
  --data-file=-
unset NEO4J_PASSWORD
read: -p: no coprocess

ERROR: (gcloud.secrets.create) Resource in projects [project-b63ed173-f777-4777-81a] is the subject of a conflict: Secret [projects/767440027550/secrets/trustbank-investigator-code] al
ready exists.
read: -p: no coprocess

ERROR: (gcloud.secrets.create) Resource in projects [project-b63ed173-f777-4777-81a] is the subject of a conflict: Secret [projects/767440027550/secrets/trustbank-neo4j-password] alrea
dy exists.
nisha.singh@WPNWCC6CWQ backend % gcloud secrets list \
  --filter='name:(trustbank-token-secret trustbank-investigator-code trustbank-neo4j-password)' \
  --format='table(name)'
ERROR: (gcloud.secrets.list) INVALID_ARGUMENT: syntax error at line 1, column 29, token ','
nisha.singh@WPNWCC6CWQ backend % gcloud secrets list \
  --filter='name:(trustbank-token-secret trustbank-investigator-code trustbank-neo4j-password)' \
  --format='table(name)'
ERROR: (gcloud.secrets.list) INVALID_ARGUMENT: syntax error at line 1, column 29, token ','
nisha.singh@WPNWCC6CWQ backend % gcloud secrets list \
  --filter="name:trustbank-" \
  --format='table(name)'
NAME
trustbank-investigator-code
trustbank-neo4j-password
trustbank-token-secret
nisha.singh@WPNWCC6CWQ backend % for SECRET in \
  trustbank-token-secret \
  trustbank-investigator-code \
  trustbank-neo4j-password
do
  gcloud secrets get-iam-policy "$SECRET" \
    --flatten='bindings[].members' \
    --filter="bindings.members:serviceAccount:${RUNTIME_SA_EMAIL}" \
    --format='table(bindings.role)'
done
ROLE
roles/secretmanager.secretAccessor
ROLE
roles/secretmanager.secretAccessor
ROLE
roles/secretmanager.secretAccessor
nisha.singh@WPNWCC6CWQ backend % gcloud run deploy "$SERVICE" \
  --image="$IMAGE" \
  --region="$REGION" \
  --service-account="$RUNTIME_SA_EMAIL" \
  --allow-unauthenticated \
  --ingress=all \
  --vpc-connector="$CONNECTOR" \
  --vpc-egress=private-ranges-only \
  --min-instances=1 \
  --max-instances=1 \
  --cpu=1 \
  --memory=1Gi \
  --timeout=60 \
  --set-env-vars="TRUSTBANK_ENVIRONMENT=deployed,TRUSTBANK_GOOGLE_CLOUD_PROJECT=${PROJECT_ID},TRUSTBANK_NEO4J_URI=bolt://10.148.0.2:7687,TRUSTBANK_NEO4J_USER=neo4j,TRUSTBANK_MODEL_NAME
=gemini-3.8-flash,GOOGLE_GENAI_USE_VERTEXAI=TRUE,GOOGLE_CLOUD_PROJECT=${PROJECT_ID},GOOGLE_CLOUD_LOCATION=${VERTEX_LOCATION}" \
  --set-secrets="TRUSTBANK_TOKEN_SECRET=trustbank-token-secret:latest,TRUSTBANK_INVESTIGATOR_CODE=trustbank-investigator-code:latest,TRUSTBANK_NEO4J_PASSWORD=trustbank-neo4j-password:l
atest"

export API_URL="$(gcloud run services describe "$SERVICE" --region="$REGION" --format='value(status.url)')"
printf '%s\n' "$API_URL"
Deploying container to Cloud Run service [trustbank-api] in project [project-b63ed173-f777-4777-81a] region [asia-southeast1]
X Deploying...
  - Creating Revision...
  . Routing traffic...
  ✓ Setting IAM Policy...
Deployment failed
ERROR: (gcloud.run.deploy) spec.template.spec.containers[0].env[9].value_from.secret_key_ref.name: Secret projects/767440027550/secrets/trustbank-investigator-code/versions/latest was
not found
spec.template.spec.containers[0].env[10].value_from.secret_key_ref.name: Secret projects/767440027550/secrets/trustbank-neo4j-password/versions/latest was not found

nisha.singh@WPNWCC6CWQ backend % read -rsp 'Investigator demo access code: ' INVESTIGATOR_CODE; echo
printf '%s' "$INVESTIGATOR_CODE" | \
```

```
  gcloud secrets versions add trustbank-investigator-code --data-file=-
unset INVESTIGATOR_CODE

read -rsp 'Neo4j VM password: ' NEO4J_PASSWORD; echo
printf '%s' "$NEO4J_PASSWORD" | \
  gcloud secrets versions add trustbank-neo4j-password --data-file=-
unset NEO4J_PASSWORD

read: -p: no coprocess

ERROR: (gcloud.secrets.versions.add) INVALID_ARGUMENT: Secret Payload cannot be empty.
read: -p: no coprocess

ERROR: (gcloud.secrets.versions.add) INVALID_ARGUMENT: Secret Payload cannot be empty.
nisha.singh@WPNWCC6CWQ backend % for SECRET in trustbank-investigator-code trustbank-neo4j-password; do
  gcloud secrets versions list "$SECRET" \
    --format='table(name,state,createTime)'
done
nisha.singh@WPNWCC6CWQ backend % read -rsp 'Investigator demo access code: ' INVESTIGATOR_CODE; echo
printf '%s' "$INVESTIGATOR_CODE" | \
  gcloud secrets versions add trustbank-investigator-code --data-file=-
unset INVESTIGATOR_CODE
read: -p: no coprocess

ERROR: (gcloud.secrets.versions.add) INVALID_ARGUMENT: Secret Payload cannot be empty.
nisha.singh@WPNWCC6CWQ backend % printf 'Investigator demo access code: ' >&2
read -rs INVESTIGATOR_CODE
echo >&2

[[ -n "$INVESTIGATOR_CODE" ]] || { echo "No code entered; stopping." >&2; return 1; }

printf '%s' "$INVESTIGATOR_CODE" | \
  gcloud secrets versions add trustbank-investigator-code --data-file=-

unset INVESTIGATOR_CODE
Investigator demo access code:
Created version [1] of the secret [trustbank-investigator-code].
nisha.singh@WPNWCC6CWQ backend % printf 'Neo4j VM password: ' >&2
read -rs NEO4J_PASSWORD
echo >&2

[[ -n "$NEO4J_PASSWORD" ]] || { echo "No password entered; stopping." >&2; return 1; }

printf '%s' "$NEO4J_PASSWORD" | \
  gcloud secrets versions add trustbank-neo4j-password --data-file=-

unset NEO4J_PASSWORD
Neo4j VM password:
Created version [1] of the secret [trustbank-neo4j-password].
nisha.singh@WPNWCC6CWQ backend % for SECRET in trustbank-investigator-code trustbank-neo4j-password; do
  gcloud secrets versions list "$SECRET" \
    --format='table(name,state,createTime)'
done
NAME  STATE    CREATED
1     enabled  2026-10-16T13:06:37
NAME  STATE    CREATED
1     enabled  2026-10-16T13:07:05
nisha.singh@WPNWCC6CWQ backend % gcloud run deploy "$SERVICE" \
  --image="$IMAGE" \
  --region="$REGION" \
  --service-account="$RUNTIME_SA_EMAIL" \
  --allow-unauthenticated \
  --ingress=all \
  --vpc-connector="$CONNECTOR" \
  --vpc-egress=private-ranges-only \
  --min-instances=1 \
  --max-instances=1 \
  --cpu=1 \
  --memory=1Gi \
  --timeout=60 \
  --set-env-vars="TRUSTBANK_ENVIRONMENT=deployed,TRUSTBANK_GOOGLE_CLOUD_PROJECT=${PROJECT_ID},TRUSTBANK_NEO4J_URI=bolt://10.148.0.2:7687,TRUSTBANK_NEO4J_USER=neo4j,TRUSTBANK_MODEL_NAME
=gemini-3.8-flash,GOOGLE_GENAI_USE_VERTEXAI=TRUE,GOOGLE_CLOUD_PROJECT=${PROJECT_ID},GOOGLE_CLOUD_LOCATION=${VERTEX_LOCATION}" \
  --set-secrets="TRUSTBANK_TOKEN_SECRET=trustbank-token-secret:latest,TRUSTBANK_INVESTIGATOR_CODE=trustbank-investigator-code:latest,TRUSTBANK_NEO4J_PASSWORD=trustbank-neo4j-password:l
atest"

export API_URL="$(gcloud run services describe "$SERVICE" --region="$REGION" --format='value(status.url)')"
printf '%s\n' "$API_URL"
Deploying container to Cloud Run service [trustbank-api] in project [project-b63ed173-f777-4777-81a] region [asia-southeast1]
✓ Deploying... Done.
  ✓ Creating Revision...
  ✓ Routing traffic...
  ✓ Setting IAM Policy...
Done.
Service [trustbank-api] revision [trustbank-api-00003-dd7] has been deployed and is serving 100 percent of traffic.
Service URL: https://trustbank-api-767440027550.asia-southeast1.run.app
https://trustbank-api-gpusuyb6jq-as.a.run.app
nisha.singh@WPNWCC6CWQ backend % curl --fail --show-error "$API_URL/health"
gcloud run services describe "$SERVICE" --region="$REGION" \
  --format='table(status.url,status.conditions[0].status,status.latestReadyRevisionName)'
{"status":"degraded","checks":{"firestore":"ok","neo4j":"down","model":"unchecked"}}URL                                                                                 STATUS  LATEST_READY_REVISION_NAME
https://trustbank-api-gpusuyb6jq-as.a.run.app  True    trustbank-api-00003-dd7
nisha.singh@WPNWCC6CWQ backend % printf 'Gemini API key: ' >&2
read -rs GEMINI_API_KEY
echo >&2

[[ -n "$GEMINI_API_KEY" ]] || { echo "No API key entered; stopping." >&2; return 1; }

if gcloud secrets describe trustbank-gemini-api-key >/dev/null 2>&1; then
  printf '%s' "$GEMINI_API_KEY" | \
    gcloud secrets versions add trustbank-gemini-api-key --data-file=-
else
  printf '%s' "$GEMINI_API_KEY" | \
    gcloud secrets create trustbank-gemini-api-key \
      --replication-policy=automatic \
      --data-file=-
fi

unset GEMINI_API_KEY
Gemini API key:
Created version [1] of the secret [trustbank-gemini-api-key].
nisha.singh@WPNWCC6CWQ backend % gcloud secrets add-iam-policy-binding trustbank-gemini-api-key \
  --member="serviceAccount:${RUNTIME_SA_EMAIL}" \
  --role="roles/secretmanager.secretAccessor"
Updated IAM policy for secret [trustbank-gemini-api-key].
bindings:
- members:
  - serviceAccount:trustbank-api-runtime@project-b63ed173-f777-4777-81a.iam.gserviceaccount.com
  role: roles/secretmanager.secretAccessor
etag: BwZd9OwiYTI=
version: 1
nisha.singh@WPNWCC6CWQ backend % gcloud run services update "$SERVICE" \
  --region="$REGION" \
  --update-env-vars="GOOGLE_GENAI_USE_VERTEXAI=FALSE" \
  --update-secrets="GOOGLE_API_KEY=trustbank-gemini-api-key:latest"
✓ Deploying... Done.
  ✓ Creating Revision...
  ✓ Routing traffic...
```

```
Done.
Service [trustbank-api] revision [trustbank-api-00004-4tl] has been deployed and is serving 100 percent of traffic.
Service URL: https://trustbank-api-767440027550.asia-southeast1.run.app
nisha.singh@WPNWCC6CWQ backend % gcloud run services describe "$SERVICE" \
  --region="$REGION" \
  --format='table(status.url,status.conditions[0].status,status.latestReadyRevisionName)'
URL                                 STATUS  LATEST_READY_REVISION_NAME
https://trustbank-api-gpusuyb6jq-as.a.run.app  True    trustbank-api-00004-4tl
nisha.singh@WPNWCC6CWQ backend % export API_URL="$(gcloud run services describe "$SERVICE" --region="$REGION" --format='value(status.url)')"
printf '%s\n' "$API_URL"
https://trustbank-api-gpusuyb6jq-as.a.run.app
nisha.singh@WPNWCC6CWQ backend % curl --fail --show-error "$API_URL/health"
gcloud run services describe "$SERVICE" --region="$REGION" \
  --format='table(status.url,status.conditions[0].status,status.latestReadyRevisionName)'
{"status":"degraded","checks":{"firestore":"ok","neo4j":"down","model":"unchecked"}}URL                                                                                 STATUS  LATEST_READY_REVISION_NAME
https://trustbank-api-gpusuyb6jq-as.a.run.app  True    trustbank-api-00004-4tl
nisha.singh@WPNWCC6CWQ backend % export CONNECTOR=trustbank-run-egress

gcloud compute networks vpc-access connectors describe "$CONNECTOR" \
  --region="$REGION" \
  --format='yaml(state,network,ipCidrRange)'
ipCidrRange: 10.8.0.0/28
network: default
state: READY
nisha.singh@WPNWCC6CWQ backend % export CONNECTOR=trustbank-run-egress

gcloud compute networks vpc-access connectors describe "$CONNECTOR" \
  --region="$REGION" \
  --format='yaml(state,network,ipCidrRange)'
ipCidrRange: 10.8.0.0/28
network: default
state: READY
nisha.singh@WPNWCC6CWQ backend % gcloud compute instances describe trustbank-neo4j \
  --zone=asia-southeast1-b \
  --format='yaml(status,networkInterfaces[0].networkIP,tags.items)'
networkInterfaces:
- networkIP: 10.148.0.2
status: RUNNING
tags:
  items:
  - trustbank-neo4j
nisha.singh@WPNWCC6CWQ backend % gcloud compute firewall-rules describe allow-trustbank-run-to-neo4j \
  --format='yaml(network,direction,allowed,sourceRanges,targetTags)'
ERROR: (gcloud.compute.firewall-rules.describe) Could not fetch resource:
 - The resource 'projects/project-b63ed173-f777-4777-81a/global/firewalls/allow-trustbank-run-to-neo4j' was not found

nisha.singh@WPNWCC6CWQ backend % gcloud compute networks vpc-access connectors describe "$CONNECTOR" \
  --region="$REGION" \
  --format='yaml(state,network,ipCidrRange)'

ipCidrRange: 10.8.0.0/28
network: default
state: READY
nisha.singh@WPNWCC6CWQ backend % gcloud compute instances describe trustbank-neo4j \
  --zone=asia-southeast1-b \
  --format='yaml(status,networkInterfaces[0].networkIP,tags.items)'
networkInterfaces:
- networkIP: 10.148.0.2
status: RUNNING
tags:
  items:
  - trustbank-neo4j
nisha.singh@WPNWCC6CWQ backend % gcloud compute firewall-rules create allow-trustbank-run-to-neo4j \
  --network="default" \
  --direction=INGRESS \
  --action=ALLOW \
  --rules=tcp:7687 \
  --source-ranges="10.8.0.0/28" \
  --target-tags=trustbank-neo4j
Creating firewall...⠹Created [https://www.googleapis.com/compute/v1/projects/project-b63ed173-f777-4777-81a/global/firewalls/allow-trustbank-run-to-neo4j].
Creating firewall...done.
NAME                          NETWORK  DIRECTION  PRIORITY  ALLOW     DENY  DISABLED
allow-trustbank-run-to-neo4j  default  INGRESS    1000      tcp:7687        False
nisha.singh@WPNWCC6CWQ backend % curl --fail --show-error "$API_URL/health"
{"status":"degraded","checks":{"firestore":"ok","neo4j":"down","model":"unchecked"}}
nisha.singh@WPNWCC6CWQ backend % gcloud compute networks vpc-access connectors describe "$CONNECTOR" \
  --region="$REGION" \
  --format='yaml(state,network,ipCidrRange)'

ipCidrRange: 10.8.0.0/28
network: default
state: READY
nisha.singh@WPNWCC6CWQ backend % gcloud compute instances describe trustbank-neo4j \
  --zone=asia-southeast1-b \
  --format='yaml(status,networkInterfaces[0].networkIP,tags.items)'
networkInterfaces:
- networkIP: 10.148.0.2
status: RUNNING
tags:
  items:
  - trustbank-neo4j
nisha.singh@WPNWCC6CWQ backend % gcloud run services describe "$SERVICE" \
  --region="$REGION" \
  --format='yaml(spec.template.metadata.annotations)'
spec:
  template:
    metadata:
      annotations:
        autoscaling.knative.dev/maxScale: '1'
        autoscaling.knative.dev/minScale: '1'
        run.googleapis.com/client-name: gcloud
        run.googleapis.com/client-version: 494.0.0
        run.googleapis.com/startup-cpu-boost: 'true'
        run.googleapis.com/vpc-access-connector: trustbank-run-egress
        run.googleapis.com/vpc-access-egress: private-ranges-only
nisha.singh@WPNWCC6CWQ backend % gcloud compute ssh trustbank-neo4j \
  --zone=asia-southeast1-b \
  --tunnel-through-iap \
  --command="sudo docker ps --format '{{.Names}}\t{{.Status}}\t{{.Ports}}'; sudo ss -ltn '( sport = :7687 )'"
Updating project ssh metadata...⠹Updated [https://www.googleapis.com/compute/v1/projects/project-b63ed173-f777-4777-81a].
Updating project ssh metadata...done.
Waiting for SSH key to propagate.
WARNING:

To increase the performance of the tunnel, consider installing NumPy. For instructions,
please see https://cloud.google.com/iap/docs/using-tcp-forwarding#increasing_the_tcp_upload_bandwidth

Warning: Permanently added 'compute.6451695967211996064' (ED25519) to the list of known hosts.
WARNING:

To increase the performance of the tunnel, consider installing NumPy. For instructions,
please see https://cloud.google.com/iap/docs/using-tcp-forwarding#increasing_the_tcp_upload_bandwidth

trustbank-neo4j Up 30 hours     0.0.0.0:7474->7474/tcp, :::7474->7474/tcp, 7473/tcp, 0.0.0.0:7687->7687/tcp, :::7687->7687/tcp
State  Recv-Q Send-Q Local Address:Port Peer Address:PortProcess
LISTEN 0      4096         0.0.0.0:7687      0.0.0.0:*
LISTEN 0      4096            [::]:7687         [::]:*
```

```
nisha.singh@WPNWCC6CWQ backend % gcloud compute ssh trustbank-neo4j \
  --zone=asia-southeast1-b \
  --tunnel-through-iap \
  --command='PASSWORD="$(curl -fsS -H "Metadata-Flavor: Google" http://metadata.google.internal/computeMetadata/v1/instance/attributes/neo4j-password)" && sudo docker exec trustbank-ne
o4j cypher-shell -u neo4j -p "$PASSWORD" "RETURN 1 AS ok;"'

WARNING:

To increase the performance of the tunnel, consider installing NumPy. For instructions,
please see https://cloud.google.com/iap/docs/using-tcp-forwarding#increasing_the_tcp_upload_bandwidth

ok
1
nisha.singh@WPNWCC6CWQ backend % gcloud compute ssh trustbank-neo4j \
  --zone=asia-southeast1-b \
  --tunnel-through-iap \
  --command='curl -fsS -H "Metadata-Flavor: Google" http://metadata.google.internal/computeMetadata/v1/instance/attributes/neo4j-password' \
  | gcloud secrets versions add trustbank-neo4j-password --data-file=-

WARNING:

To increase the performance of the tunnel, consider installing NumPy. For instructions,
please see https://cloud.google.com/iap/docs/using-tcp-forwarding#increasing_the_tcp_upload_bandwidth

Created version [2] of the secret [trustbank-neo4j-password].
nisha.singh@WPNWCC6CWQ backend % gcloud run services update "$SERVICE" \
  --region="$REGION" \
  --update-env-vars="TRUSTBANK_RUNTIME_REVISION=$(date -u +%Y%m%dT%H%M%SZ)"
✓ Deploying... Done.
  ✓ Creating Revision...
  ✓ Routing traffic...
Done.
Service [trustbank-api] revision [trustbank-api-00005-8wb] has been deployed and is serving 100 percent of traffic.
Service URL: https://trustbank-api-767440027550.asia-southeast1.run.app
nisha.singh@WPNWCC6CWQ backend % curl --fail --show-error "$API_URL/health"
{"status":"ok","checks":{"firestore":"ok","neo4j":"ok","model":"unchecked"}}
nisha.singh@WPNWCC6CWQ backend % unset TRUSTBANK_FIRESTORE_EMULATOR_HOST
.venv/bin/python -m trustbank.seed --remote "$PROJECT_ID" --reset --yes

# Set TRUSTBANK_NEO4J_URI, TRUSTBANK_NEO4J_USER, and TRUSTBANK_NEO4J_PASSWORD for VM access.
.venv/bin/python -m trustbank.graph.ingest --reset
/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/auth/_default.py:113: UserWarning: Your application has authenticated using end user cred
entials from Google Cloud SDK without a quota project. You might receive a "quota exceeded" or "API not enabled" error. See the following page for troubleshooting: https://cloud.google
.com/docs/authentication/adc-troubleshooting/user-creds.
  warnings.warn(_CLOUD_SDK_CREDENTIALS_WARNING)
reset: dataset collections cleared
customers: 22
beneficiaries: 15
accounts: 37
transactions: 279
connections: 2
zsh: command not found: #
/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/auth/_default.py:113: UserWarning: Your application has authenticated using end user cred
entials from Google Cloud SDK without a quota project. You might receive a "quota exceeded" or "API not enabled" error. See the following page for troubleshooting: https://cloud.google
.com/docs/authentication/adc-troubleshooting/user-creds.
  warnings.warn(_CLOUD_SDK_CREDENTIALS_WARNING)
Traceback (most recent call last):
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/api_core/grpc_helpers.py", line 149, in error_remapped_callable
    return _StreamingResponseIterator(
           ^^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/api_core/grpc_helpers.py", line 71, in __init__
    self._stored_first_result = next(self._wrapped)
                                ^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/grpc/_channel.py", line 547, in __next__
    return self._next()
           ^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/grpc/_channel.py", line 965, in _next
    raise self
grpc._channel._MultiThreadedRendezvous: <_MultiThreadedRendezvous of RPC that terminated with:
        status = StatusCode.PERMISSION_DENIED
        details = "Permission denied on resource project trustbank-local."
        debug_error_string = "PERMISSION_DENIED:Permission denied on resource project trustbank-local."
>

The above exception was the direct cause of the following exception:

Traceback (most recent call last):
  File "<frozen runpy>", line 198, in _run_module_as_main
  File "<frozen runpy>", line 88, in _run_code
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/src/trustbank/graph/ingest.py", line 220, in <module>
    main()
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/src/trustbank/graph/ingest.py", line 203, in main
    dataset = DatasetRepository(create_client(settings)).load()
              ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/src/trustbank/store.py", line 89, in load
    customers=read(CUSTOMERS, Customer),
              ^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/src/trustbank/store.py", line 86, in read
    return tuple(sorted(docs, key=lambda m: m.id))  # type: ignore[attr-defined]
                 ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/src/trustbank/store.py", line 85, in <genexpr>
    docs = (model.model_validate(d.to_dict()) for d in self._db.collection(name).stream())
                                                       ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/cloud/firestore_v1/stream_generator.py", line 58, in __next__
    return self._generator.__next__()
           ^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/cloud/firestore_v1/query.py", line 424, in _make_stream
    response_iterator, expected_prefix = self._get_stream_iterator(
                                         ^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/cloud/firestore_v1/query.py", line 269, in _get_stream_iterator
    response_iterator = self._client._firestore_api.run_query(
                        ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/cloud/firestore_v1/services/firestore/client.py", line 1514, in run_query
    response = rpc(
               ^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/api_core/gapic_v1/method.py", line 189, in __call__
    return wrapped_func(*args, **kwargs)
           ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/api_core/retry/retry_unary.py", line 295, in retry_wrapped_func
    return retry_target(
           ^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/api_core/retry/retry_unary.py", line 157, in retry_target
    next_sleep = _retry_error_helper(
                 ^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/api_core/retry/retry_base.py", line 215, in _retry_error_helper
    raise final_exc from source_exc
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/api_core/retry/retry_unary.py", line 148, in retry_target
    result = target()
             ^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/api_core/timeout.py", line 130, in func_with_timeout
    return func(*args, **kwargs)
           ^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/api_core/grpc_helpers.py", line 153, in error_remapped_callable
    raise exceptions.from_grpc_error(exc) from exc
google.api_core.exceptions.PermissionDenied: 403 Permission denied on resource project trustbank-local. [reason: "CONSUMER_INVALID"
domain: "googleapis.com"
metadata {
```

```
  key: "service"
  value: "firestore.googleapis.com"
}
metadata {
  key: "containerInfo"
  value: "trustbank-local"
}
metadata {
  key: "consumer"
  value: "projects/trustbank-local"
}
, locale: "en-US"
message: "Permission denied on resource project trustbank-local."
, links {
  description: "Google developers console"
  url: "https://console.developers.google.com"
}
]
nisha.singh@WPNWCC6CWQ backend % unset TRUSTBANK_FIRESTORE_EMULATOR_HOST
export TRUSTBANK_GOOGLE_CLOUD_PROJECT="$PROJECT_ID"

export TRUSTBANK_NEO4J_URI=bolt://localhost:7688
export TRUSTBANK_NEO4J_USER=neo4j
export TRUSTBANK_NEO4J_PASSWORD="$(gcloud secrets versions access latest \
  --secret=trustbank-neo4j-password)"

.venv/bin/python -m trustbank.graph.ingest --reset

unset TRUSTBANK_NEO4J_PASSWORD

/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/auth/_default.py:113: UserWarning: Your application has authenticated using end user cred
entials from Google Cloud SDK without a quota project. You might receive a "quota exceeded" or "API not enabled" error. See the following page for troubleshooting: https://cloud.google
.com/docs/authentication/adc-troubleshooting/user-creds.
  warnings.warn(_CLOUD_SDK_CREDENTIALS_WARNING)
Transaction failed and will be retried in 1.0379440551548087s (Couldn't connect to localhost:7688 (resolved to ('[::1]:7688', '127.0.0.1:7688')):
Failed to establish connection to ResolvedIPv6Address(('::1', 7688, 0, 0)) (reason [Errno 61] Connection refused)
Failed to establish connection to ResolvedIPv4Address(('127.0.0.1', 7688)) (reason [Errno 61] Connection refused))
Transaction failed and will be retried in 2.0832224909045953s (Couldn't connect to localhost:7688 (resolved to ('[::1]:7688', '127.0.0.1:7688')):
Failed to establish connection to ResolvedIPv6Address(('::1', 7688, 0, 0)) (reason [Errno 61] Connection refused)
Failed to establish connection to ResolvedIPv4Address(('127.0.0.1', 7688)) (reason [Errno 61] Connection refused))
Transaction failed and will be retried in 4.370656223839786s (Couldn't connect to localhost:7688 (resolved to ('[::1]:7688', '127.0.0.1:7688')):
Failed to establish connection to ResolvedIPv6Address(('::1', 7688, 0, 0)) (reason [Errno 61] Connection refused)
Failed to establish connection to ResolvedIPv4Address(('127.0.0.1', 7688)) (reason [Errno 61] Connection refused))
^CTraceback (most recent call last):
  File "<frozen runpy>", line 198, in _run_module_as_main
  File "<frozen runpy>", line 88, in _run_code
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/src/trustbank/graph/ingest.py", line 220, in <module>
    main()
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/src/trustbank/graph/ingest.py", line 207, in main
    reset_graph(driver)
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/src/trustbank/graph/ingest.py", line 61, in reset_graph
    records, _, _ = driver.execute_query(
                    ^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/neo4j/_sync/driver.py", line 988, in execute_query
    return session._run_transaction(
           ^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/neo4j/_sync/work/session.py", line 616, in _run_transaction
    sleep(delay)
KeyboardInterrupt

nisha.singh@WPNWCC6CWQ backend % unset TRUSTBANK_FIRESTORE_EMULATOR_HOST
export TRUSTBANK_GOOGLE_CLOUD_PROJECT="$PROJECT_ID"

export TRUSTBANK_NEO4J_URI=bolt://localhost:7688
export TRUSTBANK_NEO4J_USER=neo4j
export TRUSTBANK_NEO4J_PASSWORD="$(gcloud secrets versions access latest \
  --secret=trustbank-neo4j-password)"

.venv/bin/python -m trustbank.graph.ingest --reset

unset TRUSTBANK_NEO4J_PASSWORD

/Users/nisha.singh/dev/trustbank-ai/services/backend/.venv/lib/python3.12/site-packages/google/auth/_default.py:113: UserWarning: Your application has authenticated using end user cred
entials from Google Cloud SDK without a quota project. You might receive a "quota exceeded" or "API not enabled" error. See the following page for troubleshooting: https://cloud.google
.com/docs/authentication/adc-troubleshooting/user-creds.
  warnings.warn(_CLOUD_SDK_CREDENTIALS_WARNING)
reset: graph cleared
customers: 22
beneficiaries: 15
accounts: 37
transactions: 279
owns_customer: 22
owns_beneficiary: 15
sent: 279
paid: 279
connected: 2
integrity: ok
nisha.singh@WPNWCC6CWQ backend % cd ..
nisha.singh@WPNWCC6CWQ services % cd ..
nisha.singh@WPNWCC6CWQ trustbank-ai % npm --prefix apps/banking-web ci
npm --prefix apps/banking-web run build
firebase deploy --only hosting

added 284 packages, and audited 285 packages in 9s

84 packages are looking for funding
  run `npm fund` for details

found 0 vulnerabilities

> banking-web@0.0.0 build
> ng build

Initial chunk files | Names                |  Raw size | Estimated transfer size
main-ECT7WOPT.js    | main                 | 276.93 kB |                76.52 kB
styles-RJOX3PSV.css | styles               |   5.99 kB |                 1.70 kB

                    | Initial total        | 282.92 kB |                78.22 kB

Lazy chunk files    | Names                |  Raw size | Estimated transfer size
chunk-ebINjTTC.js   | transaction-page     | 498.24 kB |               133.27 kB
chunk-BbdDm0g7.js   | pay-status           |  22.23 kB |                 6.34 kB
chunk-9bES4dir.js   | pay-form             |   8.96 kB |                 2.90 kB
chunk-Cjjpv1Pd.js   | landing              |   5.72 kB |                 2.20 kB
chunk-BIr7Xkh6.js   | -                    |   4.59 kB |                 1.97 kB
chunk-CiiSSKtl.js   | investigation-shell  |   4.56 kB |                 1.61 kB
chunk-KklfS0wT.js   | entry                |   4.09 kB |                 1.64 kB
chunk-DlsZz8ED.js   | -                    |   3.70 kB |                 1.49 kB
chunk-COWvy8t8.js   | home                 |   2.58 kB |                 1.21 kB
chunk-CSS7m9D1.js   | customer-routes      |   1.83 kB |               862 bytes
chunk-CvAOvdUQ.js   | investigation-routes |   1.52 kB |               704 bytes
chunk-4u2CYD7O.js   | -                    | 831 bytes |               831 bytes
chunk-B0_8tRTG.js   | -                    | 682 bytes |               682 bytes

Application bundle generation complete. [2.954 seconds] - 2026-10-16T13:33:55.486Z

Output location: /Users/nisha.singh/dev/trustbank-ai/apps/banking-web/dist/banking-web
```

```
=== Deploying to 'project-b63ed173-f777-4777-81a'...

i  deploying hosting
i  hosting[trustbank-pausepay]: beginning deploy...
i  hosting[trustbank-pausepay]: found 17 files in apps/banking-web/dist/banking-web/browser
✔  hosting[trustbank-pausepay]: file upload complete
i  hosting[trustbank-pausepay]: finalizing version...
✔  hosting[trustbank-pausepay]: version finalized
i  hosting[trustbank-pausepay]: releasing new version...
✔  hosting[trustbank-pausepay]: release complete

✔  Deploy complete!

Project Console: https://console.firebase.google.com/project/project-b63ed173-f777-4777-81a/overview
Hosting URL: https://trustbank-pausepay.web.app
nisha.singh@WPNWCC6CWQ trustbank-ai % firebase deploy --only firestore --config infra/firebase.emulator.json

=== Deploying to 'project-b63ed173-f777-4777-81a'...

i  deploying firestore
i  firestore: ensuring required API firestore.googleapis.com is enabled...
✔  firestore: required API firestore.googleapis.com is enabled
i  firestore: ensuring required API firestore.googleapis.com is enabled...
i  firestore: reading indexes from firestore.indexes.json...
i  cloud.firestore: checking firestore.rules for compilation errors...
✔  cloud.firestore: rules file firestore.rules compiled successfully
i  firestore: uploading rules firestore.rules...
i  firestore: deploying indexes...
✔  firestore: deployed indexes in firestore.indexes.json successfully for (default) database
✔  firestore: released rules firestore.rules to cloud.firestore

✔  Deploy complete!

Project Console: https://console.firebase.google.com/project/project-b63ed173-f777-4777-81a/overview
nisha.singh@WPNWCC6CWQ trustbank-ai %
```