# 中通客车股份有限公司

版本状态/Rev	A/0		
记录编号/Sheet No.	ZT/MR-PD09-B000-001		
流水码/ No.	B000-104802-(20240320-01)		

### SPECIFICATION FOR ZHONGTONG BUS LCK6103GS

_	SPECIFICA	ATION FOR A		<u>DNGTONG BUS L</u>	CK0103GS			
Main specification	Overall length (mm)	10665	En	Engine	WP7.270E51			
	Overall width (mm)	2600	Engine	Engine position	Weichai engine Rear mounted			
	Overall height (mm)	3280		Model	6-cylinder, supercharging			
ifica	Inner height (mm)	2300		Max power(hp)	270			
tion	Wheel base (mm)	5000		Max torque(N.m/rpm)	1160			
	Front/rear overhang (mm)	2530/3165		displacement(L)	7.47			
	Approach/departure (°)	7.9/7.6		BoreXstroke	108X136			
	Max G.V.W. kg	16000		Fuel	Diesel			
	Seating capacity	56+1		Emision standard	Euro V			
	Model year	2025		Maximum speed	100			
	Item			Standard deploy				
c.	Chassis	Zhongtong bus		1 V				
chassis	Gear box	Manual, 6 speed+1 reverse						
is	Clutch	Ф430						
	Axle	Front:5.5 T, rear: 11 T						
	suspension	Multi-leaf spring 8/11						
	Steering	Power assistant steering						
	Brake	Dual circuit air braking, drum brake, Automatic adjustment arm, ABS.						
	Fuel tank	300 L						
	Tyre	11R22.5 tyre 6+1						
	Battery /dynamo	195A.h/150A 24V						
Вι	Body construction	Integral, Rectangle steel tube welding, phosphating						
Bus body	Interior trim	The common air conditioning interior						
эdy	Door & door pump	Front and rear folding door						
	Window, windscreen	1/3 upper sliding window,2/3 down fixed window,peony green colour,rear windscreen is closed						
	Rear mirror system	Normal reversing	mirr	or				
	A/C system	30000Kcal/h, Bitz	zer co	ompressor				
	VCD system	MP3 player						
	lamp	Front and rear integral headlamps						
	wiper	Electronic wiper, front window washer						
	Seat	56+1 with 2 point seatbelt,3+2 deploy, adjutable driver seat with three point						
		seatbelt, fabric seat fire proof						
	Paint	High grade painting						
	Others	Anti-skid Floor Leather, Driver sunshade shade, Thick cloth side curtain, Driver						
		fence(simple), Warning Triangle, Safety hammer, First aid kit, Skylights, 6 kg two						
		fire extinguishers, Get on ramp handrails, Rain gutter, Time display, (2) radiator,						
	Tool box.							

## 中通客车股份有限公司 Zhongtong Bus Holding Co.,Ltd.

版本状态/Rev	A/0
记录编号/Sheet No.	ZT/MR-PD09-B000-001
流水码/ No.	B000-104802-(20240320-01)

	SPECIFICATION FOR ZHONGTONG BUS LCK6858H						
Overall	Overall dimension (mi	n) 8570		Engine	Engine model	ISDe210-40	
	Overall width (mm)	2480			manufacturer	Cummins	
spe	Overall height (mm)	3380			Engine position	Rear	
Overall specification	Body inside height (m	m) 1940			Engine Type	6 cylinders in line,water cooling, inter-cooling	
	Wheel base (mm)	4100			Max power(kw/rpm)	155	
	Front/rear overhang (n	nm) 1810/2660	)		Max torque(N.m/rpm)	800	
	Max G.V.W.kg	12200			displacement(L)	6.7	
	Seats capacity (person)	35+1			Fuel	Diesel	
	Max. speed km/h	120			Emission standard	Euro IV	
	Model Year	2025			Luggage compartment	3.3 m³	
Items	S	Standard Equ	Standard Equipments				
	Chassis model	Zhongtong					
	Gear box	Manual					
	Clutch:	Φ395 single dry clutch					
	Axle	Front: 4.2T, rear: 8T					
	Suspension	Multi-leaf spring 7/11					
	Steering	ower assistant steering					
	Brake	Dual circuit air braking, drum brake, Automatic adjustment arm, ABS.					
	Fuel tank	200L					
	Tyre	9R22.5 (6+1)					
	Battery /dynamo	165A.h/150A					
	Others	Oil-water separator, dryer, clutch booster, automatically air - cut brake,					
Bus	Body construction	Semi-integral body					
spe	Interior trim	Molding softening interior trim, double luggage rack  Front Pneumatic Outer-Swing Door					
cifi	Door & door pump						
Bus specification	Window, windscreen	Front Laminating Glass, rear tempered glass; Side window: Push-Pull Glass right-front and Rear-End window, the rest all fully closed side window, Shallow green peony					
	Rear mirror system	Manual exterior rear view mirror					
	Defroster	Water circulating defroster					
	A/C system	22000Kcal/h,Bitzer compressor					
	Video system	MP3 player					
	Lamps	New type combination lamp front and rear, top lights, high break lamp					
	Wiper	Electric wiper with washer					
	-	Passenger seats:35+1, 2+2 layout, Adjustable, All seat belt					
	Seat	Driver seat, high seat back, air pumping, adjustable					
	Paint	Top grade paint, body design as per client's demands, the whole body cathodic electrocoati					



#### 中通客车股份有限公司 Zhongtong Bus Holding Co.,Ltd.

版本状态/Rev	A/0
记录编号/Sheet No.	ZT/MR-PD09-B000-001
流水码/ No.	B000-104802-(20240320-01)

	Color grain of plastic flooring, Time display, Soften passengers gratings, Side curtain, Remote
	control lock,Roof window with ventilation fans,Semi enclosed stainless steel tyre decorative
Others	cover,escape valve inside& outside,Automatic fire extinguisher device in the engine
	compartment, Engine compartment temperature alarm, Rain gutter, 6 kg two fire extinguishers,
	Hammers,(2) radiator,Tool box,Triangle warning signs.