

	<b>中通客车股份有限公司</b> <b>Zhongtong Bus Holding</b> <b>Co.,Ltd.</b>	版本状态/Rev	A/0
		记录编号/Sheet No.	ZT/MR-PD09-B000-001
		流水码/ No.	B000-104802-(20240320-01)

## SPECIFICATION FOR ZHONGTONG BUS LCK6720D3E

Overall specification			
Overall dimension （mm）	7225	Approach/departure （°）	18/12
Overall width （mm）	2240	Max G.V.W.kg	7250
Overall height （mm）	2930	Curb Weight(kg)	5150
Body inside height （mm）	1860	Turning radius （m）	≤8.5
Wheel base （mm）	3935	Seating capacity （person）	27+1
Front/rear overhang (mm)	1151/2139	Max. speed （km/h）	100
Model year	2025	Luggage compartment	1.1 m³
Engine			
Model	WP3NQ160E50	Max. Power Kw/rpm	118
Engine Brand	Weichai	Max.Torque Nm/rpm	480
Engine position	Front mounted	Displacement(L)	2.97
Engine Type	Diesel, in-line,4cyl, supercharging, inter-cooling, common rail	Emission standard	Euro V
Chassis			
Axle	Front disc and rear drum break		
Clutch	Single plate/dry friction		
Gear Box	Manual (6+1 Shift)		
Suspension	Leaf Spring, front stabilizer		
Steering System	Integral power steering, steering wheel adjustable		
Brake System	Dual circuit air brake, automatic brake slack adjuster, ABS, exhaust brake		
Tyres Dimensions	215/75R17.5 16PR		
Body			
Exterior	Electrophoresis antirust coating treatment, Zhongtong patented design, customer requested painting pattern		
Interior	Air conditioning interior, sun-visor for front windshield, flame retardant floor leather, luggage compartment interior panel		
Doors	Driver door and front pneumatic swing passenger door, emergency door in left side, luggage compartment door		
Windows	All fully closed side window with peony green colour, curtains for side windows, tempered glass rear windshield, sunroof.		
Seats	27 passenger seats + 1 driver seat, All seat belt		
A/C	Integrated roof A/C,14000Kcal/h		
Video/Audio	MP3 Player		
Reverse Monitor	Single camera colour reversing monitor.		
Other	Tools box,2 parking wedges,1 reflective vest, USB at drive area, hammer, acoustic package (noise reduction),1 unit 2kg fire extinguisher.		