

```
ubuntu@ip-172-31-10-183:~$ #Lab55. Secure File Deletion _shred_lab
ubuntu@ip-172-31-10-183:~$ #OBJECTIVES:Understand the importance and necessity of secure file
deletion. Learn how to use the shred command to securely delete files in a Linux environment.
Verify that shredded files are unrecoverable/
ubuntu@ip-172-31-10-183:~$ #OVERVIEW: The shred command is a powerful tool in Linux used
for securely deleting files so they cannot be recovered. Unlike a simple delete operation, which
merely removes the file's entry from the filesystem table, shred overwrites the file with random
data multiple times, making recovery difficult. This lab will guide you through using shred to
securely delete a file and verify its deletion.
ubuntu@ip-172-31-10-183:~$
ubuntu@ip-172-31-10-183:~$ #Task1:Creating_a_test-file
ubuntu@ip-172-31-10-183:~$ echo "This is a sensitive file that needs secure deletion." > sample.txt
ubuntu@ip-172-31-10-183:~$ cat sample.txt
This is a sensitive file that needs secure deletion.
ubuntu@ip-172-31-10-183:~$ #-u Option: This option not only overwrites the file but also removes
it after overwriting.
ubuntu@ip-172-31-10-183:~$ shred -u sample.txt
ubuntu@ip-172-31-10-183:~$ shred -n 5 -u sample.txt
shred: sample.txt: failed to open for writing: No such file or directory
ubuntu@ip-172-31-10-183:~$ #Task3:VerficiationOfUnrecoverability
ubuntu@ip-172-31-10-183:~$ ls -l sample.txt
ls: cannot access 'sample.txt': No such file or directory
ubuntu@ip-172-31-10-183:~$ grep "sensitive" sample.txt
grep: sample.txt: No such file or directory
ubuntu@ip-172-31-10-183:~$ #CONCLUSION: In this lab, you learned how to securely delete a file
using the shred command in Linux. By overwriting the file multiple times with random data,
shred ensures that the file cannot be easily recovered, especially on HDDs. Understanding file
recovery limitations and proper use of shred is crucial for maintaining data confidentiality.
ubuntu@ip-172-31-10-183:~$ #LabCompleted
ubuntu@ip-172-31-10-183:~$
```