

Ludo! API Server Documentation 0.0.2

Please note that API is still in the phase of planning (pre-implementation).

Function names, functionality, parameters and return types may be subject to modification.

`get_room_status(room_id)`

Returns a JSON with information about the room:

- number of players connected
- board status (a list of the tiles with pawns on them)
- player on the move

`get_time()`

Returns: Local time on the server converted to local time on the requesting machine.

`create_lobby()`

This function creates a lobby on the game server.

Returns: ID of the created lobby.

`add_player_to_lobby(player_id, lobby_id)`

This function adds the player *player_id* to the *lobby_id* lobby. Authorization is not obligatory; it's assumed that lobby ID and/or link ownership is sufficient.

Returns: Status code. (TBD)

`roll_dice(player_id)`

Returns: A value from 1-6.

Note: This process is performed server-side to prevent calling the function on the client-side and gaining an unfair advantage. After the pawn is moved, the outcome of the roll is then verified with the server to ensure data integrity.

`check_legal_moves(pawn_id)`

Returns: A legal increment of moving the pawn forward. -1 if none.

`move(pawn_id, increment)`

Moves the pawn server-side. Handles duplicate pawn issues.

Returns: Status code. (TBD)

`check_for_duplicate_pawns(tile_id)`

Returns: true if there are duplicate pawns on the *tile_id* tile, false if not.

`check_for_victory()`

Returns: ID of a player who won, -1 if no player is victorious.

`quit_lobby(player_id, lobby_id)`

Removes the player from the lobby.

Returns: Status code. (TBD)

`drop_lobby(lobby_id)`

Deletes the lobby.

Returns: Status code. (TBD)
