

## Тема 3. Управление БД в веб-приложении

Для создания базы данных MongoDB можно использовать MongoDB Cloud.

Подключение к серверу баз данных может производиться с помощью утилиты mongosh (MongoDB Shell).

### 1. Создание базы данных

```
use j_users
```

### 1. Добавление содержимого

```
db.users.insertMany([{"login":"student","password":"tneduts"}, {"login":"myuser","password":"mypas"}, {"login":"teacher","password":"qq"}, {"login":"myking","password":"myqueen"}])
```

### 1. Получение данных

```
db.users.findOne({login: "teacher"}).password
```

### 1. Подключение с помощью mongosh

```
mongosh "mongodb connection string"
```

### 1. Получение списка всех записей

```
db.users.find().map(x=>({username:x.login, password:x.password}))
```

```
Microsoft Windows [Version 10.0.19045.4529]
(c) Microsoft Corporation. All rights reserved.

C:\Users\USER>mongosh "mongodb+srv://cluster0.qr2qpss.mongodb.net/" --apiVersion 1 --username zmike2014
Enter password: *****
Current Mongosh Log ID: 6681ec3a75a54a885812ac17
Connecting to:      mongodb+srv://<credentials>@cluster0.qr2qpss.mongodb.net/?appName=mongosh+2.0.0
Using MongoDB:      7.0.11 (API Version 1)
Using Mongosh:      2.0.0
Mongosh 2.2.10 is available for download: https://www.mongodb.com/try/download/shell
For mongosh info see: https://docs.mongodb.com/mongodb-shell/

To help improve our products, anonymous usage data is collected and sent to MongoDB periodically (https://www.mongodb.com/legal/privacy-policy).
You can opt-out by running the disableTelemetry() command.

Atlas atlas-gzdwjp-shard-0 [primary] test> use j_user
switched to db j_user
Atlas atlas-gzdwjp-shard-0 [primary] j_user> db.users.insertMany([
...   { "login": "student", "password": "tneduts" },
...   { "login": "myuser", "password": "mypas" },
...   { "login": "teacher", "password": "qq" },
...   { "login": "myking", "password": "myqueen" }
... ])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId("6681ec9e75a54a885812ac18"),
    '1': ObjectId("6681ec9e75a54a885812ac19"),
    '2': ObjectId("6681ec9e75a54a885812ac1a"),
    '3': ObjectId("6681ec9e75a54a885812ac1b")
  }
}
Atlas atlas-gzdwjp-shard-0 [primary] j_user> _
```

```
Atlas atlas-gzdwjp-shard-0 [primary] j_user> db.users.find().map(x => ({ username: x.login, password: x.password }))
[
  { username: 'student', password: 'tneduts' },
  { username: 'myuser', password: 'mypas' },
  { username: 'teacher', password: 'qq' },
  { username: 'myking', password: 'myqueen' }
]
Atlas atlas-gzdwjp-shard-0 [primary] j_user>
}
}
Atlas atlas-gzdwjp-shard-0 [primary] j_user> db.users.findOne({ login: "teacher" }).password
qq
Atlas atlas-gzdwjp-shard-0 [primary] j_user>
```