

Boundary Enhancement Semantic Segmentation for Building Extraction From Remote Sensed Image

Hoin Jung, Han-Soo Choi, and Myungjoo Kang[✉], *Member, IEEE*

Abstract—Image processing via convolutional neural network (CNN) has been developed rapidly for remote sensing technology. Moreover, techniques for accurately extracting building footprints from remote sensed images have attracted considerable interest owing to their wide variety of common applications, including monitoring natural disasters and urban development. Extraction of building footprints can be performed easily by semantic segmentation using U-Net-like CNN architectures. However, obtaining precise boundaries of segmentation masks remains challenging due to various impediments surrounding target objects. In this study, we propose a method to elaborate edges of buildings detected in remote sensed images to enhance the boundaries of segmentation masks. The proposed method adopts *holistically nested edge detection (HED)*, which extracts edge features at an encoder of a given architecture. In the proposed *boundary enhancement (BE) module*, an extracted edge and segmentation mask are combined, sharing mutual information. To enable the proposed method efficiently to adapt to a wide variety of conditions, we design a distinctive approach adopting a HED unit and BE module, which is applicable to various semantic segmentation networks containing encoder-decoder structures. Experiments were conducted on five different datasets (DeepGlobe, Urban3D, WHU [high-resolution (HR), low-resolution (LR)], and Massachusetts). The results demonstrate that our proposed approaches improved on the performance of prior methods for extracting building footprints. Comparative experiments were conducted on various backbone architectures including U-Net, ResUNet++, TernaNet, and U-shape spatial pyramid pooling (USPP) to ensure the effectiveness of the proposed method. Based on various evaluation metrics and qualitative analysis, our results show that the proposed method achieved improved performance compared with prior methods for all datasets and backbone networks.

Index Terms—Boundary enhancement (BE), building footprint extraction, convolutional neural network (CNN), remote sensing, satellite imagery, semantic segmentation.

I. INTRODUCTION

VARIOUS information from remote sensed images are widely used in the fields of environment [1], [2], ocean sciences [3], geology [4], forestry [5], [6], agriculture [7], and meteorology [8]. Satellite image and aerial image processing,

called remote sensing, refers to any activity that grasps the characteristics of objects on the ground without physical contact or exploration. To this end, various studies have been conducted to obtain and analyze information on land, environments, and resources using multispectral sensors [9] or optical cameras installed on the ground, in aircraft [10], and in satellites.

This remote sensing technology is advantageous in terms of the time necessary to acquire data. Thus, in well-developed remote sensing systems, the amount of effort required to obtain data becomes much lower than that of ground measurement by conventional land surveying techniques [11]. In addition, such technologies enable the acquisition of data from a wide range of areas, including remote or inhospitable areas that humans may not be able to travel. Therefore, image processing techniques using high-resolution (HR) remote sensed images [12], [13] are needed, enabled by the fact that it has become possible in recent years to secure large amounts of such data [14]. Furthermore, the accumulated database on remote sensed images enables predicting future states of a target area by modeling, analyzing, and monitoring objects almost in real-time [15] using both current and historical information.

Recently, remote sensing technology based on image processing by deep learning has been rapidly developed. Several deep-learning-based methodologies in the remote sensing area have been suggested to analyze various types of data, including hyperspectral images (HSI), optical images, LiDAR data, and integrated multisensor data [16], [17]. Above all, the convolutional neural network (CNN) methodology has proven effective in classifying and segmenting each pixel in a given image into a semantic label [18]. Among the many object segmentation and landcover classification tasks in remote sensing, building extraction by binary semantic segmentation methods [19]–[27] is one of the most fundamental challenges because of its extensive practical application. The capability to obtain accurate and immediate building footprint information has significant benefits in monitoring urban development or detecting natural disasters [28].

For these reasons, numerous CNN architectures have been proposed to extract building footprints from the remote sensed image of the target areas. However, some extracted buildings still tend to have inaccurate edges because the encoder-decoder networks downsample the input image as a compressed feature map and upsample the feature map again as the same size as input images to classify objects pixel-wise as true or false. In this procedure, there exists a possibility that boundary information might be lost. In addition, building boundaries can

Manuscript received July 13, 2021; revised August 16, 2021; accepted August 19, 2021. Date of publication September 2, 2021; date of current version January 26, 2022. The work of Myungjoo Kang was supported in part by the National Research Foundation Grant of Korea under Grant 2015R1A5A1009350 and Grant 2021R1A2C3010887 and in part by the ICT Research and Development Program of MSIT/IITP under Grant 1711117093. (Corresponding author: Myungjoo Kang.)

Hoin Jung and Han-Soo Choi are with the Department of Computational Science and Technology, Seoul National University, Seoul 08826, South Korea.

Myungjoo Kang is with the Department of Mathematical Sciences, Seoul National University, Seoul 08826, South Korea (e-mail: mkang@snu.ac.kr).

Digital Object Identifier 10.1109/TGRS.2021.3108781

1558-0644 © 2021 IEEE. Personal use is permitted, but republication/redistribution requires IEEE permission.

See <https://www.ieee.org/publications/rights/index.html> for more information.

be easily disturbed by other objects such as shadows, trees, or various objects near a building [29]. As a result, the classified pixels near the actual boundaries become fragmented and anfractuous because of their ambiguity.

This phenomenon usually appears in encoder-decoder structures like the U-Net [30] CNN architecture, which is known as one of the most fundamental network in semantic segmentation. Because most U-Net-like networks include skip connections to preserve comprehensive semantic information of input images, such networks are not sufficiently deep to detect detailed edge features. Therefore, the proposed method aims to straighten the uncertain edge effectively while improving the semantic segmentation performance. Furthermore, this approach can be attached to any architecture with a U-Net-like structure, regardless of the depth of the backbone network, as described in the following steps.

First, the edge features of detected buildings are extracted by a *holistically nested edge detection (HED)* [31] unit attached to a given backbone encoder. The edge features are then used as inputs for the proposed *boundary enhancement (BE) module*. This BE module includes two parallel subunits detecting a boundary and segmentation masks, respectively. Each subunit shares information by a *combined probability map* to represent the likelihood of a target object. Finally, the segmentation mask feature map passes through a *positive replacement* to enhance its boundary.

In this study, experiments for various backbone networks and datasets were conducted to estimate the performance enhancement of the proposed HED unit and BE module over prior methods. U-Net [30], ResUNet++ [32], TernaNet [19], and U-shape spatial pyramid pooling (USPP) [33] were used as backbone networks in the proposed method. The DeepGlobe [34], Urban3D [35], WHU HR datasets [36], WHU low-resolution (LR) datasets [36], and Massachusetts Buildings Datasets [37] were used in the experiments because of their widespread use in this field.

Consequently, by adopting the proposed approach, the extracted building results can have crisp and delicate boundaries compared with the existing semantic segmentation methods. In addition, the proposed HED unit and BE module can be used widely with various U-Net-like backbones without a significant increase in network parameters or computational cost.

The remaining part of this article is organized as follows. In Section II, we introduce several studies related to semantic segmentation and building footprint extraction using remote sensed imagery. In Section III, the process and characteristics of our proposed method are introduced in detail, including the HED unit and BE module. The designed combination of a loss function and a training strategy is also explained. In Section IV, the feasibility of our proposed method is verified by the results of several experiments. In Section V, we present our final conclusions.

II. RELATED WORK

Recently, the semantic segmentation by CNNs has rapidly developed, showing dramatic increases in capability. A number

of semantic segmentation methodologies are adopting a deep encoder-decoder architecture achieving end-to-end and pixel-to-pixel network [30]. Also, several U-Net-like architectures have been proposed for remote sensed image, especially for building footprint extraction. TernaNet [19], which is widely used for building extraction, adopted the VGG11 [38] pretrained model as an encoder block to increase its pixel-wise classification ability. Liu *et al.* [33] proposed a bridge module between an encoder and a decoder, USPP, to learn a multiple spatial scales and global contextual information. MC-FCN [21] used a multiconstraint FCN [39] structure using subsampled ground truth. ResUNet-a [22] included a residual block structure similar to ResUNet++ [32], considering more detailed information on distance transform and color space via a multitask layer. Residual refine module was proposed by BRR-Net [40], containing a large receptive field and deeper layer to refine the input image and produce accurate building extraction.

On the other hand, few non-U-Net-like backbone networks for building extraction have been developed, such as MAP-Net [23] and DE-Net [24]. In MAP-Net, a multiparallel path and an attention module were used to preserve the spatial localization of multiscale features. DE-Net developed an upsampling method called densely upsampling convolution (DUC) to recover HR prediction maps. Nevertheless, U-Net-like architectures remain a major methodology for detecting semantic building footprint labels.

Meanwhile, some studies to use edge information for semantic segmentation [41], salient object detection [42], and building footprints extraction [25]–[27] have been conducted. A multiscale aggregation fully convolutional neural network (MA-FCN) [25] regularized the polygonized irregular boundaries of a segmentation mask using the Douglas-Peucker algorithm for postprocessing. BR-Net [26] proposed a two-way ground-truth strategy, combining segmentation loss and boundary loss. In addition, to obtain more detailed information on the boundaries of buildings, [27] proposed a boundary loss based on differentiable surrogate metric. However, many attempts to extract edge information from segmentation network are operated on the decoder and tail parts, while encoder-based feature extractions are also effective [31], [42]. To simplify our proposed system and reduce its computational cost, we adopted HED to extract edges by inserting it into a backbone network.

III. PROPOSED METHOD

In this section, we propose a method to enhance the performance of semantic segmentation in remote sensed images by obtaining crisp and straightened edges of extracted buildings. The proposed method involves two main steps. The first is a HED unit, inspired by the fundamental edge detector, HED [31], attached to a backbone encoder. Using this approach, the backbone network is enabled to extract both edges and segmentation masks. The second approach is a BE module to support the ability to detect building footprints by combining the extracted edge and segmentation mask from the HED




Fig. 1. HED unit is attached to a given backbone's encoder. The side outputs are extracted from the last feature maps in each stage being stretched as the same size as the input shape. The side outputs become an auxiliary prediction to guide the network to detect edges of the target object as being corrected by HED loss, L_{HED} . Consequently, the concatenated side outputs will be input to the BE module. Although this figure is an example based on U-Net, the HED unit can be applied to any backbone containing the encoder-decoder architecture.




Fig. 2. Structure of the BE module. H_1 is the concatenated output of the HED unit containing boundary information. H_2 is the segmentation mask produced by the backbone network. Both H_1 and H_2 are adopted to subunits of the BE module in parallel. Two parallel subunits extract and enhance both boundary and segmentation masks, producing each probability map P_1 and P_2 . The two probability maps will be integrated by *combining probability map & positive replacement*.

unit and backbone, respectively. A detailed description of this process is presented as follows.

A. HED Unit

Fig. 1 shows the first part of the proposed BE approach, the HED unit, attached to each stage of the encoder part in a backbone network. The last feature map of each stage in the encoder is extracted and compressed into a one-channel feature map by a 1×1 convolution layer and then upsampled bilinearly with the same size as the input image. We denote these results as $F_i, i \in \{1, 2, 3, 4, 5\}$ in Fig. 1.

The stretched side outputs from each stage are used in two ways. First, the side outputs are connected to the loss function,

HED loss, based on the edges of the ground truth. They are considered as auxiliary outputs to guide the encoder to detect the boundaries of the target objects. Second, the side outputs are concatenated as H_1 to be used as an input to the BE module, containing a holistically nested feature map as shown in (1)

$$H_1 = \text{concat}([F_1, F_2, \dots, F_N]) \quad (1)$$

where N is the number of the stage the architectures have. $N = 5$ is set in Fig. 1 since the exemplified architecture, U-Net, has five-stage structure. Using this procedure, the BE module can include sufficient information on a target's




Fig. 3. (a) Predicted result of probability of boundary and mask. The predicted mask does not cover the ground truth sufficiently, and the predicted boundary can supplement the deficient area. The combining method is shown in (b), merging two probability maps for segmentation mask($P_m(x_m)$) and boundaries($P_b(x_b)$) expressed in yellow lines in (a). Missed pixel prediction of mask or irregular boundary of buildings can be supplemented by the combined probability map($P_s(x)$).

boundary to encourage the tail part of the entire network to produce a smooth segmented boundary.

B. BE Module

The proposed BE module is shown in Fig. 2. To control information about the boundary and segmentation masks of the target objects, the BE module includes a two-way input, H_1 , H_2 , which is produced by the previous network, as shown in Fig. 1. H_1 is the concatenated edge output from the HED unit, which contains abundant boundary information. The other input, H_2 , is the last feature map of the backbone network containing information of the segmentation mask with not sufficiently accurate boundary footprints. The two inputs from the HED unit and backbone share their information to strengthen their feature prediction.

The BE module has a parallel subunit structure responsible for detecting boundary and segmentation masks, respectively. The boundary detection subunit includes a component similar to the SE block [43] to boost the representative power of the boundary feature map. The boundary information H_1 can be reinforced by calibrating the interdependency response between channels. The output of the SE-like block is compressed into one-channel mask by a 1×1 convolutional layer, while the last feature map is used as a probability map P_1 .

On the other hand, the segmentation mask detection subunit is the principal prediction unit of the entire network, which is




Fig. 4. Combining module consists of probability map and positive replacement. The probability map enhances the edge of segmentation mask directly, and the combined result will replace the original segmentation mask maintaining its scale by positive replacement.

used as the final segmentation output. This subunit receives two inputs, H_2 and H_3 , from the backbone network and boundary detection subunit. Sufficient boundary information is shared by H_3 from the boundary detection subunit to the segmentation mask detection subunit. Moreover, H_2 and H_3 are concatenated to use both information sources on the segmentation mask and boundary. By passing through several convolutional layers, the subunit produces a probability map P_2 .

Finally, the segmentation mask feature map is enhanced to contain precise boundary prediction by the combining module, consisting of *combining probability map* and *positive replacement*.

1) *Combining Probability Map*: Each parallel subunit in the BE module produces one-channel feature maps, P_1 and P_2 , for both the boundary and segmentation masks. P_1 and P_2 become probability maps, $P_b(x_b)$ and $P_m(x_m)$, individually by a softmax activation function, indicating the likelihood of the target object existing in a given pixel. Simultaneously, P_1 is regarded as the boundary prediction to calculate the loss function with the boundary ground truth passing through the sigmoid activation function.

Each probability map, $P_b(x_b)$ and $P_m(x_m)$, is combined by the pixel-wise addition of the probability values, as shown in Fig. 3. When the added probability values exceed 1.0 because of the overlapped prediction of the boundary and segmentation masks, the results were considered to be simply 1.0, as shown in (2). In the inference step, the pixel-wise addition is conducted on five times amplified boundary probability map, $5P_b$. Although the predicted segmentation mask could not sufficiently cover the footprint representation, the proposed method makes it possible to suggest a precise boundary to the deficient area of segmentation mask prediction

$$P_s(x) = \min(P_b(x_b) + P_m(x_m), 1). \quad (2)$$

2) *Positive Replacement*: The proposed combined probability map produces probability values $[0,1]$. However, the pixel signal values of the raw segmentation masks, P_2 , are allocated in a broad range between $(-\infty, \infty)$, before the softmax function is applied.

To obtain the refined boundary while retaining the scale of the response, P_2 is reused using the provided probability maps




Fig. 5. Raw signal values of the mask prediction (x_m) are modified by the combined probability map ($P_s(x)$). Positive signals ($\sigma(x_m)$) in x_m are removed and replaced with the scaled combined probability map ($P_s(x)\lambda(x_m)$), while the negative signals are supplemented. The adjusted prediction, final output (x_{output}), shows improved results fitting well with the ground truth.

$P_s(x)$, as shown in Fig. 4 and (3) and (4)

$$x_{\text{output}} = x_m - \sigma(x_m) + P_s(x)\lambda(x_m) \quad (3)$$

$$\lambda(x_m) = \frac{1}{N_{\text{nonzero}}} \sum_{k=0}^{N-1} \sigma(x_m)_k \quad (4)$$

where x_m is the signal value of P_2 and $\sigma(x)$ is an activation function. In these experiments, the activation function is set to a rectified linear unit (ReLU), i.e., $\sigma(x) = \max(0, x)$.

In (3) and (4), the positive parts of responses in P_2 and $\sigma(x_m)$ are removed, while the negative ones are maintained: $x_m - \sigma(x_m)$. Instead, the scaled probability map $P_s(x)\lambda(x_m)$ replaces the positive parts of the x_m as shown in (3), where the scale factor, $\lambda(x_m)$, is the average value obtained from $\sigma(x_m)$, the positive parts of P_2 . The renewed probability map, $P_s(x)\lambda(x_m)$, has sufficient information about both boundary and segmentation masks while maintaining the scale of original response of P_2 . Finally, the final output prediction mask x_{output} can be obtained representing boundary enhanced segmentation mask, as shown in Fig. 5. x_{output} passes through the sigmoid activation function to compute the loss function with the ground truth of the segmentation mask.

C. Loss Functions

The entire network should effectively detect both boundary and segmentation masks to acquire a well-regularized segmentation mask. For this reason, three different loss functions were designed for each output, situated separately as follows. The total loss will be discussed in training strategy:

$$L_{\text{total}} = f(L_{\text{HED}}, L_{\text{boundary}}, L_{\text{mask}}). \quad (5)$$

1) *Boundary Loss*: To obtain errors related to detecting the edges of objects, the binary cross-entropy (BCE) [44] loss is applied to compute the loss between predictions and ground truth for a given boundary. In the HED unit, multilevel loss is acquired by calculating the loss functions for each side output F_k , originating in the encoder of the backbone network;

$L_k = \text{BCE}(y_{\text{boundary}}, F_k)$, $F_k \in \{1, 2, \dots, N_{\text{stage}}\}$, where y_{boundary} is the ground truth of building's boundary. The summation of each loss function becomes L_{HED} , in (6).

$$L_{\text{HED}} = \sum_{k=1}^{N_{\text{stages}}} L_k \quad (6)$$

where N_{stages} means the number of encoding stage of the backbone networks. Moreover, L_{boundary} is obtained by calculating the loss function between the ground truth and the P_1 , output of the boundary detection subunit in the BE module: $L_{\text{boundary}} = \text{BCE}(y_{\text{boundary}}, \hat{y}_{\text{boundary}})$, where $\hat{y}_{\text{boundary}}$ is the predicted boundary from P_1 .

2) *Segmentation Mask Loss*: The segmentation mask loss is obtained by combining the focal loss [45] and MS-SSIM loss [46], in (7)

$$L_{\text{mask}} = L_{\text{focal}} + L_{\text{MS-SSIM}}. \quad (7)$$

Because the proposed method adopts the *combined probability map* and *positive replacement* to accurately detect both boundary and segmentation masks, structural imbalance might occur in prediction near the edge of a target. Focal loss can solve this problem by weighting the negative term in the cross-entropy loss with $\gamma = 2$. Furthermore, to preserve the structural characteristics of the target, MS-SSIM loss considers contrast, luminance, and structure at various scales to prevent the segmentation mask from being fragmented.

The MS-SSIM loss can be obtained by the following equation:

$$L_{\text{MS-SSIM}} = 1 - \prod_{j=1}^M \left(\frac{2\mu_x\mu_y + C_1}{\mu_x^2 + \mu_y^2 + C_1} \right)^{\beta_j} \left(\frac{2\sigma_{xy} + C_2}{\sigma_x^2 + \sigma_y^2 + C_2} \right)^{\gamma_j}$$

for $\mathbf{x} = \{x_i \mid i = 1, 2, \dots, M\}$ and $\mathbf{y} = \{y_i \mid i = 1, 2, \dots, M\}$, where M is the total number of scale layers, and β_j and γ_j are the parameters defining the relative importance of the components. Let μ_x , σ_x^2 , and σ_{xy} be the mean of x , the variance of x , and the covariance of x and y , respectively, between the ground truth and prediction. The small constants $C_1 = (K_1 L)^2$ and $C_2 = (K_2 L)^2$ are added to prevent the equation from being divided by zero, where L is the dynamic range of the pixel value, 1.0. In our experiments, we set $M = 5$, $K_1 = 0.1$, $K_2 = 0.3$, and $\beta_j = \gamma_j = [0.0448, 0.2856, 0.3001, 0.2363, 0.1333]$ as denoted in [46].

D. Training Strategy

The main purpose of our network is ultimately to obtain a high-quality segmentation mask. In (5), the segmentation mask loss has equal importance with the boundary loss. In addition, the value of the boundary subunit loss in the BE module, L_{boundary} , is similar to the individual loss, L_k , in the HED unit. This situation is not suitable because if the importance of L_{HED} is N_{stages} times larger than L_{boundary} and L_{mask} , the total loss drives the entire network's emphasis on edge detection rather than segmentation mask.

We designed the training procedure as two steps to deal with this conflict by supposing that each step has an intrinsic function. In the first few steps, the total loss weights in the




Fig. 6. Experimental result of the DeepGlobe dataset for each area of interest and backbone networks. The boundaries of the building footprint are straightened and manifested, while adjacent buildings are distinguished well.

HED loss to guide the network to learn multiscale boundary features in the encoding section, as mentioned in (9). All individual loss functions have equal importance to the HED loss L_k of each stage.

Second, the total loss becomes having more weight in L_{mask} , as shown in (9). The entire HED loss of each stage is regarded as a single loss value that has the same weight as L_{focal} and $L_{\text{MS-SSIM}}$. Moreover, L_{boundary} has more weight because the output of the boundary detection subunit is connected to the possibility map and affects the final segmentation mask output. In this study, (9) is applied for the first two epochs, and (9) is the dominant total loss function. Here, N is the number of stage in the backbone network

$$\begin{cases} L_{\text{HED}} + L_{\text{boundary}} + \frac{L_{\text{mask}}}{2} & (8) \\ \frac{1}{N} \times L_{\text{HED}} + L_{\text{boundary}} \times N + L_{\text{mask}} & (9) \end{cases}$$

IV. EXPERIMENTAL RESULTS

A. Datasets

In this study, extensive experiments were conducted to evaluate the proposed method for five open datasets, including DeepGlobe Dataset [34], Urban3D Challenge Dataset [35], WHU Building Dataset(HR, LR) [36], and Massachusetts Buildings Dataset [37]. In these experiments, all the training and validation subsets for each datasets were merged as a single dataset because some provided datasets were divided into train/validation/test subsets, whereas others comprised integrated data.

The DeepGlobe dataset, which was used in the DeepGlobe Building Detection Challenge and SpaceNet Building Detection Challenge, covers 3,011 km² of urban and suburban land

area, including four regions: Las Vegas, Paris, Shanghai, and Khartoum. The source images came from the WorldView-3 satellite sensor, which produces RGB and 8-band multi-spectral data containing 302,701 building footprints with a 30-cm ground sample distance (GSD). The dataset contains 650 × 650 pixel image size for all areas of interest with 9,004 and 1,589 images as the training set and testing set, respectively.

The USSOCOM Urban3D Challenge dataset was also produced by the WorldView-3 satellite containing 2-D orthorectified RGB images and 3-D digital surface models with 50 cm GSD. The source images cover over 360 km of terrain and contain roughly 157,000 building footprints with a 2048 × 2048 resolution image. In these experiments, the HR images are split into 512 × 512 pixel images with 2912 and 672 images as the training and testing sets, respectively.

The WHU building dataset includes two different sub-datasets, aerial and satellite subsets. The aerial subset, called WHU HR dataset in this article, covers 450 km² of Christchurch, New Zealand, with 30 cm GSD, containing more than 187,000 building footprints. The source images were provided with a 512 × 512 pixel size with 5772 training sets and 2416 testing sets.

The satellite subset, named WHU LR subset in this article, consists of satellite images covering 550 km² of East Asia with 2.7 m GSD. The LR subset includes 17,388 tiles with 512 × 512 pixel size containing 29,085 buildings that are separated into 13,662 training sets and 3,726 testing sets.

The Massachusetts Buildings Dataset consists of 151 aerial images with 1500 × 1500 resolution and 1.0 m GSD covering the Boston area. The entire datasets are split into 137, 10, and 4 images as the training, testing, and validation sets, respectively. Besides, merging and cropping were conducted




Fig. 7. Experimental result of the Urban 3-D Dataset for each backbone network. The boundaries of building footprint are straightened and manifested, while adjacent buildings are distinguished well.




Fig. 8. Experimental result of the WHU-HR Dataset for each backbone network. The boundaries of building footprint are straightened and manifested, while adjacent buildings are distinguished well.

to use the dataset properly. The validation set is assigned to the training set to enhance the deep learning model strictly. The 1500×1500 pixel images are cropped into nine smaller images with 512×512 resolution with overlapping, while some blank areas are abandoned. As a result, we can get 1100 images for the training set and 90 images for the testing set with 512×512 pixel size and 1.0 m GSD.

We used only 2-D RGB satellite or aerial images for all datasets, although the offered dataset contains other types of materials such as 3-D images or multispectral data. Furthermore, although some source images contain incorrect ground truth or blank areas, all images are used to train and test without abandoning. Moreover, to estimate the ability of enhancement strictly, all datasets are used as given by providers without any augmentation.

B. Implementation Details

In these experiments, we used various U-Net-like backbone network. U-Net [30], ResUNet++ [32], and TernaUSNet [19] were adopted to validate our proposed approach. U-Net includes an encoder-decoder architecture with five stages. Each stage has a typical structure with two convolution filters and two activation functions, alternately. ResUNet++ [32] is an advanced architecture for semantic segmentation containing SE blocks [43], residual blocks [47], ASPP [48], and attention blocks [49]. ResUNet++ has a four-stage structure with the same number of downsampling and upsampling sequences. However, ResUNet++ is regarded as having five stages

because it contains an ASPP bridge part acting as a fifth downsampling layer. For the proposed method, both U-Net and ResUNet++ include five side outputs, whereas TernaUSNet [19], based on VGG11 [38] encoder, contains a sixth stage and the same number of side outputs.

Our proposed HED unit connected to the encoder part of a U-Net-like network would obtain five or six side outputs depending on the backbone architecture. As a result, both outputs of the HED unit and decoder in the backbone network are used as two parallel inputs of the BE module. The structure of the BE module maintains equally regardless of the type of backbone, without a significant increase in the calculation cost. The amount of floating point operations per second (FLOPs) and the calculation parameters used are listed in Table I, as followed by the 512×512 size of input image.

The Adam [50] optimizer was used with $\beta_1 = 0.9$, $\beta_2 = 0.999$ as weight decay. The initial learning rate was set to $lr = 10^{-4}$ without a learning scheduler. The batch size was set to 4 because of a limitation on GPU usage. All hyperparameters were maintained in the same manner to conduct recursive experiments for all datasets and backbones in equivalent conditions. In the training procedure, all outputs of the network are passed through the sigmoid activation function to apply loss functions.

C. Evaluation

1) *Inference*: In the inference procedure, the output of the *positive replacement* in the BE module is used as the




Fig. 9. Experimental result of the WHU-LR Dataset for each backbone network. The boundaries of building footprint are straightened and manifested, while adjacent buildings are distinguished well.




Fig. 10. Experimental result of the Massachusetts Dataset for each backbone network. The boundaries of building footprint are straightened and manifested, while adjacent buildings are distinguished well.

TABLE I

COMPARISON OF PARAMETERS AND FLOPS ON EACH BACKBONE SHOWS THAT THE ADDITION OF PROPOSED APPROACH CAUSES MARGINAL INCREMENT

Model	Params (M)	FLOPs (G)
U-Net	34.52	130.90
U-Net + BE	34.59	140.64
ResUNet++	14.48	141.71
ResUNet++ + BE	14.52	146.64
TernausNet	22.93	84.24
TernausNet + BE	22.97	89.14
USPP	18.81	97.58
USPP + BE	18.93	112.14

TABLE II

COMPARISON OF APPLYING THE PROPOSED METHOD FOR VARIOUS BACKBONE NETWORKS ON THE DEEPGLOBE DATASET

Model	Precision	Recall	F1 Score	Jaccard
U-Net	0.82576	0.80547	0.79807	0.68606
U-Net + BE	0.82677	0.80813	0.80403	0.69218
ResUNet++	0.81605	0.76335	0.76977	0.65272
ResUNet++ + BE	0.82760	0.78717	0.78986	0.67647
TernausNet	0.84196	0.77473	0.78740	0.67618
TernausNet + BE	0.82874	0.80531	0.80436	0.69257
USPP	0.80923	0.76833	0.76970	0.65336
USPP + BE	0.83140	0.80805	0.80499	0.69476
Mean : base	0.82325	0.77797	0.78123	0.66708
Mean : base + BE	0.82862	0.80216	0.80081	0.68899

final prediction. When this segmentation mask representation passes through the sigmoid activation function in the training process, the raw results from *positive replacement* are used as a prediction result without any activation function. The positive part of the output indicates the extracted building footprints. Moreover, the negative values of the segmentation mask representation are considered as background.

2) *Metric*: To evaluate the performance of the proposed method, pixel-wise estimations were conducted, indicating the quality of each experiment. F1 score and Jaccard coefficient were used as evaluation metrics.

F1 score is defined as the harmonic mean of a model's precision and recall by classifying each pixel as true or false. F1 score is widely used to evaluate binary classification systems, commonly in semantic segmentation tasks, because

it indicates a well-balanced prediction between precision and recall.

The Jaccard coefficient is also derived from precision and recall. The Jaccard coefficient is useful for estimating semantic segmentation performance because it shows the similarity between the two structures of prediction and ground truth intuitively.

D. Results Analysis

The results of the experiments are presented in Tables II–VI. The results show that our proposed method can improve the ability to extract building footprints from optical images for all the experimental datasets and backbone networks. The F1 score and Jaccard scores for all experiments were

TABLE III

COMPARISON OF APPLYING THE PROPOSED METHOD FOR VARIOUS BACKBONE NETWORKS ON THE URBAN 3-D DATASET

Model	Precision	Recall	F1 Score	Jaccard
U-Net	0.86880	0.73122	0.78720	0.66150
U-Net + BE	0.85624	0.78489	0.81350	0.69670
ResUNet++	0.83855	0.72414	0.77028	0.64240
ResUNet+++ BE	0.84410	0.75251	0.78905	0.66244
TernausNet	0.84441	0.74676	0.78606	0.65788
TernausNet + BE	0.85607	0.75970	0.79902	0.67683
USPP	0.89237	0.75147	0.80908	0.69150
USPP + BE	0.89301	0.76556	0.81868	0.70401
Mean : base	0.86103	0.73840	0.78816	0.66332
Mean : base + BE	0.86236	0.76567	0.80506	0.68500

TABLE IV

COMPARISON OF APPLYING THE PROPOSED METHOD FOR VARIOUS BACKBONE NETWORKS ON THE WHU-HR DATASET

Model	Precision	Recall	F1 Score	Jaccard
U-Net	0.93399	0.92463	0.92396	0.86911
U-Net + BE	0.92926	0.93667	0.92793	0.87456
ResUNet++	0.91847	0.90808	0.90645	0.84237
ResUNet+++ BE	0.92230	0.91035	0.90870	0.84581
TernausNet	0.92903	0.91349	0.91558	0.85547
TernausNet + BE	0.91114	0.93838	0.91991	0.86006
USPP	0.93949	0.91584	0.91964	0.86554
USPP + BE	0.90755	0.94953	0.92241	0.86540
Mean : base	0.93025	0.91551	0.91641	0.85812
Mean : base + BE	0.91756	0.93373	0.91974	0.86146

improved, as shown in Tables II–VI. The average F1 scores of the four backbones for each dataset (DeepGlobe, Urban3D, WHU-HR, WHU-LR, and Massachusetts) were increased by about 1.43%p, 1.93%p, 0.35%p, 1.19%p, and 1.22%p, respectively, compared with baseline and proposed approaches. Similarly, the Jaccard scores also increased by approximately 1.54%p, 2.47%p, 0.45%p, 1.30%p, and 1.25%p, respectively. Furthermore, the improvement of the performance was relatively higher than the variation in computational parameters, about 0.32% on average, as shown in Table I.

The results are shown in Figs. 6–10. As shown by the red dashed circles in each experimental figure, the improved method could classify pixels more precisely, even if the target buildings had a complicated shape. In particular, although impediments may disturb the ability to detect the edge area of a target, the results show that the proposed method can maintain the rectilinear boundaries of buildings detected in remote sensing applications. Moreover, the proposed method helps classify adjacent buildings separately, which tend to be detected as single buildings. These results show that our proposed method can be used widely, regardless of area of interest and backbone network.

E. Robustness

To investigate the robustness of enhancement of the proposed method, repetitive experiments were conducted ten times with all backbone networks on the Urban3D and Massachusetts datasets representing HR and LR, respectively. Table VII shows the evaluation result of repetitive experiments.

TABLE V

COMPARISON OF APPLYING THE PROPOSED METHOD FOR VARIOUS BACKBONE NETWORKS ON THE WHU-LR ASIA DATASET

Model	Precision	Recall	F1 Score	Jaccard
U-Net	0.86461	0.70668	0.75567	0.62906
U-Net + BE	0.86525	0.73607	0.78178	0.65530
ResUNet++	0.85672	0.68817	0.74195	0.60969
ResUNet+++ BE	0.83958	0.70782	0.75089	0.61731
TernausNet	0.83262	0.76335	0.78493	0.65801
TernausNet + BE	0.84453	0.76126	0.78645	0.66162
USPP	0.88645	0.67198	0.74283	0.61374
USPP + BE	0.83906	0.72449	0.75800	0.62819
Mean : base	0.86010	0.70755	0.75635	0.62763
Mean : base + BE	0.84711	0.73241	0.76928	0.64061

TABLE VI

COMPARISON OF APPLYING THE PROPOSED METHOD FOR VARIOUS BACKBONE NETWORKS ON THE MASSACHUSETTS DATASET

Model	Precision	Recall	F1 Score	Jaccard
U-Net	0.83242	0.78581	0.80358	0.67663
U-Net + BE	0.79366	0.82605	0.80446	0.67587
ResUNet++	0.81641	0.66833	0.72758	0.57764
ResUNet+++ BE	0.79855	0.72761	0.75738	0.61007
TernausNet	0.82742	0.74835	0.78222	0.64514
TernausNet + BE	0.78833	0.79740	0.78721	0.65249
USPP	0.85439	0.77684	0.80884	0.68312
USPP + BE	0.80159	0.83593	0.81237	0.68829
Mean : base	0.83244	0.74483	0.78056	0.64563
Mean : base + BE	0.79553	0.79675	0.79035	0.65668

TABLE VII

REPETITIVE EXPERIMENTS WERE CONDUCTED TEN TIMES WITH EACH BACKBONE NETWORK

Dataset	F1-score			
	Urban3D		Massachusetts	
	Mean	Std. Dev.	Mean	Std. Dev.
U-Net	0.79315	0.00667	0.80079	0.01243
U-Net + BE	0.81578	0.00167	0.80265	0.00399
ResUNet++	0.76797	0.00632	0.73760	0.00484
ResUNet+++ BE	0.78818	0.00433	0.75048	0.00471
TernausNet	0.78173	0.00361	0.78051	0.00619
TernausNet + BE	0.80342	0.00348	0.78886	0.00304
USPP	0.80498	0.01362	0.79652	0.01452
USPP + BE	0.81878	0.00787	0.81147	0.00441

TABLE VIII

COMPARISON OF MOST RECENT BUILDING EXTRACTION METHODS ON URBAN3D DATASET AND MASSACHUSETTS DATASET

Dataset		Urban3D		Massachusetts	
Model		F1-score	Jaccard	F1-score	Jaccard
Baseline U-Net -like	U-Net	0.78720	0.66150	0.80358	0.67663
	ResUNet++	0.77028	0.64240	0.72758	0.57764
	TernausNet	0.78606	0.65788	0.78222	0.64514
	USPP	0.80908	0.69150	0.80884	0.68312
	BRR-Net	0.79960	0.67716	0.79291	0.66138
Non-U-Net -like	MAP-Net	0.81615	0.70397	0.79638	0.66657
	DE-Net	0.81694	0.70446	0.81179	0.68630
Modified U-Net -like (+BE)	U-Net	0.81350	0.69670	0.80446	0.67587
	ResUNet++	0.78905	0.66244	0.75738	0.61007
	TernausNet	0.79902	0.67683	0.78721	0.65249
	USPP	0.82163	0.70901	0.81237	0.68829
	BRR-Net	0.80893	0.69258	0.79676	0.66635

The combination of the HED unit and BE module improves the F1-score for each experiment compared with baseline without exception. Furthermore, the standard deviation results

TABLE IX

ABLATION STUDY RESULTS FOR URBAN3D DATASET. TO CONVINCE THE PERFORMANCE OF HED UNIT AND BE MODULE, ADDITIONAL EXPERIMENTS WERE EXECUTED USING BCE LOSS ONLY, WITHOUT PROPOSED COMBINATION LOSS FUNCTION AS SHOWN IN THE ABOVE TABLE AS MS

Model	Precision	Recall	F1 Score	Jaccard
U-Net	0.86880	0.73122	0.78720	0.66150
U-Net+BE+BCE	0.86190	0.76008	0.80211	0.68082
U-Net+BE+MS	0.85624	0.78489	0.81350	0.69670
ResUNet++	0.83855	0.72414	0.77028	0.64240
ResUNet++ +BE+BCE	0.83414	0.74910	0.77992	0.65088
ResUNet++ +BE+MS	0.84410	0.75251	0.78905	0.66244
TernausNet	0.84441	0.74676	0.78606	0.65788
TernausNet+BE+BCE	0.83851	0.76641	0.79493	0.67055
TernausNet+BE+MS	0.85607	0.75970	0.79902	0.67683

are lowered in modified networks. It shows that the proposed approach can stabilize the network to extract the precise building segmentation mask, regardless of the target image's resolution.

F. Comparison of Recent Method

The comparison results are shown in Table VIII. The evaluation results are improved in boundary-enhanced method for all U-Net-like architectures, including state-of-the-art (SOTA) U-Net-like methodologies, USPP, and BRR-Net. Moreover, the USPP network with the proposed method achieved a higher F1-score and Jaccard score than the recent Non-U-Net-like methods, MAP-Net and DE-Net. The Urban3D and Massachusetts datasets are adopted to prove the ability of boundary reinforcement for the HR image (0.3 m GSD) and LR image (1.0 m GSD).

The comparison results in Table VIII show that any U-Net-like network can adopt our proposed approach. Furthermore, if a well-performing backbone is given, the HED unit and BE module can supplement it to outperform other SOTA architectures.

G. Ablation Study

To investigate the contribution of the proposed approach and MS-SSIM [46] loss, we designed ablation experiments for all backbone networks on the Urban3D dataset. Similar to previous experiments, the F1 score and Jaccard score were used as evaluation metrics to estimate accuracy.

In addition to Table III, we conducted a further experiment for the baseline with the proposed HED unit and BE module without MS-SSIM loss. Unlike (7), the loss function of the mask was set as a BCE loss. The weights of each loss function were maintained equally, 1:1:1. The results are listed in Table IX. The F1 score and Jaccard score results for the additional experiments were improved in comparison to the baseline model for all backbone networks.

The scores tended to be lower than the proposed combination of the loss function. The ablation study shows that the HED unit and BE module were able to enhance the performance of semantic segmentation sufficiently, and the proposed loss function guarantees the stable improvement of performance.

V. CONCLUSION

We have proposed a method to enhance the ability of automated systems to detect the boundaries of semantic segmentation masks in building extraction from remote sensed imagery. The method is composed of two major steps: a HED unit and a BE module, which can be adopted in various U-Net-like CNNs containing an encoder-decoder architecture. The HED unit is connected to an encoder directly to detect the boundary of a target object well. The BE module is a tail part of the entire network and produces the final output by combining the information of the edge and segmentation masks by probability map and positive replacement.

For this BE method, the boundary of the extracted building footprints can be smoother than the existing semantic segmentation without a considerable increase in calculation cost.

The evaluation metrics with F1 score and Jaccard coefficient also show that this BE method produced improved output in terms of accuracy of segmentation and refined the sensitivity and specificity. Moreover, the new combination of loss functions guarantees the network to generate a segmentation-mask-preserving structure.

In addition, the experimental results show that the proposed method is feasible to both HR image (DeepGlobe, Urban3D, WHU-HR) and LR dataset (WHU-LR, Massachusetts). Consequently, the limit resolution of the proposed approach is not found through these experiments. Though we suppose that the proposed approach may not enhance the performance of extraction when the boundary and mask are not clearly distinguished due to LR or damage in a given image. Nevertheless, the combination of HED unit and BE module surely improves the extracting ability regardless of the resolution, target location, and backbone network.

In general, our research provides a new approach for amending the shape of extracted buildings while improving accuracy metrics. Currently, the proposed method is implemented in building extraction with U-Net-like CNN architectures. In future works, we intend to further study various architectures such as DeepLabv3 [51], Mask R-CNN [52], and tasks such as multiclass extraction, road detection, and land cover classification.

REFERENCES

- [1] T. Blaschke, S. Lang, E. Lorup, J. Strobl, and P. Zeil, "Object-oriented image processing in an integrated GIS/remote sensing environment and perspectives for environmental applications," *Environ. Inf. Planning, Politics Public*, vol. 2, pp. 555–570, Oct. 2000.
- [2] K. Whitehead and C. H. Hugenholtz, "Remote sensing of the environment with small unmanned aircraft systems (UASS), Part 1: A review of progress and challenges," *J. Unmanned Vehicle Syst.*, vol. 2, no. 3, pp. 69–85, 2014.
- [3] J. M. Almendros-Jiménez, L. Domene, and J. A. Piedra-Fernández, "A framework for ocean satellite image classification based on ontologies," *IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens.*, vol. 6, no. 2, pp. 1048–1063, Apr. 2013.
- [4] B. Gallo *et al.*, "Multi-temporal satellite images on topsoil attribute quantification and the relationship with soil classes and geology," *Remote Sens.*, vol. 10, no. 10, p. 1571, Oct. 2018.
- [5] D. J. Marceau, D. J. Gratton, R. A. Fournier, and J.-P. Fortin, "Remote sensing and the measurement of geographical entities in a forested environment. 2. The optimal spatial resolution," *Remote Sens. Environ.*, vol. 49, no. 2, pp. 105–117, Aug. 1994.

- [6] J. L. Ohmann, M. J. Gregory, and H. M. Roberts, "Scale considerations for integrating forest inventory plot data and satellite image data for regional forest mapping," *Remote Sens. Environ.*, vol. 151, pp. 3–15, Aug. 2014.
- [7] M. Wójtowicz, A. Wójtowicz, and J. Piekarczyk, "Application of remote sensing methods in agriculture," *Commun. Biometry Crop Sci.*, vol. 11, no. 1, pp. 31–50, 2016.
- [8] A. Zhang and G. Jia, "Monitoring meteorological drought in semiarid regions using multi-sensor microwave remote sensing data," *Remote Sens. Environ.*, vol. 134, pp. 12–23, Jul. 2013.
- [9] F. Paul, C. Huggel, and A. Kääb, "Combining satellite multispectral image data and a digital elevation model for mapping debris-covered glaciers," *Remote Sens. Environ.*, vol. 89, no. 4, pp. 510–518, Feb. 2004.
- [10] Y. Lyu, G. Vosselman, G.-S. Xia, A. Yilmaz, and M. Y. Yang, "UAVid: A semantic segmentation dataset for UAV imagery," *ISPRS J. Photogramm. Remote Sens.*, vol. 165, pp. 108–119, Jul. 2020.
- [11] S. Liang, *Comprehensive Remote Sensing*. Amsterdam, The Netherlands: Elsevier, 2017.
- [12] Y. Chen, D. Ming, and X. Lv, "Superpixel based land cover classification of VHR satellite image combining multi-scale CNN and scale parameter estimation," *Earth Sci. Informat.*, vol. 12, no. 3, pp. 341–363, Sep. 2019.
- [13] G.-S. Xia, W. Yang, J. Delon, Y. Gousseau, H. Sun, and H. Maître, "Structural high-resolution satellite image indexing," in *Proc. ISPRS TC VII Symp.-Years ISPRS*, vol. 38, 2010, pp. 298–303.
- [14] M. Chi, A. Plaza, J. A. Benediktsson, Z. Sun, J. Shen, and Y. Zhu, "Big data for remote sensing: Challenges and opportunities," *Proc. IEEE*, vol. 104, no. 11, pp. 2207–2219, Nov. 2016.
- [15] F. Petitjean, J. Inglada, and P. Gançarski, "Satellite image time series analysis under time warping," *IEEE Trans. Geosci. Remote Sens.*, vol. 50, no. 8, pp. 3081–3095, Aug. 2012.
- [16] M. Zhang, W. Li, R. Tao, H. Li, and Q. Du, "Information fusion for classification of hyperspectral and LiDAR data using IP-CNN," *IEEE Trans. Geosci. Remote Sens.*, early access, Jul. 13, 2021, doi: 10.1109/TGRS.2021.3093334.
- [17] X. Liu *et al.*, "Deep multiview union learning network for multisource image classification," *IEEE Trans. Cybern.*, early access, Nov. 5, 2020, doi: 10.1109/TCYB.2020.3029787.
- [18] X.-Y. Tong *et al.*, "Land-cover classification with high-resolution remote sensing images using transferable deep models," *Remote Sens. Environ.*, vol. 237, Feb. 2020, Art. no. 111322.
- [19] V. Iglovikov and A. Shvets, "TernausNet: U-Net with VGG11 encoder pre-trained on ImageNet for image segmentation," 2018, *arXiv:1801.05746*. [Online]. Available: <http://arxiv.org/abs/1801.05746>
- [20] W. Kang, Y. Xiang, F. Wang, and H. You, "EU-Net: An efficient fully convolutional network for building extraction from optical remote sensing images," *Remote Sens.*, vol. 11, no. 23, p. 2813, Nov. 2019.
- [21] G. Wu *et al.*, "Automatic building segmentation of aerial imagery using multi-constraint fully convolutional networks," *Remote Sens.*, vol. 10, no. 3, p. 407, 2018.
- [22] F. I. Diakogiannis, F. Waldner, P. Caccetta, and C. Wu, "ResUNet-A: A deep learning framework for semantic segmentation of remotely sensed data," *ISPRS J. Photogramm. Remote Sens.*, vol. 162, pp. 94–114, Apr. 2020.
- [23] Q. Zhu, C. Liao, H. Hu, X. Mei, and H. Li, "MAP-Net: Multiple attending path neural network for building footprint extraction from remote sensed imagery," *IEEE Trans. Geosci. Remote Sens.*, vol. 59, no. 7, pp. 6169–6181, Jul. 2021.
- [24] H. Liu *et al.*, "DE-Net: Deep encoding network for building extraction from high-resolution remote sensing imagery," *Remote Sens.*, vol. 11, no. 20, p. 2380, Oct. 2019.
- [25] S. Wei, S. Ji, and M. Lu, "Toward automatic building footprint delineation from aerial images using CNN and regularization," *IEEE Trans. Geosci. Remote Sens.*, vol. 58, no. 3, pp. 2178–2189, Mar. 2020.
- [26] G. Wu *et al.*, "A boundary regulated network for accurate roof segmentation and outline extraction," *Remote Sens.*, vol. 10, no. 8, p. 1195, Jul. 2018.
- [27] A. Bokhovkin and E. Burnaev, "Boundary loss for remote sensing imagery semantic segmentation," in *Proc. Int. Symp. Neural Netw.* Cham, Switzerland: Springer, 2019, pp. 388–401.
- [28] A. Van Etten, D. Hogan, J. M. Manso, J. Shermeyer, N. Weir, and R. Lewis, "The multi-temporal urban development spacenet dataset," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit.*, Jun. 2021, pp. 6398–6407.
- [29] K. Zhao, J. Kang, J. Jung, and G. Sohn, "Building extraction from satellite images using mask R-CNN with building boundary regularization," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. Workshops (CVPRW)*, Jun. 2018, pp. 247–251.
- [30] O. Ronneberger, P. Fischer, and T. Brox, "U-Net: Convolutional networks for biomedical image segmentation," in *Proc. Int. Conf. Med. Image Comput. Comput.-Assist. Intervent.* Cham, Switzerland: Springer, 2015, pp. 234–241.
- [31] S. Xie and Z. Tu, "Holistically-nested edge detection," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*, Dec. 2015, pp. 1395–1403.
- [32] D. Jha *et al.*, "ResUNet++: An advanced architecture for medical image segmentation," in *Proc. IEEE Int. Symp. Multimedia (ISM)*, Dec. 2019, pp. 1–6.
- [33] Y. Liu, L. Gross, Z. Li, X. Li, X. Fan, and W. Qi, "Automatic building extraction on high-resolution remote sensing imagery using deep convolutional encoder-decoder with spatial pyramid pooling," *IEEE Access*, vol. 7, pp. 128774–128786, 2019.
- [34] I. Demir *et al.*, "DeepGlobe 2018: A challenge to parse the Earth through satellite images," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. Workshops (CVPRW)*, Jun. 2018, pp. 172–181.
- [35] H. R. Goldberg, S. Wang, G. A. Christie, and M. Z. Brown, "Urban 3D challenge: Building footprint detection using orthorectified imagery and digital surface models from commercial satellites," *Proc. SPIE*, vol. 10645, Apr. 2018, Art. no. 1064503.
- [36] S. Ji, S. Wei, and M. Lu, "Fully convolutional networks for multisource building extraction from an open aerial and satellite imagery data set," *IEEE Trans. Geosci. Remote Sens.*, vol. 57, no. 1, pp. 574–586, Jan. 2019.
- [37] V. Mnih, "Machine learning for aerial image labeling," Ph.D. dissertation, Univ. Toronto, Toronto, ON, Canada, 2013.
- [38] K. Simonyan and A. Zisserman, "Very deep convolutional networks for large-scale image recognition," 2014, *arXiv:1409.1556*. [Online]. Available: <http://arxiv.org/abs/1409.1556>
- [39] J. Long, E. Shelhamer, and T. Darrell, "Fully convolutional networks for semantic segmentation," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, Jun. 2015, pp. 3431–3440.
- [40] Z. Shao, P. Tang, Z. Wang, N. Saleem, S. Yam, and C. Sommai, "BRNet: A fully convolutional neural network for automatic building extraction from high-resolution remote sensing images," *Remote Sens.*, vol. 12, no. 6, p. 1050, Mar. 2020.
- [41] Y. Kim, S. Kim, T. Kim, and C. Kim, "CNN-based semantic segmentation using level set loss," in *Proc. IEEE Winter Conf. Appl. Comput. Vis. (WACV)*, Jan. 2019, pp. 1752–1760.
- [42] Z. Chen, H. Zhou, J. Lai, L. Yang, and X. Xie, "Contour-aware loss: Boundary-aware learning for salient object segmentation," *IEEE Trans. Image Process.*, vol. 30, pp. 431–443, 2021.
- [43] J. Hu, L. Shen, and G. Sun, "Squeeze-and-excitation networks," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit.*, Jun. 2018, pp. 7132–7141.
- [44] C. E. Shannon, "A mathematical theory of communication," *Bell Syst. Tech. J.*, vol. 27, no. 3, pp. 379–423, Jul./Oct. 1948.
- [45] T.-Y. Lin, P. Goyal, R. Girshick, K. He, and P. Dollár, "Focal loss for dense object detection," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*, Oct. 2017, pp. 2980–2988.
- [46] H. Zhao, O. Gallo, I. Frosio, and J. Kautz, "Loss functions for image restoration with neural networks," *IEEE Trans. Comput. Imag.*, vol. 3, no. 1, pp. 47–57, Mar. 2017.
- [47] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, Jun. 2016, pp. 770–778.
- [48] L.-C. Chen, G. Papandreou, I. Kokkinos, K. Murphy, and A. L. Yuille, "DeepLab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected CRFs," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 40, no. 4, pp. 834–848, Apr. 2017.
- [49] H. Li, P. Xiong, J. An, and L. Wang, "Pyramid attention network for semantic segmentation," 2018, *arXiv:1805.10180*. [Online]. Available: <http://arxiv.org/abs/1805.10180>
- [50] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," 2014, *arXiv:1412.6980*. [Online]. Available: <http://arxiv.org/abs/1412.6980>
- [51] L.-C. Chen, G. Papandreou, F. Schroff, and H. Adam, "Rethinking atrous convolution for semantic image segmentation," 2017, *arXiv:1706.05587*. [Online]. Available: <http://arxiv.org/abs/1706.05587>
- [52] K. He, G. Gkioxari, P. Dollár, and R. Girshick, "Mask R-CNN," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*, Oct. 2017, pp. 2961–2969.



Hoin Jung received the B.S. degree in aircraft system engineering from the Department of Aerospace and Mechanical Engineering, Korea Aerospace University, Goyang, South Korea, in 2014. He is pursuing the M.S. degree with the Department of Computational Science and Technology, Seoul National University, Seoul, South Korea.

From 2014 to 2017, he was a Mechanical Engineer with the Korea Air Force as an Officer. From 2017 to 2020, he was a Mechanical Engineer with the Department of Digital Appliances, Samsung Electronics Company Ltd. His research interest includes remote sensed image processing using deep learning.



Myungjoo Kang (Member, IEEE) received the B.S. degree in mathematics from Seoul National University, Seoul, South Korea, and the Ph.D. degree in mathematics from the University of California at Los Angeles, Los Angeles, CA, USA, in 1996.

He was with the Department of Electrical and Computer Engineering, University of California at San Diego, CA, USA, as a Postdoctoral Researcher, from 1996 to 2000. He was an Assistant Professor from 2003 to 2007 and an Associate Professor from 2008 to 2013 with the Department of Mathematical Sciences, Seoul National University, where he has been a Professor since 2014. His research interests include mathematical image processing, numerical schemes and computational fluid dynamics, and image processing using deep learning.



Han-Soo Choi received the B.S. degree in mathematics from Kookmin University, Seoul, South Korea, in 2011, the M.S. degree in mechatronics from Korea University, Seoul, in 2015, and the Ph.D. degree from the Department of Computational Science and Technology, Seoul National University, Seoul, in 2020.

He is a Training Researcher with the Research Institute of Mathematics, Seoul National University. His research interest includes image processing using deep learning.