


Ecohydraulical Feedback Simulation Documentation and Manual



Gavan McGrath

School of Earth and Environment, The University of Western Australia,
M087, 35 Stirling Highway, Crawley, Western Australia, 6009

Christoph Hinz

Tobias Nanu Frechen

Brandenburg University of Technology, Hydrology and Water Resources Management,
Konrad-Wachsmann-Allee 6, 03046 Cottbus, Germany

DRAFT of 3rd October, 2012, 18:56

Contents

1	Introduction	1
2	Theoretical principles	2
2.1	Simulation model	2
2.2	Runoff generation	2
2.3	Surface water flow	2
2.4	Short range facilitation	2
2.5	Evaporation and transpiration	2
2.6	Vegetation change	2
2.7	Microtopography	2
3	Application	3
3.1	Build from source	3
3.1.1	Unix Systems	3
3.2	Installation	3
3.2.1	System requirements	3
3.3	Application prerequisites	3
3.4	Data preperation	3
3.5	Parameterization	3
3.6	Simulation	3
3.7	Output	3
3.8	Appraise and visualize results	3
3.8.1	in R	3
3.8.2	in R and \LaTeX (knitr-method)	3
3.8.3	in Excel	3
4	Implementation	4
4.1	Overview	4
4.2	Implementation strategy	4
4.3	Subroutines	4
4.3.1	Simulation	4
4.3.2	Green-ampt infiltration	6
4.3.3	<i>Nanu:</i> <u>TwoDRandPos</u> [cannot guess what this means]	6
4.3.4	Kinematic wave primer	7
4.3.5	Kinematic wave	7
4.3.6	Kinematic wave order	8
4.3.7	OneDRandList (a,mn)	8
4.3.8	Lookup for direction	8
4.3.9	Routing with kernel	9
4.3.10	Infiltration Probability	9
4.3.11	List Convolve	10
4.3.12	Erosion	10
4.3.13	Splash	10
4.3.14	Find holes	10
4.3.15	Evaporation	11
4.3.16	Neighbours	12
4.3.17	LSDs	12
4.3.18	Array rotation	13
4.3.19	Pos1D	13
4.3.20	GD8 fow directions	13

4.3.21	New GD8 flow directions	13
4.3.22	fdirLookup(dirnxy, idirn)	14
4.3.23	Array sort	14
4.3.24	endShift	14
4.3.25	makeOrds	15
4.3.26	Vegetation Change	15
4.4	Customizability	15

List of Figures, Tables and Listings	16
---	-----------

Index	19
--------------	-----------

References	21
-------------------	-----------

A Appendix	22
-------------------	-----------

Draft status

- Suggestions for overall structuring welcomed!
- what means Dimensions: [:,:] ?
- subroutines and comments on the variables are from file `coupledModel.f90`
- `\subroutine{<name>}{<arguments>}` for displaying a subroutine with its arguments. `<name>` automatically gets an (emphasized) index entry and a label.
- `\inout{<input entries>}{<output entries>}` is for a list of input and output arguments. Missing values get replaced by "no input" or "no output".
- `\inoutentry[<option>]{<variableName>}{type}{dimensions}{description}` for an entry in the input output list. `<option>` can be empty or "emph" for an emphasized index entry or "none" for no index entry.
- `\begin{usessubs}` is an environment of used subroutines.
- `\usessubentry{<subroutineName>}` is for an entry in the `usessubs` environment. Entries automatically get an (not emphasized) index entry and a reference to the associated subroutine.
- I am using the keyword `index` to index all parameter and variable names. Good idea? Or shall we make a list with all parameter and variable names and their description and unit? Like:

Table 1: variables					
variable	type	dimensions	nom	unit	description
climParams	[8-byte real]	[4]			climate parameters
infiltrParams	[8-byte real]	[6]			vegetation and soil kernel parameters
evapParams	[8-byte real]	[8]			evaporation parameters
discharge	[integer]	[m,n]	Q	[m ³ /s]	discharge
alpha	[8-byte real]	[m,n]	α		

My suggestion for collaboration: let's use the package "trackchanges". *Nanu:* Editing [could look like this] with the following commands:

```
\add[editor]{added text}

\remove[editor]{removed text}

\change[editor]{removed text}{added text}

\note[editor]{note text}

\annotate[editor]{text to annotate}{note text}
```

1 Introduction

2 Theoretical principles

2.1 Simulation model

Runoff, soil moisture storage, transpiration and plant-bare soil transitions are numerically modeled on a lattice of square cells. The model simulates the following spatially distributed water balance:

$$\frac{\partial w_i}{\partial t} = P_i + R_i - Q_i - E_i - \sum_n T_n \quad (1)$$

2.2 Runoff generation

2.3 Surface water flow

2.4 Short range facilitation

2.5 Evaporation and transpiration

2.6 Vegetation change

2.7 Microtopography

3 Application

3.1 Build from source

3.1.1 Unix Systems

To use the gfortran compiler execute the following in terminal:

```
gfortran coupledModel.f90
```

On Unix systems an `.out` file is generated. To execute this, type the following into the terminal:

```
./a.out
```

3.2 Installation

3.2.1 System requirements

3.3 Application prerequisites

3.4 Data preperation

3.5 Parameterization

3.6 Simulation

3.7 Output

3.8 Appraise and visualize results

3.8.1 in R

3.8.2 in R and \LaTeX (knitr-method)

<http://yihui.name/knitr/>

3.8.3 in Excel




Figure 1: flow chart of the main program

4 Implementation

4.1 Overview

4.2 Implementation strategy

4.3 Subroutines

4.3.1 Simulation

```

SimCODE(m, n, mn, simflags, climParams, infiltParams, evapParams,
vegParams, erParams, resultsFID)

```




Figure 2: flow chart of subroutine SimCode (simulation execution)

input

m	[integer]	number of rows
n	[integer]	number of columns
mn	[integer]	= m·n
simflags	[integer] [6]	[1] ... is for this, [2] ... is for that, <i>Nanu:</i> [should be explained!]
climParams	[8-byte real] [4]	<i>Nanu:</i> <u>climate parameters</u> [how to input these?]
infiltrParams	[8-byte real] [6]	<i>Nanu:</i> vegetation and soil kernel parameters
evapParams	[8-byte real] [8]	evaporation parameters
vegParams	[8-byte real] [5]	vegetation <i>Nanu:</i> and soil kernel parameters
erParams	[8-byte real] [4]	<i>Nanu:</i> <u>vegetation and soil kernel parameters</u> [what specific?]
resultsFID	[character] [len=8]	results file id code

output

no output

Uses subroutines:

GD8(), cf. page 13
 InfiltrProb(), cf. page 9
 RoutingWithKernel(), cf. page 9
 Erosion(), cf. page 10
 Splash(), cf. page 10
 Evaporation(), cf. page 11
 VegChange(), cf. page 15

4.3.2 Green-ampt infiltration

GAInfiltr(m, n, dt, inflow, Ksat, wfs, cumInfiltr, infex)

Nanu: Green-ampt infiltration calculation. [Literature?]

input

m, n	[integer]	
dt	[8-byte real]	
inflow	[8-byte real] [m,n]	surface runoff + precipitation ($R + P$)
wfs	[8-byte real] [m,n]	<i>Nanu:</i> <u>wetting front suction * moisture deficit</u> [formula?]
cumInfiltr	[8-byte real] [m,n]	<i>Nanu:</i> <u>cumulative infiltration</u> [nomenclature?]

output

infex	[8-byte real] [m,n]	infiltration excess
cumInfiltr	[8-byte real] [m,n]	cumulative infiltration

4.3.3 *Nanu:* TwoDRandPos [cannot guess what this means]

TwoDRandPos(randOrder, m, n, mn)

input

m, n	[integer]
randOrder	[integer] [mn, 2]

output

randOrder	[integer] [mn, 2]
-----------	-------------------

Uses subroutines:

OneDRandList(), cf. page 8

4.3.4 Kinematic wave primer

KWPrimer(m, n, topog, manningsN, mask, solOrder, flowdirns, alpha, deltax, solMax)

Iterate over space to generate calculation a mask. The mask is a 9 x 1 array where 1s indicate that a neighbour (as defined by the position in mask(x,y)) discharges to the cell at x,y

input

m,n	[integer]	
topog	[integer]	[mn, n]
manningsN	[integer]	[mn, n]

output

deltax	[8-byte real]	[m,n]	
alpha	[8-byte real]	[m,n]	
solMax	[integer]		
solOrder	[integer]	[m,n]	
flowdirns	[integer]	[m,n]	flow directions
mask	[integer]	[m,n,9]	

Uses subroutines:

GD8(), cf. page 13

KMWOrder(), cf. page 8

Neighbours(), cf. page 12

Lookupfdir(), cf. page 8

4.3.5 Kinematic wave

KinematicWave(m, n, ndx, dt, iex, flowdirns, solOrder, solMax, mask, alpha, deltax, disOld, disNew)

This subroutine calculates the kinematic wave equation for surface runoff in a network for a single time step. The flow network is given by the GD8 algorithm calculated on the topography. We assume no interaction between adjacent flow pathways i.e. water does not overflow in a direction not specified by the GD8 network. iex is the excess water from *Nanu:* precip - infiltration + GW discharge [display as formula?].

$$iex(m, n, 1) = qit$$

Nanu: [should this be displayed as formula or as code?]

$$iex(m, n, 2) = qitPlus$$

Nanu: manningsN the roughness coefficient [is this in the right place?]

Nanu: init a value passed to initialise the variables [same for this]

input

m,n	[integer]	
ndx	[integer]	
solMax	[integer]	
flowdirns	[integer]	[m,n] flow directions
solOrder	[integer]	[m,n]
mask	[integer]	[m,n]
alpha	[8-byte real]	[m,n]
deltax	[8-byte real]	[m,n]
dt	[8-byte real]	time step
disOld, disNew	[8-byte real]	[m,n, ndx]
iex	[8-byte real]	[m,n,2]

output

disOld, disNew	[8-byte real]	[m,n,ndx]
----------------	---------------	-----------

4.3.6 Kinematic wave order

KMWOrder(flowdirns, m, n, solutionOrder)

Subroutine assigns values to the matrix `solutionOrder` to tell the Kinematic Wave subroutine in which order to solve the KM equation on the drainage network. Values of 1 assigned to top of catchment, 2 to 1st downstream node etc.. Value at a point is the maximum travel distance to that point from all points above it.

input

m,n	[integer]
flowdirns	[integer] [m,n] flow directions

output

solutionOrder	[integer] [n,n]
---------------	-----------------

Uses subroutines:

Lookupfdir(), cf. page 8

4.3.7 OneDRandList (a,mn)

OneDRandList (a, mn)

input

mn	[integer]
a	[integer] [mn,2]

output

a	[integer] [mn,2]
---	------------------

4.3.8 Lookup for direction

Lookupfdir(dirn, dx, dy)

input

dirn	[integer]
------	-----------

output

dx, dy	[integer]
--------	-----------

4.3.9 Routing with kernel

RoutingWithKernel(*m, n, mn, precip, infiltKern, storeKern, newflowdirns, topog, store, discharge, outflow*)

input

<i>m, n</i>	[integer]	
<i>mn</i>	[integer]	
<i>infiltKern</i>	[8-byte real]	[<i>m, n</i>]
<i>storeKern</i>	[8-byte real]	[<i>m, n</i>]
<i>topog</i>	[8-byte real]	[<i>m, n</i>]
<i>precip</i>	[integer]	[<i>m, n</i>]
<i>store</i>	[integer]	[<i>m, n</i>]
<i>newflowdirns</i>	[integer]	[<i>m, n</i>] flow directions

output

<i>outflow</i>	[integer]	
<i>store</i>	[integer]	[<i>m, n</i>]
<i>newflowdirns</i>	[integer]	[<i>m, n</i>] new flow directions
<i>discharge</i>	[integer]	[<i>m, n</i>]

Notice: Periodic boundary conditions can only really be defined simply for an inclined plane with two adjacent edges defined as the boundary from which particles are routed to the opposite boundary. For simplicity it is assumed that the landscape slopes downwards in the direction of lower *x* and *y*.

Uses subroutines:

OneDRandList(), cf. page 8
 TwoDRandPos(), cf. page 6
 Lookupfdir(), cf. page 8
 Neighbours(), cf. page 12
 fdirLookup(), cf. page 14

4.3.10 Infiltration Probability

InfiltProb(*veg, m, n, K0, ie, rfx, rfy, kf, Kmax, dx, dy, iProb*)

This subroutine calculates the spatial distributed infiltration probability.

input

<i>m, n</i>	[integer]	dimensions of the spatial arrays
<i>rfx, rfy</i>	[integer]	maximum radius for plant effects on soil properties
<i>kf</i>	[integer]	
<i>veg</i>	[integer]	[<i>m, n</i>] vegetation matrix
<i>K0</i>	[8-byte real]	
<i>ie</i>	[8-byte real]	
<i>Kmax</i>	[8-byte real]	
<i>dx, dy</i>	[8-byte real]	length scales of lattice

output

<i>iProb</i>	[8-byte real]	[<i>m, n</i>] infiltration probability matrix
--------------	---------------	---

4.3.11 List Convolve

ListConvolve(base, kernel, convol, m, n, m1, n1)

input

m, n [integer]
 m1, n1 [integer]
 base [integer] [m,n]
 kernel [integer] [m,n]

output

convol [] [m,n]

4.3.12 Erosion

Erosion(discharge, topog, newflowdirns, flowResistance, m, n)

input

m, n [integer] dimensions of the spatial arrays
 discharge [integer] [m,n] discharge has units of mm/year
 newflowdirns [integer] [m,n] new flow directions
 flowResistance [8-byte real] [m,n] flow resistance; effective d_{40} grainsize in mm
 topog [8-byte real] [m,n] topography

output

topog [8-byte real] [m,n] topography

Uses subroutines:

Lookupfdir(), cf. page 8

4.3.13 Splash

Splash(topog, veg, Dv, Db, m, n)

input

m, n [integer] dimensions of the spatial arrays
 veg [integer] [m,n]
 topog [8-byte real] [m,n] topography
 Dv, Db [8-byte real] m^2/kyr

output

topog [8-byte real] [m,n] topography

Uses subroutines:

Neighbours(), cf. page 12

4.3.14 Find holes

FindHoles(newtopog, holes)

input

newtopog [8-byte real] [::] topography

output

holes [8-byte real] [::]

Listing 1: a program listing could look like this; notice the language sensitive formatting

```

1 SUBROUTINE FindHoles(newtopog,holes)
2 IMPLICIT NONE
3
4 REAL*8, DIMENSION(:,:), INTENT(IN) :: newtopog
5 INTEGER, INTENT(OUT) :: holes
6
7 INTEGER :: m,n,i,j,k,l
8 m=SIZE(newtopog,1)
9 n=SIZE(newtopog,2)
10
11 DO i=2,m-1
12 DO j=2,n-1
13   holes=0
14   DO k=-1,1
15   DO l=-1,1
16     IF (newtopog(i,j) < newtopog(i + k, j + l)) THEN
17       holes = holes + 1
18     END IF
19   END DO
20 END DO
21 IF (holes.ge.8) THEN
22   holes = 1
23   RETURN
24 END IF
25 END DO
26 END DO
27
28 END SUBROUTINE FindHoles

```

Listing 1 shows, how code can be inserted into the document. With line numbers and Fortran specific code highlighting.

It is possible to refer to individual lines inside the listing with \LaTeX commands `\label{}` and `\ref{}`, so references get updated if the code changes. For example line 16 in listing 1, where the first `IF`-condition begins.

The code in the listing could be loaded from an external file (for example the actual Fortran file).

4.3.15 Evaporation

Evaporation(veg, eTActual, bareE, store, tsteps, rcx, rcy, kc, dx, dy, params)

This version cycles through sites and evaporates water from site and neighbouring sites if vegetated.

input

veg	[integer]	[.:]
eTActual	[integer]	[.:]
bareE	[integer]	[.:]
store	[integer]	[.:]
tsteps	[integer]	
rcx, rcy, kc	[8-byte real]	
dx, dy	[8-byte real]	
params	[8-byte real]	[7]

output

store	[integer]	[.:]
eTActual	[integer]	[.:]
bareE	[integer]	[.:]

Uses subroutines:

TwoDRandPos(), cf. page 6

4.3.16 Neighbours

Neighbours(order, posij, dom, neighbours)

input

order	[integer]
posij	[integer] [2]
dom	[integer] [2]

output

neighbours	[integer]	[<i>Nanu:</i> <u>$(order*2+1)**2,2$</u> [as formula?]]
------------	-----------	--

4.3.17 LSDs

LSDs(order, posxy, topog, m, n, lsdList)

This function returns the matrix positions:

LSD1: the position of the neighbouring cell with the steepest slope downhill

LSD2: the position of the neighbouring cell with second steepest slope adjacent LSD1

otherpos: the position of the other neighbouring cell the mirror reflection about LSD1 of LSD2

input

m, n	[integer]
posxy	[integer] [2]
topog	[8-byte real] [m,n]

output

lsdList	[integer]	[3,2]
---------	-----------	-------

Uses subroutines:

Neighbours(), cf. page 12

RotateArray(), cf. page 13

4.3.18 Array rotation

RotateArray(list, m, n, leftorRight)

input

m, n [integer]
 list [integer] [m,n]
 leftorRight [integer]

output

list [integer] [m,n]

4.3.19 Pos1D

Pos1d(list, m, n, match, rownum)

input

m, n [integer]
 list [integer] [m,n]
 match [integer] [n]

output

rownum [integer] [m]

4.3.20 GD8 fow directions

GD8(topog, flowdirns, m, n)

input

m, n [integer]
 topog [8-byte real] [m,n]

output

flowdirns [integer] [m,n] flow directions

Uses subroutines:

makeOrds(), cf. page 15
 Pos1d(), cf. page 13
 endShift(), cf. page 14
 LSDs(), cf. page 12
 fdirLookup(), cf. page 14
 RotateArray(), cf. page 13

4.3.21 New GD8 flow directions

NewGD8(topog, lakes, flowdirns, m, n)

Calculates flow directions following the GD8-algorithm of Paik (2008)

input

m, n [integer]
 lakes [integer] [m,n]
 topog [8-byte real] [m,n]

output

flowdirns [integer] [m,n] flow directions

Uses subroutines:

makeOrds(), cf. page 15
 Pos1d(), cf. page 13
 endShift(), cf. page 14
 LSDs(), cf. page 12
 fdirLookup(), cf. page 14
 Neighbours(), cf. page 12

4.3.22 fdirLookup(dirnxy, idirn)

fdirLookup(dirnxy, idirn)

input

dirnxy [integer] [2]

output

idirn [integer]

4.3.23 Array sort

qsortd(x, ind, n, incdec)

This subroutine uses an order $n \cdot \log(n)$ quick sort to sort a real (double precision/8-byte) array $x(n)$ into increasing order.

input

x(n) [8-byte real] vector of length n to be sorted
 n [integer] length of the array x(n)
 incdec [integer] if positive the ind is returned so values decreasing order
 incdec [integer]

output

ind(n) [integer] vector of length $\geq n$; sequence of indices $1, \dots, n$ permuted in the same fashion as x would be: $y(i) = x(ind(i))$

ind is initialized to the ordered sequence of indices $1, \dots, n$, and all interchanges are applied to ind. x is divided into two portions by picking a central element t . The first and last elements are compared with t , and interchanges are applied as necessary so that the three values are in ascending order. Interchanges are then applied so that all elements greater than t are in the upper portion of the array and all elements less than t are in the lower portion. The upper and lower indices of one of the portions are saved in local arrays, and the process is repeated iteratively on the other portion. When a portion is completely sorted, the process begins again by retrieving the indices bounding another unsorted portion.

Note: IU and IL must be dimensioned $\geq \log(n)$ where log has base 2.

Credit goes to Robert Renka Oak Ridge Natl. Lab.

4.3.24 endShift

endShift(arr, rownum, mn, n)

input

```
rown [integer]
n     [integer]
mn    [integer]
arr   [integer] [mn,n]
```

output

```
arr [integer] [mn,n]
```

4.3.25 makeOrds

```
makeOrds(topog, ords, m, n)
```

input

```
m,n [integer]
topog [8-byte real] [m,n]
```

output

```
ords [integer] [size(topog),2]
```

Uses subroutines:

```
qsortd(), cf. page 14
```

4.3.26 Vegetation Change

```
VegChange(veg, m, n, vegParams, store, actualET, isEmerge, isGrow)
```

input

```
m,n [integer]
isGrow [integer]
isEmerge [integer]
vegParams [8-byte real] [5]
veg [integer] [m,n]
store [integer] [m,n]
actualET [integer] [m,n]
```

output

```
veg [integer] [m,n]
store [integer] [m,n]
actualET [integer] [m,n]
```

4.4 Customizability

List of Figures

1	flow chart of the main program	4
2	flow chart of subroutine SimCode (simulation execution)	5

List of Tables

1	variables	V
---	---------------------	---

List of Listings

1 a program listing could look like this; notice the language sensitive formatting 11

Index

a, 8
actualET, 15
alpha, 7, 8
arr, 15

bareE, 12
base, 10

climParams, 6
convol, 10
cumInfilt, 6

deltax, 7, 8
dirn, 8
dirnxy, 14
discharge, 9, 10
disOld, disNew, 8
disOld, disNew, 8
dom, 12
dt, 6, 8
Dv, Db, 10
dx, dy, 9, 12
dx, dy, 8

endShift(), 13, **14**, 14
Erosion(), 6, **10**
erosion, 10
erParams, 6
eTActual, 12
Evaporation(), 6, **11**
evaporation, 11
evapParams, 6

fdirLookup(), 9, 13, **14**, 14
FindHoles(), **10**
flow directions, 13
flowdirns, 7, 8, 13
flowResistance, 10

GAInfilt(), **6**
GD8(), 6, 7, **13**
GD8-algorithm, 13

holes, 11

idirn, 14
ie, 9
iex, 8
incdec, 14
ind(n), 14
infex, 6
infiltKern, 9
infiltParams, 6
InfiltProb(), 6, **9**
infiltration, 9
inflow, 6
iProb, 9
isEmerge, 15
isGrow, 15

K0, 9
kernel, 10
kf, 9
kinematic wave, 7
KinematicWave(), **7**
Kmax, 9
KMWOrder(), 7, **8**
KWPrimer(), **7**

lakes, 13
leftorRight, 13
list, 13
ListConvolve(), **10**
Lookupfdir(), 7, **8**, 8–10
lsdList, 12
LSDs(), **12**, 13, 14

m, **6**
m, n, 6–10, 12, 13, 15
m1, n1, 10
makeOrds(), 13, 14, **15**
manningsN, 7
mask, 7, 8
match, 13
mn, 6, 8, 9, 15

n, 6, 14, 15
ndx, 8
Neighbours(), 7, 9, 10, **12**, 12, 14
neighbs, 12
newflowdirns, 9, 10
NewGD8(), **13**
newtopog, 11

OneDRandList(), 7, **8**, 9
order, 12
ords, 15
outflow, 9

params, 12
Pos1d(), **13**, 13, 14
posij, 12
posxy, 12
precip, 9

qsortd(), **14**, 15

randOrder, 6
rcx, rcy, kc, 12
resultsFID, 6
rfx, rfy, 9
RotateArray(), 12, **13**, 13
RoutingWithKernel(), 6, **9**
rown, 15
rownum, 13

SimCODE(), **4**
simflags, 6
simulation, 4
solMax, 7, 8

solOrder, 7, 8
solutionOrder, 8
Splash(), 6, **10**
store, 9, 12, 15
storeKern, 9

topog, 7, 9, 10, 12, 13, 15
tsteps, 12
TwoDRandPos(), **6**, 9, 12

veg, 9, 10, 12, 15
VegChange(), 6, **15**
vegParams, 6, 15

water balance, 2
wfs, 6

 $x(n)$, 14

References

- Paik, K. (2008). Global search algorithm for nondispersive flow path extraction. *Journal of Geophysical Research*, 113(F4):F04001.

A Appendix