

☰ CS50 Manual Pages

NAME

☐ less comfortable

atoi, atol, atoll - convert a string to an integer

LIBRARY

Show

SYNOPSIS

☐ less comfortable

```
#include <stdlib.h>
int atoi(const char *nptr);
long atol(const char *nptr);
long long atoll(const char *nptr);
```

Feature Test Macro Requirements for glibc (see [feature_test_macros\(7\)](#)):

Show

DESCRIPTION

☐ less comfortable

The [atoi\(\)](#) function converts the initial portion of the string pointed to by `nptr` to `int`. The behavior is the same as

```
strtol(nptr, NULL, 10);
```

except that `atoi()` does not detect errors.

The `atol()` and `atoll()` functions behave the same as `atoi()`, except that they convert the initial portion of the string to their return type of `long` or `long long`.

RETURN VALUE

 less comfortable

This function returns its input, `s`, as an `int`.

EXAMPLE

 less comfortable

```
#include <stdio.h>
#include <stdlib.h>

int main(void)
{
    printf("This is CS%i\n", atoi("50"));
}
```

ATTRIBUTES

Show

VERSIONS

Show

STANDARDS

[Show](#)

HISTORY

[Show](#)

BUGS

[Show](#)

SEE ALSO

[atof\(3\)](#), [strtod\(3\)](#), [strtol\(3\)](#), [strtoul\(3\)](#)