

☰ CS50 Manual Pages

NAME

☒ less comfortable

isdigit - check whether a character is a digit

LIBRARY

Standard C library (`libc`, `-lc`)

SYNOPSIS

☐ less comfortable

```
#include <ctype.h>
int isalnum(int c);
int isalpha(int c);
int iscntrl(int c);
int isdigit(int c);
int isgraph(int c);
int islower(int c);
int isprint(int c);
int ispunct(int c);
int isspace(int c);
int isupper(int c);
int isxdigit(int c);
int isascii(int c);
int isblank(int c);
int isalnum_l(int c, locale_t locale);
int isalpha_l(int c, locale_t locale);
int isblank_l(int c, locale_t locale);
int iscntrl_l(int c, locale_t locale);
int isdigit_l(int c, locale_t locale);
```

```
int isgraph_l(int c, locale_t locale);  
int islower_l(int c, locale_t locale);  
int isprint_l(int c, locale_t locale);  
int ispunct_l(int c, locale_t locale);  
int isspace_l(int c, locale_t locale);  
int isupper_l(int c, locale_t locale);  
int isxdigit_l(int c, locale_t locale);  
int isascii_l(int c, locale_t locale);
```

Feature Test Macro Requirements for glibc (see [feature_test_macros\(7\)](#)):

Show

DESCRIPTION

 less comfortable

This function checks whether `c` is a decimal digit (`'0'` through `'9'`) or not. In other words, it checks whether the [ASCII](#) value of `c` is between 48 and 57, inclusive.

RETURN VALUE

 less comfortable

This function returns a non-zero `int` if `c` is a decimal digit and `0` if `c` is not a decimal digit.

EXAMPLE

 less comfortable

```
#include <cs50.h>  
#include <ctype.h>  
#include <stdio.h>
```

```
int main(void)
{
    char c = get_char("Input: ");
    if (isdigit(c))
    {
        printf("Your input is a digit.\n");
    }
    else
    {
        printf("Your input is not a digit.\n");
    }
}
```

ATTRIBUTES

For an explanation of the terms used in this section, see [attributes\(7\)](#).

Interface	Attribute	Value
isalnum() , isalpha() , isascii() , isblank() , iscntrl() , isdigit() , isgraph() , islower() , isprint() , ispunct() , isspace() , isupper() , isxdigit()	Thread safety	MT-Safe

STANDARDS

[isalnum\(\)](#)
[isalpha\(\)](#)
[iscntrl\(\)](#)
[isdigit\(\)](#)
[isgraph\(\)](#)
[islower\(\)](#)
[isprint\(\)](#)
[ispunct\(\)](#)

[isspace\(\)](#)
[isupper\(\)](#)
[isxdigit\(\)](#)
[isblank\(\)](#)

C11, POSIX.1-2008.

[isascii\(\)](#)
[isalnum_l\(\)](#)
[isalpha_l\(\)](#)
[isblank_l\(\)](#)
[iscntrl_l\(\)](#)
[isdigit_l\(\)](#)
[isgraph_l\(\)](#)
[islower_l\(\)](#)
[isprint_l\(\)](#)
[ispunct_l\(\)](#)
[isspace_l\(\)](#)
[isupper_l\(\)](#)
[isxdigit_l\(\)](#)

POSIX.1-2008.

[isascii_l\(\)](#)

GNU.

HISTORY

Show

CAVEATS

Show

SEE ALSO

[iswalnum\(3\)](#), [iswalpha\(3\)](#), [iswblank\(3\)](#), [iswcntrl\(3\)](#), [iswdigit\(3\)](#),
[iswgraph\(3\)](#), [iswlower\(3\)](#), [iswprint\(3\)](#), [iswpunct\(3\)](#), [iswspace\(3\)](#),
[iswupper\(3\)](#), [iswxdigit\(3\)](#), [newlocale\(3\)](#), [setlocale\(3\)](#), [toascii\(3\)](#),
[tolower\(3\)](#), [toupper\(3\)](#), [uselocale\(3\)](#), [ascii\(7\)](#), [locale\(7\)](#)

