

---

Lecture 5


# Fragments

**Course: Mobile App Development**


By: Tho C. Mai  
Nha Trang University


# Fragments

- Activity is a container for views => typically fills the entire screen
- Fragments are introduced for large screen devices
  - One activity contains several mini-activities (fragments)



Activity 1







# Using Fragments

- Create a new **Fragment**, and name it **Fragment1**
- In the res/layout folder, we have **fragment\_1.xml**. Populate it with the following code

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout
    xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:tools="http://schemas.android.com/tools"
    android:orientation="vertical"
    android:layout_width="fill_parent"
    android:layout_height="fill_parent"
    android:background="#00FF00"
    tools:context=".Fragment1">
    <TextView
        android:layout_width="fill_parent"
        android:layout_height="wrap_content"
        android:text="This is fragment #1"
        android:textColor="#000000"
        android:textSize="25sp" />
</LinearLayout>
```



# Using Fragments

- Also Create a new **Fragment**, and name it **Fragment2**
- in the res/layout folder, we have **fragment\_2.xml**. Populate it as follows


```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout
    xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:tools="http://schemas.android.com/tools"
    android:orientation="vertical"
    android:layout_width="fill_parent"
    android:layout_height="fill_parent"
    android:background="#00FF00"
    tools:context=".Fragment1">
    <TextView
        android:layout_width="fill_parent"
        android:layout_height="wrap_content"
        android:text="This is fragment #2"
        android:textColor="#000000"
        android:textSize="25sp" />
</LinearLayout>
```



# Using Fragments

- In activity\_main.xml, replace all with in the following code:

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"
    android:layout_height="match_parent"    tools:context=".MainActivity">
    <fragment
        android:name="com.maicuongtho.fragments.Fragment1"
        android:id="@+id/fragment1"
        android:layout_weight="1"
        android:layout_width="fill_parent"
        android:layout_height="match_parent" />
    <fragment
        android:name="com.maicuongtho.fragments.Fragment2"
        android:id="@+id/fragment2"
        android:layout_weight="1"
        android:layout_width="fill_parent"
        android:layout_height="match_parent" />
</LinearLayout>
```



# Adding Fragments Dynamically



- In the same project, modify the activity\_main.xml file by commenting out the two <fragment> elements

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    tools:context=".MainActivity"
    android:orientation="vertical" >
    <!-- <fragment-->
    ...
    <!-- <fragment-->
    ...
</LinearLayout>
```


# Adding Fragments Dynamics

- Add lines in the following code to the MainActivity.java file

```
protected void onCreate(Bundle savedInstanceState) {  
    super.onCreate(savedInstanceState);  
    // setContentView(R.layout.activity_main);  
    FragmentManager fragmentManager = getSupportFragmentManager();  
    FragmentTransaction fragmentTransaction = fragmentManager.beginTransaction();  
    //---get the current display info---  
    DisplayMetrics display = this.getResources().getDisplayMetrics();  
    int width = display.widthPixels;    int height = display.heightPixels;  
    if (width > height) { //---landscape mode---  
        Fragment1 fragment1 = new Fragment1();  
        // android.R.id.content refers to the content view of the activity  
        fragmentTransaction.replace(android.R.id.content, fragment1);  
    }  
    else { //---portrait mode---  
        Fragment2 fragment2 = new Fragment2();  
        fragmentTransaction.replace(android.R.id.content, fragment2);  
    }  
    fragmentTransaction.commit();  
}
```


Remove: `setContentView(R.layout.activity_main);`

**FragmentTransaction** class to perform fragment transactions (such as add, remove, or replace) in your activity





# Interactions between Fragments





# Interactions between Fragments

- An activity might contain two or more fragments working together to present a coherent UI to the user
  - E.g.: the user taps on an item in that fragment, details about the selected item might be displayed in another fragment
- Continue in the same project, add bolded statements to **fragment\_1.xml**

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout
    xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:tools="http://schemas.android.com/tools"
    android:orientation="vertical" android:layout_width="fill_parent"
    android:layout_height="fill_parent" android:background="#00FF00"
    tools:context=".Fragment1">
    <TextView
        android:id="@+id/lblFragment1"
        android:layout_width="fill_parent"
        android:layout_height="wrap_content"
        android:text="This is fragment #1"
        android:textColor="#000000"
        android:textSize="25sp" />
</LinearLayout>
```


# Interactions between Fragments



- Add the following bolded lines to fragment\_2.xml

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout

.....
<Button
    android:id="@+id/btnGetText"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="Get text in Fragment #1"
    android:textColor="#000000"
    android:onClick="onClick" />
<TextView
    android:id="@+id/lblStatus"
    android:layout_width="fill_parent"
    android:layout_height="wrap_content"
    android:text="Status Area"
    android:textColor="#000000"
    android:textSize="25sp" />
</LinearLayout>
```



# Interactions between Fragments



- In activity\_main.xml, uncomment the two fragments:

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"    android:layout_height="match_parent"
    tools:context=".MainActivity"        android:orientation="vertical">
    <fragment
        android:name="com.maicuongtho.fragments.Fragment1"
        android:id="@+id/fragment1"
        android:layout_weight="1"
        android:layout_width="fill_parent"
        android:layout_height="match_parent" />
    <fragment
        android:name="com.maicuongtho.fragments.Fragment2"
        android:id="@+id/fragment2"
        android:layout_weight="1"
        android:layout_width="fill_parent"
        android:layout_height="match_parent" />
</LinearLayout>
```

# Interactions between Fragments



- Modify the MainActivity.java file by commenting out the code added in the previous step, and **add setContentView() back**

```
package com.maicuongtho.fragments;
.....
public class MainActivity extends AppCompatActivity {

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
        //    fragmentManager fragmentManager = getSupportFragmentManager();
        //.....
        //    fragmentTransaction.commit();
    }
}
```

# Interactions between Fragments



- Add the bolded statements to the Fragment2.java

Fragment2.java

```
...
public class Fragment2 extends Fragment {
...
    @Override
    public View onCreateView(LayoutInflater inflater, ViewGroup container,
        return inflater.inflate(R.layout.fragment_2, container, false);
    }
    @Override
    public void onStart() {
        super.onStart();
        Button btnGetText = (Button) getActivity().findViewById(R.id.btnGetText); //---Button view---
        btnGetText.setOnClickListener(new View.OnClickListener() { //---Button click---
            public void onClick(View v) {
                TextView lbl = (TextView) getActivity().findViewById(R.id.lblFragment1);
                TextView statusarea = (TextView) getActivity().findViewById(R.id.lblStatus);
                statusarea.setText("Fragment#1's text shows: "+lbl.getText());
            }
        });
    }
}
```

use a LayoutInflater object to inflate the UI from the specified XML file

# Your turn

I fear not the man who has practiced 10,000 kicks once,  
but I fear the man who has practiced one kick 10,000 times.  
Bruce Lee



## ■ Practice 7,8,9/ Exercice 7,8,9

- 1) Repeat the examples by yourself (new project for each case)
- 2) Push it to your github repository
  - ✓ With a report with screenshots of the final app in action, data structures used/class design, and the implementation logic.

## □ Practice 10/ Exercice 10 (Homework #4)

# Homework #4



- Notepad app with custom keypad
  - Top fragment: display the note entered
  - Bottom fragment: display several rows of letters, numbers, and symbols (each as a button) for text input; when a user pushes a button, the corresponding input is appended in the top fragment

## What to submit:

- Push it to your github repository,
    - a report with screenshots of the final app in action, data structures used/class design, and the implementation logic.
-