```
No.      Time          Source            Destination       Protocol  Length  Info
     331 12.364554      128.119.245.12    202.141.190.132   TCP       66       80 → 64146 [SYN, ACK] Seq=0 Ack=1
Win=29200 Len=0 MSS=1460 SACK_PERM WS=128
Frame 331: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface \Device\NPF_{8F4CCA7D-037E-4F4A-
A903-982EA39577AF}, id 0
    Section number: 1
    Interface id: 0 (\Device\NPF_{8F4CCA7D-037E-4F4A-A903-982EA39577AF})
        Interface name: \Device\NPF_{8F4CCA7D-037E-4F4A-A903-982EA39577AF}
        Interface description: WLAN
    Encapsulation type: Ethernet (1)
    Arrival Time: Oct 30, 2023 17:01:28.878835000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1698656488.878835000 seconds
    [Time delta from previous captured frame: 0.019694000 seconds]
    [Time delta from previous displayed frame: 0.019694000 seconds]
    [Time since reference or first frame: 12.364554000 seconds]
    Frame Number: 331
    Frame Length: 66 bytes (528 bits)
    Capture Length: 66 bytes (528 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:tcp]
    [Coloring Rule Name: HTTP]
    [Coloring Rule String: http || tcp.port == 80 || http2]
Ethernet II, Src: VMware_9f:00:7f (00:50:56:9f:00:7f), Dst: LiteonTe_9d:af:b3 (74:4c:a1:9d:af:b3)
    Destination: LiteonTe_9d:af:b3 (74:4c:a1:9d:af:b3)
        Address: LiteonTe_9d:af:b3 (74:4c:a1:9d:af:b3)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: VMware_9f:00:7f (00:50:56:9f:00:7f)
        Address: VMware_9f:00:7f (00:50:56:9f:00:7f)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 202.141.190.132
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x04 (DSCP: LE, ECN: Not-ECT)
        0000 01.. = Differentiated Services Codepoint: Lower Effort (1)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 52
    Identification: 0x0000 (0)
    010. .... = Flags: 0x2, Don't fragment
        0... .... = Reserved bit: Not set
        .1.. .... = Don't fragment: Set
        ..0. .... = More fragments: Not set
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 33
    Protocol: TCP (6)
    Header Checksum: 0x5b2a [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 128.119.245.12
    Destination Address: 202.141.190.132
Transmission Control Protocol, Src Port: 80, Dst Port: 64146, Seq: 0, Ack: 1, Len: 0
    Source Port: 80
    Destination Port: 64146
    [Stream index: 9]
    [Conversation completeness: Incomplete, DATA (15)]
    [TCP Segment Len: 0]
    Sequence Number: 0     (relative sequence number)
    Sequence Number (raw): 147694906
    [Next Sequence Number: 1     (relative sequence number)]
    Acknowledgment Number: 1     (relative ack number)
    Acknowledgment number (raw): 311548425
    1000 .... = Header Length: 32 bytes (8)
    Flags: 0x012 (SYN, ACK)
        000. .... .... = Reserved: Not set
        ...0 .... .... = Accurate ECN: Not set
        .... 0... .... = Congestion Window Reduced: Not set
        .... .0.. .... = ECN-Echo: Not set
        .... ..0. .... = Urgent: Not set
        .... ...1 .... = Acknowledgment: Set
        .... .... 0... = Push: Not set
        .... .... .0.. = Reset: Not set
        .... .... ..1. = Syn: Set
```

```
        [Expert Info (Chat/Sequence): Connection establish acknowledge (SYN+ACK): server port 80]
            [Connection establish acknowledge (SYN+ACK): server port 80]
            [Severity level: Chat]
            [Group: Sequence]
        .... .... ...0 = Fin: Not set
        [TCP Flags: ········A··S·]
    Window: 29200
    [Calculated window size: 29200]
    Checksum: 0x68d5 [unverified]
    [Checksum Status: Unverified]
    Urgent Pointer: 0
    Options: (12 bytes), Maximum segment size, No-Operation (NOP), No-Operation (NOP), SACK permitted, No-Operation
(NOP), Window scale
        TCP Option - Maximum segment size: 1460 bytes
            Kind: Maximum Segment Size (2)
            Length: 4
            MSS Value: 1460
        TCP Option - No-Operation (NOP)
            Kind: No-Operation (1)
        TCP Option - No-Operation (NOP)
            Kind: No-Operation (1)
        TCP Option - SACK permitted
            Kind: SACK Permitted (4)
            Length: 2
        TCP Option - No-Operation (NOP)
            Kind: No-Operation (1)
        TCP Option - Window scale: 7 (multiply by 128)
            Kind: Window Scale (3)
            Length: 3
            Shift count: 7
            [Multiplier: 128]
    [Timestamps]
        [Time since first frame in this TCP stream: 0.270570000 seconds]
        [Time since previous frame in this TCP stream: 0.270570000 seconds]
    [SEQ/ACK analysis]
        [This is an ACK to the segment in frame: 321]
        [The RTT to ACK the segment was: 0.270570000 seconds]
        [iRTT: 0.270649000 seconds]
No.     Time          Source            Destination         Protocol Length Info
    489 13.565270     128.119.245.12    202.141.190.132     TCP      60      80 → 64146 [ACK] Seq=1 Ack=153069
Win=264960 Len=0
Frame 489: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface \Device\NPF_{8F4CCA7D-037E-4F4A-
A903-982EA39577AF}, id 0
    Section number: 1
    Interface id: 0 (\Device\NPF_{8F4CCA7D-037E-4F4A-A903-982EA39577AF})
        Interface name: \Device\NPF_{8F4CCA7D-037E-4F4A-A903-982EA39577AF}
        Interface description: WLAN
    Encapsulation type: Ethernet (1)
    Arrival Time: Oct 30, 2023 17:01:30.079551000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1698656490.079551000 seconds
    [Time delta from previous captured frame: 0.000000000 seconds]
    [Time delta from previous displayed frame: 0.000000000 seconds]
    [Time since reference or first frame: 13.565270000 seconds]
    Frame Number: 489
    Frame Length: 60 bytes (480 bits)
    Capture Length: 60 bytes (480 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:tcp]
    [Coloring Rule Name: HTTP]
    [Coloring Rule String: http || tcp.port == 80 || http2]
Ethernet II, Src: NewH3CTe_09:10:02 (30:5f:77:09:10:02), Dst: LiteonTe_9d:af:b3 (74:4c:a1:9d:af:b3)
    Destination: LiteonTe_9d:af:b3 (74:4c:a1:9d:af:b3)
        Address: LiteonTe_9d:af:b3 (74:4c:a1:9d:af:b3)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: NewH3CTe_09:10:02 (30:5f:77:09:10:02)
        Address: NewH3CTe_09:10:02 (30:5f:77:09:10:02)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
    Padding: 000000000000
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 202.141.190.132
    0100 .... = Version: 4
```

```
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x04 (DSCP: LE, ECN: Not-ECT)
        0000 01.. = Differentiated Services Codepoint: Lower Effort (1)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 40
    Identification: 0x1046 (4166)
    010. .... = Flags: 0x2, Don't fragment
        0... .... = Reserved bit: Not set
        .1.. .... = Don't fragment: Set
        ..0. .... = More fragments: Not set
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 33
    Protocol: TCP (6)
    Header Checksum: 0x4af0 [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 128.119.245.12
    Destination Address: 202.141.190.132
Transmission Control Protocol, Src Port: 80, Dst Port: 64146, Seq: 1, Ack: 153069, Len: 0
    Source Port: 80
    Destination Port: 64146
    [Stream index: 9]
    [Conversation completeness: Incomplete, DATA (15)]
    [TCP Segment Len: 0]
    Sequence Number: 1    (relative sequence number)
    Sequence Number (raw): 147694907
    [Next Sequence Number: 1    (relative sequence number)]
    Acknowledgment Number: 153069    (relative ack number)
    Acknowledgment number (raw): 311701493
    0101 .... = Header Length: 20 bytes (5)
    Flags: 0x010 (ACK)
        000. .... .... = Reserved: Not set
        ...0 .... .... = Accurate ECN: Not set
        .... 0... .... = Congestion Window Reduced: Not set
        .... .0.. .... = ECN-Echo: Not set
        .... ..0. .... = Urgent: Not set
        .... ...1 .... = Acknowledgment: Set
        .... .... 0... = Push: Not set
        .... .... .0.. = Reset: Not set
        .... .... ..0. = Syn: Not set
        .... .... ...0 = Fin: Not set
        [TCP Flags: ·······A····]
    Window: 2070
    [Calculated window size: 264960]
    [Window size scaling factor: 128]
    Checksum: 0xbdb3 [unverified]
    [Checksum Status: Unverified]
    Urgent Pointer: 0
    [Timestamps]
        [Time since first frame in this TCP stream: 1.471286000 seconds]
        [Time since previous frame in this TCP stream: 0.000000000 seconds]
    [SEQ/ACK analysis]
        [This is an ACK to the segment in frame: 473]
        [The RTT to ACK the segment was: 0.275886000 seconds]
        [iRTT: 0.270649000 seconds]
```