

SE FR Component Library

Knowledge base — for the LWC_Library_Agent

GENERATED 2026-05-09 · SOLUTION ENGINEERING FRANCE

Table of contents

[Canonical component table](#)

[Cookbook recipes](#)

[Release notes](#)

[Contributors](#)

[About — design principles, reading a component page](#)

[Library standards, install methods, configuration, data setup](#)

Per-component pages

[seFrAccountHealth](#)

[seFrAccountStrategyPlan](#)

[seFrActiveSegments](#)

[seFrActivityFeed](#)

[seFrAgentforceHeader](#)

[seFrAlertsRibbon](#)

[seFrConsentManager](#)

[seFrContactCard](#)

[seFrContactsCarousel](#)

[seFrCustomerOrders](#)

[seFrCustomerSalesSummary](#)

[seFrFieldRepHome](#)

[seFrFilesGallery](#)

[seFrKanbanBoard](#)

[seFrKpiLauncher](#)

[seFrMetricTile](#)

[seFrMyEvents](#)

[seFrMyTasks](#)

[seFrNearbyAccountsMap](#)

[seFrOrderEntry](#)

[seFrOrderSummary](#)

[seFrPipelineSnapshot](#)

[seFrPromptLauncher](#)

[seFrRecordHighlights](#)

[seFrRelatedRecordCard](#)

[seFrRevenueDashboard](#)

[seFrSmartRecommendations](#)

[seFrSplashBanner](#)

[seFrTelesalesRepHome](#)

[seFrTerritoryMap](#)

[seFrTimelinePhases](#)

[seFrVoiceNoteTaker](#)

Canonical component table

How to read this table: every row is a real component. Names follow the `seFr*` convention and are the only valid component identifiers — anything else (e.g. "Account 360", "Performance") is a category or persona heading, not a component. When asked "what components are there?", list rows from this table.

Per-component details (full prose, key props, edge-cases, install steps, data prereqs) live further down in this document under the "Component · `seFrXxx` " sections.

API NAME	MASTER LABEL	TAGLINE	CATEGORIES	PERSONAS	SURFACES	OBJECTS	DATA MODE
seFrAccountHealth	SE FR - Account Health	Quantitative account health score (0-100) with verdict level and weighted positive / negative signals.	Account 360°	Sales	RecordPage	Account	live
seFrAccountStrategyPlan	SE FR - Account Strategy Plan	Narrative account plan with editable KPIs, target gauge, SWOT 2x2 and quarterly action plan.	Account 360°	Sales	RecordPage	Account	mock
seFrActiveSegments	SE FR - Active Segments	Compact panel showing the marketing / Data Cloud segments the record belongs to, as colored badges.	Marketing & Data	Marketing	AppPage, HomePage, RecordPage	Any	mock
seFrActivityFeed	SE FR - Activity Feed	Unified activity timeline aggregating 16+ Salesforce record types in a single feed with rich filtering.	Account 360°	Sales, Service	RecordPage	Account, Contact	live
seFrAgentforceHeader	SE FR - Agentforce Header	Astro-themed Home page header with a search / dictation box that forwards questions to the Agentforce panel.	Agentforce & AI	All	HomePage	Any	mock
seFrAlertsRibbon	SE FR - Alerts Ribbon	Configurable alerts ribbon combining declarative record-driven rules with always-on static banners.	Account 360°	Sales, Service	AppPage, HomePage, RecordPage	Account, Contact, Case, Opportunity, Lead, Order, Contract	mock
seFrConsentManager	SE FR - Consent Manager	Per-channel GDPR consent toggle panel binding each channel to a boolean field on the current record.	Marketing & Data	Marketing, Service	RecordPage	Contact, Lead, Account	live
seFrContactCard	SE FR - Contact Card	Visual contact card with animated waves, avatar, address, configurable gauges and optional Einstein prompt summary.	Account 360°, Agentforce & AI	Sales, FieldSales, Telesales, Service, Marketing	RecordPage	Contact, Account, Case, Opportunity, Order, Lead	hybrid
seFrContactsCarousel	SE FR - Contacts Carousel	Horizontal carousel of an Account's Contacts with avatars, role badges and quick Email / Call actions.	Account 360°	Sales, FieldSales, Telesales, Service, Marketing	RecordPage	Account	live

API NAME	MASTER LABEL	TAGLINE	CATEGORIES	PERSONAS	SURFACES	OBJECTS	DATA MODE
seFrCustomerOrders	SE FR - Customer Orders	Last order detail card plus searchable, sortable, filterable order history for an Account or Contact.	Account 360°	Sales, Telesales	RecordPage	Account, Contact	live
seFrCustomerSalesSummary	SE FR - Customer Sales Summary	B2C-leaning sales summary with KPI tiles and breakdowns by Category, Brand and Store.	Account 360°	Retail, Marketing	RecordPage	Contact, Account	mock
seFrFieldRepHome	SE FR - Field Sales - Rep Home	Field Sales rep home page with greeting, KPIs, priority accounts, hot leads, product penetration and campaign calendar.	Dashboards & KPIs	FieldSales	AppPage, HomePage	Any	hybrid
seFrFilesGallery	SE FR - Files Gallery	Visual gallery of files attached to any record with image thumbnails, doctype icons and drag-and-drop upload.	Transverse	Sales, FieldSales, Telesales, Service, Marketing	RecordPage	Any	live
seFrKanbanBoard	SE FR - Kanban Board	Generic kanban board with native drag & drop on any whitelisted SObject (Case, Opp, Lead, Order, Task, Account).	Sales Productivity	Service, Telesales	AppPage, HomePage, RecordPage	Any	live
seFrKpiLauncher	SE FR - KPI Launcher	Configurable grid of 3-6 clickable KPI tiles with icon, value, color and link, ready out of the box.	Dashboards & KPIs	All	AppPage, HomePage, RecordPage	Any	mock
seFrMetricTile	SE FR - Metric Tile	Single-metric tile with 4 chart styles (line / area / bar / mini-donut), comparison series, target line and currency formatting.	Dashboards & KPIs, Marketing & Data	Sales, FieldSales, Telesales, Service, Marketing	AppPage, HomePage, RecordPage	Any	mock
seFrMyEvents	SE FR - My Events	Today's calendar as a compact vertical timeline that fits a sidebar column, with Google-Calendar-style overlap.	Sales Productivity	All	AppPage, HomePage, RecordPage	Any	live
seFrMyTasks	SE FR - My Tasks	Compact 'My Tasks' sidebar panel grouped by due date with one-click completion.	Sales Productivity	All	AppPage, HomePage, RecordPage	Any	live
seFrNearbyAccountsMap	SE FR - Nearby Accounts Map	Interactive map of nearby accounts	Geo & Field	FieldSales	AppPage, HomePage	Any	live

API NAME	MASTER LABEL	TAGLINE	CATEGORIES	PERSONAS	SURFACES	OBJECTS	DATA MODE
		using the browser's geolocation with Haversine distance sort.					
seFrOrderEntry	SE FR - Order Entry	Full-grid order entry on an Account or Case with stock, AI-recommended quantities and discounts, persisted as real Order records.	Sales Productivity	Telesales	RecordPage	Account, Case	live
seFrOrderSummary	SE FR - Order Summary	Most recent Order linked to a Case with products, total, delivery info and edit / delete / submit actions.	Sales Productivity	Service	RecordPage	Case	live
seFrPipelineSnapshot	SE FR - Pipeline Snapshot	Account-level pipeline visualization with summary tiles and one column per Opportunity stage.	Account 360°	Sales	RecordPage	Account, Opportunity	live
seFrPromptLauncher	SE FR - Prompt Launcher	Configurable AI panel running Salesforce Prompt Templates via Invocable Actions, with auto-filled record context.	Agentforce & AI	All	AppPage, HomePage, RecordPage	Any	live
seFrRecordHighlights	SE FR - Record Highlights	Custom highlights panel with round image, key fields and action buttons, working on 8 standard objects.	Account 360°	All	RecordPage	Account, Contact, Opportunity, Case, Lead, Order, Contract, Quote	live
seFrRelatedRecordCard	SE FR - Related Record Card	Vertical sidebar card showing the counterpart record (Contact / Account) with key fields and avatar.	Account 360°	Sales, FieldSales, Telesales, Service, Marketing	RecordPage	Account, Contact, Case, Opportunity, Order	live
seFrRevenueDashboard	SE FR - Revenue Dashboard	3-year revenue mini-dashboard with KPI tiles and a side-by-side monthly bar chart.	Account 360°, Dashboards & KPIs	Sales, FieldSales, Telesales	RecordPage	Account	mock
seFrSmartRecommendations	SE FR - Smart Recommendations	Context-aware Next Best Action panel with 1-6 recommendations, relevance score and per-card overrides.	Agentforce & AI	Sales, FieldSales, Telesales, Service, Marketing	RecordPage	Account, Contact, Case, Order	mock
seFrSplashBanner	SE FR - Splash Banner	Welcome banner with 8 animated background styles (waves, aurora, mesh, orbs, conic,	Transverse	All	AppPage, HomePage, RecordPage	Any	mock

API NAME	MASTER LABEL	TAGLINE	CATEGORIES	PERSONAS	SURFACES	OBJECTS	DATA MODE
		geometric, constellation, grid) in pure CSS / SVG.					
seFrTelesalesRepHome	SE FR - Telesales - Rep Home	Telesales rep home page with KPIs, live cases and orders tables, calls to make and 3 mini charts.	Dashboards & KPIs	Telesales	AppPage, HomePage	Any	hybrid
seFrTerritoryMap	SE FR - Territory Map	Interactive territory map with geocoded Accounts, pipeline color coding, sidebar filters and CSV export.	Geo & Field	FieldSales, Sales	AppPage, HomePage	Any	live
seFrTimelinePhases	SE FR - Timeline Phases	Horizontal multi-phase timeline with date axis, 'Today' marker and done / pending state per phase.	Sales Productivity	Sales	AppPage, HomePage, RecordPage	Any	mock
seFrVoiceNoteTaker	SE FR - Voice Note Taker	Dictate a voice note via the Web Speech API and save it as a completed Task linked to the current record.	Geo & Field	FieldSales	RecordPage	Account, Contact, Lead, Opportunity	live

Cookbook recipes

Pre-built component bundles for typical demo scenarios. Each recipe groups components that work well together on the same page or persona context.

Account 360°

Drop-in record page for B2B Sales — highlights, health gauge, pipeline, activity timeline, and AI recommendations.

Primary persona: Sales

- seFrRecordHighlights — Record Highlights
- seFrAccountHealth — Account Health
- seFrPipelineSnapshot — Pipeline Snapshot
- seFrActivityFeed — Activity Feed
- seFrSmartRecommendations — Smart Recommendations

Field Sales cockpit

Mobile-first Home page for reps in the field — map, agenda, voice notes and KPIs.

Primary persona: FieldSales

- seFrFieldRepHome — Field Sales - Rep Home
- seFrNearbyAccountsMap — Nearby Accounts Map
- seFrTerritoryMap — Territory Map
- seFrMyEvents — My Events
- seFrVoiceNoteTaker — Voice Note Taker
- seFrKpiLauncher — KPI Launcher

Service desk

Case-centric record page with order history, kanban, alerts and smart actions.

Primary persona: Service

- `seFrAlertsRibbon` — Alerts Ribbon
- `seFrCustomerOrders` — Customer Orders
- `seFrOrderSummary` — Order Summary
- `seFrKanbanBoard` — Kanban Board
- `seFrSmartRecommendations` — Smart Recommendations

Agentforce demo

Showcase page tuned for AI-driven scenarios — hero banner, prompt launcher, and recommendations.

Primary persona: Agents

- `seFrAgentforceHeader` — Agentforce Header
- `seFrPromptLauncher` — Prompt Launcher
- `seFrSmartRecommendations` — Smart Recommendations
- `seFrSplashBanner` — Splash Banner

Marketing 360°

Contact-centric page with consent management, segment membership and engagement signals.

Primary persona: Marketing

- `seFrActiveSegments` — Active Segments
- `seFrConsentManager` — Consent Manager
- `seFrActivityFeed` — Activity Feed
- `seFrCustomerSalesSummary` — Customer Sales Summary

Full pack

All components in one go — for when you want everything pre-loaded.

Primary persona: All

Every component in the library (32 total).

Release notes

Curated release history. Newest first.

v2.8 — 2026-05-08

Prompt Launcher rebuilt + manifest-driven pipeline

The `seFrPromptLauncher` component replaces the old chat — it runs Salesforce Prompt Templates via Invocable Actions, with auto-injected record context and HTML / Markdown rendering. The library now runs on a central manifest that drives the README, deck, agent knowledge base and this site.

v2.7 — 2026-05-03

8 new components

A big batch of generic, reusable components covering pipeline, timelines, contacts, kanban, KPIs, files and alerts — `seFrPipelineSnapshot`, `seFrTimelinePhases`, `seFrContactsCarousel`, `seFrAccountHealth`, `seFrKanbanBoard`, `seFrMetricTile`, `seFrFilesGallery`, `seFrAlertsRibbon`.

v2.6 — 2026-04-30

Bilingual FR / EN across the board

Every component (except `seFrAgentforceHeader`) now exposes a `language` prop with full FR/EN dictionaries. App Builder values still win — a French SE demoing to a German prospect can override individual labels without switching the whole language.

v2.4 — 2026-04-29

My Events refonte

Compact sidebar layout, side-by-side overlapping events (Google Calendar style), live "now" line, Join button for Zoom / Teams / Meet / WebEx links.

v2.0 — 2026-04-24

Initial release

11 components extracted from the "Coup de Pâtes" B2B bakery demo, generalized into industry-neutral building blocks.

Contributors

SEs who authored or contributed components to the library. Lionel Braun is the maintainer; external contributors keep the *original author* credit on their components.

Lionel Braun — Maintainer

31 components.

- `seFrAccountHealth` — Account Health
- `seFrAccountStrategyPlan` — Account Strategy Plan
- `seFrActiveSegments` — Active Segments
- `seFrActivityFeed` — Activity Feed
- `seFrAgentforceHeader` — Agentforce Header
- `seFrAlertsRibbon` — Alerts Ribbon
- `seFrConsentManager` — Consent Manager
- `seFrContactsCarousel` — Contacts Carousel
- `seFrCustomerOrders` — Customer Orders
- `seFrCustomerSalesSummary` — Customer Sales Summary
- `seFrFieldRepHome` — Field Sales - Rep Home
- `seFrFilesGallery` — Files Gallery
- `seFrKanbanBoard` — Kanban Board
- `seFrKpiLauncher` — KPI Launcher
- `seFrMetricTile` — Metric Tile
- `seFrMyEvents` — My Events
- `seFrMyTasks` — My Tasks
- `seFrNearbyAccountsMap` — Nearby Accounts Map
- `seFrOrderEntry` — Order Entry
- `seFrOrderSummary` — Order Summary
- `seFrPipelineSnapshot` — Pipeline Snapshot
- `seFrPromptLauncher` — Prompt Launcher
- `seFrRecordHighlights` — Record Highlights
- `seFrRelatedRecordCard` — Related Record Card
- `seFrRevenueDashboard` — Revenue Dashboard
- `seFrSmartRecommendations` — Smart Recommendations
- `seFrSplashBanner` — Splash Banner
- `seFrTelesalesRepHome` — Telesales - Rep Home
- `seFrTerritoryMap` — Territory Map
- `seFrTimelinePhases` — Timeline Phases
- `seFrVoiceNoteTaker` — Voice Note Taker

Charly Ansel (charly.ansel@salesforce.com, integrated 2026-05-05)

- `seFrContactCard` — Contact Card

About — design principles, reading a component page

Why this library



Faster demos

Drop a vetted component on a page, configure via App Builder, demo in minutes — not days.



Prettier demos

Easy wow. Components are visually polished — subtle animations, consistent palette, design care — so your demos go beyond the raw Lightning standard.



Stay generic

Every component is industry-neutral. Customize via properties, not by editing code.



Share & contribute

One pool of components owned collectively by the SE France team.

Design principles

- **Lightning base components first.** `lightning-card`, `lightning-button`, `lightning-datatable` & co. are translated by the platform — we use them wherever possible.
- **Custom strings become properties.** Anything that could reasonably need renaming is an `@api` with a French default.
- **Demo data as JSON / CSV props.** Dashboards with mock KPIs accept those as stringified JSON / CSV so SEs can swap the dataset in App Builder.
- **Currency & locale exposed.** `currencyCode` (default `EUR`) and `localeTag` (default `fr-FR`) are properties.
- **Standard fields first.** The library uses only Salesforce standard fields by default. No mandatory custom field.
- **Schema-safe Apex.** Where an optional custom field *can* enrich the UI, Apex checks for its existence before referencing it — deploys succeed regardless.
- **Bilingual FR / EN.** Every component exposes a `language` prop with FR/EN dictionaries baked in.

Reading a component page

Each component page carries:

- **Name** — human name displayed in the App Builder master label. Example: `Account Health`.
- **API name** — technical LWC identifier in camelCase. Example: `seFrAccountHealth`.
- **Tagline** — one-line pitch, what you'd use to sell the component in 5 seconds.
- **Chips** — 3-4 wow features. Examples: `SVG donut gauge`, `Native drag & drop`, `4 chart styles`.
- **Status badges** — labels at the top of the page. Examples: `● Stable`, `🌟 New`, `🤖 AI-ready`, `📱 Mobile-ready`, `No Apex`.
- **Personas** — target teams. Examples: `🔴 Sales`, `🚗 Field Sales`, `📞 Service`, `🧑 Agentforce`.
- **Targets** — page types where the component can land. Example: `Home · App · Record`.
- **Objects** — supported SObjects on Record Pages. Examples: `Account`, `Contact / Lead / Account`, `Any`.
- **Apex** — optional Apex dependencies, local or shared. Examples: `SE_FR_AccountHealthController`, `SE_FR_ImageFileController` (shared), `none`.
- **Data mode** — how the component behaves towards org data. Values: `live` (reads/writes real records), `hybrid` (real if present, else mock), `mock` (100% prop-driven, no org dependency).
- **Pitch** — short paragraph that fleshes out the tagline.
- **SE benefit** — the demo angle that lands, the moment the prospect looks up from their screen.
- **Configurable settings** — 3-5 key props to tune in App Builder. Examples: `chartStyle`, `seriesJson`, `currencyCode`.
- **All properties** — full table (name, type, default, description) read straight from the component's `js-meta.xml`.
- **Quick install** — the 4 deploy methods (Deploy button, CLI, AI assistant, Lightning Studio).
- **Original author / Maintained by** — original author and library maintainer (shown when an external contributor wrote the component).
- **Categories** — the library categories the component belongs to. Examples: `Account 360°`, `Agentforce & AI`.
- **Featured in cookbook** — Cookbook recipes that bundle this component.
- **Often used with** — components of the same category typically dropped together.

From browse to live demo in minutes

1

Pick

Browse the catalog, filter by persona / surface / data mode. Add multiple components to bundle.

2

Connect

OAuth into your demo org. Tokens live in your browser session only.

3

Deploy

Components land in your org. Drag-and-drop on the right page in App Builder. Tune props. Demo-ready.

Library standards, install methods, configuration, data setup

Quick install

Every component is a self-contained zip — LWC bundle plus dedicated Apex and any shared Apex it depends on. The fastest path:

1. Browse to [Components](#) and pick what you need.
2. Click **Connect to my org** in the top right — OAuth flow into your demo org.
3. Click **Deploy** on each component (or bundle them in the cart).
4. Open App Builder, drag the component on a page, configure in the property panel.

💡 Tip: if you prefer the terminal, jump straight to the [Deploy via CLI](#) section below.

Deploy via CLI

If you prefer the Salesforce CLI, every component zip is downloadable from the component page:

```
# 1. Download the zip from the component detail page
# 2. Unzip & deploy
unzip seFr<Name>.zip
sf project deploy start \
  --source-dir seFr<Name> \
  --target-org <your-alias>
```

AI assistant (Claude Code / Cursor)

The "no-effort" deploy: let your AI assistant handle everything. Works equally well with **Claude Code** or **Cursor** (or any IDE assistant that can execute shell commands).

1. Download the zip(s) from the component pages — one per component, or the full pack from the [Cookbook](#).
2. Open your project in Claude Code or Cursor. Drag-and-drop the `.zip` file(s) straight into the chat.
3. Ask the assistant: *"Unzip these components and deploy them to my Salesforce org via the CLI"*. Mention the org alias if you have several (e.g. `SE_FR_SD0`).
4. The assistant unzips, identifies the SFDX structure and runs `sf project deploy start` with the right arguments. It also handles shared Apex if any.
5. Open App Builder, drag the components onto the right page, configure the properties.

Prereq: the Salesforce `sf` CLI installed and the target org authenticated (`sf org login web --alias <alias>`) — the assistant can do that for you if not already done.

💡 Why this rocks: zero command to type, zero folder-structure hassle. The assistant reads the library, understands the structure, and deploys. Best for bundling 5-10 components at once.

Lightning Studio (Chrome)

For a "manual" install directly from the browser, no CLI or IDE — handy when you don't have the CLI configured locally, or for a quick ad-hoc deploy.

1. Install the **Lightning Studio** Chrome extension (from the Chrome Web Store).
2. Download the component zip from its detail page, then unzip locally.
3. Log in to your target org. Click the Lightning Studio icon in the Chrome toolbar.
4. Create a new LWC with the same name (e.g. `seFrAccountHealth`). For each file in the bundle (`.js` , `.html` , `.css` , `.js-meta.xml`), open the local file, copy all content, paste it into the Lightning Studio editor, then **Save**.
5. If the component has Apex dependencies, repeat the same flow for *Apex Class* (create the class, paste each `.cls` , save).
6. Open App Builder, drag the `SE FR - <Name>` component on the right page, configure the properties.
7. **Hard refresh** the page (`Cmd + Shift + R` on Mac, `Ctrl + Shift + R` on Windows) to force the compiled bundle to reload.

💡 Handy way to bootstrap or for Apex-free components. For multi-component deploys or proper CI, prefer the CLI or the site's Deploy button.

Configure in App Builder

Once the component is deployed, you find it in App Builder in the left palette under `SE FR - <Name>` . Drag it onto the page, the right panel exposes every `@api` property of the component.

Palette naming conventions

- **LWC API name:** `seFr<Name>` (camelCase, no underscore). It's the bundle folder name and internal HTML tag.
- **App Builder master label:** `SE FR - <Human name>` . This is what you see in the left palette and in the page title bar.
- **Apex class** (if applicable): `SE_FR_<Name>Controller` .

Input formats (props)

Complex-type properties accept two formats depending on the component:

- **CSV / pipe-separated:** most common. One line per item, fields split by `|` , items split by comma or newline. Example `seFrAlertsRibbon.rulesCsv` :

```
AnnualRevenue>1000000|warning|utility:warning|Compte stratégique|Voir|/lightning/o/Account/list
LastActivityDate<Today-30|info|utility:clock|Aucune activité depuis 30j||
```

- **JSON array**: for numeric or structured data. Example `seFrMetricTile.seriesJson` :

```
[2.1, 2.4, 2.7, 3.0, 3.2, 3.1, 3.3, 3.5, 3.4, 3.6, 3.7, 3.85]
```

Each property's *description* in App Builder spells out the expected format. If it says "CSV" or "*pipe-separated*", use the first format. If it says "*JSON array*", use the second.

Per-instance override

Every default is overridable per page: whatever you type in App Builder always wins over the component's baked-in default. You can have 3 instances of the same component on 3 pages with 3 different configs.

Bilingual FR / EN

All components support French and English. Each LWC exposes a `language` prop:

- `fr` — library default
- `en` — for international demos

Override per-instance in App Builder. Strings, dates, currency and computed labels (month names, status pills) all switch at runtime.

Data modes

Components fall into three data modes:

- `live` — reads / writes real records
- `hybrid` — real data + mock fallback when fields are missing or empty
- `mock` — fully scripted client-side, zero org dependency

This makes the components safe to drop on a brand-new org for a one-shot demo.

Named Credential setup

Some Agentforce-related components need a Named Credential called `Agentforce_API`. The full setup chain (Connected App + Auth Provider + External Credential + Permission Set Mapping + Named Credential) is in the technical user guide (FR).

👉 [Read the technical user guide \(FR\)](#) →

Compatibility with a standard SDO

Components run on the standard Salesforce data model with zero mandatory custom field. Everything they read (Account, Contact, Opportunity, Case, Order, Task, Event, ContentDocumentLink...) ships out of the box on any SDO.

A few components *can* use custom fields specific to the Cust360 SDO (customer signals) or MAPS (field visits). When absent, the component silently falls back to mock — no crash, no error.

- `seFrAccountHealth` — optionally uses `NPS__c` and `SDO_MAPS_Days_Since_Last_Visit__c` to enrich signals. Without these, the score is computed from standard fields only (`AnnualRevenue` , `LastActivityDate` , `Open Cases`, `Orders`).
- `seFrContactCard` , `seFrRelatedRecordCard` — optionally use `SDO_Cust360_Contact_Picture_URL__c` , `SDO_Cust360_ChurnRisk__c` . Without these, the avatar is manually uploadable (see below) and gauges are hidden.
- `seFrNearbyAccountsMap` — uses standard `BillingLatitude` / `BillingLongitude` . For the "days since last visit" indicator, uses `SDO_MAPS_Days_Since_Last_Visit__c` if present.

Simplified image upload

Components that display images (`seFrRecordHighlights` , `seFrContactCard` , `seFrRelatedRecordCard` , `seFrFilesGallery`) use **ContentDocument** attached to the record — not Static Resources or org-specific `ImageURL__c` fields.

Concretely: on the deployed component, click the avatar / image zone, pick a local file, the image is saved as a `ContentVersion` + `ContentDocumentLink` on the current record, and the rendition URL is used automatically. No admin setup, no external host, no custom field.

Shared logic lives in `SE_FR_ImageFileController` (shared Apex) — deployed once, reused by every image-aware component.

Make the demo shine — vary the data

On a fresh org, several Live components (Activity Feed, Pipeline Snapshot, Customer Orders, My Events...) look thin. For an optimal demo, **vary the data around your showcase account**:

- **Stagger dates**: Opportunity `CloseDate` across 6 rolling months, Order `EffectiveDate` across 24 months, future Events `StartDateTime` within the next 14 days, varied Task `ActivityDate` .

- **Mix statuses:** Opportunities across several `StageName` values (Prospecting / Qualification / Proposal / Closed Won), Cases across several `Status` values (New / Working / Escalated / Closed), Orders mix Activated / Draft.
- **Upload images:** Contact avatar via `seFrContactCard`, Account photo via `seFrRecordHighlights`, files via `seFrFilesGallery` — a few uploads are enough to add depth.
- **French addresses** (or whatever matches your demo): `BillingStreet`, `BillingCity`, `BillingPostalCode`, `BillingLatitude` / `BillingLongitude` on Accounts. `seFrNearbyAccountsMap` and `seFrTerritoryMap` light up.
- **Realistic activity on the showcase account:** 1-2 recent completed Tasks, 1-2 upcoming Events, 1-2 open Cases, 3-5 Opportunities across varied stages, a few Activated Orders. This feeds Activity Feed, Pipeline Snapshot, Customer Orders, Account Health in parallel.

💡 Tip: generate this data setup in seconds via **Claude Code** or **Cursor**. Point the assistant at your target org (authenticated CLI), give it your showcase Account Id, ask it to write an idempotent Apex script that staggers dates / statuses / Tasks / Events along the lines above. Run the script via `sf apex run` — no manual admin needed.

Naming conventions (internal)

Internal conventions used by the maintainer. You don't have to follow them to contribute — the maintainer adapts your components to the standard.

- LWC folder / JS class : `seFr` + PascalCase (ex : `seFrAccountStrategyPlan`)
- Apex class : `SE_FR_` + PascalCase (ex : `SE_FR_AccountHealthController`)
- App Builder master label : `SE FR` – `<Human name>`
- Custom strings : French defaults, overridable via `language` or explicit prop

Schema-safe Apex

Where an optional custom field *can* enrich the UI (e.g. `NPS__c`), Apex checks `Schema.SObjectType.X.fields.getMap()` before referencing it so deploys succeed regardless of whether the field exists.

Library defaults

- `language` : `fr`
- `currencyCode` : `EUR`
- `localeTag` : `fr-FR`
- No UI copy ever reveals mock/demo mode

Component · Account Health (`seFrAccountHealth`)

API name: `seFrAccountHealth` · **Categories:** Account 360° · **Surfaces:** RecordPage · **Objects:** Account · **Data mode:** live · **Mobile-ready:** no · **Apex:** `SE_FR_AccountHealthController`

seFrAccountHealth (Account Account Health)

B2B — SVG donut gauge (0-100) + verdict level (Excellent / Healthy / Watch / At risk / Critical) + list of positive / negative signals used in the computation. Complementary to `seFrAccountWeather` (qualitative verdict) — this one is quantitative. Bilingual EN / FR.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account
- **App Builder label:** `SE FR` – Account Health

Apex dependency

`SE_FR_AccountHealthController.getSnapshot(accountId)`. Schema-safe on optional custom fields (`NPS__c`, `SDO_MAPS_Days_Since_Last_Visit__c`).

Scoring logic

Starts at 50 (neutral). Each signal adds / subtracts weighted points:

- Revenue $\geq$ threshold $\rightarrow$ +10 ; below $\rightarrow$ -5
- Recent activity $\rightarrow$ +10 ; stale $\rightarrow$ -10
- Recent visit $\rightarrow$ +5 ; stale $\rightarrow$ -5
- Open Opportunities $\rightarrow$ +10 per signal
- Open Cases (≥ 3) $\rightarrow$ -15 ; any open $\rightarrow$ -5

- Recent Orders (90d) → +10 ; none → -5
- NPS ≥ 9 → +10 ; ≤ 6 → -10
- ≥3 Contacts mapped → +3

Clamped to [0, 100]. Level thresholds: ≥85 Excellent, ≥65 Healthy, ≥45 Watch, ≥25 At risk, <25 Critical.

Properties

NAME	DEFAULT	DESCRIPTION
language	en	en or fr .
cardTitle	—	Override the default ("Account Health" / "Santé du compte").
revenueThreshold	500000	AnnualRevenue below this is a negative signal.
inactivityThresholdDays	45	
staleVisitThresholdDays	60	Uses SDO_MAPS_Days_Since_Last_Visit__c — skipped if absent.

Install

1. Deploy `classes/SE_FR_AccountHealthController.cls` .
2. Unzip `seFrAccountHealth.zip` , deploy the LWC bundle.
3. Drop `SE FR – Account Health` on an Account record page.

Data enrichment prerequisites

The score is only as rich as the data. On a fresh SDO, many Accounts will score 50 (neutral — no signal fires). To get a varied demo:

- Set **AnnualRevenue** on the showcase Account (above or below the threshold depending on the story).
- Ensure **LastActivityDate** is recent. This field is derived from Tasks / Events — create at least one recent Task if needed.
- Have **at least 1 open Opportunity** and **1 recent Order (≤90 days)**.
- Optional: if `NPS__c` exists on the org, populate it with 9+ or ≤6 to trigger the NPS signal.

Component · Account Strategy Plan (`seFrAccountStrategyPlan`)

API name: `seFrAccountStrategyPlan` · **Categories:** Account 360° · **Surfaces:** RecordPage · **Objects:** Account · **Data mode:** mock · **Mobile-ready:** no · **Apex:** none

seFrAccountStrategyPlan

Narrative account plan for the Account record page. Four blocks:

1. **Performance snapshot** — 4 KPI tiles + annual-target progress bar.
2. **Strategic positioning** — SWOT in a 2x2 grid (Strengths / Weaknesses / Opportunities / Threats), each card with bullets.
3. **Action plan** — rows with a quarter chip, action + owner, and a color-coded status pill.
4. **Strategic notes** — free text.

All values are **pre-filled from App Builder defaults** and **editable on the page** via the "Edit" button in the card header — SEs can tune the content live during a demo.

Where to drop it

- **Target:** Lightning Record Page
- **Object:** Account
- **App Builder label:** SE FR – Account Strategy Plan

Apex dependencies

None.

How editing works

- Click the pencil icon in the header → enters edit mode.
- All fields (KPIs/target values, SWOT bullets, action rows, notes) become editable inline.
- "Reset" restores the App Builder defaults. "Done editing" returns to the narrative view.
- The footer "Save plan" / "Submit to manager" fire toasts (demo-only; no persistence).

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
cardTitle / cardIcon	String	Account Strategy & Action Plan / standard:goals	Card header.
currencyCode / localeTag	String / String	USD / en-US	Currency & locale for formatting.
kpiPreviousYearLabel / Value	String / Int	Revenue (Y-1) / 45000	KPI 1 (primary — accent color).
kpiRunRateLabel / Value	String / Int	Run rate / 3800	KPI 2 (rendered as X / mo).
kpiPotentialLabel / Value	String / Int	Portfolio potential / 80000	KPI 3.
kpiShareLabel / Value	String / String	Share of wallet / 56%	KPI 4 (raw text).
annualTargetLabel / Default	String / Int	Annual target / 55000	Target for the progress bar.
ytdRevenueLabel / Default	String / Int	YTD revenue / 38000	Current-year progress value.
strengthsCsv	String	see meta.xml	SWOT — Strengths bullets (comma- or newline-separated).
weaknessesCsv	String	see meta.xml	SWOT — Weaknesses bullets.
opportunitiesCsv	String	see meta.xml	SWOT — Opportunities bullets.
threatsCsv	String	see meta.xml	SWOT — Threats bullets.
actionPlanCsv	String	see meta.xml	Rows as Quarter Action Owner Status , comma-separated. Status: Not started , In progress , On track , At risk , Done .
strategyNotesDefault	String	see meta.xml	Strategic notes — default text.

Install

1. Unzip seFrAccountStrategyPlan.zip , deploy the LWC bundle.
2. Drop SE FR – Account Strategy Plan on an Account record page.
3. Configure the defaults to match the account you're showing.

Legacy

Props `logisticOptionsCsv` , `competitorOptionsCsv` , `riskOptionsCsv` , `leversOptionsCsv` are kept for backwards compatibility with v1 pages but are no longer used by the new UI.

Component · Active Segments (`seFrActiveSegments`)

API name: `seFrActiveSegments` · **Categories:** Marketing & Data · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

seFrActiveSegments (Active Segments)

Displays a short, configurable list of marketing / Data Cloud segments as badges inside a lightning-card . The card title automatically shows the segment count: Active Segments (4) .

Where to drop it

- **Targets:** Lightning Record Page, App Page, Home Page
- **App Builder label:** SE FR – Active Segments

Apex dependencies

None.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
cardTitle	String	Active Segments	Title prefix — shown as <title> (N) .
cardIcon	String	standard:groups	SLDS icon identifier for the card header.
segmentsCsv	String	Back-to-School Parents, Sport Sun-wear Affinity, Progressive Lens Switchers, Web-to-Store Frequent	Comma-separated segment names. Each becomes a badge.

Install

1. Unzip `seFrActiveSegments.zip` , deploy the LWC bundle.
2. Drop `SE FR – Active Segments` on any page and set `segmentsCsv` to the customer's segments.

Origin

Genericized from the `krysActiveSegments` Krys demo component.

Component · Activity Feed (`seFrActivityFeed`)

API name: `seFrActivityFeed` · **Categories:** Account 360° · **Surfaces:** RecordPage · **Objects:** Account, Contact · **Data mode:** live · **Mobile-ready:** no · **Apex:** `SE_FR_ActivityFeedController`

seFrActivityFeed

Aggregated activity timeline for an Account or Contact. Shows **16+ record types** in a unified feed: Tasks, Events, EmailMessages, VoiceCalls, MessagingSessions, LiveChatTranscripts, Orders, Cases, Opportunities, Quotes, Contracts, Visits, Files (ContentDocument), Chatter posts (FeedItem), Survey Responses.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Contact
- **App Builder label:** SE FR – Activity Feed

Apex dependency

- `SE_FR_ActivityFeedController.getActivityFeed(recordId, includeRelatedContacts, daysBack, daysForward)` — returns a unified `List<FeedEntry>` . Schema-safe: each object is queried only if present and accessible; any failure is caught per-source so a missing object never breaks the whole feed.

Feed sources

SOURCE	ACTIVITY DATE	LINK ROUTE
Task	ActivityDate (fallback CreatedDate)	WhatId / WhoId
Event	StartDateTime	WhatId / WhoId
EmailMessage	MessageDate	RelatedToId = recordId
VoiceCall	CallStartDateTime	AccountId / RelatedRecordId
MessagingSession	StartTime	AccountId / ContactId
LiveChatTranscript	StartTime	AccountId / ContactId
Order	CreatedDate	AccountId
Case	CreatedDate	AccountId / ContactId
Opportunity	CreatedDate	AccountId
Quote	CreatedDate	Opportunity.AccountId
Contract	CreatedDate	AccountId
Visit	ActualVisitEndTime if completed, else PlannedVisitStartTime	AccountId
ContentDocumentLink	SystemModstamp	LinkedEntityId = recordId
FeedItem	CreatedDate	ParentId = recordId
SurveyResponse	SystemModstamp	SurveySubjectId = recordId

On an **Account**, enabling `includeRelatedContacts` (default) also pulls activities of the account's related Contacts. On a **Contact**, the feed always includes the contact's own activities + Orders/Cases/Opportunities of its Account.

UI behavior

- Top toolbar: **Log a Call / Email / New Task / New Event / Schedule Visit** — each triggers the standard quick action of the object (via `standard__quickAction`). The exact button set is configurable.
- Filter panel (toggle with the funnel icon): date range (all / next 7d / past 7d / past 30d), activity types (checkbox grid), sort asc/desc.
- Items are grouped: **Upcoming & pending** section at the top (anything `isFuture = true`), then one group per month for past items.
- Items are collapsed by default — click a row to expand and see the description (with formatting preserved).
- `Task.Description` is rendered verbatim on expand — so notes saved by `seFrVoiceNoteTaker` are fully visible.
- Refresh button re-invokes the wired Apex.
- "Expand all" / "Collapse all" toggles every item at once.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
<code>cardTitle</code>	String	Activity Feed	
<code>cardIcon</code>	String	<code>standard:activations</code>	
<code>includeRelatedContacts</code>	Boolean	<code>true</code>	On Account pages, also pull activities of the account's Contacts.
<code>defaultDaysBack</code>	Integer	365	History window.
<code>defaultDaysForward</code>	Integer	90	Future window (events, pending tasks, planned visits).
<code>defaultSortDesc</code>	Boolean	<code>true</code>	Newest first.
<code>expandedByDefault</code>	Boolean	<code>false</code>	Expand all items on load.
<code>enabledActionsCsv</code>	String	<code>LogACall,Email,NewTask,NewEvent,NewVisit</code>	Comma-separated list of toolbar quick-action buttons. API names must match quick actions available on the object's page layout.

Install

1. Deploy `classes/SE_FR_ActivityFeedController.cls` .
2. Unzip `seFrActivityFeed.zip` , deploy the LWC bundle.
3. Drop `SE FR – Activity Feed` on an Account or Contact record page.

4. Verify that the Account/Contact page layout exposes the quick actions you listed in `enabledActionsCsv` — the toolbar buttons launch the standard quick actions of the object.

Prerequisites — user timezone

The `defaultDaysBack` / `defaultDaysForward` filters compute date windows using the **running user's timezone**, and the grouping by month ("April 2026", etc.) displays each activity's date in the user timezone. Most Salesforce SDOs ship with the org set to `America/Los_Angeles` — if your user also inherits that timezone, activities may appear under unexpected months (or the wrong side of "Upcoming").

Before using the component, set **your user's timezone to your local value**:

- Setup → **Personal Information** → *Time Zone* → pick your local value (e.g. (GMT+01:00) Central European Time (Europe/Paris) / (GMT+02:00) in summer).
- Save, refresh the tab.

You don't need to change the **org** timezone — only the user timezone.

Known limitations

- Quick action names (`LogACall` , `Email` , `NewTask` , `NewEvent` , `NewVisit`) are the **global** API names. Some orgs may use different action names (e.g. custom quick actions) — adjust `enabledActionsCsv` accordingly.
- The component does not deduplicate activities that exist on both the account and a related contact (could appear twice if linked to both via `WhatId` and `WhoId` on the same Task). That's Salesforce's own standard behavior.
- `ListEmail` and `SMS` don't have dedicated SObjects — they show up as Tasks with `TaskSubtype` = `'ListEmail'` / `'Call'` / custom subtypes.

Component · Agentforce Header (`seFrAgentforceHeader`)

API name: `seFrAgentforceHeader` · **Categories:** Agentforce & AI · **Surfaces:** HomePage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

seFrAgentforceHeader

Home-page header with a floating Astro image and a search/dictation box that forwards the user's question to the standard Agentforce / Einstein panel.

Where to drop it

- Target:** Lightning Home Page
- App Builder label:** `SE_FR` — Agentforce Header

Dependencies

- Static resource named `astro_agentforce` containing the Astro image (PNG).
- The org must have the Agentforce / Einstein utility button available in the app — the component finds the button by its `title` attribute (containing "Agentforce" or "Einstein") and triggers a click.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
<code>speechLocale</code>	String	<code>en-US</code>	BCP 47 locale for the browser's Web Speech Recognition API (<code>fr-FR</code> , <code>es-ES</code> , <code>de-DE</code> , ...).
<code>idlePlaceholder</code>	String	<code>Ask me a question...</code>	Input placeholder when idle.
<code>listeningPlaceholder</code>	String	<code>Listening...</code>	Input placeholder while dictating.

Install

- Create the static resource** (required — otherwise the component fails to compile):
 - Setup → **Static Resources** → *New*.

- Name: astro_agentforce , Cache Control: Public.
- Upload a PNG of Astro (Salesforce mascot). Save.

1. Unzip seFrAgentforceHeader.zip , deploy the LWC bundle.
2. Drop SE_FR – Agentforce Header on the Home page.

Component · Alerts Ribbon (seFrAlertsRibbon)

API name: seFrAlertsRibbon · **Categories:** Account 360° · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Account, Contact, Case, Opportunity, Lead, Order, Contract · **Data mode:** mock · **Mobile-ready:** no · **Apex:** none

SE FR - Alerts Ribbon (seFrAlertsRibbon)

Configurable alerts ribbon. Two complementary sources for the alert list:

- **Rule-driven alerts** (Record Page only) — declarative rules evaluated against the current record's fields.
- **Static alerts** (any page) — always shown, useful for system status banners, demo-mode disclaimers, release announcements.

3 visual variants (banner / solid / minimal), 2 densities (comfortable / compact), 4 severities (info / success / warning / error), optional sticky-on-scroll behavior.

Targets

- lightning__RecordPage
- lightning__HomePage
- lightning__AppPage

Quick start

Drop the component on a record page, paste this in **Rule-driven alerts**:

```
AnnualRevenue<500000|warning||Small account – prioritize upsell|Open opportunities|/lightning/o/Opportunity/list
LastActivityDate isBlank|info||No activity logged in the last 30 days||
Industry=Banking|success||Banking – flag for compliance review||
```

You get 3 stacked banners, color-coded.

Rule grammar

Format (one per line, or comma-separated):

```
<field><op><value>|<severity>|<icon>|<message>|<ctaLabel>|<ctaUrl>
```

TOKEN	DESCRIPTION
<field>	API name of a field on the current SObject (e.g. AnnualRevenue , Industry , LastActivityDate)
<op>	= != > < >= <= contains startsWith endsWith isBlank isNotBlank
<value>	The value to compare against (omitted for isBlank / isNotBlank)
<severity>	info (default) / success / warning / error
<icon>	Optional SLDS icon name. Falls back to a severity-default icon when empty
<message>	The text shown in the banner
<ctaLabel>	Optional CTA button label
<ctaUrl>	Optional CTA URL — relative (/lightning/...) or absolute (https://...)

Static alerts

Format (one per line):

```
<severity>|<icon>|<message>|<ctaLabel>|<ctaUrl>
```

Static alerts ignore the record context. Use them on Home / App pages, or to add demo-mode banners on top of rule-driven ones on a Record page.

Visual variants

ALERTVARIANT	LOOK
banner (default)	Soft pastel background + accent border-left + saturated icon
solid	Saturated background, white text — high-contrast attention grabber
minimal	White background, accent bar only — ultra-sober

Density

DENSITY	BEHAVIOR
comfortable (default)	Full message, wraps to multiple lines
compact	Single line, message truncated with ellipsis

Sticky on scroll

Set `stickyOnScroll = true` to keep the ribbon pinned to the top of the page on scroll. Useful for warning / error severity that shouldn't scroll out of view.

Properties

PROPERTY	DEFAULT	DESCRIPTION
language	fr	fr / en
rulesCsv	–	Rule-driven alerts (Record Page only)
staticAlertsCsv	–	Static alerts (any page)
visualStyle	inline	inline (no card chrome) / card (wrapped in lightning-card with title + count pill)
alertVariant	banner	banner / solid / minimal
density	comfortable	comfortable / compact
cardTitle	–	Override (used when visualStyle = card)
cardIcon	standard:announcement	SLDS icon name (used when visualStyle = card)
hideDismissButton	false	Hide the per-alert dismiss x
maxAlerts	0	Cap (0 = unlimited)
stickyOnScroll	false	Pin the ribbon at the top of the page on scroll

SE benefits

- **No Apex required** — rules and static alerts are configured entirely in App Builder.
- **Schema-safe** — fields referenced by rules are queried via LDS; missing fields silently skip the rule.
- **Demo storytelling** — type the right rule and a banner appears the moment the SE opens the right account ("This account is at risk", "Renewal due in 14 days").

Component · Consent Manager (`seFrConsentManager`)

API name: <code>seFrConsentManager</code> · Categories: Marketing & Data · Surfaces: RecordPage · Objects: Contact, Lead, Account · Data mode: live · Mobile-ready: yes · Apex: none

seFrConsentManager (Consent Manager)

Toggle panel to manage per-channel consent / GDPR opt-in on a record. Each channel binds to a boolean field on the current object; the component loads the current value, flips it on toggle, and saves back via `lightning/uiRecordApi` — no Apex required.

Where to drop it

- **Target:** Lightning Record Page

- **Objects:** Contact (default), Lead, Account — works on any object that has the fields configured in `channelsCsv`.
- **App Builder label:** SE FR – Consent Manager

Apex dependencies

None.

Default channels (zero custom field)

CHANNEL	FIELD	INVERTED?
Email	HasOptedOutOfEmail	✓ (stored as opt-out)
Phone	DoNotCall	✓
WhatsApp	HasOptedOutOfFax	✓ (field repurposed — lets the demo run on a vanilla org)

With these defaults the component deploys on any Contact record page without creating a single custom field.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
cardTitle	String	Contact Preferences & GDPR	Card title
cardIcon	String	standard:task2	Card icon
channelsCsv	String	Email HasOptedOutOfEmail true,Phone DoNotCall true,WhatsApp HasOptedOutOfFax true	One item label
toggleActiveLabel	String	Allowed	Show active label
toggleInactiveLabel	String	Refused	Show inactive label
successMessage	String	Contact preferences updated.	Success message
errorMessage	String	Update failed.	Error message

channelsCsv format

Each channel is three pipe-separated parts, channels separated by commas:

```
<label>|<fieldApiName>|<inverted>
```

- `label` — toggle label shown in the UI.
- `fieldApiName` — the boolean field on the current object.
- `inverted` — `true` when the field stores **opt-out** semantics (e.g. `HasOptedOutOfEmail`, `DoNotCall`). The toggle shows the inverse so that "on" always means "consent given".

Examples:

- Custom opt-in fields: `Email|Email_OptIn__c|false,SMS|SMS_OptIn__c|false`
- Mix of standard and custom: `Email|HasOptedOutOfEmail|true,SMS|SMS_OptIn__c|false,Mail|HasOptedOutOfMail|true`

Install

1. Unzip `seFrConsentManager.zip`, deploy the LWC bundle.
2. If you use custom opt-in/opt-out fields, make sure they exist on the object and the running user has edit access.
3. Drop `SE FR – Consent Manager` on a Contact / Lead / Account record page and set `channelsCsv` to match the customer's data model.

Known caveats

- **HasOptedOutOfFax re-purposed for WhatsApp** in the defaults — purely a demo convenience to avoid requiring a custom field. Replace with a real `WhatsApp_OptIn__c` in production demos if the customer has one.
- The component needs the running user to have **edit** access to each backing field; otherwise `updateRecord` fails and the toggle reverts.

Origin

Genericized from the `krysConsentManager` Krys demo component.

Component · Contact Card (`seFrContactCard`)

API name: `seFrContactCard` · **Categories:** Account 360°, Agentforce & AI · **Surfaces:** RecordPage · **Objects:** Contact, Account, Case, Opportunity, Order, Lead · **Data mode:** hybrid · **Mobile-ready:** yes · **Apex:** `SE_FR_ContactCardController`, `SE_FR_ImageFileController`, `SE_FR_ImageFileController` (shared)

SE FR - Contact Card

Original author: Charly Ansel <charly.ansel@salesforce.com>

Maintained in library by: Lionel Braun

Genericized / library-integrated: 2026-05-05

Visual contact card with an animated-waves background, avatar, name / email / phone, mailing address and up to 3 configurable gauges. Auto-resolves the Contact Id from the current record page (Contact → self, Account → Person/primary Contact, Case/Opportunity/Order → `ContactId` , Lead / custom objects → `Contact__c`).

Why SEs love it

- **Portrait-style card** — signature animated waves background (toggleable) makes the card stand out on a record page.
- **Works out-of-box** — schema-safe Apex: every optional field (image URL, customer ID, gauges) is skipped silently if absent.
- **Same upload pattern as Record Highlights** — `imageMode=file` stores the avatar as a standard File on the Contact, click to replace. No custom schema required.
- **Up to 3 gauges** configurable at will (label + field API name + icon).
- **Optional Einstein prompt summary** — off by default; when enabled, a "Summarize" button runs a chosen Prompt Template inline.

Properties (highlights)

PROPERTY	DEFAULT	DESCRIPTION
<code>language</code>	<code>fr</code>	<code>fr</code> or <code>en</code> .
<code>cardTitle</code>	"Contact"	Override only if needed.
<code>imageMode</code>	<code>field</code>	<code>field</code> (URL in a field on Contact) or <code>file</code> (click to upload, same logic as Record Highlights).
<code>imageFieldApiName</code>	<code>SD0_Cust360_Contact_Picture_URL__c</code>	Image URL field when <code>imageMode=field</code> . Schema-safe.
<code>showCustomerId</code> / <code>customerIdFieldApiName</code>	<code>false</code> / <code>SD0_Cust360_Id__c</code>	Extra "ID" line.
<code>gauge1Label</code> / <code>gauge1FieldApiName</code> / <code>gauge1Icon</code>	<code>Churn risk</code> / <code>SD0_Cust360_ChurnRisk__c</code> / <code>utility:warning</code>	Primary gauge.
<code>gauge2*</code> / <code>gauge3*</code>	(empty)	Up to 2 additional gauges, all optional.
<code>showWaves</code>	<code>false</code>	Animated wave shapes in the background.
<code>isDarkBackground</code> / <code>backgroundColor</code> / <code>backgroundImageUrl</code>	<code>false</code> / <code>—</code> / <code>—</code>	Look & feel.
<code>waveColorOne</code> / <code>waveColorTwo</code>	<code>greys</code>	Colors of the two waves.
<code>enablePromptSummary</code>	<code>false</code>	Turn on to show a "Summarize" button.
<code>promptTemplateApiName</code> / <code>promptInputApiName</code> / <code>autoPromptOnLoad</code>	<code>—</code> / <code>Input:Contact</code> / <code>false</code>	Einstein Prompt Template settings when the summary is enabled.

Data enrichment prerequisites

- Out-of-box works on any Contact with the standard fields (FirstName, LastName, Email, Phone, MailingAddress).

- For the image to show via `imageMode=field`, the Contact must have the SDO Cust360 picture field populated (SDO-specific) OR the SE can switch to `imageMode=file` and upload an image manually.
- For the churn gauge to show, the Contact must have a value in `SD0_Cust360_ChurnRisk__c` (0-100). Otherwise the gauge is silently hidden.
- The Einstein prompt summary requires an existing Prompt Template in the org with the right input name.

Apex dependencies

- `SE_FR_ContactCardController` — Contact Id resolver, schema-safe Contact fetch, Einstein prompt wrapper.
- `SE_FR_RecordHighlightsController` — shared with Record Highlights for the File-based image pattern (only used when `imageMode=file`).

Credit

The original design (animated waves, avatar layout, gauge + Einstein prompt) comes from Charly Ansel's `canContactCard` bundle. This library version is a genericized, bilingual, schema-safe rewrite that merges the parent/child pair into a single component and aligns naming + conventions with the `SE_FR` library. The prompt logic is preserved but gated off by default.

Component · Contacts Carousel (`seFrContactsCarousel`)

API name: `seFrContactsCarousel` · **Categories:** Account 360° · **Surfaces:** RecordPage · **Objects:** Account · **Data mode:** live · **Mobile-ready:** no · **Apex:** `SE_FR_ContactsCarouselController`

seFrContactsCarousel (Contacts Carousel)

B2B — Horizontal carousel of the Contacts linked to the current Account. Each card shows an avatar (photo or initials fallback), name, title, an optional **role badge** (Champion / Detractor / DMU) and Email / Call quick actions. Bilingual EN / FR.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account
- **App Builder label:** `SE FR – Contacts Carousel`

Apex dependency

`SE_FR_ContactsCarouselController.getContacts(accountId, limitCount, orderBy)`.

Properties

NAME	DEFAULT	DESCRIPTION
<code>language</code>	<code>en</code>	<code>en</code> or <code>fr</code> .
<code>cardTitle</code>	—	Override the default.
<code>limitCount</code>	24	Max Contacts fetched (1–100).
<code>orderBy</code>	<code>LastActivityDate DESC NULLS LAST</code>	Whitelisted: <code>LastActivityDate DESC NULLS LAST</code> / <code>Name ASC</code> / <code>CreatedDate DESC</code> / <code>Title ASC NULLS LAST</code> .
<code>visibleCount</code>	4	Cards shown per page. Arrows paginate by this amount.
<code>badgesCsv</code>	—	Per-contact badge overlay. Format: <code>Eliott Mercier=Champion #2e844a,Mathieu Bernard=Detractor #ba0517</code> . Match is case-insensitive on <code>Contact.Name</code> .
<code>hideNewContactButton</code>	<code>false</code>	

Install

1. Deploy `classes/SE_FR_ContactsCarouselController.cls`.
2. Unzip `seFrContactsCarousel.zip`, deploy the LWC bundle.
3. Drop `SE FR – Contacts Carousel` on an Account record page.

Data enrichment prerequisites

- Contacts should have **Title** and **Department** filled in for the card to look complete. Blank fields display an empty line.
- `Contact.PhotoURL` is a **read-only standard field** populated automatically from the Contact's Chatter profile photo. It cannot be set via DML. Contacts without a Chatter photo will show **initials on a colored background** — the component is designed for that and it looks clean.
- For the **role badges** to appear, populate the `badgesCsv` property with the names exactly as they appear in `Contact.Name`. Mismatches are silently ignored.
- Best demos have at least **4-6 Contacts on the Account** with distinct titles (C-level, manager, user champion, IT...).

Component · Customer Orders (`seFrCustomerOrders`)

API name: `seFrCustomerOrders` · **Categories:** Account 360° · **Surfaces:** RecordPage · **Objects:** Account, Contact · **Data mode:** live · **Mobile-ready:** no · **Apex:** `SE_FR_CustomerOrdersController`

seFrCustomerOrders (Customer Orders)

B2B / B2C — Lists the orders linked to an Account or a Contact. Two blocks:

1. **Last order** — full detail card of the most recent order (number, status, amount, effective date, line items with product images), inspired by `seFrOrderSummary` but **read-only** (no replace / delete / ERP submit — this panel is about history).
2. **Order history** — compact list of the previous orders with **Search** (by order number), **Sort**, optional **Status filter** and a **View all** link.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Contact
- **App Builder label:** SE FR – Customer Orders

What "linked to a customer" means

When placed on an **Account** page, the component shows `Order.AccountId = recordId`.

When placed on a **Contact** page, the component is exhaustive: the union of

- `BillToContactId = contactId`
- `ShipToContactId = contactId`
- `Contact__c = contactId` (only if the custom lookup exists on Order)
- `AccountId = contact.AccountId` (orders of the contact's account)

This way, a contact linked to a bakery's Account also sees the orders placed by the bakery itself, not just orders where the contact is named explicitly.

Apex dependency

`SE_FR_CustomerOrdersController.getCustomerOrders(recordId, objectApiName, limitCount, statusFilter, sortBy, searchTerm, productImageFieldApiName)` — bundled here in `classes/`.

Returns:

```
{
  "latest": { / OrderDetail with line items / },
  "history": [ / OrderSummary[] excluding the latest / ],
  "totalCount": 42
}
```

Actions

- **New order** — opens the standard Order new form, pre-filling `AccountId` when we can resolve it (from the current Account page or from the latest order on Contact page).
- **Refresh** — re-runs the Apex wire.
- **Search** — case-insensitive substring match on `OrderNumber`.

- **Sort** — Date (new/old), Amount (high/low), Order number (A-Z / Z-A).
- **Status picker** — visible only when `statusFilter` is populated; lets the SE narrow the list on-page.
- **View all** — navigates to the Account's Orders related list on Account pages, or the Order object home on Contact pages. Hidden if we already show everything.

Properties (App Builder)

NAME	TYPE	DEFAULT	DESCRIPTION
language	String	en	en or fr .
cardTitle	String	—	Override the dictionary default (<code>Orders</code> / <code>Commandes</code>).
cardIcon	String	standard:orders	
historyLimit	Integer	10	Server-side LIMIT (1–50).
currencyCode	String	USD	ISO 4217.
localeTag	String	en-US	Used for date formatting.
statusFilter	String	—	CSV whitelist of <code>Order.Status</code> values. When set, shows a status dropdown in the toolbar.
defaultSort	String	EffectiveDate DESC	Whitelisted.
productImageFieldApiName	String	Image_URL__c	Schema-safe.
productImageFallbackUrl	String	—	Used when the product field is empty / absent.
hideNewOrderButton	Boolean	false	
hideViewAllLink	Boolean	false	

Install

1. Deploy `classes/SE_FR_CustomerOrdersController.cls` .
2. Unzip `seFrCustomerOrders.zip` , deploy the LWC bundle.
3. Drop `SE FR – Customer Orders` on an Account or Contact record page.
4. Adjust the `historyLimit` , `statusFilter` , `defaultSort` , `language` in App Builder as needed.

Data enrichment prerequisites

- On an **Account** page, any Order linked via `Order.AccountId` is picked up — no extra work needed if the Account already has orders.
- On a **Contact** page, the query unions `BillToContactId` , `ShipToContactId` , `Contact__c` (if the custom lookup exists on the org), and `AccountId = contact.AccountId` . If a Contact has no direct link and no parent Account with orders, the empty state shows the "Create the first order" CTA — intentional.
- For the **line-item detail** on the latest order card to show images, `Product2` records must have an image URL in the `Image_URL__c` field (or the field you configure via `productImageFieldApiName`). Fallback URL available through `productImageFallbackUrl` when none of the products carry an image.

Known caveats

- On an **Account** page, the "View all" button uses the standard "Orders" related list. If the Account page layout hides that related list, the navigation still works — Salesforce routes to the related-object view.
- `Order.AccountNumber` and custom fields are not fetched by default. Use the standard Order page to see them.
- Product images rely on a `Product2.Image_URL__c` -style custom field. Configure `productImageFieldApiName` or `productImageFallbackUrl` for your data model.

Component · Customer Sales Summary (`seFrCustomerSalesSummary`)

API name: `seFrCustomerSalesSummary` · **Categories:** Account 360° · **Surfaces:** RecordPage · **Objects:** Contact, Account · **Data mode:** mock · **Mobile-ready:** no · **Apex:** none

seFrCustomerSalesSummary (Customer Sales Summary)

B2C-leaning customer-level sales summary for a **Contact / Person Account / Account** record page. Three KPI tiles + three bar-chart columns (by **Category / Brand / Store**).

This complements `seFrRevenueDashboard` (which is B2B, Account-centric, 3-year revenue chart). Here the angle is *"what did this shopper buy and where"* — useful on retail demos with store networks and multi-brand portfolios.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Contact, Account (works with Person Account since Person Account pages use the Account record page)
- **App Builder label:** SE FR – Customer Sales Summary

Apex dependency

None — demo data provided via App Builder properties.

Properties

Same CSV-driven shape as before — see the meta.xml for the full list. Formats:

- `categoriesCsv / brandsCsv` — `label|percent|color`
- `storesCsv` — `label|visits|barWidthPercent|color`

Origin

Renamed from `seFrRetailSalesDashboard` (v2.3 → v2.4). The old component is kept in the library as deprecated for backwards compat.

Component · Field Sales - Rep Home (`seFrFieldRepHome`)

API name: `seFrFieldRepHome`

· **Categories:** Dashboards & KPIs

· **Surfaces:** AppPage, HomePage

· **Objects:** Any

· **Data mode:** hybrid

· **Mobile-ready:** no

· **Apex:** `SE_FR_FieldSalesController`

seFrFieldRepHome (Field Sales — Rep Home)

B2B — Home / App page for a **field sales rep**. Greeting, 4 KPI tiles, priority accounts (dynamic), hot leads (dynamic), product-penetration bars and campaign calendar.

Where to drop it

- **Target:** Lightning Home Page, App Page (**not Record**)
- **App Builder label:** SE FR – Field Sales – Rep Home

Apex dependency

`SE_FR_FieldSalesController` — now exposes full filter arguments:

- `getPriorityAccounts(recordTypeName, ownerScope, orderBy, limitCount)`
- `getMyLeads(rating, ownerScope, limitCount)`

Filters (App Builder)

PROPERTY	DEFAULT	NOTES
<code>accountRecordType</code>	<code>SD0_Account_Simple</code>	Standard Salesforce SDO B2B record type. Leave empty for all types.
<code>accountOwnerScope</code>	<code>mine</code>	'mine' = running user's accounts; 'all' = any owner. Use 'all' on fresh demo orgs.
<code>accountOrderBy</code>	<code>Name</code>	Whitelisted: <code>Name</code> <code>LastActivityDate DESC</code> <code>NULLS LAST</code> <code>AnnualRevenue DESC</code> <code>NULLS LAST</code> <code>CreatedDate DESC</code> .
<code>accountLimit</code>	<code>6</code>	Up to 50.
<code>leadRating</code>	<code>Hot</code>	<code>Hot</code> <code>Warm</code> <code>Cool</code> <code>Any</code> .
<code>leadOwnerScope</code>	<code>mine</code>	
<code>leadLimit</code>	<code>6</code>	

Styling

Shares the SE_FR palette declared at the top of the CSS (brand blue, SLDS success green, warning orange, error red). KPI tile top border and value color map 1:1 to the palette for a homogeneous look across the Home page.

Origin

Renamed from `seFrFieldSalesDashboard` (v2.3 → v2.4). The old bundle is kept in the library as deprecated.

Component · Files Gallery (`seFrFilesGallery`)

API name: `seFrFilesGallery` · Categories: Transverse · Surfaces: RecordPage · Objects: Any · Data mode: live · Mobile-ready: yes · Apex: `SE_FR_FilesGalleryController`

seFrFilesGallery (Files Gallery)

B2B / B2C — Visual gallery of the files linked to the current record. Image thumbnails (via the standard Salesforce rendition endpoint), doctype icons for non-images (PDF, Word, Excel...), click-to-preview and a drag-and-drop upload area. Bilingual EN / FR.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** any record type — the component queries `ContentDocumentLink` by `LinkedEntityId`.
- **App Builder label:** SE FR – Files Gallery

Apex dependency

`SE_FR_FilesGalleryController.GetFiles(recordId, limitCount)`. Queries the latest `ContentVersion` for each document linked to the record.

Properties

NAME	DEFAULT	DESCRIPTION
<code>language</code>	<code>en</code>	<code>en</code> or <code>fr</code> .
<code>cardTitle</code>	<code>—</code>	Override the default.
<code>limitCount</code>	<code>20</code>	Server-side LIMIT (1–100).
<code>hideUploadButton</code>	<code>false</code>	

Install

1. Deploy `classes/SE_FR_FilesGalleryController.cls`.
2. Unzip `seFrFilesGallery.zip`, deploy the LWC bundle.
3. Drop `SE FR – Files Gallery` on any record page.

Data enrichment prerequisites

- The record must have **at least one** `ContentDocumentLink` attached. On a fresh SDO, most records have none — the component shows an empty state.
- **Images** (PNG / JPG / GIF / WEBP) display as thumbnails via the rendition endpoint. Non-images show a doctype icon and the filename — the thumbnail slot is not used.
- **Preview** uses the standard `filePreview` named page; behaviour matches Salesforce Files.

Component · Kanban Board (`seFrKanbanBoard`)

API name: `seFrKanbanBoard` · Categories: Sales Productivity · Surfaces: AppPage, HomePage, RecordPage · Objects: Any · Data mode: live · Mobile-ready: no · Apex: `SE_FR_KanbanBoardController`

SE FR - Kanban Board (`seFrKanbanBoard`)

Generic kanban board for **any whitelisted SObject** (Case · Opportunity · Lead · Order · Task · Account). Drag-and-drop updates the group-by field on the record. Auto-detects scoping when placed on a Record Page.

Targets

- lightning__HomePage
- lightning__AppPage
- lightning__RecordPage

Quick start

Drop on a Home Page — defaults to **Case · group by Status · display Subject**:

```
subjectApiName = Case
groupByField   = Status
displayField   = Subject
filterClause   = IsClosed = false
```

You get a kanban with one column per Case status, draggable cards.

On a Record Page

Set `recordScopeField` to a lookup field on the queried object that points at the host record's Id:

HOST PAGE	COMMON SCOPE FIELDS
Account	AccountId (works on Case, Opportunity, Order)
Contact	ContactId (Case), WhoId (Task)
Case	ParentId (sub-cases)

Leave empty to disable scoping (kanban shows all matching records, not bound to the host).

Properties

PROPERTY	DEFAULT	DESCRIPTION
language	fr	fr / en
cardTitle	–	Override
cardIcon	standard:kanban	SLDS icon
subjectApiName	Case	Whitelisted object to query
groupByField	Status	Picklist field used to form the columns
displayField	Subject	Field shown as the card title
secondaryField	Priority	Secondary chip / detail on the card
amountField	–	Currency field summed per column (e.g. Amount on Opp)
filterClause	IsClosed = false	Raw SOQL WHERE fragment (injected as-is)
recordScopeField	AccountId (Record Page)	Lookup field tying queried records to the host record
limitCount	100	Server-side LIMIT (1-500)
maxPerColumn	6	Cards shown before a "Show all (N)" link
disableDragDrop	false	Off by default — drag-drop updates the group-by field
currencyCode	EUR	Used by the column total formatter
localeTag	en-US	Locale used by Intl.NumberFormat

Drag & drop

By default, dropping a card in another column issues a `LightningRecordEditForm` save on the group-by field. Toggle `disableDragDrop = true` if you want the kanban to be read-only (e.g. demo videos, screenshots).

Whitelisted SOjects

The component restricts itself to a curated set to stay schema-safe across orgs:

Case · Opportunity · Lead · Order · Task · Account

To extend the list, edit the Apex `SE_FR_KanbanBoardController` whitelist + add a `<targetConfig>` row in the meta.xml.

SE benefits

- **One component, 6 SObjects** — same kanban for "my open cases" (Home), "team pipeline" (App Page), "Account-scoped opportunities" (Record Page).
- **Drag-drop status update** — visually striking demo moment for service / sales workflows.
- **Auto column detection** — picklist values define the columns automatically; no manual config per status.
- **Currency-aware totals** — set `amountField = Amount` on Opportunity and each column displays its sum in EUR / USD / whatever locale you configure.

Component · KPI Launcher (`seFrKpiLauncher`)

API name: `seFrKpiLauncher` · **Categories:** Dashboards & KPIs · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

seFrKpiLauncher (KPI Launcher)

Configurable grid of 3 to 6 clickable KPI tiles. Each tile accepts a label, value, sublabel, SLDS icon, color and link. Empty labels hide the tile — display anywhere from 3 to 6 tiles without code changes.

Where to drop it

- **Target:** Lightning Home Page / App Page / Record Page
- **App Builder label:** SE FR – KPI Launcher

Apex dependency

None (all values are static, driven by App Builder properties).

Properties

Each of the 6 tiles exposes the same 6 properties. Leave `kpiNLabel` empty to hide the corresponding tile.

PROPERTY SUFFIX	TYPE	DESCRIPTION
Label	String	Main tile title. Empty hides the tile.
Value	String	Big number / percentage / text shown on the tile.
Sublabel	String	Small caption below the value.
Icon	String	SLDS icon reference, e.g. <code>standard:account</code> , <code>standard:event</code> , <code>utility:einstein</code> . See SLDS Icons .
Color	String	Hex color driving the tile's accent + hover state. Defaults vary per tile.
Link	String	Destination on click. Accepts Lightning URLs (<code>/lightning/o/Lead/list?filterName=Recent</code>), nav items (<code>/lightning/n/maps__Maps</code>) or absolute URLs (<code>https://...</code>).

Plus:

- `cardTitle` (String, optional) — when set, wraps the grid in a standard `lightning-card` matching every other SE_FR component's title style. Leave empty to render the raw grid (same look as before).
- `cardIcon` (String, default `standard:metrics`) — icon next to the card title when `cardTitle` is set.

Tile behavior

- Tiles without a link stay visually clickable but do nothing on click.
- Tiles with `https://...` links open in a new tab; internal paths navigate via standard Lightning navigation.
- Hover effect inverts the color — background turns to the tile's `Color` , text turns white.
- Grid is responsive (`repeat(auto-fit, minmax(160px, 1fr))`) — tiles reflow on narrow containers.

Install

1. Unzip `seFrKpiLauncher.zip` , deploy the LWC bundle.
2. Drop `SE FR – KPI Launcher` on a Home, App or Record page.
3. Configure each KPI in App Builder. Start by filling KPI 1–3; add KPI 4–6 if needed.

Component · Metric Tile (`seFrMetricTile`)

API name: `seFrMetricTile` · **Categories:** Dashboards & KPIs, Marketing & Data · **Surfaces:** `AppPage`, `HomePage`, `RecordPage` · **Objects:** Any · **Data mode:** `mock` · **Mobile-ready:** yes · **Apex:** none

SE FR - Metric Tile (`seFrMetricTile`)

Single-metric tile with a configurable inline trend chart. **4 chart styles** (line / area / bar / mini-donut), optional **comparison series**, **target line**, and **currency formatting** via `Intl.NumberFormat` .

Designed to stack horizontally on a Home Page or App Page (3-4 tiles per row), or to sit standalone on a Record Page sidebar.

Targets

- `lightning__HomePage`
- `lightning__AppPage`
- `lightning__RecordPage`

The 4 chart styles

CHARTSTYLE	VISUAL	USE CASE
line (default)	Smooth line + last-point dot	Trend curve, no surface emphasis
area	Same as line + filled area below	Volume / surface emphasis
bar	Vertical bars with rounded tops	Discrete monthly values
mini-donut	Radial gauge filling <code>currentValue</code> / <code>targetValue</code>	Goal completion / quota / health %

Quick start

Drop on a Home Page, no config — you get a sample 12-month revenue curve with a green `+14,2%` trend badge.

For a real metric:

```
metricLabel      = "Pipeline"
currentValue     = 1250000
currencyCode     = "EUR"
seriesJson      = [820000, 880000, 950000, 1020000, 1080000, 1130000, 1180000, 1250000]
chartStyle      = "area"
trendDisplay    = "+12,8%"
```

For a goal-completion donut:

```
metricLabel      = "Quarterly target"
currentValue     = 850000
targetValue      = 1000000
currencyCode     = "EUR"
chartStyle       = "mini-donut"
showTargetLabel  = true
```

For a forecast vs. actual line:

```
seriesJson       = [...actual]
secondarySeriesJson = [...forecast]
secondarySeriesColor = "#747474"
chartStyle       = "line"
```

Properties

Headline

PROPERTY	DEFAULT	DESCRIPTION
language	fr	fr / en
cardTitle	–	Override
cardIcon	standard:metrics	SLDS icon
hideCardTitle	false	Render bare tile (no card chrome) — useful when stacking
metricLabel	dictionary default	Small label above the headline
currentValueDisplay	–	Manual text override (wins over numeric)
currentValue	–	Numeric value, auto-formatted via Intl.NumberFormat
currencyCode	EUR	ISO 4217

Chart

PROPERTY	DEFAULT	DESCRIPTION
chartStyle	line	line / area / bar / mini-donut
seriesJson	sample 12-month curve	JSON array of numbers
secondarySeriesJson	–	Optional comparison series (dashed line)
secondarySeriesColor	#747474	Secondary series color
targetValue	–	Horizontal target line on line/area/bar; denominator on mini-donut
targetLineColor	#FE9339	Target line color
showTargetLabel	false	Show "Target XX €" chip next to the metric label

Y-axis scaling

PROPERTY	DEFAULT	DESCRIPTION
scalingMode	auto	auto (data min/max) / from-zero / fixed
yMin	–	Used when scalingMode = fixed
yMax	–	Used when scalingMode = fixed

Visual

PROPERTY	DEFAULT	DESCRIPTION
accentColor	#0176d3	Primary chart color
donutTrack	#E5E5E5	Mini-donut background ring
height	70	Chart inner height (px)
width	0 (auto)	Override viewBox width
trendDisplay	+14,2%	Sign drives badge color

SE benefits

- **No Apex required** — pure props-driven, configured entirely in App Builder.
- **Compact + dense-dashboard ready** — set hideCardTitle = true and stack 4 tiles in a row of a Home Page, all aligned.
- **AI/forecast demos** — a secondary dashed line is the simplest way to overlay "actuals vs. forecast" without building a real chart component.
- **Goal-completion mini-donut** — visually striking for "we're 85% to target" demo moments without needing a real Performance Goal in the org.

Design rationale

Pure SVG, no chart library — keeps the bundle ~3 KB and avoids Locker / CSP issues. All animations are CSS-driven (path-fade, bar-grow, donut stroke-dashoffset transition).

Component · My Events (seFrMyEvents)

API name: seFrMyEvents · **Categories:** Sales Productivity · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_AgendaController, SE_FR_AgendaController (shared)

seFrMyEvents (My Day — Events timeline)

Today's calendar for the running user, as a **vertical timeline** sized to fit a sidebar column. Kept compact on purpose: auto-trims empty hours, shows only 3 upcoming items, and lays overlapping events side-by-side (Google Calendar style) instead of stacking them on top of each other.

Where to drop it

- **Targets:** Home Page, App Page, Record Page
- **App Builder label:** SE FR – My Events

Apex dependency

SE_FR_AgendaController.getMyEvents(daysAhead, maxRows) — shared Apex class, standard fields only.

Features

- **Today timeline** — each non-all-day event positioned proportionally on a configurable hour axis (default 08:00→20:00). Clicking an event opens its record.
- **Auto-trim** (default ON) — the timeline starts `autoTrimPaddingMin` minutes before the first event and ends the same padding after the last event (clamped between `startHour` and `endHour`, default padding 30min). Short days feel short, long days still fit. Disable via `disableAutoTrim` to render the full `[startHour, endHour]` range. When the day has no non-all-day events, the timeline block is not rendered at all.
- **Overlap handling** — overlapping events are placed side-by-side into columns (1/N width each) so nothing is hidden behind another event.
- **Short events** — < 30 min visible duration renders in a compact layout (title only, no footer) so they don't spill out of their block.
- **Now line** — a red horizontal line + `HH:MM` • `now` label, refreshed every 60 seconds. Auto-trim always keeps the now-line in the visible range when today's time falls between `startHour` and `endHour`.
- **"in N min" badge** — shown on events starting within 30 minutes, or "now" on events currently running.
- **All-day band** — compact pill band above the timeline for all-day events.
- **Colour-coded types** — each event gets a left border + tint derived from `Event.Type` via a CSV map (fallback to "Other").
- **Join button** — if `Location` or `Description` contains a Zoom / Teams / Meet / WebEx URL, a Join button opens it in a new tab. Toggle via `hideJoinButton`.
- **Upcoming list** — next 3 future-day events (default `daysAhead = 2`) in a compact list under the timeline, grouped by day label.
- **Refresh / New event** icons in the header.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
cardTitle	String	My Day	Card title.
cardIcon	String	standard:event	Card icon.
startHour	Integer	8	Earliest hour shown when auto-trim is off or can't narrow further.
endHour	Integer	20	Latest hour shown (same rule).
disableAutoTrim	Boolean	false	Auto-trim is ON by default. Turn on to always render the full <code>startHour</code> → <code>endHour</code> window.
autoTrimPaddingMin	Integer	30	Empty-hour margin kept before the first event and after the last event when auto-trim is on. Set to 0 to crop exactly to the events.
daysAhead	Integer	2	Days to fetch (today = 1).
maxEvents	Integer	10	Server-side LIMIT.
localeTag	String	en-US	Time formatting.
typeColorsCsv	String	see meta.xml	Type <code>#hex</code> entries, comma-separated.
hideNowLine	Boolean	false	Hide the red "now" line.
hideJoinButton	Boolean	false	Hide the Join button even when a meeting URL is detected.
emptyStateMessage	String	Nothing scheduled today.	Shown when no event falls in the window.

Install

1. Deploy `SE_FR_AgendaController` (bundled in `classes/` here; also lives in `_shared_apex/`).
2. Unzip `seFrMyEvents.zip`, deploy the LWC bundle.
3. Drop `SE FR – My Events` on the right column of a Home / App / Record page.

Prerequisites — user timezone

`Date.today()` in Apex and `TODAY / THIS_WEEK` SOQL filters resolve against the **running user's timezone**, not the org timezone. Most Salesforce SDOs ship with the org set to `America/Los_Angeles` — if your user also inherits that timezone, a 09:00 Paris meeting stored as `07:00Z` will appear as `00:00` and today's events may be picked up under yesterday or tomorrow.

Before using the component, make sure **your user's timezone matches your local time**:

- Setup → **Personal Information** → *Time Zone* → pick your local value (e.g. (GMT+01:00) Central European Time (Europe/Paris) in winter / (GMT+02:00) Central European Summer Time (Europe/Paris) in summer).
- Save, refresh the tab.

You don't need to change the **org** timezone (Setup → Company Information) — that has much broader side-effects (Business Hours, Reports, audit trails). Changing only the user timezone is the standard SE practice on a shared SDO.

Type toggles (in-UI "calendars")

When events carry an `Event.Type` value (Call / Meeting / Demo / Training / Other in the default palette), the component shows one coloured chip per distinct type present today. **Click a chip to mute / unmute that type** in the timeline — handy when too many auto-created events clutter the day. Muted chips remain visible (greyed + struck-through) so you can re-enable them.

Use `typesFilterCsv` on the meta.xml to hard-scope the component to a subset of types (e.g. `Meeting,Demo`) before the in-UI toggles apply — great to hide a type globally on a shared page.

Known caveats — external calendars (Gmail / Outlook)

Salesforce surfaces Gmail / Outlook events in the **standard calendar** via **Einstein Activity Capture (EAC)**, which stores them in a private dataset that's **not queryable via SOQL** (`Event` only contains records created inside Salesforce). This means the component cannot show EAC-synced meetings — no LWC on the platform can. To still have external meetings visible here, either:

- manually create the meeting as a Salesforce `Event`, or
- use the Lightning for Outlook / Gmail "log email / event" action which creates a real `Event` record.

Other caveats

- Events longer than the visible timeline are clipped to the effective bounds (the block fills from the visible portion only).
- Join-URL detection is a regex over `Location + Description`; custom URLs won't be detected.
- The "now" line refreshes every 60 seconds. If the component sits hidden in a tab for a long time, it picks up the next minute on re-render.

Component · My Tasks (`seFrMyTasks`)

API name: `seFrMyTasks` · **Categories:** Sales Productivity · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** live · **Mobile-ready:** yes · **Apex:** `SE_FR_AgendaController`, `SE_FR_AgendaController` (shared)

seFrMyTasks (My Tasks)

Compact "My Tasks" panel designed for a **sidebar column** on a Home / App / Record page. Reads the running user's tasks, auto-groups them by due date, lets the user complete a task with a click.

Where to drop it

- **Targets:** Home Page, App Page, Record Page
- **App Builder label:** `SE FR – My Tasks`

Apex dependency

`SE_FR_AgendaController.getMyTasks(filter, maxRows)` — shared Apex class, standard fields only.

Features

- **Filter dropdown** in the header — Today / Mine / Overdue / Upcoming / Completed. Label shows the current filter.
- **Auto-grouping** — rows are bucketed client-side into Overdue / Today / Tomorrow / This week / Later / No date / Completed. Empty buckets are hidden.
- **Interactive checkbox** — clicking the checkbox flips `Task.Status` between Completed and In Progress via `updateRecord`, then refreshes the list (so the task moves groups). Fixes the v2.x bug where the checkbox was always disabled.
- **Urgent flag** — High-priority or overdue tasks show a red flag icon and red date.
- **" + New Task "** button in the header opens the standard new-task page.
- **"View all "** button navigates to the Task home list.
- **Optional quick actions** (off by default) — on hover, shows Email and Log-a-Call buttons. Turn on with `showQuickActions`.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
<code>cardTitle</code>	String	My Tasks	Card title.
<code>cardIcon</code>	String	<code>standard:task</code>	Card icon.
<code>defaultFilter</code>	String	Upcoming	Initial filter. One of the <code>filterOptionsCsv</code> values.
<code>filterOptionsCsv</code>	String	<code>Today,Mine,Overdue,Upcoming,Completed</code>	Filter dropdown entries.
<code>maxTasks</code>	Integer	10	Server-side row LIMIT (1–50).
<code>localeTag</code>	String	en-US	Used to format the due date.
<code>showQuickActions</code>	Boolean	false	Reveals Email / Log-a-Call icons on row hover.
<code>emptyStateMessage</code>	String	No tasks for this filter.	Shown when the filter returns no row.

Install

1. Deploy `SE_FR_AgendaController` (bundled in `classes/` here; also lives in `_shared_apex/` if you need it for other components).
2. Unzip `seFrMyTasks.zip`, deploy the LWC bundle.
3. Drop `SE FR – My Tasks` on the right column of a Home / App / Record page.

Prerequisites — user timezone

The Today / Overdue / Upcoming filters use SOQL date literals (`TODAY` , `<` , `>=`) that resolve against the **running user's timezone**. Most Salesforce SDOs ship with the org set to `America/Los_Angeles` — if your user also inherits that timezone, tasks due today in Paris may be bucketed as yesterday or tomorrow.

Before using the component, set **your user's timezone to your local value**:

- Setup → **Personal Information** → *Time Zone* → pick your local value (e.g. (GMT+01:00) Central European Time (Europe/Paris) in winter / (GMT+02:00) Central European Summer Time (Europe/Paris) in summer).
- Save, refresh the tab.

You don't need to change the **org** timezone — only the user timezone.

Known caveats

- "Reopen" sets `Status = 'In Progress'`. If your org's Task status picklist doesn't include that value, change it in `handleToggleComplete`.
- Quick actions rely on `Contact.SendEmail` (Who) and `Global.LogACall` — both are present out of the box on standard orgs.

Component · Nearby Accounts Map (`seFrNearbyAccountsMap`)

API name: `seFrNearbyAccountsMap` · **Categories:** Geo & Field · **Surfaces:** `AppPage`, `HomePage` · **Objects:** Any · **Data mode:** live · **Mobile-ready:** yes · **Apex:** `SE_FR_NearbyAccountsController`, `SE_FR_NearbyAccountsController` (shared)

seFrNearbyAccountsMap

Interactive map showing nearby accounts from a configurable origin point. Uses the standard `lightning-map` with custom pin styling. By default, the component **uses the browser's geolocation** so the map centers on wherever the SE currently is, and silently falls back to a configurable lat/lng if the browser denies the permission or is on HTTP.

Where to drop it

- **Target:** Lightning Home Page / App Page
- **App Builder label:** SE FR – Nearby Accounts Map

Apex dependency

- `SE_FR_NearbyAccountsController.getNearbyAccounts(limitCount, recordTypeName)` — located in `_shared_apex/` .
- Behavior: first tries accounts owned by the running user; if that set is empty, falls back to accounts of any owner so the component still shows data on a fresh demo org.

Origin — auto vs manual

ORIGINMODE	BEHAVIOR
auto (default)	Calls <code>navigator.geolocation.getCurrentPosition()</code> in <code>connectedCallback</code> . Browser prompts the user once per origin. Cached position up to 5 min old is reused. Requires HTTPS (Salesforce is HTTPS). On denial / timeout / unsupported browser, falls back silently to <code>originLatitude</code> / <code>originLongitude</code> .
manual	Always uses the provided <code>originLatitude</code> / <code>originLongitude</code> .

This means the default deployment works out of the box for any SE: the first time they open the page, they approve the browser prompt, and the map centers on them.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
<code>cardTitle</code>	String	Nearby Accounts	
<code>listSubtitle</code>	String	Accounts and prospects nearby	Shown in the map's list view.
<code>limitCount</code>	Integer	10	Max accounts queried from Apex.
<code>recordTypeName</code>	String	—	Optional. <code>RecordType DeveloperName</code> on Account (leave empty for all).
<code>originMode</code>	String	auto	<code>auto</code> (browser geolocation, fallback to lat/lng) or <code>manual</code> .
<code>originLatitude</code>	String	48.859215	Fallback / manual latitude (decimal degrees). Defaults to central Paris (11e).
<code>originLongitude</code>	String	2.379175	Fallback / manual longitude.
<code>originLabel</code>	String	My location	Title of the origin marker.
<code>priorityFirstMarker</code>	Boolean	false	If true, the first account pin is shown in red.
<code>zoomLevel</code>	Integer	13	Initial map zoom.

Install

1. Deploy `_shared_apex/classes/SE_FR_NearbyAccountsController.cls` first (if not already present in the org).
2. Unzip `seFrNearbyAccountsMap.zip` , deploy the LWC bundle.
3. Drop `SE FR – Nearby Accounts Map` on a Home or App page.
4. First load: accept the browser geolocation prompt. The map re-centers on you. If you prefer a fixed origin, set `originMode = 'manual'` and tune the lat/lng.

Data enrichment prerequisites

- The Apex query returns Accounts where `BillingStreet != null` . Accounts without a billing address are invisible on the map.
- **Geocoding precedence:** the component prefers `BillingLatitude` / `BillingLongitude` (set by Salesforce's data.com geocoding service or manually) and falls back to `Street + City + PostalCode + Country` only when lat/lng are missing. On a fresh SDO without data.com geocoding, server-side geocoding via Bing Maps is slow and can silently fail — **pre-seeding `BillingLatitude` / `BillingLongitude` on the target Accounts is the most reliable way to guarantee pins appear.**
- For a Paris-based demo, point the Accounts at Paris addresses and set `BillingLatitude` / `BillingLongitude` in the 48.85 / 2.37 neighbourhood. The `SE_FR_SDO` org has 12 Accounts pre-seeded in the 11th arrondissement — use those to validate.

- The distance label under each pin title is computed client-side via haversine from the origin point, so it's only accurate when lat/lng are present.

Component · Order Entry (`seFrOrderEntry`)

API name: `seFrOrderEntry` · **Categories:** Sales Productivity · **Surfaces:** RecordPage · **Objects:** Account, Case · **Data mode:** live · **Mobile-ready:** no · **Apex:** `SE_FR_OrderEntryController`

seFrOrderEntry

Full-grid order entry component for an Account (or for a Case linked to an Account). Displays products with stock, price, AI-recommended quantity and discount, a running order total, and a confirmation modal. Saves as a real `Order + OrderItem` records.

Where to drop it

- **Target:** Lightning Record Page
- **Object:** Account *or* Case (works on either — uses the Account when on an Account page, the Case's `AccountId` when on a Case page).
- **App Builder label:** `SE_FR – Order Entry`

Apex dependencies

- `SE_FR_OrderEntryController` — exposes `getProductsList(...)` and `createOrderFromGrid(...)` .

Standard fields used

- `Product2.Family` — product category column in the grid (falls back to "Uncategorized" if blank).
- `Order.SalesChannelId` — set from the `salesChannelId` property (lookup to `SalesChannel`).
- `Order.EndDate` — set from the delivery date picker.

Optional custom field

- `Product2.Image_URL__c` (URL) — if present, used as fallback to `ProductMedia.URI` . Gracefully skipped if absent.

Properties (highlights)

NAME	TYPE	DEFAULT	DESCRIPTION
<code>cardTitle</code>	String	Order Entry	
<code>cardIcon</code>	String	<code>standard:orders</code>	
<code>recordLimit</code>	Integer	25	Max products shown.
<code>currencyCode</code>	String	USD	Passed to <code>lightning-datatable</code> currency columns.
<code>currencySymbol</code>	String	\$	Inline rendering next to prices.
<code>localeTag</code>	String	en-US	
<code>fullScreenTitleTemplate</code>	String	Order entry for {account}	Displayed in full-screen mode. {account} placeholder.
<code>noAccountMessage</code>	String	Link an account to this case before starting an order.	Shown when placed on a Case that has no <code>AccountId</code> .
<code>erpCheckboxLabel</code>	String	Send directly to ERP	Label of the final confirmation checkbox.
<code>filter1..5</code>	String	—	Dynamic SOQL fragments added to the <code>Product2</code> query (e.g. <code>Family = 'Widgets'</code>).
<code>salesChannelId</code>	String	—	Optional. 18-char Id of a <code>SalesChannel</code> record set on <code>Order.SalesChannelId</code> at creation.
<code>productImageFieldApiName</code>	String	<code>Image_URL__c</code>	Field on <code>Product2</code> holding an image URL. Schema-safe — skipped if the field is absent.
<code>productImageFallbackUrl</code>	String	—	URL shown when no image is found on the product or in <code>ProductMedia</code> .

Install

1. Deploy `classes/SE_FR_OrderEntryController.cls` first.
2. Unzip `seFrOrderEntry.zip`, deploy the LWC bundle.
3. Drop `SE_FR – Order Entry` on an Account or Case record page.
4. Configure card title, currency, filters.

Component · Order Summary (`seFrOrderSummary`)

API name: `seFrOrderSummary` · **Categories:** Sales Productivity · **Surfaces:** RecordPage · **Objects:** Case · **Data mode:** live · **Mobile-ready:** no · **Apex:** `SE_FR_OrderSummaryController`

seFrOrderSummary

Displays the **most recent Order** associated with the current Case. The Account is resolved first from `Case.AccountId`; if missing, from `Case.Contact.AccountId`. Shows products, total amount and delivery info, with actions to edit delivery details, delete, or submit (marks the Order status as `Activated`).

Where to drop it

- **Target:** Lightning Record Page
- **Object:** Case
- **App Builder label:** `SE_FR – Order Summary`

Apex dependencies

- `SE_FR_OrderSummaryController` — exposes `getOrderDetailsFromCase`, `submitOrderToERP`, `saveDeliveryDetails`, `deleteOrderRecord`.

Standard fields used

- `Case.AccountId`, `Case.ContactId` + `Contact.AccountId` — to resolve which Account to look up orders for.
- `Order.EndDate` — displayed as "estimated delivery date" and edited via the delivery form.
- `Order.Status` — set to `Activated` when the user clicks "Submit order".

Optional custom field

- `Product2.Image_URL__c` (URL) — if present, shows a thumbnail in the product list. Gracefully skipped.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
<code>cardTitle</code>	String	Linked Order	
<code>cardIcon</code>	String	<code>standard:orders</code>	
<code>showBottomSeparator</code>	Boolean	<code>true</code>	Shows a horizontal "OR" divider at the bottom of the card.
<code>separatorLabel</code>	String	OR	Text inside the divider.
<code>currencyCode</code>	String	USD	
<code>successMessage</code>	String	<code>Order submitted.</code>	Toast on submit.
<code>deleteConfirmMessage</code>	String	<code>Delete this order?</code>	Browser <code>confirm()</code> prompt.
<code>emptyStateMessage</code>	String	<code>No order found for this case.</code>	Displayed when the Case has no resolvable Account or that Account has no Order.
<code>productImageFieldApiName</code>	String	<code>Image_URL__c</code>	Field on <code>Product2</code> holding an image URL. Schema-safe.
<code>productImageFallbackUrl</code>	String	—	URL used when no image is found on the product.

Replace action

Beyond the auto-resolved order (latest order of the Case's account / contact's account), clicking **Replace** opens a record picker so the user can manually select any Order. That choice is held in memory only — reloading the page reverts to the auto-resolved order. Use the

"Back to default" link in the blue banner to clear the override.

Install

- 1. Deploy classes/SE_FR_OrderSummaryController.cls .
- 2. Unzip seFrOrderSummary.zip , deploy the LWC bundle.
- 3. Drop SE_FR – Order Summary on a Case record page.

Component · Pipeline Snapshot (seFrPipelineSnapshot)

API name: seFrPipelineSnapshot · Categories: Account 360° · Surfaces: RecordPage · Objects: Account, Opportunity · Data mode: live · Mobile-ready: no · Apex: SE_FR_PipelineSnapshotController

seFrPipelineSnapshot (Pipeline Snapshot)

B2B — Account-level pipeline visualisation. Three summary tiles at the top (total pipeline, weighted total, opportunity count) and one column per Opportunity.StageName with the list of deals in each stage. Bilingual EN / FR.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Opportunity (on Opportunity, resolves the parent AccountId)
- **App Builder label:** SE FR – Pipeline Snapshot

Apex dependency

SE_FR_PipelineSnapshotController.getPipeline(recordId, objectApiName, limitCount, includeClosed) .

Properties

NAME	DEFAULT	DESCRIPTION
language	en	en or fr . Translates the tile labels and the Stage column names (Prospecting → Prospection, etc.).
cardTitle	—	Override the default ("Pipeline Snapshot" / "Aperçu du pipeline").
currencyCode	USD	
localeTag	en-US	
limitCount	40	1–200.
includeClosed	false	Include Closed Won / Closed Lost columns.
hideNewOppButton	false	

Install

- 1. Deploy classes/SE_FR_PipelineSnapshotController.cls .
- 2. Unzip seFrPipelineSnapshot.zip , deploy the LWC bundle.
- 3. Drop SE FR – Pipeline Snapshot on an Account or Opportunity record page.

Data enrichment prerequisites

The component is most impactful on an Account that owns **several Opportunities at different stages**. A fresh SDO often has:

- few Opps on a typical Account, or
- all Opps on the same Stage ("Closed Won" by default on Omega Inc., for example).

Component · Prompt Launcher (seFrPromptLauncher)

API name: seFrPromptLauncher · Categories: Agentforce & AI · Surfaces: AppPage, HomePage, RecordPage · Objects: Any · Data mode: live · Mobile-ready: no · Apex: SE_FR_PromptLauncherController

SE FR - Prompt Launcher (seFrPromptLauncher)

> ⚠️ The bundle is still named `seFrPromptLauncher` for backward compatibility with FlexiPages that already reference it. The component itself is now a **Prompt Launcher**: the chat surface was retired because the Agent API isn't provisioned on most demo orgs.

A configurable AI panel that runs Salesforce **Prompt Templates** via the Invocable Actions endpoint. The SE picks which prompts to expose, the user clicks one, the response renders inline with HTML formatting.

Targets

- `lightning__AppPage`
- `lightning__HomePage`
- `lightning__RecordPage`

What it does

1. Shows a **pill switcher** at the top — one button per applicable prompt.
2. The component **filters** prompts to those compatible with the host record type (`objects` array in the config). On a Home Page, prompts with an empty `objects` array show.
3. If the active prompt requires user inputs (e.g. "Text to summarize"), they appear as a small form. **Record context is auto-filled** — you don't ask the user to type the recordId.
4. Click **Run**, the response renders in a colored panel with copy + save-as-Note actions.
5. **Re-run** with the same inputs in one click.
6. **Save as Note** persists the AI response on the current record (only on Record Pages).

Quick start

Drop on a **Record Page** (Account, Contact, Opportunity, Lead, Case) — the default catalogue auto-detects the record type and shows the right summary prompt.

Drop on a **Home Page** — the default catalogue shows "Summarize text" and "Refine text" (input-driven prompts that don't need a record).

For a custom catalogue, paste a JSON array in the **Prompts catalogue (JSON)** property.

Default catalogue

The component ships with a default catalogue covering the common SDO-shipped prompt templates:

PROMPT API NAME	VISIBLE LABEL	AVAILABLE ON
<code>einstein_gpt__summarizeAccountDefault</code>	Account summary	Account record pages
<code>einstein_gpt__summarizeContact</code>	Contact summary	Contact record pages
<code>einstein_gpt__summarizeDeal</code>	Deal summary	Opportunity record pages
<code>einstein_gpt__summarizeLead</code>	Lead summary	Lead record pages
<code>svc_emp_intelligence__SummarizeRecord</code>	Case summary	Case record pages
<code>einstein_gpt__summarizeText</code>	Summarize text	Anywhere (free-text input)
<code>einstein_gpt__refineText</code>	Refine text	Anywhere (free-text input)

To override, paste your own JSON array in the **Prompts catalogue (JSON)** property.

Prompt config — JSON shape

```
[
  {
    "apiName": "einstein_gpt__summarizeAccountDefault",
    "label": "Account summary",
    "icon": "utility:summarydetail",
    "objects": ["Account"],
    "recordInputName": "Input:Account"
  },
  {
    "apiName": "my_custom_template__competitorAnalysis",
    "label": "Competitor analysis",
    "icon": "utility:opportunity",
    "objects": ["Account"],
    "recordInputName": "Input:Account",
    "userInputs": [
      { "name": "competitor", "label": "Main competitor", "type": "text", "required": true }
    ]
  },
  {
    "apiName": "einstein_gpt__refineText",
    "label": "Refine text",
    "icon": "utility:magicwand",
    "objects": [],
    "userInputs": [
      { "name": "textToRephrase", "label": "Text to refine", "type": "textarea", "required": true }
    ]
  }
]
```

FIELD	REQUIRED	DESCRIPTION
apiName	yes	Prompt template DeveloperName (with namespace if any)
label	yes	Visible button label
icon	no	SLDS icon. Defaults to utility:einstein if omitted
objects	no	Array of host SObject API names. Empty/omitted → always show
recordInputName	no	Input name auto-filled with the host record's Id (e.g. Input:Account). Omit on Home Page prompts
userInputs	no	Array of business-level inputs the user types in. See below

userInputs[] shape:

```
{
  "name": "competitor",           // input name as expected by the prompt template
  "label": "Main competitor",     // visible label
  "type": "text",                // text | textarea | number | picklist
  "required": true,              // optional, defaults to false
  "placeholder": "Microsoft",    // optional
  "options": ["A", "B", "C"]     // for type=picklist only
}
```

The component **only asks for business-level inputs**. Technical inputs the prompt template expects (record id, prompt version id, internal flags) are filled automatically or omitted.

How to find available prompt templates on your org

```
sf apex run --target-org <your-org-alias> --apex-code 'HttpRequest req = new HttpRequest();
req.setEndpoint("callout:Agentforce_API/services/data/v62.0/actions/custom/generatePromptResponse");
req.setMethod("GET");
req.setHeader("Accept", "application/json");
HttpResponse res = new Http().send(req);
System.debug(res.getBody());'
```

The body lists every prompt template accessible to the user. Look at the `name` field for the `apiName` to plug into the JSON.

Properties

PROPERTY	DEFAULT	DESCRIPTION
language	fr	fr / en
cardTitle	–	Override
cardIcon	standard:einstein	SLDS icon
namedCredential	Agentforce_API	Routes the Invocable Action callout
promptsJson	– (uses default catalogue)	JSON array as documented above
autoRunFirstPrompt	false	When ON, the first applicable prompt runs automatically as soon as the page loads
resultAccent	blue	Result panel accent: blue / purple / green
height	480	Component height in pixels

Named Credential setup

The component calls `callout:Agentforce_API/services/data/v62.0/actions/custom/generatePromptResponse/...`. The Named Credential injects OAuth.

If `Agentforce_API` doesn't exist in your org, create it via Setup → Named Credentials. See the audit doc or any of the related Salesforce setup guides for the OAuth dance — same setup as for any Apex callout to the Salesforce REST API.

Troubleshooting

ERROR	CAUSE	FIX
Prompt config is invalid	JSON syntax error in <code>promptsJson</code>	Check the JSON in App Builder; the component validates and shows the parser message
No prompt configured for this record type	Host page object isn't covered by any catalogue entry	Add an entry with <code>objects: ["YourObject"]</code> or set <code>objects: []</code>
HTTP 404 in the result panel	Prompt API name wrong, or template not deployed on the org	List templates with the SOQL command above and copy the exact <code>name</code>
HTTP 401 / 403	Named Credential / OAuth issue	Re-authorize the Named Credential in Setup
Named Credential not found	NC missing	Create it (see above)

SE benefits

- **Real AI responses** on demo orgs that don't have full Agentforce API enabled — leverages the standard Invocable Action endpoint that's available everywhere Einstein is.
- **Auto-detection of record context** — drop on an Account record page, the right summary prompt shows up. No per-page config needed for the common cases.
- **Multi-prompt switcher** — pose 1 component on a record page, the user has 2-3 AI buttons available without you needing 2-3 components.
- **Save as Note** — one click to attach the AI output to the current record. Demos the platform's content storage without leaving the page.
- **HTML rendering** — Salesforce's prompt templates often return rich text (links, bold, lists). The component renders them properly via `lwc:dom="manual"` (same pattern as Contact Card's prompt summary).

Component · Record Highlights (`seFrRecordHighlights`)

API name: `seFrRecordHighlights` · **Categories:** Account 360° · **Surfaces:** RecordPage · **Objects:** Account, Contact, Opportunity, Case, Lead, Order, Contract, Quote · **Data mode:** live · **Mobile-ready:** yes · **Apex:** `SE_FR_RecordHighlightsController`, `SE_FR_ImageFileController`, `SE_FR_ImageFileController` (shared)

seFrRecordHighlights (Record Highlights)

Custom highlights panel for an **Account** or a **Contact** record page. Shows a round image, the record name, a configurable field strip and two action buttons.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Contact, Opportunity, Case, Lead, Order, Contract, Quote
- **App Builder label:** SE FR – Record Highlights

Record source — which record gets displayed

RECORDSOURCE	WHAT IS DISPLAYED
current (default)	The record on the current page. Example: drop on Contact → shows the Contact.
parent	The parent Account linked to the current record. On an Account page, this resolves to the Parent Account via <code>ParentId</code> . Supported lookups: Contact→AccountId, Opportunity→AccountId, Case→AccountId, Lead→ConvertedAccountId, Order→AccountId, Contract→AccountId, Quote→AccountId.

Classic examples:

- Show the **Contact** on a Contact page → drop on Contact, `recordSource = current` (default).
- Show the **Account** on a Contact page → drop on Contact, `recordSource = parent` .
- Show the **parent Account** on an Account page (the hierarchy parent) → drop on Account, `recordSource = parent` .
- Show the **Account** on an Opportunity, Case, Order, Contract or Quote page → drop on that object, `recordSource = parent` .

When `parent` is selected but the lookup is empty, an inline message is shown ("This Contact is not linked to an Account.") — no card noise.

(Folder and technical component name stay `seFrRecordHighlights` for v1 compat — drop it from the palette under the master label above.)

Apex dependencies

None.

Behavior

- If `customImageUrl` is set, that URL is used.
- Otherwise the component reads `imageFieldApiName` on the current record (default `ImageUrl__c`). Schema-safe: if the field doesn't exist, the image falls back silently.
- When no image is available, a large SLDS icon is shown in the circle — `standard:account` or `standard:contact` based on the current object.
- Buttons adapt to the object:
- Account: **Edit + View Account Hierarchy** (opens `/lightning/r/Account/<id>/hierarchy`).
- Contact: **Edit + Email** (triggers the standard `Contact.SendEmail` quick action).
- Toggle `disableRealButtons` to hide the real actions and show `fakeButtonLabels` (CSV) as demo buttons.
- Field strip is driven by one of two properties depending on the object: `accountFieldsList` or `contactFieldsList` .
- Image size (diameter in px) configurable via `imageSize` (default 90).

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
<code>recordSource</code>	String	<code>current</code>	<code>current</code> or <code>parent</code> . See the table above.
<code>accountFieldsList</code>	String	<code>AccountNumber, Industry, Type, Phone</code>	Comma-separated field API names shown on Account.
<code>contactFieldsList</code>	String	<code>Title, Email, Phone, Department</code>	Comma-separated field API names shown on Contact.
<code>customImageUrl</code>	String	—	Direct image URL (overrides the record field).
<code>imageFieldApiName</code>	String	<code>ImageUrl__c</code>	Field holding the record's image URL.
<code>imageSize</code>	Integer	<code>90</code>	Diameter of the round image, in pixels.
<code>disableRealButtons</code>	Boolean	<code>false</code>	When on, hide Edit/secondary action and show fake demo buttons.
<code>fakeButtonLabels</code>	String	<code>Create Quote, Schedule Visit</code>	Comma-separated labels for the demo buttons.

Legacy `fieldsList` property is preserved (for v1 pages) but marked deprecated — use `accountFieldsList` instead.

Install

1. Unzip `seFrRecordHighlights.zip` , deploy the LWC bundle.

2. Drop `SE_FR – Record Highlights` on an Account or Contact record page.

Component · Related Record Card (`seFrRelatedRecordCard`)

API name: `seFrRelatedRecordCard` · **Categories:** Account 360° · **Surfaces:** RecordPage · **Objects:** Account, Contact, Case, Opportunity, Order · **Data mode:** live · **Mobile-ready:** yes · **Apex:** `SE_FR_RelatedRecordCardController`, `SE_FR_ImageFileController`, `SE_FR_ImageFileController` (shared)

SE FR - Related Record Card

Vertical card (Contact / Account avatar + key fields) showing the counterpart of the current record. Designed for a narrow sidebar column on Account, Contact, Case, Opportunity or Order record pages.

Pick behaviour

CURRENT RECORD	TARGET=AUTO DISPLAYS	DATA SOURCE
Account	Primary / first Contact	<code>Account.PersonContactId</code> (Person Account) → first child Contact
Contact	Account	<code>Contact.AccountId</code>
Case	Account	<code>Case.AccountId</code>
Opportunity	Account	<code>Opportunity.AccountId</code>
Order	Account	<code>Order.AccountId</code>

Force a specific target with `target=account` or `target=contact` (e.g. show the Contact behind a Case via `Case.ContactId` — set `target=contact` on a Case page).

Properties

PROPERTY	DEFAULT	DESCRIPTION
<code>language</code>	<code>fr</code>	<code>en</code> or <code>fr</code> . Controls titles, buttons, empty state.
<code>target</code>	<code>auto</code>	<code>auto</code> / <code>account</code> / <code>contact</code> .
<code>cardTitle</code>	<i>(language default)</i>	Override only if you want a custom title.
<code>cardIcon</code>	<i>(auto)</i>	SLDS icon name. Defaults to <code>standard:account</code> or <code>standard:contact</code> .
<code>fieldsCsv</code>	<i>(target-specific)</i>	Comma-separated API names. Contact: <code>Title,Department,Email,Phone,MobilePhone</code> . Account: <code>Industry,Type,Phone,Website,AnnualRevenue,NumberOfEmployees</code> . Unknown fields are silently skipped.
<code>imageFieldApiName</code>	<code>PhotoURL</code>	Works out-of-box for Contact. For Account, point to a custom image URL field (or leave; the card shows initials).

Visual behaviour

- Avatar: image if available, otherwise gradient circle with initials.
- Click on the header → opens the related record.
- Phone / email / url fields render as clickable links (`tel:` , `mailto:` , external URL).
- Empty state when the source record has no counterpart (e.g. a Case without `AccountId`).

Apex dependency

`SE_FR_RelatedRecordCardController` — deploy once per org.

Component · Revenue Dashboard (`seFrRevenueDashboard`)

API name: `seFrRevenueDashboard` · **Categories:** Account 360°, Dashboards & KPIs · **Surfaces:** RecordPage · **Objects:** Account · **Data mode:** mock · **Mobile-ready:** no · **Apex:** none

seFrRevenueDashboard

3-year revenue mini-dashboard with 3 KPI tiles and a monthly bar chart comparing three years side by side. Fully configurable — you can change labels, years, max scale, and provide a custom monthly dataset via JSON.

Where to drop it

- **Target:** Lightning Record Page
- **Object:** Account
- **App Builder label:** SE_FR – Revenue Dashboard

Apex dependencies

None.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
cardTitle	String	Delivered Revenue (3 years)	
cardIcon	String	standard:performance	
currencyCode	String	USD	
localeTag	String	en-US	
year1Label / year2Label / year3Label	String x 3	2024 / 2025 / 2026	Chart legend + bar tooltips.
kpi1Label / Value	String / Integer	YTD Revenue / 38550	Currency-formatted.
kpi2Label / Value	String / String	YoY Trend / +14.2%	Raw text.
kpi3Label / Value	String / Integer	Previous Year Total / 114200	Currency-formatted.
chartMaxScale	Integer	15000	Y-axis maximum. Y-axis labels are auto-computed at 1/3 intervals.
chartDataJson	String (rich)	12-month sample	JSON array [{"month": "Jan", "y1": 8200, "y2": 8900, "y3": 9500}, ...] .

Install

1. Unzip seFrRevenueDashboard.zip , deploy the LWC bundle.
2. Drop SE_FR – Revenue Dashboard on an Account record page.
3. Replace chartDataJson with your dataset.

Data enrichment prerequisites

The component is **purely driven by the chartDataJson property** — it does **not** query Orders or Opportunities automatically. Two paths:

- **Demo mode (recommended for pitches):** leave the default sample data, or override chartDataJson in App Builder with a hand-crafted narrative (e.g. show a growth curve that matches the customer story you're telling).
- **Data-backed mode:** populate chartDataJson from real org data via an Apex invocable or a pre-processing Flow. Requires the SE to write the bridging logic.

If you want an automatic "derived from real Orders" variant, pair this component with seFrMetricTile instead, which can be fed from an Apex wire. seFrRevenueDashboard stays intentionally static for demo flexibility.

Component · Smart Recommendations (seFrSmartRecommendations)

API name: seFrSmartRecommendations · **Categories:** Agentforce & AI · **Surfaces:** RecordPage · **Objects:** Account, Contact, Case, Order · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

seFrSmartRecommendations

Context-aware "Next Best Action" panel that shows 1–6 recommendations depending on the object type the record page is on. Each recommendation has a title, a reason, a fake relevance score, and an action button. Admins can override any recommendation's title and reason via properties.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Contact, Case, Order
- **App Builder label:** SE_FR – Smart Recommendations

Apex dependencies

None.

Display modes

- **Global** (*default*): shows the first 2 recommendations for the current object type.
- **Targeted**: shows only the recommendations configured for a specific record ID. You can configure up to 3 target records, each with a comma-separated list of recommendation indices (e.g. 1,3,4).

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
cardTitle	String	Smart Recommendations	
displayMode	String (picklist)	Global	Global or Targeted .
targetId1..3	String × 3	—	Record Id that activates the matching targetRecos* list.
targetRecos1..3	String × 3	—	Comma-separated indices 1..6 to show on that record.
customTitle1..6 / customDesc1..6	String × 12	—	Override default title / description per recommendation. Leave empty to use the built-in text for the current object type.

Install

1. Unzip seFrSmartRecommendations.zip , deploy the LWC bundle.
2. Drop SE_FR – Smart Recommendations on an Account / Contact / Case / Order record page.
3. Optionally override titles / descriptions to fit the customer context.

Component · Splash Banner (seFrSplashBanner)

API name: seFrSplashBanner · **Categories:** Transverse · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

SE FR - Splash Banner (seFrSplashBanner)

Bannière d'accueil / splash screen avec fond animé. **8 styles de fond** au choix, tous en pur CSS + SVG inline (zéro librairie externe). Le SE configure juste un titre, un sous-titre optionnel et le style de fond — tout le reste est paramétrable depuis App Builder (couleurs, hauteur, vitesse, alignement, bouton CTA).

Targets

- lightning__HomePage
- lightning__AppPage
- lightning__RecordPage

Les 8 styles de fond

BGSTYLE	VIBE	CAS D'USAGE
waves	doux, organique (clin d'oeil aux vagues de Charly Ansel)	bannière welcome standard
aurora	aurores boréales, blend screen	luxe / premium / cosmétique
mesh	mesh gradient Stripe homepage	SaaS moderne, dashboard
orbs	sphères flottantes blurred (Apple keynote)	élégant, généraliste
conic	conic gradient qui tourne (Vercel)	flashy, dev-tool, AI
geometric	low-poly SVG triangulé qui pulse	tech, WWDC
constellation	points reliés type étoiles	data, AI, futuriste
grid	blueprint avec pulse + scan-line	tech, monitoring, "matrix-light"

Tous les fonds respectent `prefers-reduced-motion` (animations désactivées si l'utilisateur a activé la préférence d'accessibilité système).

Propriétés (App Builder)

PROPRIÉTÉ	DESCRIPTION
title	Titre principal (centré, gros). Émojis acceptés.
subtitle	Sous-titre optionnel sous le titre.
textSize	<code>s</code> / <code>m</code> / <code>l</code> (défaut) / <code>xl</code>
bgStyle	Voir tableau ci-dessus. Défaut : <code>waves</code> .
colorPrimary	Couleur 1 (CSS hex, rgb, named). Défaut bleu Lightning <code>#0176d3</code> .
colorSecondary	Couleur 2. Défaut violet <code>#a445ff</code> .
colorTertiary	Couleur 3. Défaut rose <code>#ff6ec7</code> . Ignorée par <code>waves</code> (qui n'en utilise que 2).
height	Hauteur en pixels. Défaut 220.
darkText	Off (défaut, texte blanc) / On (texte noir).
animationSpeed	<code>slow</code> / <code>normal</code> (défaut) / <code>fast</code>
alignment	<code>center</code> (défaut) / <code>left</code> / <code>right</code>
ctaLabel	Label du bouton optionnel sous le texte.
ctaUrl	URL du bouton (Salesforce relative ou absolue).

Conseils visuels

- Pour un effet **premium** : `aurora` + couleurs pastel (rose / violet / bleu) + `darkText=false` .
- Pour un effet **tech / Agentforce** : `conic` ou `constellation` + couleurs vives (bleu / violet / cyan).
- Pour un effet **discret** : `waves` ou `orbs` + une seule couleur de marque + animation `slow` .
- Pour une **landing page d'app** : `mesh` + 3 couleurs de marque, hauteur 300px, CTA "Explorer".

Aucune dépendance Apex

Composant 100% front. Pas d'Apex requis. Aucun champ custom.

Component · Telesales - Rep Home (`seFrTelesalesRepHome`)

API name: `seFrTelesalesRepHome` · **Categories:** Dashboards & KPIs · **Surfaces:** `AppPage`, `HomePage` · **Objects:** Any · **Data mode:** `hybrid` · **Mobile-ready:** no · **Apex:** `SE_FR_TelesalesController`

seFrTelesalesRepHome (Telesales — Rep Home)

B2B — Home / App page for a **telesales / inside-sales rep**. Greeting, 4 KPI tiles, **live cases table**, **live orders table**, calls to make (mock), 3 mini charts (channel / subject / monthly closed), training & news cards.

> **Tasks panel** lives in the dedicated sidebar component `seFrMyTasks` — drop it on the right column of the page to get the task list.

Where to drop it

- **Target:** Lightning Home Page, App Page (**not Record**)
- **App Builder label:** SE FR – Telesales – Rep Home

Apex dependency

SE_FR_TelesalesController (bundled in classes/):

- `getIncomingCases(statusesCsv, ownerScope, limitCount)` — open Case records.
- `getOrdersToValidate(statusesCsv, ownerScope, limitCount)` — Order records by status.

Everything else on this dashboard (calls, news, mini-charts) stays mock JSON configurable via App Builder because there is no standard source of truth.

Dynamic data filters (App Builder)

PROPERTY	DEFAULT	NOTES
caseStatusesCsv	New,Working,Waiting on Customer,Escalated	Any Case.Status value on your org.
caseOwnerScope	all	'mine' filters on the running user — use 'all' in a fresh SDO where demo cases aren't owned by the running user.
caseLimit	6	Up to 50.
caseListView	Recent	Used by the "View all" button.
orderStatusesCsv	Draft	Default matches "orders to validate".
orderOwnerScope	all	
orderLimit	6	
orderListView	Recent	

Columns on both datatables are now real Salesforce data: case/order number linked to the record, account linked to its record, date, channel (Case.Origin / Order.SalesChannel.SalesChannelName), status, amount for orders.

Styling

Shares the SE_FR palette declared at the top of the CSS (SLDS-aligned brand/success/warning/error colors). KPI tiles, bar charts and news cards all use the same palette.

Origin

Renamed from `seFrTelesalesDashboard` (v2.3 → v2.4). The old bundle is kept in the library as deprecated.

Component · Territory Map (`seFrTerritoryMap`)

API name: `seFrTerritoryMap`

Categories: Geo & Field

Surfaces: `AppPage`, `HomePage`

Objects: Any

Data mode: live

Mobile-ready: no

Apex: `SE_FR_TerritoryMapController`

SE FR - Territory Map (`seFrTerritoryMap`)

Carte interactive du territoire commercial : Accounts géolocalisés via leur Billing Address, code couleur par tier de pipeline ouvert, filtres latéraux (Owner / RecordType / fourchette de montant ouvert / étapes opportunité), tuiles KPI et export CSV de la sélection visible.

Targets

- `lightning__HomePage`
- `lightning__AppPage`

> Pas de `lightning__RecordPage` : le composant est conçu pour une vue agrégée du territoire, pas pour une record page.

Apex

- `SE_FR_TerritoryMapController.getTerritoryAccounts(limitCount, recordTypeName, ownerScope, amountMin, amountMax, stagesCsv)` — renvoie une liste de `TerritoryAccount` enrichis (sommes / counts d'opportunités, count des cases ouverts) basés

sur les Accounts ayant `BillingLatitude` / `BillingLongitude` non nuls.

- `getStageNames()` — picklist `OpportunityStage` .
- `getAccountRecordTypes()` — `RecordTypes` Account actifs.

Schema-safe : tous les champs sont des standards. Aucune dépendance custom requise.

Propriétés (App Builder)

PROPRIÉTÉ	DESCRIPTION
<code>language</code>	'fr' (défaut) / 'en'
<code>cardTitle</code>	Titre du composant (override)
<code>limitCount</code>	Max accounts (1-200, défaut 100)
<code>defaultOwnerScope</code>	mine (défaut) / all
<code>defaultRecordType</code>	DeveloperName du RecordType Account pré-sélectionné
<code>defaultStagesCsv</code>	Étapes opportunité pré-sélectionnées (séparées par virgule)
<code>currencyCode</code>	Code ISO 4217 (défaut EUR)
<code>zoomLevel</code>	Zoom initial de la carte (défaut 6)
<code>filtersOpenByDefault</code>	Panneau de filtres ouvert par défaut

Couleurs des pins

- **Rouge** (top 20%) : pipeline ouvert élevé
- **Orange** (top 50%) : pipeline ouvert moyen
- **Vert** : pipeline ouvert faible mais > 0
- **Gris** : aucun pipeline ouvert

Les seuils sont calculés sur la liste visible (relatifs, pas absolus) — le top tier reste toujours saillant quel que soit le territoire.

KPIs affichés

- Nombre de comptes visibles
- Pipeline ouvert total (formaté compact, ex. 12,5 M €)
- Total opportunités ouvertes
- Total cases ouverts

Export CSV

Le bouton `Exporter visible` génère un CSV (encodage UTF-8 BOM, séparateur virgule, guillemets pour les valeurs contenant des caractères spéciaux) téléchargé côté navigateur.

Comportements

- Click sur un pin → ouvre la fiche Account dans Lightning.
- Le panneau de filtres reste collapsable via l'icône entonnoir (variant `brand` quand ouvert).
- Si `defaultOwnerScope = mine` ne renvoie rien, l'Apex bascule automatiquement sur "tous owners" (utile sur les SDOs vierges).

Component · Timeline Phases (`seFrTimelinePhases`)

API name: `seFrTimelinePhases` · **Categories:** Sales Productivity · **Surfaces:** `AppPage`, `HomePage`, `RecordPage` · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

SE FR - Timeline Phases (`seFrTimelinePhases`)

Horizontal multi-phase timeline. Visualizes a journey, project, or sales-cycle with phases positioned on a date axis, a "Today" marker, and a done / pending state per phase.

Targets

- `lightning__RecordPage`
- `lightning__AppPage`

- lightning__HomePage

Quick start

Drop on an Account record page — defaults to a 5-phase sales cycle (Prospection → Découverte → Démo → Proposition → Closing). The vertical "Today" line auto-positions.

Customizing phases

Set `phasesJson` to a JSON array:

```
[
  { "label": "Onboarding", "date": "2026-01-15", "done": true },
  { "label": "Discovery", "date": "2026-02-08", "done": true },
  { "label": "Demo", "date": "2026-03-12", "done": true },
  { "label": "Proposal", "date": "2026-04-22", "done": false },
  { "label": "Closing", "date": "2026-05-30", "done": false }
]
```

Each phase: `label` (string), `date` (YYYY-MM-DD), `done` (boolean).

Default phase sets (when `phasesJson` is empty)

SCOPE	DEFAULT PHASES
record (default)	Sales cycle — Prospection → Découverte → Démo → Proposition → Closing
home	Fiscal milestones — Q1 kick-off → Q2 ramp-up → Q3 expansion → Q4 year-end

Properties

PROPERTY	DEFAULT	DESCRIPTION
language	fr	fr / en (drives default labels)
scope	record	record / home (drives default phases)
cardTitle	–	Override
cardIcon	standard:timesheet	SLDS icon
phasesJson	–	JSON array (overrides defaults)
localeTag	fr-FR	Locale used to format phase dates
hideTodayMarker	false	Hide the vertical "Today" line

SE benefits

- **Visualizes a journey or process state** without needing custom objects, flows, or path components.
- **Type the phases directly in App Builder** — paste a JSON array, see it render. Useful for "this customer is at step 3 of onboarding" demo moments.
- **"Today" marker auto-positioned** on the date axis — gives an instant sense of progress vs. plan.
- **Two default sets** (sales cycle for Account pages, fiscal milestones for Home pages) keep the component demo-ready out of the box.

Component · Voice Note Taker (`seFrVoiceNoteTaker`)

API name: `seFrVoiceNoteTaker` · **Categories:** Geo & Field · **Surfaces:** RecordPage · **Objects:** Account, Contact, Lead, Opportunity · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_VoiceNoteController, SE_FR_VoiceNoteController (shared)

seFrVoiceNoteTaker

Dictate a voice note using the browser's Web Speech API, edit it manually if needed, and save it as a completed `Task` linked to the current record. Works on Account, Contact, Lead or Opportunity — the recordId is routed to `Task.WhoId` for Contact/Lead, `Task.WhatId` otherwise.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Contact, Lead, Opportunity
- **App Builder label:** SE FR – Voice Note Taker

Apex dependency

- `SE_FR_VoiceNoteController.saveVoiceNoteForRecord(recordId, noteText, taskSubject)` (in `_shared_apex/`).

Browser requirement

Voice recognition relies on `window.SpeechRecognition` / `webkitSpeechRecognition`. Works in Chrome, Edge and Safari — Firefox shows the unsupported-browser message.

Task created

FIELD	VALUE
Subject	<code>taskSubject</code> property (default <code>Visit notes (voice dictation)</code>)
Description	The note text (transcribed speech + manual edits)
Status	Completed
ActivityDate	Today
Priority	Normal
WhoId or WhatId	the current record, routed by object type

The activity feed component (to be built later) will display `Task.Description` verbatim when the Task was created by this component.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
<code>cardTitle</code>	String	Voice Note Taker	
<code>cardIcon</code>	String	<code>standard:voice_call</code>	SLDS icon.
<code>speechLocale</code>	String	en-US	BCP 47 locale for speech recognition.
<code>taskSubject</code>	String	<code>Visit notes (voice dictation)</code>	Subject on the created Task.
<code>recordingHint</code>	String	<code>Listening... Speak now.</code>	Shown while recording.
<code>textareaLabel</code> / <code>textareaPlaceholder</code>	String × 2	English defaults	Customize the editable area.
<code>startButtonLabel</code> / <code>stopButtonLabel</code> / <code>saveButtonLabel</code>	String × 3	English defaults	Button labels.
<code>unsupportedBrowserMessage</code>	String	Voice recognition is not supported by your browser. Use Google Chrome.	Fallback message.
<code>successMessage</code>	String	Note saved as a Task successfully.	Success toast message.

Install

1. Deploy `_shared_apex/classes/SE_FR_VoiceNoteController.cls` first.
2. Unzip `seFrVoiceNoteTaker.zip`, deploy the LWC bundle.
3. Drop SE FR – Voice Note Taker on an Account / Contact / Lead / Opportunity record page.