CCO FR Component Library

Knowledge base — for the LWC_Library_Agent

GENERATED 2026-11-09 · SOLUTION ENGINEERING FRANCE

Table of contents

Canonical component table
Cookbook recipes
Release notes
Contributors
About — design principles, reading a component page
Library standards, install methods, configuration, data setup
Per-component pages
seFrAccountHealth
seFrAccountStrategyPlan
seFrActiveSegments
seFrActivityFeed
seFrAgentforceHeader
seFrAlertsRibbon
seFrBusinessCardScanner
seFrConsentManager
seFrContactCard
seFrContactsCarousel
seFrCustomerOrders
seFrCustomerSalesSummary
seFrEngagementHistory
seFrFieldRepHome
seFrFilesGallery
seFrKanbanBoard
seFrKpiLauncher
seFrLeadFirstTouch
seFrMetricTile
seFrMyEvents
seFrMyTasks
seFrNearbyAccountsMap
seFrOrderEntry
seFrOrderSummary
seFrPipelineSnapshot
seFrPromptLauncher
seFrRecordActions
seFrRecordHighlights
seFrRelatedRecordCard
seFrRetailExecSchema
seFrRevenueDashboard
seFrServiceContracts
seFrSmartRecommendations
seFrSplashBanner
seFrSubscribersList
seFrTelesalesRepHome
seFrTerritoryMap
seFrTimelinePhases
seFrVisitCheckIn
seFrVisitKanban
seFrVisitPlan
seFrVisitProductCheck
seFrVisitQuickOrder
seFrVisitRestockOrder
seFrVisitShelfCompliance
seFrVisitShelfSpace
seFrVisitSummaryAI
seFrVoiceNoteTaker

Canonical component table

How to read this table: every row is a real component. Names follow the `seFr*` convention and are the only valid component identifiers — anything else (e.g. "Account 360°", "Performance") is a category or persona heading, not a component. When asked "what components are there?", list rows from this table.

Per-component details (full prose, key props, edge-cases, install steps, data prereqs) live further down in this document under the "Component · `seFrXxx`" sections.

API NAME	MASTER LABEL	TAGLINE	CATEGORIES	PERSONAS	SURFACES	OBJECTS	DATA MOD
`seFrAccountHealth`	CCO FR - Account Health	Quantitative account health score (0-100) with verdict level and weighted positive / negative signals.	Sales	Sales	RecordPage	Account	live
`seFrAccountStrategyPlan`	CCO FR - Account Strategy Plan	Narrative account plan with editable KPIs, target gauge, SWOT 2x2 and quarterly action plan.	Sales	Sales	RecordPage	Account	mock
`seFrActiveSegments`	CCO FR - Active Segments	Compact panel showing the marketing / Data Cloud segments the record belongs to, as colored badges.	Marketing	Marketing	AppPage, HomePage, RecordPage	Any	mock
`seFrActivityFeed`	CCO FR - Activity Feed	Unified activity timeline aggregating 16+ Salesforce record types in a single feed with rich filtering.	Transverse	Sales, FieldSales, Telesales, Service, Marketing	RecordPage	Account, Contact	live
`seFrAgentforceHeader`	CCO FR - Agentforce Header	Astro-themed Home page header with a search / dictation box that forwards questions to the Agentforce panel.	Transverse	All	HomePage	Any	mock
`seFrAlertsRibbon`	CCO FR - Alerts Ribbon	Configurable alerts ribbon combining declarative record-driven rules with always-on static banners.	Service	Sales, Service	AppPage, HomePage, RecordPage	Account, Contact, Case, Opportunity, Lead, Order, Contract	mock
`seFrBusinessCardScanner`	CCO FR - Business Card Scanner	Drop business card photos, get editable lead cards pre-filled by a simulated OCR, then bulk-create the leads.	Retail Execution	Sales, FieldSales, Retail, Marketing	AppPage, HomePage, RecordPage	Any	mock
`seFrConsentManager`	CCO FR - Consent Manager	Per-channel GDPR consent toggle panel binding each channel to a boolean field on the current record.	Marketing	Marketing, Service	RecordPage	Contact, Lead, Account	live
`seFrContactCard`	CCO FR - Contact Card	Visual contact card with animated waves, avatar, address, configurable gauges and optional Einstein prompt summary.	Transverse	Sales, FieldSales, Telesales, Service, Marketing	RecordPage	Contact, Account, Case, Opportunity, Order, Lead	hybri
`seFrContactsCarousel`	CCO FR - Contacts Carousel	Horizontal carousel of an	Transverse	Sales, FieldSales,	RecordPage	Account	live

API NAME	MASTER LABEL	TAGLINE	CATEGORIES	PERSONAS	SURFACES	OBJECTS	DATA MOD
		Account's Contacts with avatars, role badges and quick Email / Call actions.		Telesales, Service, Marketing			
`seFrCustomerOrders`	CCO FR - Customer Orders	Last order detail card plus searchable, sortable, filterable order history for an Account or Contact.	Sales	Sales, Telesales	RecordPage	Account, Contact, Visit__c	live
`seFrCustomerSalesSummary`	CCO FR - Customer Sales Summary	B2C-leaning sales summary with KPI tiles and breakdowns by Category, Brand and Store.	Marketing	Retail, Marketing	RecordPage	Contact, Account	mock
`seFrEngagementHistory`	CCO FR - Engagement History	Configurable marketing engagement timeline with colored typed icons and inline search.	Marketing	Marketing, Sales	AppPage, HomePage, RecordPage	Lead, Contact, Account	mock
`seFrFieldRepHome`	CCO FR - Field Sales - Rep Home	Field Sales rep home page with greeting, KPIs, priority accounts, hot leads, product penetration and campaign calendar.	Dashboards & KPIs	FieldSales	AppPage, HomePage	Any	hybri
`seFrFilesGallery`	CCO FR - Files Gallery	Visual gallery of files attached to any record with image thumbnails, doctype icons and drag-and-drop upload.	Transverse	Sales, FieldSales, Telesales, Service, Marketing	RecordPage	Any	live
`seFrKanbanBoard`	CCO FR - Kanban Board	Generic kanban board with native drag & drop on any whitelisted SObject (Case, Opp, Lead, Order, Task, Account).	Service	Service, Telesales	AppPage, HomePage, RecordPage	Any	live
`seFrKpiLauncher`	CCO FR - KPI Launcher	Configurable grid of 3-6 clickable KPI tiles with icon, value, color and link, ready out of the box.	Dashboards & KPIs	All	AppPage, HomePage, RecordPage	Any	mock
`seFrLeadFirstTouch`	CCO FR - Lead First Touch	Lead "First Touch Capture" mock — drop notes, paste a transcript, get simulated AI meeting notes, then simulated follow-up Tasks and Events.	Retail Execution	Sales, FieldSales, Telesales, Retail	AppPage, HomePage, RecordPage	Lead	mock

API NAME	MASTER LABEL	TAGLINE	CATEGORIES	PERSONAS	SURFACES	OBJECTS	DATA MOD
`seFrMetricTile`	CCO FR - Metric Tile	Single-metric tile with 4 chart styles (line / area / bar / mini-donut), comparison series, target line and currency formatting.	Dashboards & KPIs	Sales, FieldSales, Telesales, Service, Marketing	AppPage, HomePage, RecordPage	Any	mock
`seFrMyEvents`	CCO FR - My Events	Today's calendar as a compact vertical timeline that fits a sidebar column, with Google-Calendar-style overlap.	Productivity	All	AppPage, HomePage	Any	live
`seFrMyTasks`	CCO FR - My Tasks	Compact 'My Tasks' sidebar panel grouped by due date with one-click completion.	Productivity	All	AppPage, HomePage	Any	live
`seFrNearbyAccountsMap`	CCO FR - Nearby Accounts Map	Interactive map of nearby accounts using the browser's geolocation with Haversine distance sort.	Geo & Field	FieldSales	AppPage, HomePage	Any	live
`seFrOrderEntry`	CCO FR - Order Entry	Full-grid order entry on an Account or Case with stock, AI-recommended quantities and discounts, persisted as real Order records.	Sales	Telesales	RecordPage	Account, Case, Visit__c	live
`seFrOrderSummary`	CCO FR - Order Summary	Most recent Order linked to a Case with products, total, delivery info and edit / delete / submit actions.	Service	Service	RecordPage	Case	live
`seFrPipelineSnapshot`	CCO FR - Pipeline Snapshot	Account-level pipeline visualization with summary tiles and one column per Opportunity stage.	Sales	Sales	RecordPage	Account, Opportunity	live
`seFrPromptLauncher`	CCO FR - Prompt Launcher	Configurable AI panel running Salesforce Prompt Templates via Invocable Actions, with auto-filled record context.	Productivity	All	AppPage, HomePage, RecordPage	Any	live
`seFrRecordActions`	CCO FR - Record Actions	Compact record-page toolbar for Account, Contact, Lead, Opportunity and Case — one primary button (Screen Flow or	Transverse	Sales, FieldSales, Telesales, Service	RecordPage	Account, Contact, Opportunity, Case, Lead	hybri

API NAME	MASTER LABEL	TAGLINE	CATEGORIES	PERSONAS	SURFACES	OBJECTS	DATA MOD
		standard New Task / Event / Case / Opportunity form) + an inline Einstein AI summary.					
`seFrRecordHighlights`	CCO FR - Record Highlights	Custom highlights panel with round image, key fields and action buttons, working on 8 standard objects.	Transverse	All	RecordPage	Account, Contact, Opportunity, Case, Lead, Order, Contract	live
`seFrRelatedRecordCard`	CCO FR - Related Record Card	Vertical sidebar card showing the counterpart record (Contact / Account) with key fields and avatar.	Transverse	Sales, FieldSales, Telesales, Service, Marketing	RecordPage	Account, Contact, Case, Opportunity, Order	live
`seFrRevenueDashboard`	CCO FR - Revenue Dashboard	3-year revenue mini-dashboard with KPI tiles and a side-by-side monthly bar chart.	Dashboards & KPIs	Sales, FieldSales, Telesales	RecordPage	Account	mock
`seFrServiceContracts`	CCO FR - Service Contracts	Active service contracts per Account with deadline countdown, trade badge, SLA and open work order counter.	Service	Service, FieldSales	RecordPage	Account, Case, Contact, Opportunity, WorkOrder	live
`seFrSmartRecommendations`	CCO FR - Smart Recommendations	Context-aware Next Best Action panel with 1-6 recommendations, relevance score and per-card overrides.	Productivity	Sales, FieldSales, Telesales, Service, Marketing	RecordPage	Account, Contact, Case, Order, Opportunity, Lead	mock
`seFrSplashBanner`	CCO FR - Splash Banner	Welcome banner with 8 animated background styles (waves, aurora, mesh, orbs, conic, geometric, constellation, grid) in pure CSS / SVG.	Transverse	All	AppPage, HomePage, RecordPage	Any	mock
`seFrSubscribersList`	CCO FR - Subscribers List	Live account team panel with profile photos, roles and record navigation.	Service	Service, FieldSales, Sales	AppPage, HomePage, RecordPage	Any	live
`seFrTelesalesRepHome`	CCO FR - Telesales - Rep Home	Telesales rep home page with KPIs, live cases and orders tables, calls to make and 3 mini charts.	Dashboards & KPIs	Telesales	AppPage, HomePage	Any	hybri
`seFrTerritoryMap`	CCO FR - Territory Map	Interactive territory map with geocoded Accounts, pipeline color coding,	Geo & Field	FieldSales, Sales	AppPage, HomePage	Any	live

API NAME	MASTER LABEL	TAGLINE	CATEGORIES	PERSONAS	SURFACES	OBJECTS	DATA MOD
		sidebar filters and CSV export.					
`seFrTimelinePhases`	CCO FR - Timeline Phases	Horizontal multi-phase timeline with date axis, 'Today' marker and done / pending state per phase.	Productivity	Sales	AppPage, HomePage, RecordPage	Any	mock
`seFrVisitCheckIn`	CCO FR - Visit Check-In	Check-in / Check-out terrain en un clic sur la visite, avec chrono et récapitulatif de durée.	Retail Execution	FieldSales, Retail	RecordPage	Visit__c	live
`seFrVisitKanban`	CCO FR - Visit Kanban	Kanban des visites du compte - glisser-deposer pour faire avancer une visite de Planifiee a Terminee.	Retail Execution	FieldSales, Sales, Retail	RecordPage	Account	live
`seFrVisitPlan`	CCO FR - Visit Plan	Checklist "Plan d'action" sur une visite terrain — démarre, séquence, clôture.	Retail Execution	FieldSales, Retail	RecordPage	Visit__c	live
`seFrVisitProductCheck`	CCO FR - Visit Product Check	Relevé produits terrain depuis le Standard Pricebook — Présent / Rupture / prix constaté par produit.	Retail Execution	FieldSales, Retail	RecordPage	Visit__c	live
`seFrVisitQuickOrder`	CCO FR - Commande rapide (catalogue visuel)	Visual product catalogue with contextual recommendations (out-of-stock, missing products, low shelf share) and a cart with line + global discount.	Retail Execution	Sales, FieldSales, Retail	AppPage, RecordPage	Visit__c, Account	mock
`seFrVisitRestockOrder`	CCO FR - Réassort auto (ruptures relevé)	Turns out-of-stock products found during the shelf survey into a Draft restock Order in one click.	Retail Execution	Sales, FieldSales, Retail	RecordPage	Visit__c, Account	live
`seFrVisitShelfCompliance`	CCO FR - Visit Shelf Compliance	Photos de linéaire sur une visite, galerie et analyse Agentforce (mock en repli).	Retail Execution	FieldSales, Retail	RecordPage	Visit__c	live
`seFrVisitShelfSpace`	CCO FR - Visit Shelf Space	Relevé linéaire manuel — part de linéaire (PDL) marque vs concurrence par catégorie et segment, avec historique.	Retail Execution	FieldSales, Retail	RecordPage	Visit__c	mock

API NAME	MASTER LABEL	TAGLINE	CATEGORIES	PERSONAS	SURFACES	OBJECTS	DATA MOD
`seFrVisitSummaryAI`	CCO FR - Resume de Visite IA	Résumé IA (Agentforce / Einstein) d'une visite terrain — synthèse, points clés et actions recommandées.	Retail Execution	FieldSales, Retail	AppPage, HomePage, RecordPage	Visit__c, Account	live
`seFrVoiceNoteTaker`	CCO FR - Voice Note Taker	Dictate a voice note via the Web Speech API and save it as a completed Task linked to the current record.	Geo & Field	FieldSales	RecordPage	Account, Contact, Lead, Opportunity, Visit__c	live

Cookbook recipes

Pre-built component bundles for typical demo scenarios. Each recipe groups components that work well together on the same page or persona context.

🏢 Account 360°

Drop-in record page for B2B Sales — highlights, health gauge, pipeline, activity timeline, contacts carousel, related records and AI recommendations.

Primary persona: Sales

- `seFrRecordHighlights` — Record Highlights
- `seFrAccountHealth` — Account Health
- `seFrPipelineSnapshot` — Pipeline Snapshot
- `seFrActivityFeed` — Activity Feed
- `seFrContactsCarousel` — Contacts Carousel
- `seFrRelatedRecordCard` — Related Record Card
- `seFrSmartRecommendations` — Smart Recommendations
- `seFrAccountStrategyPlan` — Account Strategy Plan
- `seFrRevenueDashboard` — Revenue Dashboard
- `seFrCustomerOrders` — Customer Orders
- `seFrRecordActions` — Record Actions

🚗 Field Sales cockpit

Mobile-first Home page for reps in the field — priority accounts, map, agenda, tasks, voice notes and KPIs.

Primary persona: FieldSales

- `seFrFieldRepHome` — Field Sales - Rep Home
- `seFrNearbyAccountsMap` — Nearby Accounts Map
- `seFrTerritoryMap` — Territory Map
- `seFrMyEvents` — My Events
- `seFrMyTasks` — My Tasks
- `seFrVoiceNoteTaker` — Voice Note Taker
- `seFrKpiLauncher` — KPI Launcher

📞 Service desk

Case-centric record page with service contracts, account team, order history, kanban, alerts and smart actions.

Primary persona: Service

- `seFrAlertsRibbon` — Alerts Ribbon
- `seFrServiceContracts` — Service Contracts
- `seFrSubscribersList` — Subscribers List
- `seFrCustomerOrders` — Customer Orders
- `seFrOrderSummary` — Order Summary
- `seFrKanbanBoard` — Kanban Board
- `seFrSmartRecommendations` — Smart Recommendations

🤖 Agentforce demo

Showcase page tuned for AI-driven scenarios — hero banner, prompt launcher, and recommendations.

Primary persona: Agents

- `seFrAgentforceHeader` — Agentforce Header
- `seFrPromptLauncher` — Prompt Launcher
- `seFrSmartRecommendations` — Smart Recommendations
- `seFrSplashBanner` — Splash Banner

🎯 Marketing 360°

Contact-centric page with engagement history, consent management, segment membership and signals.

Primary persona: Marketing

- `seFrActiveSegments` — Active Segments
- `seFrConsentManager` — Consent Manager
- `seFrEngagementHistory` — Engagement History
- `seFrActivityFeed` — Activity Feed
- `seFrCustomerSalesSummary` — Customer Sales Summary
- `seFrSubscribersList` — Subscribers List

🏬 Retail Execution — Visit workflow

Full store-visit lifecycle on the Visit record page — check-in/out, action-plan checklist, product and shelf-space survey, shelf photo compliance with Agentforce analysis, restock order and AI visit summary.

Primary persona: Retail

- `seFrVisitCheckIn` — Visit Check-In
- `seFrVisitPlan` — Visit Plan
- `seFrVisitProductCheck` — Visit Product Check
- `seFrVisitShelfSpace` — Visit Shelf Space
- `seFrVisitShelfCompliance` — Visit Shelf Compliance
- `seFrVisitQuickOrder` — Commande rapide (catalogue visuel)
- `seFrVisitRestockOrder` — Réassort auto (ruptures relevé)
- `seFrVisitSummaryAI` — Resume de Visite IA
- `seFrVoiceNoteTaker` — Voice Note Taker
- `seFrFilesGallery` — Files Gallery

🛒 Retail Execution — Rep home & account

Retail rep's day — Home with agenda, tasks and nearby stores, business-card/lead capture, and the Account page with visit kanban, quick orders and key-account actions.

Primary persona: Retail

- `seFrFieldRepHome` — Field Sales - Rep Home
- `seFrMyEvents` — My Events
- `seFrMyTasks` — My Tasks
- `seFrNearbyAccountsMap` — Nearby Accounts Map
- `seFrBusinessCardScanner` — Business Card Scanner
- `seFrLeadFirstTouch` — Lead First Touch
- `seFrVisitKanban` — Visit Kanban
- `seFrVisitQuickOrder` — Commande rapide (catalogue visuel)
- `seFrRecordActions` — Record Actions

☎️ Telesales cockpit

Inside-sales Home and order desk — KPIs, live cases and orders, kanban, order entry and customer history.

Primary persona: Telesales

- `seFrTelesalesRepHome` — Telesales - Rep Home
- `seFrKpiLauncher` — KPI Launcher
- `seFrKanbanBoard` — Kanban Board
- `seFrOrderEntry` — Order Entry
- `seFrCustomerOrders` — Customer Orders
- `seFrMyTasks` — My Tasks
- `seFrMetricTile` — Metric Tile

📈 Opportunity & pipeline

Opportunity record page — sales-cycle timeline, highlights, pipeline snapshot, contact and related-record cards, recommendations.

Primary persona: Sales

- `seFrRecordHighlights` — Record Highlights
- `seFrTimelinePhases` — Timeline Phases
- `seFrPipelineSnapshot` — Pipeline Snapshot
- `seFrContactCard` — Contact Card
- `seFrRelatedRecordCard` — Related Record Card
- `seFrRecordActions` — Record Actions
- `seFrSmartRecommendations` — Smart Recommendations
- `seFrServiceContracts` — Service Contracts

📦 Full pack

All components in one go — for when you want everything pre-loaded.

Primary persona: All

Every component in the library (47 total).

Release notes

Curated release history. Newest first.

v —

What's next on the roadmap

- 🤖 **Submit via org-connect (no-zip)** — connect your org, tick the components, the site bundles and validates for you. No more manual uploads.
- 🧪 **Auto-deploy + validity check** — each submission gets deployed to a sandbox to catch errors (broken components, missing deps, schema-unsafe). An MCP agent walks the contributor through fixes.
- 👥 **Contributor space** — personal page per contributor: track components, downloads, deploys, user feedback, new submissions in a few clicks.
- 🏆 **Gamification** — badges, leaderboard, per-component impact counters (downloads, deploys, likes). Make contributing rewarding and visible.
- 📊 **Admin / steering page** — centralized dashboard: full analytics, submission and feedback review, contributor management, moderation.

v2.9 — 2026-05-12

The site goes on Heroku, 1-click deploy to your demo org

The site is now hosted on Heroku. Connect your org via OAuth, pick components or a cookbook, deploy in seconds — multi-select, bundles, confirmation modal, progress tracking and a persistent summary after deploy. New "See it live" button drops you in the showcase org read-only with no login. Full server-side usage tracking (Postgres) to steer the lib. Submit / Feedback / Contact forms persisted in DB and notified by email. Submit with attachment (.zip or .txt, 2 MB max).

v2.8 — 2026-05-08

Prompt Launcher rebuilt + manifest-driven pipeline

The `seFrPromptLauncher` component replaces the old chat — it runs Salesforce Prompt Templates via Invocable Actions, with auto-injected record context and HTML / Markdown rendering. The library now runs on a central manifest that drives the README, deck, agent knowledge base and this site.

v2.7 — 2026-05-03

8 new components

A big batch of generic, reusable components covering pipeline, timelines, contacts, kanban, KPIs, files and alerts — `seFrPipelineSnapshot`, `seFrTimelinePhases`, `seFrContactsCarousel`, `seFrAccountHealth`, `seFrKanbanBoard`, `seFrMetricTile`, `seFrFilesGallery`, `seFrAlertsRibbon`.

v2.6 — 2026-04-30

Bilingual FR / EN across the board

Every component (except `seFrAgentforceHeader`) now exposes a `language` prop with full FR/EN dictionaries. App Builder values still win — a French SE demoing to a German prospect can override individual labels without switching the whole language.

v2.4 — 2026-04-29

My Events refonte

Compact sidebar layout, side-by-side overlapping events (Google Calendar style), live "now" line, Join button for Zoom / Teams / Meet / WebEx links.

v2.0 — 2026-04-24

Initial release

11 components extracted from the "Coup de Pâtes" B2B bakery demo, generalized into industry-neutral building blocks.

Contributors

SEs who authored or contributed components to the library. Lionel Braun is the maintainer; external contributors keep the *original author* credit on their components.

Lionel Braun — Maintainer

41 components.

- `seFrAccountHealth` — Account Health
- `seFrAccountStrategyPlan` — Account Strategy Plan
- `seFrActiveSegments` — Active Segments
- `seFrActivityFeed` — Activity Feed
- `seFrAgentforceHeader` — Agentforce Header
- `seFrAlertsRibbon` — Alerts Ribbon
- `seFrConsentManager` — Consent Manager
- `seFrContactsCarousel` — Contacts Carousel
- `seFrCustomerOrders` — Customer Orders
- `seFrCustomerSalesSummary` — Customer Sales Summary
- `seFrFieldRepHome` — Field Sales - Rep Home
- `seFrFilesGallery` — Files Gallery
- `seFrKanbanBoard` — Kanban Board
- `seFrKpiLauncher` — KPI Launcher
- `seFrMetricTile` — Metric Tile
- `seFrMyEvents` — My Events
- `seFrMyTasks` — My Tasks
- `seFrNearbyAccountsMap` — Nearby Accounts Map
- `seFrOrderEntry` — Order Entry
- `seFrOrderSummary` — Order Summary
- `seFrPipelineSnapshot` — Pipeline Snapshot
- `seFrPromptLauncher` — Prompt Launcher
- `seFrRecordActions` — Record Actions
- `seFrRecordHighlights` — Record Highlights
- `seFrRelatedRecordCard` — Related Record Card
- `seFrRevenueDashboard` — Revenue Dashboard
- `seFrSmartRecommendations` — Smart Recommendations
- `seFrSplashBanner` — Splash Banner
- `seFrTelesalesRepHome` — Telesales - Rep Home
- `seFrTerritoryMap` — Territory Map
- `seFrTimelinePhases` — Timeline Phases
- `seFrVisitCheckIn` — Visit Check-In
- `seFrVisitKanban` — Visit Kanban
- `seFrVisitPlan` — Visit Plan
- `seFrVisitProductCheck` — Visit Product Check
- `seFrVisitQuickOrder` — Commande rapide (catalogue visuel)
- `seFrVisitRestockOrder` — Réassort auto (ruptures relevé)
- `seFrVisitShelfCompliance` — Visit Shelf Compliance
- `seFrVisitShelfSpace` — Visit Shelf Space
- `seFrVisitSummaryAI` — Resume de Visite IA
- `seFrVoiceNoteTaker` — Voice Note Taker

Yann Jourdain (integrated 2026-10-23)

- `seFrBusinessCardScanner` — Business Card Scanner
- `seFrLeadFirstTouch` — Lead First Touch

Charly Ansel (integrated 2026-05-05)

- `seFrContactCard` — Contact Card

Thomas Plaindoux (integrated 2026-05-28)

- `seFrEngagementHistory` — Engagement History
- `seFrServiceContracts` — Service Contracts
- `seFrSubscribersList` — Subscribers List

About — design principles, reading a component page

Why this library

⚡

Faster demos

Drop a vetted component on a page, configure via App Builder, demo in minutes — not days.

✨

Prettier demos

Easy wow. Components are visually polished — subtle animations, consistent palette, design care — so your demos go beyond the raw Lightning standard.

🧩

Stay generic

Every component is industry-neutral. Customize via properties, not by editing code.

🤝

Share & contribute

One pool of components, designed and maintained by the SE France team. Yours belongs here too.

Releases & roadmap

The **What's new** page gathers the release history and the roadmap of upcoming evolutions — org-connect submission, contributor space, gamification, advanced admin page…

See what's new →

Want to contribute?

The library grows thanks to SEs who share their components. Add yours, or check out the SEs who already joined.

See the contributors

Design principles

- **Lightning base components first.** `lightning-card`, `lightning-button`, `lightning-datatable` & co. are translated by the platform — we use them wherever possible.
- **Custom strings become properties.** Anything that could reasonably need renaming is an `@api` with a French default.
- **Demo data as JSON / CSV props.** Dashboards with mock KPIs accept those as stringified JSON / CSV so SEs can swap the dataset in App Builder.
- **Currency & locale exposed.** `currencyCode` (default `EUR`) and `localeTag` (default `fr-FR`) are properties.
- **Standard fields first.** The library uses only Salesforce standard fields by default. No mandatory custom field.
- **Schema-safe Apex.** Where an optional custom field *can* enrich the UI, Apex checks for its existence before referencing it — deploys succeed regardless.
- **Bilingual FR / EN.** Every component exposes a `language` prop with FR/EN dictionaries baked in.

Component map by category

Last updated: 09/11/2026 · 47 components

CATEGORY	#	COMPONENTS
✨ **Transverse**	9	Activity Feed, Agentforce Header, Contact Card, Contacts Carousel, Files Gallery, Record Actions, Record Highlights, Related Record Card, Splash Banner
⚡ **Productivity**	5	My Events, My Tasks, Prompt Launcher, Smart Recommendations, Timeline Phases
💼 **Sales**	5	Account Health, Account Strategy Plan, Customer Orders, Order Entry, Pipeline Snapshot
🛠️ **Service**	5	Alerts Ribbon, Kanban Board, Order Summary, Service Contracts, Subscribers List
🎯 **Marketing**	4	Active Segments, Consent Manager, Customer Sales Summary, Engagement History
📊 **Dashboards & KPIs**	5	Field Sales - Rep Home, KPI Launcher, Metric Tile, Revenue Dashboard, Telesales - Rep Home
🚗 **Geo & Field**	3	Nearby Accounts Map, Territory Map, Voice Note Taker
🏬 **Retail Execution**	11	Business Card Scanner, Lead First Touch, Visit Check-In, Visit Kanban, Visit Plan, Visit Product Check, Commande rapide (catalogue visuel), Réassort auto (ruptures relevé), Visit Shelf Compliance, Visit Shelf Space, Resume de Visite IA

Reading a component page

Each component page carries:

- **Name** — human name displayed in the App Builder master label. Example: `Account Health`.
- **API name** — technical LWC identifier in camelCase. Example: `seFrAccountHealth`.
- **Tagline** — one-line pitch, what you'd use to sell the component in 5 seconds.
- **Chips** — 3-4 wow features. Examples: `SVG donut gauge`, `Native drag & drop`, `4 chart styles`.
- **Status badges** — labels at the top of the page. Examples: `● Stable`, `✨ New`, `🤖 AI-ready`, `📱 Mobile-ready`, `No Apex`.
- **Personas** — target teams. Examples: `📌 Sales`, `🚗 Field Sales`, `📞 Service`, `🤖 Agentforce`.
- **Targets** — page types where the component can land. Example: `Home · App · Record`.
- **Objects** — supported SObjects on Record Pages. Examples: `Account`, `Contact / Lead / Account`, `Any`.
- **Apex** — optional Apex dependencies, local or shared. Examples: `SE_FR_AccountHealthController`, `SE_FR_ImageFileController (shared)`, *none*.
- **Data mode** — how the component behaves towards org data. Values: `live` (reads/writes real records), `hybrid` (real if present, else mock), `mock` (100% prop-driven, no org dependency).
- **Pitch** — short paragraph that fleshes out the tagline.
- **SE benefit** — the demo angle that lands, the moment the prospect looks up from their screen.
- **Configurable settings** — 3-5 key props to tune in App Builder. Examples: `chartStyle`, `seriesJson`, `currencyCode`.
- **All properties** — full table (name, type, default, description) read straight from the component's `js-meta.xml`.
- **Quick install** — the 4 deploy methods (Deploy button, CLI, AI assistant, Lightning Studio).
- **Original author** / **Maintained by** — original author and library maintainer (shown when an external contributor wrote the component).
- **Categories** — the library category the component belongs to. Examples: `Sales`, `Service`, `Productivity`.
- **Featured in cookbook** — Cookbook recipes that bundle this component.
- **Often used with** — components of the same category typically dropped together.

Library standards, install methods, configuration, data setup

Quick install

Every component is a self-contained zip — LWC bundle plus dedicated Apex and any shared Apex it depends on. The fastest path:

1. Browse to Components and pick what you need.
2. Click **Connect to my org** in the top right — OAuth flow into your demo org.
3. Click **Deploy** on each component (or bundle them in the cart).
4. Open App Builder, drag the component on a page, configure in the property panel.

💡 Tip: if you prefer the terminal, jump straight to the Deploy via CLI section below.

Deploy via CLI

If you prefer the Salesforce CLI, every component zip is downloadable from the component page:

```
# 1. Download the zip from the component detail page
# 2. Unzip & deploy
unzip seFr<Name>.zip
sf project deploy start \
  --source-dir seFr<Name> \
  --target-org <your-alias>
```

AI assistant (Claude Code / Cursor)

The "no-effort" deploy: let your AI assistant handle everything. Works equally well with **Claude Code** or **Cursor** (or any IDE assistant that can execute shell commands).

1. Download the zip(s) from the component pages — one per component, or the full pack from the Cookbook.
2. Open your project in Claude Code or Cursor. Drag-and-drop the `.zip` file(s) straight into the chat.
3. Ask the assistant: *"Unzip these components and deploy them to my Salesforce org via the CLI"*. Mention the org alias if you have several (e.g. `SE_FR_SDO`).
4. The assistant unzips, identifies the SFDX structure and runs `sf project deploy start` with the right arguments. It also handles shared Apex if any.
5. Open App Builder, drag the components onto the right page, configure the properties.

Prereq: the Salesforce `sf` CLI installed and the target org authenticated (`sf org login web --alias <alias>`) — the assistant can do that for you if not already done.

💡 Why this rocks: zero command to type, zero folder-structure hassle. The assistant reads the library, understands the structure, and deploys. Best for bundling 5-10 components at once.

Lightning Studio (Chrome)

For a "manual" install directly from the browser, no CLI or IDE — handy when you don't have the CLI configured locally, or for a quick ad-hoc deploy.

1. Install the **Lightning Studio** Chrome extension (from the Chrome Web Store).
2. Download the component zip from its detail page, then unzip locally.
3. Log in to your target org. Click the Lightning Studio icon in the Chrome toolbar.
4. Create a new LWC with the same name (e.g. `seFrAccountHealth`). For each file in the bundle (`.js`, `.html`, `.css`, `.js-meta.xml`), open the local file, copy all content, paste it into the Lightning Studio editor, then **Save**.
5. If the component has Apex dependencies, repeat the same flow for *Apex Class* (create the class, paste each `.cls`, save).
6. Open App Builder, drag the `CCO FR – <Name>` component on the right page, configure the properties.
7. **Hard refresh** the page (`Cmd` + `Shift` + `R` on Mac, `Ctrl` + `Shift` + `R` on Windows) to force the compiled bundle to reload.

💡 Handy way to bootstrap or for Apex-free components. For multi-component deploys or proper CI, prefer the CLI or the site's Deploy button.

Configure in App Builder

Once the component is deployed, you find it in App Builder in the left palette under `CCO FR – <Name>`. Drag it onto the page, the right panel exposes every `@api` property of the component.

Palette naming conventions

- **LWC API name**: `seFr<Name>` (camelCase, no underscore). It's the bundle folder name and internal HTML tag.
- **App Builder master label**: `CCO FR – <Human name>`. This is what you see in the left palette and in the page title bar.
- **Apex class** (if applicable): `SE_FR_<Name>Controller`.

Input formats (props)

Complex-type properties accept two formats depending on the component:

- **CSV / pipe-separated**: most common. One line per item, fields split by `|`, items split by comma or newline. Example `seFrAlertsRibbon.rulesCsv`:

```
AnnualRevenue>1000000|warning|utility:warning|Compte stratégique|Voir|/lightning/o/Account/list
LastActivityDate<Today-30|info|utility:clock|Aucune activité depuis 30j||
```

- **JSON array**: for numeric or structured data. Example `seFrMetricTile.seriesJson`:

```
[2.1, 2.4, 2.7, 3.0, 3.2, 3.1, 3.3, 3.5, 3.4, 3.6, 3.7, 3.85]
```

Each property's *description* in App Builder spells out the expected format. If it says *"CSV"* or *"pipe-separated"*, use the first format. If it says *"JSON array"*, use the second.

Per-instance override

Every default is overridable per page: whatever you type in App Builder always wins over the component's baked-in default. You can have 3 instances of the same component on 3 pages with 3 different configs.

Bilingual FR / EN

All components support French and English. Each LWC exposes a `language` prop:

- `fr` — library default
- `en` — for international demos

Override per-instance in App Builder. Strings, dates, currency and computed labels (month names, status pills) all switch at runtime.

Data modes

Components fall into three data modes:

- `live` — reads / writes real records
- `hybrid` — real data + mock fallback when fields are missing or empty
- `mock` — fully scripted client-side, zero org dependency

This makes the components safe to drop on a brand-new org for a one-shot demo.

Named Credential setup

A few Agentforce-related components — typically `seFrPromptLauncher`, and the "Summarize" button on `seFrContactCard` / `seFrSmartRecommendations` — make authenticated REST callouts to the org's Salesforce API to run Prompt Templates. Without a Named Credential, these calls fail.

The expected Named Credential is `Agentforce_API` (library convention). It's used to reach any `/services/data/...` endpoint of the org: Prompt Templates, Agent API, custom REST.

Setup ~10 minutes, done **once per org**. The chain: Connected App (scopes `api chatbot_api refresh_token einstein_gpt_api`) → *Salesforce*-type Auth Provider reusing the Connected App credentials → OAuth 2.0 / Browser Flow External Credential pointing to the Auth Provider → Permission Set mapping the External Credential principal to your user → Named Credential `Agentforce_API` pointing to `https://<your-domain>.my.salesforce.com` via the External Credential.

Common pitfalls: **PKCE** is checked by default on both the Connected App AND the Auth Provider — uncheck on both. **External Credential** requires Spring '23 or later. **Permission Set mapping** is done via the *External Credential Principal Access* section, not via Object/Field permissions. The **Named Credential name** must match `Agentforce_API` exactly (case-sensitive).

Quick test from the Developer Console:

```
HttpRequest req = new HttpRequest();
req.setEndpoint('callout:Agentforce_API/services/data/v62.0/actions/custom/generatePromptResponse');
req.setMethod('GET');
HttpResponse res = new Http().send(req);
System.debug(res.getStatusCode() + ' ' + res.getBody().abbreviate(500));
```

Should return **200** + the prompt list. **401/403** = re-check External Credential / Permission Set. **404** = wrong URL. *"Named Credential not found"* = NC missing or misnamed.

Permission Sets for the running user

On top of the custom `Agentforce_API_Access` permset (which opens the External Credential), assign these standard Salesforce permsets to the user who needs to run the Prompt Templates:

- `EinsteinGPTPromptTemplateUser` — run Prompt Templates from UI and Apex.
- `Agentforce_API_Access` — the custom permset from the tutorial above, mapping the External Credential principal to the user.
- `EinsteinGPTSalesSummaries` *(optionnel)* — enhances some Contact / Opportunity summaries.

For `seFrContactCard` in AI Summary mode and `seFrPromptLauncher`, here are example standard Prompt Template API names to set on the `promptTemplateApiName` prop:

- `einstein_gpt__summarizeContact` — Contact summary (AI-enriched memo).
- `einstein_gpt__summarizeRecord` — generic summary for Account / Opportunity / Case.
- `einstein_gpt__draftEmailFromTemplate` — email draft from a template.

Fields read by the template must be **visible to the user** (FLS Read). Otherwise the merge context comes through empty and the template returns an empty response. If you see "Empty prompt response": check FLS on the read fields (`Title`, `Department`, `Email`, etc.).

Required Static Resources

Only one component needs an external Static Resource: `seFrAgentforceHeader`, which displays the Astro (Salesforce mascot) image as a background.

Good news: as of the current library version, the image is **auto-bundled** in `seFrAgentforceHeader.zip`. If you deploy via the site's **"Deploy to my org"** button or via `sf project deploy start -d _deploy/`, the Static Resource is created automatically. **No manual action needed.**

If you deploy via an alternative method (e.g. drag-drop in VS Code) that ignores the zip's `staticresources/` subfolder, create the resource manually:

1. Setup → Static Resources → **New**
2. Name : `astro_agentforce` (exact, case-sensitive — the LWC import points to this name)
3. Cache Control : `Public`
4. File : upload a PNG of Astro. The image is in `seFrAgentforceHeader.zip` (under `staticresources/astro_agentforce.png`) or in the repo source under `Original Assets/IMAGES/astro_agentforce.png`.
5. Save

Common gotchas (and fixes)

Issues that come up when setting up the library for the first time on an org. When in doubt, scroll back to this list.

- **« We couldn't access the credential(s) Agentforce_External_Auth »** → the `Agentforce_API_Access` permset isn't assigned to the running user. Setup → Permission Sets → Manage Assignments → Add.
- **"Empty prompt response"** → either `EinsteinGPTPromptTemplateUser` is missing, or FLS is blocking fields read by the template (`Title`, `Department`, etc.).
- **"Invalid reference astro_agentforce"** → the `astro_agentforce` Static Resource is missing in the target org. If you deploy via the site button, it's automatic. Otherwise see Static Resources above.

Compatibility with a standard SDO

Components run on the standard Salesforce data model with zero mandatory custom field. Everything they read (Account, Contact, Opportunity, Case, Order, Task, Event, ContentDocumentLink…) ships out of the box on any SDO.

A few components *can* use custom fields specific to the Cust360 SDO (customer signals) or MAPS (field visits). When absent, the component silently falls back to mock — no crash, no error.

- `seFrAccountHealth` — optionally uses `NPS__c` and `SDO_MAPS_Days_Since_Last_Visit__c` to enrich signals. Without these, the score is computed from standard fields only (`AnnualRevenue`, `LastActivityDate`, Open Cases, Orders).
- `seFrContactCard`, `seFrRelatedRecordCard` — optionally use `SDO_Cust360_Contact_Picture_URL__c`, `SDO_Cust360_ChurnRisk__c`. Without these, the avatar is manually uploadable (see below) and gauges are hidden.
- `seFrNearbyAccountsMap` — uses standard `BillingLatitude` / `BillingLongitude`. For the "days since last visit" indicator, uses `SDO_MAPS_Days_Since_Last_Visit__c` if present.

Simplified image upload

Components that display images (`seFrRecordHighlights`, `seFrContactCard`, `seFrRelatedRecordCard`, `seFrFilesGallery`) use **ContentDocument** attached to the record — not Static Resources or org-specific `ImageURL__c` fields.

Concretely: on the deployed component, click the avatar / image zone, pick a local file, the image is saved as a `ContentVersion` + `ContentDocumentLink` on the current record, and the rendition URL is used automatically. No admin setup, no external host, no custom field.

Shared logic lives in `SE_FR_ImageFileController` (shared Apex) — deployed once, reused by every image-aware component.

Make the demo shine — vary the data

On a fresh org, several Live components (Activity Feed, Pipeline Snapshot, Customer Orders, My Events…) look thin. For an optimal demo, **vary the data around your showcase account**:

- **Stagger dates**: Opportunity `CloseDate` across 6 rolling months, Order `EffectiveDate` across 24 months, future Events `StartDateTime` within the next 14 days, varied Task `ActivityDate`.
- **Mix statuses**: Opportunities across several `StageName` values (Prospecting / Qualification / Proposal / Closed Won), Cases across several `Status` values (New / Working / Escalated / Closed), Orders mix Activated / Draft.
- **Upload images**: Contact avatar via `seFrContactCard`, Account photo via `seFrRecordHighlights`, files via `seFrFilesGallery` — a few uploads are enough to add depth.
- **French addresses** (or whatever matches your demo): `BillingStreet`, `BillingCity`, `BillingPostalCode`, `BillingLatitude` / `BillingLongitude` on Accounts. `seFrNearbyAccountsMap` and `seFrTerritoryMap` light up.
- **Realistic activity on the showcase account**: 1-2 recent completed Tasks, 1-2 upcoming Events, 1-2 open Cases, 3-5 Opportunities across varied stages, a few Activated Orders. This feeds Activity Feed, Pipeline Snapshot, Customer Orders, Account Health in parallel.

💡 Tip: generate this data setup in seconds via **Claude Code** or **Cursor**. Point the assistant at your target org (authenticated CLI), give it your showcase Account Id, ask it to write an idempotent Apex script that staggers dates / statuses / Tasks / Events along the lines above. Run the script via `sf apex run` — no manual admin needed.

Naming conventions (internal)

Internal conventions used by the maintainer. You don't have to follow them to contribute — the maintainer adapts your components to the standard.

- LWC folder / JS class : `seFr` + PascalCase (ex : `seFrAccountStrategyPlan`)
- Apex class : `SE_FR_` + PascalCase (ex : `SE_FR_AccountHealthController`)
- App Builder master label : `CCO FR – <Human name>`
- Custom strings : French defaults, overridable via `language` or explicit prop

Schema-safe Apex

Where an optional custom field *can* enrich the UI (e.g. `NPS__c`), Apex checks `Schema.SObjectType.X.fields.getMap()` before referencing it so deploys succeed regardless of whether the field exists.

Library defaults

- `language` : `fr`
- `currencyCode` : `EUR`
- `localeTag` : `fr-FR`
- No UI copy ever reveals mock/demo mode

Component · Account Health (`seFrAccountHealth`)

> **API name:** `seFrAccountHealth` · **Categories:** Sales · **Surfaces:** RecordPage · **Objects:** Account · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_AccountHealthController

Summary: Quantitative account health score (0-100) with verdict level and weighted positive / negative signals.

Key configurable props / settings of seFrAccountHealth:

- Score field, signal fields (CSV)
- Color thresholds
- Card title override

SE benefit: Reads Cust360 SDO standard fields by default (e.g. churn risk, sentiment, NPS). On orgs without those fields, falls back to mocked signals — never crashes, always demo-ready.

seFrAccountHealth (Account Account Health)

B2B — SVG donut gauge (0-100) + verdict level (Excellent / Healthy / Watch / At risk / Critical) + list of positive / negative signals used in the computation. Complementary to `seFrAccountWeather` (qualitative verdict) — this one is quantitative. Bilingual EN / FR.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account
- **App Builder label:** `CCO FR – Account Health`

Apex dependency

`SE_FR_AccountHealthController.getSnapshot(accountId)` . Schema-safe on optional custom fields (`NPS__c` , `SDO_MAPS_Days_Since_Last_Visit__c`).

Scoring logic

Starts at 50 (neutral). Each signal adds / subtracts weighted points:

- Revenue ≥ threshold → +10 ; below → −5
- Recent activity → +10 ; stale → −10
- Recent visit → +5 ; stale → −5
- Open Opportunities → +10 per signal
- Open Cases (≥3) → −15 ; any open → −5
- Recent Orders (90d) → +10 ; none → −5
- NPS ≥ 9 → +10 ; ≤ 6 → −10
- ≥3 Contacts mapped → +3

Clamped to [0, 100]. Level thresholds: ≥85 Excellent, ≥65 Healthy, ≥45 Watch, ≥25 At risk, <25 Critical.

Properties

NAME	DEFAULT	DESCRIPTION
`language`	`en`	`en` or `fr`.
`cardTitle`	—	Override the default ("Account Health" / "Santé du compte").
`revenueThreshold`	500000	AnnualRevenue below this is a negative signal.
`inactivityThresholdDays`	45	
`staleVisitThresholdDays`	60	Uses `SDO_MAPS_Days_Since_Last_Visit__c` — skipped if absent.

Install

1. Deploy `classes/SE_FR_AccountHealthController.cls`.
2. Unzip `seFrAccountHealth.zip`, deploy the LWC bundle.
3. Drop `CCO FR – Account Health` on an Account record page.

Data enrichment prerequisites

The score is only as rich as the data. On a fresh SDO, many Accounts will score 50 (neutral — no signal fires). To get a varied demo:

- Set **`AnnualRevenue`** on the showcase Account (above or below the threshold depending on the story).
- Ensure **`LastActivityDate`** is recent. This field is derived from Tasks / Events — create at least one recent Task if needed.
- Have **at least 1 open Opportunity** and **1 recent Order (≤90 days)**.
- Optional: if `NPS__c` exists on the org, populate it with 9+ or ≤6 to trigger the NPS signal.

Component · Account Strategy Plan (`seFrAccountStrategyPlan`)

> **API name:** `seFrAccountStrategyPlan` · **Categories:** Sales · **Surfaces:** RecordPage · **Objects:** Account · **Data mode:** mock · **Mobile-ready:** no · **Apex:** none

Summary: Narrative account plan with editable KPIs, target gauge, SWOT 2x2 and quarterly action plan.

Key configurable props / settings of seFrAccountStrategyPlan:

- Section labels & default content
- Owner avatar override

SE benefit: Inline editable from the page — no record write. Great visual for "strategic-account" demo moments, even on bare orgs.

seFrAccountStrategyPlan

Narrative account plan for the Account record page. Four blocks:

1. **Performance snapshot** — 4 KPI tiles + annual-target progress bar.
2. **Strategic positioning** — SWOT in a 2×2 grid (Strengths / Weaknesses / Opportunities / Threats), each card with bullets.
3. **Action plan** — rows with a quarter chip, action + owner, and a color-coded status pill.
4. **Strategic notes** — free text.

All values are **pre-filled from App Builder defaults** and **editable on the page** via the "Edit" button in the card header — SEs can tune the content live during a demo.

Where to drop it

- **Target:** Lightning Record Page
- **Object:** Account
- **App Builder label:** `CCO FR – Account Strategy Plan`

Apex dependencies

None.

How editing works

- Click the pencil icon in the header → enters edit mode.
- All fields (KPIs/target values, SWOT bullets, action rows, notes) become editable inline.
- "Reset" restores the App Builder defaults. "Done editing" returns to the narrative view.
- The footer "Save plan" / "Submit to manager" fire toasts (demo-only; no persistence).

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle` / `cardIcon`	String	`Account Strategy & Action Plan` / `standard:goals`	Card header.
`currencyCode` / `localeTag`	String / String	`USD` / `en-US`	Currency & locale for formatting.
`kpiPreviousYearLabel` / `Value`	String / Int	`Revenue (Y-1)` / `45000`	KPI 1 (primary — accent color).
`kpiRunRateLabel` / `Value`	String / Int	`Run rate` / `3800`	KPI 2 (rendered as `X / mo`).
`kpiPotentialLabel` / `Value`	String / Int	`Portfolio potential` / `80000`	KPI 3.
`kpiShareLabel` / `Value`	String / String	`Share of wallet` / `56%`	KPI 4 (raw text).
`annualTargetLabel` / `Default`	String / Int	`Annual target` / `55000`	Target for the progress bar.
`ytdRevenueLabel` / `Default`	String / Int	`YTD revenue` / `38000`	Current-year progress value.
`strengthsCsv`	String	see meta.xml	SWOT — Strengths bullets (comma- or newline-separated).
`weaknessesCsv`	String	see meta.xml	SWOT — Weaknesses bullets.
`opportunitiesCsv`	String	see meta.xml	SWOT — Opportunities bullets.
`threatsCsv`	String	see meta.xml	SWOT — Threats bullets.
`actionPlanCsv`	String	see meta.xml	Rows as `Quarter|Action|Owner|Status`, comma-separated. Status: `Not started`, `In progress`, `On track`, `At risk`, `Done`.
`strategyNotesDefault`	String	see meta.xml	Strategic notes — default text.

Install

1. Unzip `seFrAccountStrategyPlan.zip`, deploy the LWC bundle.
2. Drop `CCO FR – Account Strategy Plan` on an Account record page.
3. Configure the defaults to match the account you're showing.

Legacy

Props `logisticOptionsCsv`, `competitorOptionsCsv`, `riskOptionsCsv`, `leversOptionsCsv` are kept for backwards compatibility with v1 pages but are no longer used by the new UI.

Component · Active Segments (`seFrActiveSegments`)

> **API name:** `seFrActiveSegments` · **Categories:** Marketing · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Compact panel showing the marketing / Data Cloud segments the record belongs to, as colored badges.

Key configurable props / settings of seFrActiveSegments:

- Up to 6 segment slots (label, audience size, last-updated)

SE benefit: Sets a marketing-aware tone on a Contact page without requiring a Data Cloud connection — props-driven storytelling.

seFrActiveSegments (Active Segments)

Displays a short, configurable list of marketing / Data Cloud segments as badges inside a `lightning-card`. The card title automatically shows the segment count: `Active Segments (4)`.

Where to drop it

- **Targets:** Lightning Record Page, App Page, Home Page
- **App Builder label:** `CCO FR – Active Segments`

Apex dependencies

None.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`Active Segments`	Title prefix — shown as `<title> (N)`.
`cardIcon`	String	`standard:groups`	SLDS icon identifier for the card header.
`segmentsCsv`	String	`Back-to-School Parents, Sport Sun-wear Affinity, Progressive Lens Switchers, Web-to-Store Frequent`	Comma-separated segment names. Each becomes a badge.

Install

1. Unzip `seFrActiveSegments.zip`, deploy the LWC bundle.
2. Drop `CCO FR – Active Segments` on any page and set `segmentsCsv` to the customer's segments.

Origin

Genericized from the `krysActiveSegments` Krys demo component.

Component · Activity Feed (`seFrActivityFeed`)

> **API name:** `seFrActivityFeed` · **Categories:** Transverse · **Surfaces:** RecordPage · **Objects:** Account, Contact · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_ActivityFeedController

Summary: Unified activity timeline aggregating 16+ Salesforce record types in a single feed with rich filtering.

Key configurable props / settings of seFrActivityFeed:

- Days back / forward window
- Include related contacts
- Object types displayed

SE benefit: Pulls from `Task`, `Event`, `EmailMessage`, `VoiceCall`, `MessagingSession`, `LiveChatTranscript`, `Order`, `Case`, `Opportunity`, `Quote`, `Contract`, `Visit`, `ContentDocumentLink`, `FeedItem`, `SurveyResponse` — and uses business-meaningful dates (CloseDate, EffectiveDate, StartDate) instead of CreatedDate.

seFrActivityFeed

Aggregated activity timeline for an Account or Contact. Shows **16+ record types** in a unified feed: Tasks, Events, EmailMessages, VoiceCalls, MessagingSessions, LiveChatTranscripts, Orders, Cases, Opportunities, Quotes, Contracts, Visits, Files (ContentDocument), Chatter posts (FeedItem), Survey Responses.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Contact
- **App Builder label:** `CCO FR – Activity Feed`

Apex dependency

- `SE_FR_ActivityFeedController.getActivityFeed(recordId, includeRelatedContacts, daysBack, daysForward)` — returns a unified `List<FeedEntry>`. Schema-safe: each object is queried only if present and accessible; any failure is caught per-source so a missing object never breaks the whole feed.

Feed sources

SOURCE	ACTIVITY DATE	LINK ROUTE
`Task`	`ActivityDate` (fallback `CreatedDate`)	`WhatId` / `WhoId`
`Event`	`StartDateTime`	`WhatId` / `WhoId`
`EmailMessage`	`MessageDate`	`RelatedToId = recordId`
`VoiceCall`	`CallStartDateTime`	`AccountId` / `RelatedRecordId`
`MessagingSession`	`StartTime`	`AccountId` / `ContactId`
`LiveChatTranscript`	`StartTime`	`AccountId` / `ContactId`
`Order`	`CreatedDate`	`AccountId`
`Case`	`CreatedDate`	`AccountId` / `ContactId`
`Opportunity`	`CreatedDate`	`AccountId`
`Quote`	`CreatedDate`	`Opportunity.AccountId`
`Contract`	`CreatedDate`	`AccountId`
`Visit`	`ActualVisitEndTime` if completed, else `PlannedVisitStartTime`	`AccountId`
`ContentDocumentLink`	`SystemModstamp`	`LinkedEntityId = recordId`
`FeedItem`	`CreatedDate`	`ParentId = recordId`
`SurveyResponse`	`SystemModstamp`	`SurveySubjectId = recordId`

On an **Account**, enabling `includeRelatedContacts` (default) also pulls activities of the account's related Contacts. On a **Contact**, the feed always includes the contact's own activities + Orders/Cases/Opportunities of its Account.

UI behavior

- Top toolbar: **Log a Call / Email / New Task / New Event / Schedule Visit** — each triggers the standard quick action of the object (via `standard__quickAction`). The exact button set is configurable.
- Filter panel (toggle with the funnel icon): date range (all / next 7d / past 7d / past 30d), activity types (checkbox grid), sort asc/desc.
- Items are grouped: **Upcoming & pending** section at the top (anything `isFuture = true`), then one group per month for past items.
- Items are collapsed by default — click a row to expand and see the description (with formatting preserved).
- `Task.Description` is rendered verbatim on expand — so notes saved by `seFrVoiceNoteTaker` are fully visible.
- Refresh button re-invokes the wired Apex.
- "Expand all" / "Collapse all" toggles every item at once.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`Activity Feed`	
`cardIcon`	String	`standard:activations`	
`includeRelatedContacts`	Boolean	`true`	On Account pages, also pull activities of the account's Contacts.
`defaultDaysBack`	Integer	`365`	History window.
`defaultDaysForward`	Integer	`90`	Future window (events, pending tasks, planned visits).
`defaultSortDesc`	Boolean	`true`	Newest first.
`expandedByDefault`	Boolean	`false`	Expand all items on load.
`enabledActionsCsv`	String	`LogACall,Email,NewTask,NewEvent,NewVisit`	Comma-separated list of toolbar quick-action buttons. API names must match quick actions available on the object's page layout.

Install

1. Deploy `classes/SE_FR_ActivityFeedController.cls`.

2. Unzip `seFrActivityFeed.zip`, deploy the LWC bundle.
3. Drop `CCO FR – Activity Feed` on an Account or Contact record page.
4. Verify that the Account/Contact page layout exposes the quick actions you listed in `enabledActionsCsv` — the toolbar buttons launch the standard quick actions of the object.

Prerequisites — user timezone

The `defaultDaysBack` / `defaultDaysForward` filters compute date windows using the **running user's timezone**, and the grouping by month ("April 2026", etc.) displays each activity's date in the user timezone. Most Salesforce SDOs ship with the org set to `America/Los_Angeles` — if your user also inherits that timezone, activities may appear under unexpected months (or the wrong side of "Upcoming").

Before using the component, set **your user's timezone to your local value**:

- Setup → **Personal Information** → *Time Zone* → pick your local value (e.g. `(GMT+01:00) Central European Time (Europe/Paris)` / `(GMT+02:00)` in summer).
- Save, refresh the tab.

You don't need to change the **org** timezone — only the user timezone.

Known limitations

- Quick action names (`LogACall`, `Email`, `NewTask`, `NewEvent`, `NewVisit`) are the **global** API names. Some orgs may use different action names (e.g. custom quick actions) — adjust `enabledActionsCsv` accordingly.
- The component does not deduplicate activities that exist on both the account and a related contact (could appear twice if linked to both via `WhatId` and `WhoId` on the same Task). That's Salesforce's own standard behavior.
- `ListEmail` and `SMS` don't have dedicated SObjects — they show up as Tasks with `TaskSubtype = 'ListEmail'` / `'Call'` / custom subtypes.

Component · Agentforce Header (`seFrAgentforceHeader`)

> **API name:** `seFrAgentforceHeader` · **Categories:** Transverse · **Surfaces:** HomePage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Astro-themed Home page header with a search / dictation box that forwards questions to the Agentforce panel.

Key configurable props / settings of seFrAgentforceHeader:

- Title / subtitle
- CTA label + URL
- Astro animation toggle

SE benefit: Speech-to-text via the browser API — speak a question, click "Send", and the transcribed text lands in your clipboard. Paste it into the standard Agentforce panel for a fluid AI demo entry. (No real Agentforce integration — the UI fakes the gesture.)

seFrAgentforceHeader

Home-page header with a floating Astro image and a search/dictation box that forwards the user's question to the standard Agentforce / Einstein panel.

Where to drop it

- **Target:** Lightning Home Page
- **App Builder label:** `SE_FR – Agentforce Header`

Dependencies

- Static resource named `astro_agentforce` containing the Astro image (PNG).
- The org must have the Agentforce / Einstein utility button available in the app — the component finds the button by its `title` attribute (containing "Agentforce" or "Einstein") and triggers a click.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`speechLocale`	String	`en-US`	BCP 47 locale for the browser's Web Speech Recognition API (`fr-FR` , `es-ES` , `de-DE` , …).
`idlePlaceholder`	String	`Ask me a question…`	Input placeholder when idle.
`listeningPlaceholder`	String	`Listening…`	Input placeholder while dictating.

Install

1. **Create the static resource** (required — otherwise the component fails to compile):

- Setup → **Static Resources** → *New*.
- Name: `astro_agentforce` , Cache Control: Public.
- Upload a PNG of Astro (Salesforce mascot). Save.

1. Unzip `seFrAgentforceHeader.zip` , deploy the LWC bundle.
2. Drop `SE_FR — Agentforce Header` on the Home page.

Component · Alerts Ribbon (`seFrAlertsRibbon`)

> **API name:** `seFrAlertsRibbon` · **Categories:** Service · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Account, Contact, Case, Opportunity, Lead, Order, Contract · **Data mode:** mock · **Mobile-ready:** no · **Apex:** none

Summary: Configurable alerts ribbon combining declarative record-driven rules with always-on static banners.

Key configurable props / settings of seFrAlertsRibbon:

- `rulesCsv` · field-based rules (Record Page only)
- `staticAlertsCsv` · always-on alerts (any page)
- `visualStyle` · inline / card
- `alertVariant` · banner / solid / minimal
- `density` · comfortable / compact
- `stickyOnScroll`

SE benefit: Rule-driven mode evaluates a tiny DSL against the current record's fields ("AnnualRevenue<500000|warning|...") — drop on any record page, the right alert pops on the right account, no code.

CCO FR - Alerts Ribbon (`seFrAlertsRibbon`)

Configurable alerts ribbon. Two complementary sources for the alert list:

- **Rule-driven alerts** (Record Page only) — declarative rules evaluated against the current record's fields.
- **Static alerts** (any page) — always shown, useful for system status banners, demo-mode disclaimers, release announcements.

3 visual variants (banner / solid / minimal), 2 densities (comfortable / compact), 4 severities (info / success / warning / error), optional sticky-on-scroll behavior.

Targets

- `lightning__RecordPage`
- `lightning__HomePage`
- `lightning__AppPage`

Quick start

Drop the component on a record page, paste this in **Rule-driven alerts**:

```
AnnualRevenue<500000|warning||Small account — prioritize upsell|Open opportunities|/lightning/o/Opportunity/list
LastActivityDate isBlank|info||No activity logged in the last 30 days||
Industry=Banking|success||Banking — flag for compliance review||
```

You get 3 stacked banners, color-coded.

Rule grammar

Format (one per line, or comma-separated):

```
<field><op><value>|<severity>|<icon>|<message>|<ctaLabel>|<ctaUrl>
```

TOKEN	DESCRIPTION
`<field>`	API name of a field on the current SObject (e.g. `AnnualRevenue`, `Industry`, `LastActivityDate`)
`<op>`	`=` `!=` `>` `<` `>=` `<=` `contains` `startsWith` `endsWith` `isBlank` `isNotBlank`
`<value>`	The value to compare against (omitted for `isBlank` / `isNotBlank`)
`<severity>`	`info` (default) / `success` / `warning` / `error`
`<icon>`	Optional SLDS icon name. Falls back to a severity-default icon when empty
`<message>`	The text shown in the banner
`<ctaLabel>`	Optional CTA button label
`<ctaUrl>`	Optional CTA URL — relative (`/lightning/...`) or absolute (`https://...`)

Static alerts

Format (one per line):

```
<severity>|<icon>|<message>|<ctaLabel>|<ctaUrl>
```

Static alerts ignore the record context. Use them on Home / App pages, or to add demo-mode banners on top of rule-driven ones on a Record page.

Visual variants

ALERTVARIANT	LOOK
`banner` (default)	Soft pastel background + accent border-left + saturated icon
`solid`	Saturated background, white text — high-contrast attention grabber
`minimal`	White background, accent bar only — ultra-sober

Density

DENSITY	BEHAVIOR
`comfortable` (default)	Full message, wraps to multiple lines
`compact`	Single line, message truncated with ellipsis

Sticky on scroll

Set `stickyOnScroll = true` to keep the ribbon pinned to the top of the page on scroll. Useful for warning / error severity that shouldn't scroll out of view.

Properties

PROPERTY	DEFAULT	DESCRIPTION
`language`	`fr`	`fr` / `en`
`rulesCsv`	–	Rule-driven alerts (Record Page only)
`staticAlertsCsv`	–	Static alerts (any page)
`visualStyle`	`inline`	`inline` (no card chrome) / `card` (wrapped in `lightning-card` with title + count pill)
`alertVariant`	`banner`	`banner` / `solid` / `minimal`
`density`	`comfortable`	`comfortable` / `compact`
`cardTitle`	–	Override (used when `visualStyle = card`)
`cardIcon`	`standard:announcement`	SLDS icon name (used when `visualStyle = card`)
`hideDismissButton`	`false`	Hide the per-alert dismiss ×
`maxAlerts`	`0`	Cap (0 = unlimited)
`stickyOnScroll`	`false`	Pin the ribbon at the top of the page on scroll

SE benefits

- **No Apex required** — rules and static alerts are configured entirely in App Builder.
- **Schema-safe** — fields referenced by rules are queried via LDS; missing fields silently skip the rule.
- **Demo storytelling** — type the right rule and a banner appears the moment the SE opens the right account ("This account is at risk", "Renewal due in 14 days").

Component · Business Card Scanner (`seFrBusinessCardScanner`)

> **API name:** `seFrBusinessCardScanner` · **Categories:** Retail Execution · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Drop business card photos, get editable lead cards pre-filled by a simulated OCR, then bulk-create the leads.

Key configurable props / settings of seFrBusinessCardScanner:

- language - 'fr' (default) or 'en'
- cardTitle / cardIcon - override title and standard:* icon
- simulatedDelayMs - fake OCR latency (default 1200)
- maxCards - cap on cards in the list (default 10)
- autoCreate - pulse the create button once a card is ready

SE benefit: Demo the "card to lead" capture story at a trade show or in a store visit on any dev org, with no Apex, no prompt template and no setup.

CCO FR - Business Card Scanner

Original source: Yann Jourdain, "Cartes de visite → Leads" (cvCapture / cvDropZone / cvLeadCard + Apex + Agentforce prompt)
Ported to library by: Lionel Braun
Library-integrated: 2026-10-23

Consolidated into a single bundle. The original three LWCs are inlined, and the Apex, Flow, GenAI prompt template and custom labels are removed.

How it works

1. Empty state shows a dashed dropzone. Drop images or click to select (hidden `input type=file`, `image/*`, multiple).
2. Each file becomes a card tile with a base64 preview (FileReader) and a "processing" skeleton.
3. After `simulatedDelayMs`, the tile is filled with one of 4 rotating fake personas (Dubois, Moreau, Lefebvre, Petit). Non-image files end in an error state with a Retry button.
4. Fields (first name, last name, company, title, email, mobile, phone) are editable. Last name and company are required for a card to count as ready.
5. "Create N leads" waits 1 second, shows a success toast, and removes the created cards. No record is actually created.

Mock mode

No Apex, no callouts, no custom labels. Renders on any dev-edition org. To go real, replace the timer in `_startOcr` with the original Agentforce OCR call and the timer in `handleCreate` with a Lead insert.

Properties

PROPERTY	DEFAULT	NOTES
language	fr	fr or en
cardTitle	(dictionary)	Title override
cardIcon	standard:lead	Must be a standard:* icon
simulatedDelayMs	1200	Fake OCR latency
maxCards	10	Extra files are ignored with a warning toast
autoCreate	false	Pulses the create button when a card is ready

Component · Consent Manager (`seFrConsentManager`)

> **API name:** `seFrConsentManager` · **Categories:** Marketing · **Surfaces:** RecordPage · **Objects:** Contact, Lead, Account · **Data mode:** live · **Mobile-ready:** yes · **Apex:** none

Summary: Per-channel GDPR consent toggle panel binding each channel to a boolean field on the current record.

Key configurable props / settings of seFrConsentManager:

- Channels CSV (override) · format `label|fieldApiName|inverted`
- Toggle / success / error label overrides
- Card title / icon override

SE benefit: Default channels map onto Salesforce standard fields: `HasOptedOutOfEmail`, `DoNotCall`, `HasOptedOutOfFax` (used as a stand-in for WhatsApp opt-out). Drop on Contact / Lead / Account → it just works, no custom field required.

seFrConsentManager (Consent Manager)

Toggle panel to manage per-channel consent / GDPR opt-in on a record. Each channel binds to a boolean field on the current object; the component loads the current value, flips it on toggle, and saves back via `lightning/uiRecordApi` — no Apex required.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Contact (default), Lead, Account — works on any object that has the fields configured in `channelsCsv`.
- **App Builder label:** `CCO FR – Consent Manager`

Apex dependencies

None.

Default channels (zero custom field)

CHANNEL	FIELD	INVERTED?
Email	`HasOptedOutOfEmail`	✅ (stored as opt-out)
Phone	`DoNotCall`	✅
WhatsApp	`HasOptedOutOfFax`	✅ (field repurposed — lets the demo run on a vanilla org)

With these defaults the component deploys on any Contact record page without creating a single custom field.

Sample mode (no config needed)

When `channelsCsv` is left empty, the component renders a **sample set of channels** (Email / SMS / Phone / WhatsApp… with realistic allowed/refused states, localised via `language`) so the card is never empty on a fresh page. Toggles are read-only in this mode. Set `channelsCsv` to bind the real fields.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`Contact Preferences & GDPR`	Card header title.
`cardIcon`	String	`standard:task2`	Card header icon.
`channelsCsv`	String	*(empty → sample channels)*	One channel per comma-separated item. Format: `label|fieldApiName|inverted`.
`toggleActiveLabel`	String	`Allowed`	Shown when a toggle is on.
`toggleInactiveLabel`	String	`Refused`	Shown when a toggle is off.
`successMessage`	String	`Contact preferences updated.`	Success toast text.
`errorMessage`	String	`Update failed.`	Error toast text.

`channelsCsv` format

Each channel is three pipe-separated parts, channels separated by commas:

```
<label>|<fieldApiName>|<inverted>
```

- `label` — toggle label shown in the UI.
- `fieldApiName` — the boolean field on the current object.
- `inverted` — `true` when the field stores **opt-out** semantics (e.g. `HasOptedOutOfEmail`, `DoNotCall`). The toggle shows the inverse so that "on" always means "consent given".

Examples:

- Custom opt-in fields: `Email|Email_OptIn__c|false,SMS|SMS_OptIn__c|false`
- Mix of standard and custom: `Email|HasOptedOutOfEmail|true,SMS|SMS_OptIn__c|false,Mail|HasOptedOutOfMail|true`

Install

1. Unzip `seFrConsentManager.zip`, deploy the LWC bundle.
2. If you use custom opt-in/opt-out fields, make sure they exist on the object and the running user has edit access.
3. Drop `CCO FR – Consent Manager` on a Contact / Lead / Account record page and set `channelsCsv` to match the customer's data model.

Known caveats

- `HasOptedOutOfFax` **re-purposed for WhatsApp** in the defaults — purely a demo convenience to avoid requiring a custom field. Replace with a real `WhatsApp_OptIn__c` in production demos if the customer has one.
- The component needs the running user to have **edit** access to each backing field; otherwise `updateRecord` fails and the toggle reverts.

Origin

Genericized from the `krysConsentManager` Krys demo component.

Component · Contact Card (`seFrContactCard`)

> **API name:** `seFrContactCard` · **Categories:** Transverse · **Surfaces:** RecordPage · **Objects:** Contact, Account, Case, Opportunity, Order, Lead · **Data mode:** hybrid · **Mobile-ready:** yes · **Apex:** SE_FR_ContactCardController, SE_FR_ImageFileController

Summary: Visual contact card with animated waves, avatar, address, configurable gauges and optional Einstein prompt summary.

Key configurable props / settings of seFrContactCard:

- Up to 3 gauges (label, field, icon, lower/higher-better semantics)
- Image · URL field OR click-to-upload File
- Customer ID line (toggle + field)
- Animated wave colors / theme accent
- Einstein prompt summary · default `einstein_gpt__summarizeContact` (the SDO-shipped template, not a true Salesforce standard)

SE benefit: Built-in "Summarize" button using the SDO-shipped contact-summary prompt — drop on a Contact / Case / Account page and you get an AI inline summary out of the box. Click the avatar to upload a contact photo (no schema work required).

CCO FR - Contact Card

Original author: Charly Ansel
Maintained in library by: Lionel Braun
Genericized / library-integrated: 2026-05-05

Visual contact card with an animated-waves background, avatar, name / email / phone, mailing address and up to 3 configurable gauges. Auto-resolves the Contact Id from the current record page (Contact → self, Account → Person/primary Contact, Case/Opportunity/Order → `ContactId`, Lead / custom objects → `Contact__c`).

Why SEs love it

- **Portrait-style card** — signature animated waves background (toggleable) makes the card stand out on a record page.
- **Works out-of-box** — schema-safe Apex: every optional field (image URL, customer ID, gauges) is skipped silently if absent.
- **Same upload pattern as Record Highlights** — `imageMode=file` stores the avatar as a standard File on the Contact, click to replace. No custom schema required.
- **Up to 3 gauges** configurable at will (label + field API name + icon).
- **Optional Einstein prompt summary** — off by default; when enabled, a "Summarize" button runs a chosen Prompt Template inline.

Properties (highlights)

PROPERTY	DEFAULT	DESCRIPTION
`language`	`fr`	`fr` or `en`.
`cardTitle`	"Contact"	Override only if needed.
`imageMode`	`field`	`field` (URL in a field on Contact) or `file` (click to upload, same logic as Record Highlights).
`imageFieldApiName`	`SDO_Cust360_Contact_Picture_URL__c`	Image URL field when `imageMode=field`. Schema-safe.
`showCustomerId` / `customerIdFieldApiName`	false / `SDO_Cust360_Id__c`	Extra "ID" line.
`gauge1Label` / `gauge1FieldApiName` / `gauge1Icon`	`Churn risk` / `SDO_Cust360_ChurnRisk__c` / `utility:warning`	Primary gauge.
`gauge2*` / `gauge3*`	*(empty)*	Up to 2 additional gauges, all optional.
`showWaves`	false	Animated wave shapes in the background.
`isDarkBackground` / `backgroundColor` / `backgroundImageUrl`	false / — / —	Look & feel.
`waveColorOne` / `waveColorTwo`	greys	Colors of the two waves.
`enablePromptSummary`	false	Turn on to show a "Summarize" button.
`promptTemplateApiName` / `promptInputApiName` / `autoPromptOnLoad`	— / `Input:Contact` / false	Einstein Prompt Template settings when the summary is enabled.

Data enrichment prerequisites

- Out-of-box works on any Contact with the standard fields (FirstName, LastName, Email, Phone, MailingAddress).
- For the image to show via `imageMode=field`, the Contact must have the SDO Cust360 picture field populated (SDO-specific) OR the SE can switch to `imageMode=file` and upload an image manually.
- For the churn gauge to show, the Contact must have a value in `SDO_Cust360_ChurnRisk__c` (0-100). Otherwise the gauge is silently hidden.
- The Einstein prompt summary requires an existing Prompt Template in the org with the right input name.

Apex dependencies

- `SE_FR_ContactCardController` — Contact Id resolver, schema-safe Contact fetch, Einstein prompt wrapper.

- `SE_FR_RecordHighlightsController` — shared with Record Highlights for the File-based image pattern (only used when `imageMode=file`).

Credit

The original design (animated waves, avatar layout, gauge + Einstein prompt) comes from Charly Ansel's `canContactCard` bundle. This library version is a genericized, bilingual, schema-safe rewrite that merges the parent/child pair into a single component and aligns naming + conventions with the SE_FR library. The prompt logic is preserved but gated off by default.

Component · Contacts Carousel (`seFrContactsCarousel`)

> **API name:** `seFrContactsCarousel` · **Categories:** Transverse · **Surfaces:** RecordPage · **Objects:** Account · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_ContactsCarouselController, SE_FR_ImageFileController

Summary: Horizontal carousel of an Account's Contacts with avatars, role badges and quick Email / Call actions.

Key configurable props / settings of seFrContactsCarousel:

- Visible contact count
- Card field list
- Quick actions

SE benefit: Visual replacement for the standard Contacts related list — much more demo-friendly than a flat table.

seFrContactsCarousel (Contacts Carousel)

B2B — Horizontal carousel of the Contacts linked to the current Account. Each card shows an avatar (photo or initials fallback), name, title, an optional **role badge** (Champion / Detractor / DMU) and Email / Call quick actions. Bilingual EN / FR.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account
- **App Builder label:** `CCO FR – Contacts Carousel`

Apex dependency

`SE_FR_ContactsCarouselController.getContacts(accountId, limitCount, orderBy)`.

Properties

NAME	DEFAULT	DESCRIPTION
`language`	`en`	`en` or `fr`.
`cardTitle`	—	Override the default.
`limitCount`	24	Max Contacts fetched (1–100).
`orderBy`	`LastActivityDate DESC NULLS LAST`	Whitelisted: `LastActivityDate DESC NULLS LAST` / `Name ASC` / `CreatedDate DESC` / `Title ASC NULLS LAST`.
`visibleCount`	4	Cards shown per page. Arrows paginate by this amount.
`badgesCsv`	—	Per-contact badge overlay. Format: `Eliott Mercier=Champion|#2e844a,Mathieu Bernard=Detractor|#ba0517`. Match is case-insensitive on `Contact.Name`.
`hideNewContactButton`	`false`	

Install

1. Deploy `classes/SE_FR_ContactsCarouselController.cls`.
2. Unzip `seFrContactsCarousel.zip`, deploy the LWC bundle.
3. Drop `CCO FR – Contacts Carousel` on an Account record page.

Data enrichment prerequisites

- Contacts should have **Title** and **Department** filled in for the card to look complete. Blank fields display an empty line.

- `Contact.PhotoURL` is a **read-only standard field** populated automatically from the Contact's Chatter profile photo. It cannot be set via DML. Contacts without a Chatter photo will show **initials on a colored background** — the component is designed for that and it looks clean.
- For the **role badges** to appear, populate the `badgesCsv` property with the names exactly as they appear in `Contact.Name`. Mismatches are silently ignored.
- Best demos have at least **4-6 Contacts on the Account** with distinct titles (C-level, manager, user champion, IT...).

Component · Customer Orders (`seFrCustomerOrders`)

> **API name:** `seFrCustomerOrders` · **Categories:** Sales · **Surfaces:** RecordPage · **Objects:** Account, Contact, Visit__c · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_CustomerOrdersController

Summary: Last order detail card plus searchable, sortable, filterable order history for an Account or Contact.

Key configurable props / settings of seFrCustomerOrders:

- Max rows
- Filter by status / date range
- `productImageFieldApiName` · default `Image_URL__c`

SE benefit: Renders product images per line — turns a plain list into a visual catalog reminiscent of an e-commerce order history. Compatible with SDO product image fields out of the box.

seFrCustomerOrders (Customer Orders)

B2B / B2C — Lists the orders linked to an Account or a Contact. Two blocks:

1. **Last order** — full detail card of the most recent order (number, status, amount, effective date, line items with product images), inspired by `seFrOrderSummary` but **read-only** (no replace / delete / ERP submit — this panel is about history).
2. **Order history** — compact list of the previous orders with **Search** (by order number), **Sort**, optional **Status filter** and a **View all** link.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Contact
- **App Builder label:** `CCO FR – Customer Orders`

What "linked to a customer" means

When placed on an **Account** page, the component shows `Order.AccountId = recordId`.
When placed on a **Contact** page, the component is exhaustive: the union of

- `BillToContactId = contactId`
- `ShipToContactId = contactId`
- `Contact__c = contactId` (only if the custom lookup exists on Order)
- `AccountId = contact.AccountId` (orders of the contact's account)

This way, a contact linked to a bakery's Account also sees the orders placed by the bakery itself, not just orders where the contact is named explicitly.

Apex dependency

`SE_FR_CustomerOrdersController.getCustomerOrders(recordId, objectApiName, limitCount, statusFilter, sortBy, searchTerm, productImageFieldApiName)` — bundled here in `classes/`.
Returns:

```
{
  "latest": { / OrderDetail with line items / },
  "history": [ / OrderSummary[] excluding the latest / ],
  "totalCount": 42
}
```

Actions

- **New order** — opens the standard Order new form, pre-filling `AccountId` when we can resolve it (from the current Account page or from the latest order on Contact page).
- **Refresh** — re-runs the Apex wire.
- **Search** — case-insensitive substring match on `OrderNumber`.
- **Sort** — Date (new/old), Amount (high/low), Order number (A-Z / Z-A).
- **Status picker** — visible only when `statusFilter` is populated; lets the SE narrow the list on-page.
- **View all** — navigates to the Account's Orders related list on Account pages, or the Order object home on Contact pages. Hidden if we already show everything.

Properties (App Builder)

NAME	TYPE	DEFAULT	DESCRIPTION
`language`	String	`en`	`en` or `fr`.
`cardTitle`	String	—	Override the dictionary default (`Orders` / `Commandes`).
`cardIcon`	String	`standard:orders`	
`historyLimit`	Integer	`10`	Server-side LIMIT (1–50).
`currencyCode`	String	`USD`	ISO 4217.
`localeTag`	String	`en-US`	Used for date formatting.
`statusFilter`	String	—	CSV whitelist of `Order.Status` values. When set, shows a status dropdown in the toolbar.
`defaultSort`	String	`EffectiveDate DESC`	Whitelisted.
`productImageFieldApiName`	String	`Image_URL__c`	Schema-safe.
`productImageFallbackUrl`	String	—	Used when the product field is empty / absent.
`hideNewOrderButton`	Boolean	`false`	
`hideViewAllLink`	Boolean	`false`	

Install

1. Deploy `classes/SE_FR_CustomerOrdersController.cls`.
2. Unzip `seFrCustomerOrders.zip`, deploy the LWC bundle.
3. Drop `CCO FR – Customer Orders` on an Account or Contact record page.
4. Adjust the `historyLimit`, `statusFilter`, `defaultSort`, `language` in App Builder as needed.

Data enrichment prerequisites

- On an **Account** page, any Order linked via `Order.AccountId` is picked up — no extra work needed if the Account already has orders.
- On a **Contact** page, the query unions `BillToContactId`, `ShipToContactId`, `Contact__c` (if the custom lookup exists on the org), and `AccountId = contact.AccountId`. If a Contact has no direct link and no parent Account with orders, the empty state shows the "Create the first order" CTA — intentional.
- For the **line-item detail** on the latest order card to show images, `Product2` records must have an image URL in the `Image_URL__c` field (or the field you configure via `productImageFieldApiName`). Fallback URL available through `productImageFallbackUrl` when none of the products carry an image.

Known caveats

- On an **Account** page, the "View all" button uses the standard "Orders" related list. If the Account page layout hides that related list, the navigation still works — Salesforce routes to the related-object view.
- `Order.AccountNumber` and custom fields are not fetched by default. Use the standard Order page to see them.
- Product images rely on a `Product2.Image_URL__c`-style custom field. Configure `productImageFieldApiName` or `productImageFallbackUrl` for your data model.

Component · Customer Sales Summary (`seFrCustomerSalesSummary`)

> **API name:** `seFrCustomerSalesSummary` · **Categories:** Marketing · **Surfaces:** RecordPage · **Objects:** Contact, Account · **Data mode:** mock · **Mobile-ready:** no · **Apex:** none

Summary: B2C-leaning sales summary with KPI tiles and breakdowns by Category, Brand and Store.

Key configurable props / settings of seFrCustomerSalesSummary:

- Time window
- Categories shown

SE benefit: Same component covers B2B and B2C scenarios — auto-detects Person Account vs. business Account and adapts the layout.

seFrCustomerSalesSummary (Customer Sales Summary)

B2C-leaning customer-level sales summary for a **Contact / Person Account / Account** record page. Three KPI tiles + three bar-chart columns (by **Category / Brand / Store**).

This complements `seFrRevenueDashboard` (which is B2B, Account-centric, 3-year revenue chart). Here the angle is *"what did this shopper buy and where"* — useful on retail demos with store networks and multi-brand portfolios.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Contact, Account (works with Person Account since Person Account pages use the Account record page)
- **App Builder label:** `CCO FR – Customer Sales Summary`

Apex dependency

None — demo data provided via App Builder properties.

Properties

Same CSV-driven shape as before — see the meta.xml for the full list. Formats:

- `categoriesCsv` / `brandsCsv` — `label|percent|color`
- `storesCsv` — `label|visits|barWidthPercent|color`

Origin

Renamed from `seFrRetailSalesDashboard` (v2.3 → v2.4). The old component is kept in the library as deprecated for backwards compat.

Component · Engagement History (`seFrEngagementHistory`)

> **API name:** `seFrEngagementHistory` · **Categories:** Marketing · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Lead, Contact, Account · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Configurable marketing engagement timeline with colored typed icons and inline search.

Key configurable props / settings of seFrEngagementHistory:

- Event types, emails, lists, ages (pipe-separated)
- Show/hide search (toggle icon)
- Card title override

SE benefit: Demonstrates a Marketing Cloud-style engagement history without needing MCAE installed. Perfect for demos on scratch orgs or SDOs without Marketing Cloud connectivity.

CCO FR - Engagement History

Configurable marketing engagement timeline showing Email Opens/Sends/Clicks/Bounces, SMS, Form Submits, and Page Views. Each event type gets a colored icon badge. Includes an inline search (toggled via a round icon button in the card header) that filters across all columns.

Key features

- **8 recognized event types** with distinct icons and colors (Email Open/Sent/Click/Bounce, SMS Sent/Click, Form Submit, Page View)
- **Bilingual type keys** — supports both FR and EN event type names in the same component instance
- **Inline search** — toggle via round icon button (library standard), filters across type, email, list and age columns without covering the title
- **Pagination** — 6 events visible by default, expand via round chevron button (8 values pre-filled in defaults to trigger the toggle)
- **Zero Apex / zero SOQL** — all data comes from App Builder properties (pipe-separated values)
- **Bilingual** FR / EN via `language` prop
- **Responsive** — works on mobile and desktop, narrow column compatible

Data enrichment prerequisites

None — this component operates in mock/configuration mode. All displayed data is injected via App Builder properties. No org data is queried.

Sample data

With no `eventTypes` / `eventEmails` / `eventLists` / `eventAges` set, the timeline shows a built-in realistic sample (localised via `language`), so the card is never empty. Provide any of the four properties to override with your own events.

Properties

PROPERTY	TYPE	DEFAULT	DESCRIPTION
`language`	String	`fr`	`'fr'` or `'en'` — controls card title, search placeholder, empty state
`cardTitle`	String	*(dict)*	Override the card title
`cardIcon`	String	`standard:activations`	SLDS icon
`showSearch`	Boolean	`true`	Show the search toggle button
`searchPlaceholder`	String	*(dict)*	Override search placeholder
`eventTypes`	String	*(sample)*	Pipe-separated event types (FR or EN keys accepted)
`eventEmails`	String	*(sample)*	Pipe-separated email subjects (aligned by index)
`eventLists`	String	*(sample)*	Pipe-separated lists/campaigns (aligned by index)
`eventAges`	String	*(sample)*	Pipe-separated relative ages (aligned by index)

Supported Event Types

FR KEY	EN KEY	ICON	COLOR
Email ouvert	Email Open	`utility:email`	Blue
Email envoye	Email Sent	`utility:send`	Indigo
Email clique	Email Click	`utility:link`	Green
Email rejete	Email Bounce	`utility:warning`	Red
SMS envoye	SMS Sent	`utility:chat`	Purple
SMS clique	SMS Click	`utility:link`	Purple
Formulaire	Form Submit	`utility:edit_form`	Cyan
Page vue	Page View	`utility:preview`	Slate

Component · Field Sales - Rep Home (`seFrFieldRepHome`)

> **API name:** `seFrFieldRepHome` · **Categories:** Dashboards & KPIs · **Surfaces:** AppPage, HomePage · **Objects:** Any · **Data mode:** hybrid · **Mobile-ready:** no · **Apex:** SE_FR_FieldSalesController

Summary: Field Sales rep home page with greeting, KPIs, priority accounts, hot leads, product penetration and campaign calendar.

Key configurable props / settings of seFrFieldRepHome:

- Number of tasks / events shown
- KPI tiles (label, value, target)

- Quick action links

SE benefit: One Home page with all the field-sales context preloaded — no need to assemble 5 components on a custom App Page.

seFrFieldRepHome (Field Sales — Rep Home)

B2B — Home / App page for a **field sales rep**. Greeting, 4 KPI tiles, priority accounts (dynamic), hot leads (dynamic), product-penetration bars and campaign calendar.

Where to drop it

- **Target:** Lightning Home Page, App Page (**not Record**)
- **App Builder label:** `CCO FR – Field Sales – Rep Home`

Apex dependency

`SE_FR_FieldSalesController` — now exposes full filter arguments:

- `getPriorityAccounts(recordTypeName, ownerScope, orderBy, limitCount)`
- `getMyLeads(rating, ownerScope, limitCount)`

Filters (App Builder)

PROPERTY	DEFAULT	NOTES
`accountRecordType`	`SDO_Account_Simple`	Standard Salesforce SDO B2B record type. Leave empty for all types.
`accountOwnerScope`	`mine`	`'mine'` = running user's accounts; `'all'` = any owner. Use `'all'` on fresh demo orgs.
`accountOrderBy`	`Name`	Whitelisted: `Name` | `LastActivityDate DESC NULLS LAST` | `AnnualRevenue DESC NULLS LAST` | `CreatedDate DESC`.
`accountLimit`	6	Up to 50.
`leadRating`	`Hot`	`Hot` | `Warm` | `Cool` | `Any`.
`leadOwnerScope`	`mine`	
`leadLimit`	6	

Styling

Shares the SE_FR palette declared at the top of the CSS (brand blue, SLDS success green, warning orange, error red). KPI tile top border and value color map 1:1 to the palette for a homogeneous look across the Home page.

Origin

Renamed from `seFrFieldSalesDashboard` (v2.3 → v2.4). The old bundle is kept in the library as deprecated.

Component · Files Gallery (`seFrFilesGallery`)

> **API name:** `seFrFilesGallery` · **Categories:** Transverse · **Surfaces:** RecordPage · **Objects:** Any · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_FilesGalleryController

Summary: Visual gallery of files attached to any record with image thumbnails, doctype icons and drag-and-drop upload.

Key configurable props / settings of seFrFilesGallery:

- Max files, visible count in carousel
- Show / hide upload + delete buttons

SE benefit: Real image thumbnails (not just generic doctype icons) — pull product photos, brand assets, contracts. Drag-drop upload zone is custom-built (not the native `lightning-file-upload`) so the layout looks clean in narrow sidebar columns.

seFrFilesGallery (Files Gallery)

B2B / B2C — Visual gallery of the files linked to the current record. Image thumbnails (via the standard Salesforce rendition endpoint), doctype icons for non-images (PDF, Word, Excel…), click-to-preview and a drag-and-drop upload area. Bilingual EN / FR.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** any record type — the component queries `ContentDocumentLink` by `LinkedEntityId`.
- **App Builder label:** `CCO FR – Files Gallery`

Apex dependency

`SE_FR_FilesGalleryController.getFiles(recordId, limitCount)`. Queries the latest `ContentVersion` for each document linked to the record.

Properties

NAME	DEFAULT	DESCRIPTION
`language`	`en`	`en` or `fr`.
`cardTitle`	—	Override the default.
`limitCount`	20	Server-side LIMIT (1–100).
`hideUploadButton`	`false`	

Install

1. Deploy `classes/SE_FR_FilesGalleryController.cls`.
2. Unzip `seFrFilesGallery.zip`, deploy the LWC bundle.
3. Drop `CCO FR – Files Gallery` on any record page.

Data enrichment prerequisites

- The record must have **at least one** `ContentDocumentLink` attached. On a fresh SDO, most records have none — the component shows an empty state.
- **Images** (PNG / JPG / GIF / WEBP) display as thumbnails via the rendition endpoint. Non-images show a doctype icon and the filename — the thumbnail slot is not used.
- **Preview** uses the standard `filePreview` named page; behaviour matches Salesforce Files.

Component · Kanban Board (`seFrKanbanBoard`)

> **API name:** `seFrKanbanBoard` · **Categories:** Service · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_KanbanBoardController

Summary: Generic kanban board with native drag & drop on any whitelisted SObject (Case, Opp, Lead, Order, Task, Account).

Key configurable props / settings of seFrKanbanBoard:

- Object type, status field
- Visible columns
- Card field list

SE benefit: Same component supports 6 SObjects — drop on a Home Page (all my open cases), an App Page (team kanban), or a Record Page (Account-scoped cases). Drag-drop instantly updates the status field.

CCO FR - Kanban Board (`seFrKanbanBoard`)

Generic kanban board for **any whitelisted SObject** (Case · Opportunity · Lead · Order · Task · Account). Drag-and-drop updates the group-by field on the record. Auto-detects scoping when placed on a Record Page.

Targets

- `lightning__HomePage`
- `lightning__AppPage`
- `lightning__RecordPage`

Quick start

Drop on a Home Page — defaults to **Case · group by Status · display Subject**:

```
sobjectApiName  = Case
groupByField    = Status
displayField    = Subject
filterClause    = IsClosed = false
```

You get a kanban with one column per Case status, draggable cards.

On a Record Page

Set `recordScopeField` to a lookup field on the queried object that points at the host record's Id:

HOST PAGE	COMMON SCOPE FIELDS
Account	`AccountId` (works on Case, Opportunity, Order)
Contact	`ContactId` (Case), `WhoId` (Task)
Case	`ParentId` (sub-cases)

Leave empty to disable scoping (kanban shows all matching records, not bound to the host).

Properties

PROPERTY	DEFAULT	DESCRIPTION
`language`	`fr`	`fr` / `en`
`cardTitle`	–	Override
`cardIcon`	`standard:kanban`	SLDS icon
`sobjectApiName`	`Case`	Whitelisted object to query
`groupByField`	`Status`	Picklist field used to form the columns
`displayField`	`Subject`	Field shown as the card title
`secondaryField`	`Priority`	Secondary chip / detail on the card
`amountField`	–	Currency field summed per column (e.g. `Amount` on Opp)
`filterClause`	`IsClosed = false`	Raw SOQL `WHERE` fragment (injected as-is)
`recordScopeField`	`AccountId` (Record Page)	Lookup field tying queried records to the host record
`limitCount`	`100`	Server-side `LIMIT` (1-500)
`maxPerColumn`	`6`	Cards shown before a "Show all (N)" link
`disableDragDrop`	`false`	Off by default — drag-drop updates the group-by field
`currencyCode`	`EUR`	Used by the column total formatter
`localeTag`	`en-US`	Locale used by `Intl.NumberFormat`

Drag & drop

By default, dropping a card in another column issues a `LightningRecordEditForm` save on the group-by field. Toggle `disableDragDrop = true` if you want the kanban to be read-only (e.g. demo videos, screenshots).

Whitelisted SObjects

The component restricts itself to a curated set to stay schema-safe across orgs:

`Case` · `Opportunity` · `Lead` · `Order` · `Task` · `Account`

To extend the list, edit the Apex `SE_FR_KanbanBoardController` whitelist + add a `<targetConfig>` row in the meta.xml.

SE benefits

- **One component, 6 SObjects** — same kanban for "my open cases" (Home), "team pipeline" (App Page), "Account-scoped opportunities" (Record Page).
- **Drag-drop status update** — visually striking demo moment for service / sales workflows.
- **Auto column detection** — picklist values define the columns automatically; no manual config per status.
- **Currency-aware totals** — set `amountField = Amount` on Opportunity and each column displays its sum in EUR / USD / whatever locale you configure.

Component · KPI Launcher (`seFrKpiLauncher`)

> **API name:** `seFrKpiLauncher` · **Categories:** Dashboards & KPIs · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Configurable grid of 3-6 clickable KPI tiles with icon, value, color and link, ready out of the box.

Key configurable props / settings of seFrKpiLauncher:

- Up to 8 tiles (label, value, trend %, target URL)
- Color accent per tile
- Layout (grid / horizontal)

SE benefit: Most-tunable component in the library (40+ properties). Click-through targets let you stage navigation flows during a demo without writing a Flow or App Builder action.

seFrKpiLauncher (KPI Launcher)

Configurable grid of 3 to 6 clickable KPI tiles. Each tile accepts a label, value, sublabel, SLDS icon, color and link. Empty labels hide the tile — display anywhere from 3 to 6 tiles without code changes.

Where to drop it

- **Target:** Lightning Home Page / App Page / Record Page
- **App Builder label:** `CCO FR – KPI Launcher`

Apex dependency

None (all values are static, driven by App Builder properties).

Properties

Each of the 6 tiles exposes the same 6 properties. Leave `kpiNLabel` empty to hide the corresponding tile.

PROPERTY SUFFIX	TYPE	DESCRIPTION
`Label`	String	Main tile title. **Empty hides the tile.**
`Value`	String	Big number / percentage / text shown on the tile.
`Sublabel`	String	Small caption below the value.
`Icon`	String	SLDS icon reference, e.g. `standard:account` , `standard:event` , `utility:einstein` . See SLDS Icons.
`Color`	String	Hex color driving the tile's accent + hover state. Defaults vary per tile.
`Link`	String	Destination on click. Accepts Lightning URLs (`/lightning/o/Lead/list?filterName=Recent`), nav items (`/lightning/n/maps__Maps`) or absolute URLs (`https://…`).

Plus:

- `cardTitle` (String, optional) — when set, wraps the grid in a standard `lightning-card` matching every other SE_FR component's title style. Leave empty to render the raw grid (same look as before).
- `cardIcon` (String, default `standard:metrics`) — icon next to the card title when `cardTitle` is set.

Tile behavior

- Tiles without a link stay visually clickable but do nothing on click.
- Tiles with `https://…` links open in a new tab; internal paths navigate via standard Lightning navigation.
- Hover effect inverts the color — background turns to the tile's `Color` , text turns white.
- Grid is responsive (`repeat(auto-fit, minmax(160px, 1fr))`) — tiles reflow on narrow containers.

Install

1. Unzip `seFrKpiLauncher.zip` , deploy the LWC bundle.
2. Drop `CCO FR – KPI Launcher` on a Home, App or Record page.
3. Configure each KPI in App Builder. Start by filling KPI 1–3; add KPI 4–6 if needed.

Component · Lead First Touch (`seFrLeadFirstTouch`)

> **API name:** `seFrLeadFirstTouch` · **Categories:** Retail Execution · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Lead · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Lead "First Touch Capture" mock — drop notes, paste a transcript, get simulated AI meeting notes, then simulated follow-up Tasks and Events.

Key configurable props / settings of seFrLeadFirstTouch:

- `language` · fr (default) or en
- `cardTitle` · optional override · `cardIcon` · default `standard:lead_insights`
- `mockTranscript` · optional initial transcript text
- `simulatedDelayMs` · default 1500 (activity creation uses 2/3 of it)

SE benefit: Shows the full "capture at the booth, AI writes the notes, follow-ups are created" story on any dev org in seconds, with no custom field, Apex class or Agentforce setup.

CCO FR - Lead First Touch (`seFrLeadFirstTouch`)

Original source: Yann Jourdain, `LeadFirstTouch` (`leadftFileUpload`)
Ported to library by: Lionel Braun
Library-integrated: 2026-10-23

What it does

Two-column card for Lead pages (stacked on narrow screens):

- **Contexte humain** — a styled dropzone (click adds a fake file chip, nothing is uploaded) and a transcript textarea.
- **Assistant Agentforce** — "Générer les notes IA" waits `simulatedDelayMs` with a spinner, then renders canned markdown-style notes inline. "Créer les activités" stays disabled until notes exist, then after ~2/3 of the delay shows a toast and 3 fake Task/Event records that "would be created".

Targets

`lightning__RecordPage` (object Lead), `lightning__AppPage` , `lightning__HomePage` .

Properties

PROPERTY	DEFAULT	NOTES
`language`	`fr`	`fr` or `en` .
`cardTitle`	—	Default `First Touch Capture` .
`cardIcon`	`standard:lead_insights`	
`mockTranscript`	—	Pre-fills the transcript box.
`simulatedDelayMs`	`1500`	Fake AI latency.

Live mode wiring (not included)

This is a mock. To make it real, as in Yann's original:

1. Add Lead fields `First_Touch_Transcript__c` and `First_Touch_Notes__c` .
2. Apex `FirstTouchNotesGenerator.generateNotes(Id leadId)` (`@AuraEnabled`) calling a GenAI prompt template that turns the transcript into notes stored in `First_Touch_Notes__c` .
3. Apex `LeadActivityCreator.createActivitiesFromLWC(Id leadId)` (`@AuraEnabled`) calling a second prompt template that returns JSON, then inserting Tasks and Events.
4. Replace `lightning-file-upload` for the dropzone, `lightning-record-edit-form` for the transcript, and the two `setTimeout` handlers with the imperative Apex calls.

Lineage notes

- Custom "agentforce-card" chrome replaced by `lightning-card` with SLDS classes; emojis replaced by `lightning-icon` .
- All strings moved to a FR/EN `LABELS` dictionary.
- Markdown is rendered by a tiny block parser into template elements (no `innerHTML`).

Component · Metric Tile (`seFrMetricTile`)

> **API name:** `seFrMetricTile` · **Categories:** Dashboards & KPIs · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Single-metric tile with 4 chart styles (line / area / bar / mini-donut), comparison series, target line and currency formatting.

Key configurable props / settings of seFrMetricTile:

- `chartStyle` · line / area / bar / mini-donut
- `seriesJson`, `secondarySeriesJson` (forecast vs actual)
- `targetValue` + dashed target line + chip
- `currentValue` + `currencyCode` · auto Intl format
- `scalingMode` · auto / from-zero / fixed

SE benefit: Compact tile, dashboard-ready — set `hideCardTitle = true` to stack 4 tiles in a row aligned. Mini-donut variant is the striking "85% to target" demo moment without configuring a real Performance Goal.

CCO FR - Metric Tile (`seFrMetricTile`)

Single-metric tile with a configurable inline trend chart. **4 chart styles** (line / area / bar / mini-donut), optional **comparison series**, **target line**, and **currency formatting** via `Intl.NumberFormat`.

Designed to stack horizontally on a Home Page or App Page (3-4 tiles per row), or to sit standalone on a Record Page sidebar.

Targets

- `lightning__HomePage`
- `lightning__AppPage`
- `lightning__RecordPage`

The 4 chart styles

CHARTSTYLE	VISUAL	USE CASE
`line` (default)	Smooth line + last-point dot	Trend curve, no surface emphasis
`area`	Same as line + filled area below	Volume / surface emphasis
`bar`	Vertical bars with rounded tops	Discrete monthly values
`mini-donut`	Radial gauge filling currentValue / targetValue	Goal completion / quota / health %

Quick start

Drop on a Home Page, no config — you get a sample 12-month revenue curve with a green `+14,2%` trend badge.

For a real metric:

```
metricLabel        = "Pipeline"
currentValue       = 1250000
currencyCode       = "EUR"
seriesJson         = [820000, 880000, 950000, 1020000, 1080000, 1130000, 1180000, 1250000]
chartStyle         = "area"
trendDisplay       = "+12,8%"
```

For a goal-completion donut:

```
metricLabel        = "Quarterly target"
currentValue       = 850000
targetValue        = 1000000
currencyCode       = "EUR"
chartStyle         = "mini-donut"
showTargetLabel    = true
```

For a forecast vs. actual line:

```
seriesJson          = [...actual]
secondarySeriesJson  = [...forecast]
secondarySeriesColor = "#747474"
chartStyle          = "line"
```

Properties

Headline

PROPERTY	DEFAULT	DESCRIPTION
`language`	`fr`	`fr` / `en`
`cardTitle`	–	Override
`cardIcon`	`standard:metrics`	SLDS icon
`hideCardTitle`	`false`	Render bare tile (no card chrome) — useful when stacking
`metricLabel`	dictionary default	Small label above the headline
`currentValueDisplay`	–	Manual text override (wins over numeric)
`currentValue`	–	Numeric value, auto-formatted via `Intl.NumberFormat`
`currencyCode`	`EUR`	ISO 4217

Chart

PROPERTY	DEFAULT	DESCRIPTION
`chartStyle`	`line`	`line` / `area` / `bar` / `mini-donut`
`seriesJson`	sample 12-month curve	JSON array of numbers
`secondarySeriesJson`	–	Optional comparison series (dashed line)
`secondarySeriesColor`	`#747474`	Secondary series color
`targetValue`	–	Horizontal target line on line/area/bar; denominator on mini-donut
`targetLineColor`	`#FE9339`	Target line color
`showTargetLabel`	`false`	Show "Target XX €" chip next to the metric label

Y-axis scaling

PROPERTY	DEFAULT	DESCRIPTION
`scalingMode`	`auto`	`auto` (data min/max) / `from-zero` / `fixed`
`yMin`	–	Used when `scalingMode = fixed`
`yMax`	–	Used when `scalingMode = fixed`

Visual

PROPERTY	DEFAULT	DESCRIPTION
`accentColor`	`#0176d3`	Primary chart color
`donutTrack`	`#E5E5E5`	Mini-donut background ring
`height`	`70`	Chart inner height (px)
`width`	`0` (auto)	Override viewBox width
`trendDisplay`	`+14,2%`	Sign drives badge color

SE benefits

- **No Apex required** — pure props-driven, configured entirely in App Builder.
- **Compact + dense-dashboard ready** — set `hideCardTitle = true` and stack 4 tiles in a row of a Home Page, all aligned.
- **AI/forecast demos** — a secondary dashed line is the simplest way to overlay "actuals vs. forecast" without building a real chart component.
- **Goal-completion mini-donut** — visually striking for "we're 85% to target" demo moments without needing a real Performance Goal in the org.

Design rationale

Pure SVG, no chart library — keeps the bundle ~3 KB and avoids Locker / CSP issues. All animations are CSS-driven (path-fade, bar-grow, donut stroke-dashoffset transition).

Component · My Events (`seFrMyEvents`)

> **API name:** `seFrMyEvents` · **Categories:** Productivity · **Surfaces:** AppPage, HomePage · **Objects:** Any · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_AgendaController

Summary: Today's calendar as a compact vertical timeline that fits a sidebar column, with Google-Calendar-style overlap.

Key configurable props / settings of seFrMyEvents:

- Days forward
- Show / hide attendees, location
- Card title override

SE benefit: Useful in both Field Sales (today's appointments) and as a transversal "agenda" widget on any persona's Home Page.

seFrMyEvents (My Day — Events timeline)

Today's calendar for the running user, as a **vertical timeline** sized to fit a sidebar column. Kept compact on purpose: auto-trims empty hours, shows only 3 upcoming items, and lays overlapping events side-by-side (Google Calendar style) instead of stacking them on top of each other.

Where to drop it

- **Targets:** Home Page, App Page, Record Page
- **App Builder label:** `CCO FR – My Events`

Apex dependency

`SE_FR_AgendaController.getMyEvents(daysAhead, maxRows)` — shared Apex class, standard fields only.

Features

- **Today timeline** — each non-all-day event positioned proportionally on a configurable hour axis (default 08:00→20:00). Clicking an event opens its record.
- **Auto-trim** (default ON) — the timeline starts `autoTrimPaddingMin` minutes before the first event and ends the same padding after the last event (clamped between `startHour` and `endHour`, default padding 30min). Short days feel short, long days still fit. Disable via `disableAutoTrim` to render the full `[startHour, endHour]` range. When the day has no non-all-day events, the timeline block is not rendered at all.
- **Overlap handling** — overlapping events are placed side-by-side into columns (1/N width each) so nothing is hidden behind another event.
- **Short events** — < 30 min visible duration renders in a compact layout (title only, no footer) so they don't spill out of their block.
- **Now line** — a red horizontal line + `HH:MM • now` label, refreshed every 60 seconds. Auto-trim always keeps the now-line in the visible range when today's time falls between startHour and endHour.
- **"in N min" badge** — shown on events starting within 30 minutes, or "now" on events currently running.
- **All-day band** — compact pill band above the timeline for all-day events.
- **Colour-coded types** — each event gets a left border + tint derived from `Event.Type` via a CSV map (fallback to "Other").
- **Join button** — if `Location` or `Description` contains a Zoom / Teams / Meet / WebEx URL, a Join button opens it in a new tab. Toggle via `hideJoinButton`.
- **Upcoming list** — next **3** future-day events (default `daysAhead = 2`) in a compact list under the timeline, grouped by day label.
- **Refresh / New event** icons in the header.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`My Day`	Card title.
`cardIcon`	String	`standard:event`	Card icon.
`startHour`	Integer	`8`	Earliest hour shown when auto-trim is off or can't narrow further.
`endHour`	Integer	`20`	Latest hour shown (same rule).
`disableAutoTrim`	Boolean	`false`	Auto-trim is ON by default. Turn on to always render the full `startHour → endHour` window.
`autoTrimPaddingMin`	Integer	`30`	Empty-hour margin kept before the first event and after the last event when auto-trim is on. Set to 0 to crop exactly to the events.
`daysAhead`	Integer	`2`	Days to fetch (today = 1).
`maxEvents`	Integer	`10`	Server-side LIMIT.
`localeTag`	String	`en-US`	Time formatting.
`typeColorsCsv`	String	see meta.xml	`Type|#hex` entries, comma-separated.
`hideNowLine`	Boolean	`false`	Hide the red "now" line.
`hideJoinButton`	Boolean	`false`	Hide the Join button even when a meeting URL is detected.
`emptyStateMessage`	String	`Nothing scheduled today.`	Shown when no event falls in the window.

Install

1. Deploy `SE_FR_AgendaController` (bundled in `classes/` here; also lives in `_shared_apex/`).
2. Unzip `seFrMyEvents.zip`, deploy the LWC bundle.
3. Drop `CCO FR – My Events` on the right column of a Home / App / Record page.

Prerequisites — user timezone

`Date.today()` in Apex and `TODAY` / `THIS_WEEK` SOQL filters resolve against the **running user's timezone**, not the org timezone. Most Salesforce SDOs ship with the org set to `America/Los_Angeles` — if your user also inherits that timezone, a 09:00 Paris meeting stored as `07:00Z` will appear as `00:00` and today's events may be picked up under yesterday or tomorrow.

Before using the component, make sure **your user's timezone matches your local time**:

- Setup → **Personal Information** → *Time Zone* → pick your local value (e.g. `(GMT+01:00) Central European Time (Europe/Paris)` in winter / `(GMT+02:00) Central European Summer Time (Europe/Paris)` in summer).
- Save, refresh the tab.

You don't need to change the **org** timezone (Setup → Company Information) — that has much broader side-effects (Business Hours, Reports, audit trails). Changing only the user timezone is the standard SE practice on a shared SDO.

Type toggles (in-UI "calendars")

When events carry an `Event.Type` value (Call / Meeting / Demo / Training / Other in the default palette), the component shows one coloured chip per distinct type present today. **Click a chip to mute / unmute that type** in the timeline — handy when too many auto-created events clutter the day. Muted chips remain visible (greyed + struck-through) so you can re-enable them.
Use `typesFilterCsv` on the meta.xml to hard-scope the component to a subset of types (e.g. `Meeting,Demo`) before the in-UI toggles apply — great to hide a type globally on a shared page.

Known caveats — external calendars (Gmail / Outlook)

Salesforce surfaces Gmail / Outlook events in the **standard calendar** via **Einstein Activity Capture (EAC)**, which stores them in a private dataset that's **not queryable via SOQL** (`Event` only contains records created inside Salesforce). This means the component cannot show EAC-synced meetings — no LWC on the platform can. To still have external meetings visible here, either:

- manually create the meeting as a Salesforce `Event`, or
- use the Lightning for Outlook / Gmail "log email / event" action which creates a real Event record.

Other caveats

- Events longer than the visible timeline are clipped to the effective bounds (the block fills from the visible portion only).

- Join-URL detection is a regex over `Location` + `Description`; custom URLs won't be detected.
- The "now" line refreshes every 60 seconds. If the component sits hidden in a tab for a long time, it picks up the next minute on re-render.

Component · My Tasks (`seFrMyTasks`)

> **API name:** `seFrMyTasks` · **Categories:** Productivity · **Surfaces:** AppPage, HomePage · **Objects:** Any · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_AgendaController

Summary: Compact 'My Tasks' sidebar panel grouped by due date with one-click completion.

Key configurable props / settings of seFrMyTasks:

- Days back / forward
- Show / hide priority chip
- Card title override

SE benefit: Same controller as My Events (single Apex class for both) — guarantees consistent date logic and shared maintenance.

seFrMyTasks (My Tasks)

Compact "My Tasks" panel designed for a **sidebar column** on a Home / App / Record page. Reads the running user's tasks, auto-groups them by due date, lets the user complete a task with a click.

Where to drop it

- **Targets:** Home Page, App Page, Record Page
- **App Builder label:** `CCO FR – My Tasks`

Apex dependency

`SE_FR_AgendaController.getMyTasks(filter, maxRows)` — shared Apex class, standard fields only.

Features

- **Filter dropdown** in the header — Today / Mine / Overdue / Upcoming / Completed. Label shows the current filter.
- **Auto-grouping** — rows are bucketed client-side into Overdue / Today / Tomorrow / This week / Later / No date / Completed. Empty buckets are hidden.
- **Interactive checkbox** — clicking the checkbox flips `Task.Status` between `Completed` and `In Progress` via `updateRecord`, then refreshes the list (so the task moves groups). Fixes the v2.x bug where the checkbox was always disabled.
- **Urgent flag** — High-priority or overdue tasks show a red flag icon and red date.
- **"+ New Task"** button in the header opens the standard new-task page.
- **"View all"** button navigates to the Task home list.
- **Optional quick actions** (off by default) — on hover, shows Email and Log-a-Call buttons. Turn on with `showQuickActions`.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`My Tasks`	Card title.
`cardIcon`	String	`standard:task`	Card icon.
`defaultFilter`	String	`Upcoming`	Initial filter. One of the `filterOptionsCsv` values.
`filterOptionsCsv`	String	`Today,Mine,Overdue,Upcoming,Completed`	Filter dropdown entries.
`maxTasks`	Integer	`10`	Server-side row LIMIT (1–50).
`localeTag`	String	`en-US`	Used to format the due date.
`showQuickActions`	Boolean	`false`	Reveals Email / Log-a-Call icons on row hover.
`emptyStateMessage`	String	`No tasks for this filter.`	Shown when the filter returns no row.

Install

1. Deploy `SE_FR_AgendaController` (bundled in `classes/` here; also lives in `_shared_apex/` if you need it for other components).

2. Unzip `seFrMyTasks.zip`, deploy the LWC bundle.
3. Drop `CCO FR – My Tasks` on the right column of a Home / App / Record page.

Prerequisites — user timezone

The `Today` / `Overdue` / `Upcoming` filters use SOQL date literals (`TODAY`, `<`, `>=`) that resolve against the **running user's timezone**. Most Salesforce SDOs ship with the org set to `America/Los_Angeles` — if your user also inherits that timezone, tasks due today in Paris may be bucketed as yesterday or tomorrow.

Before using the component, set **your user's timezone to your local value**:

- Setup → **Personal Information** → *Time Zone* → pick your local value (e.g. `(GMT+01:00) Central European Time (Europe/Paris)` in winter / `(GMT+02:00) Central European Summer Time (Europe/Paris)` in summer).
- Save, refresh the tab.

You don't need to change the **org** timezone — only the user timezone.

Known caveats

- "Reopen" sets `Status = 'In Progress'`. If your org's Task status picklist doesn't include that value, change it in `handleToggleComplete`.
- Quick actions rely on `Contact.SendEmail` (Who) and `Global.LogACall` — both are present out of the box on standard orgs.

Component · Nearby Accounts Map (`seFrNearbyAccountsMap`)

> **API name:** `seFrNearbyAccountsMap` · **Categories:** Geo & Field · **Surfaces:** AppPage, HomePage · **Objects:** Any · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_NearbyAccountsController

Summary: Interactive map of nearby accounts using the browser's geolocation with Haversine distance sort.

Key configurable props / settings of seFrNearbyAccountsMap:

- Origin mode · auto geolocation / manual lat-lng
- Max accounts displayed, RecordType filter
- Highlight first account as priority

SE benefit: Browser geolocation prompt for a "wow" moment in field demos. Falls back to a fixed origin (Place de la Bastille) when permission is denied — never breaks the demo.

seFrNearbyAccountsMap

Interactive map showing nearby accounts from a configurable origin point. Uses the standard `lightning-map` with custom pin styling. By default, the component **uses the browser's geolocation** so the map centers on wherever the SE currently is, and silently falls back to a configurable lat/lng if the browser denies the permission or is on HTTP.

Where to drop it

- **Target:** Lightning Home Page / App Page
- **App Builder label:** `CCO FR – Nearby Accounts Map`

Apex dependency

- `SE_FR_NearbyAccountsController.getNearbyAccounts(limitCount, recordTypeName)` — located in `_shared_apex/`.
- Behavior: first tries accounts owned by the running user; if that set is empty, falls back to accounts of any owner so the component still shows data on a fresh demo org.

Origin — auto vs manual

ORIGINMODE	BEHAVIOR
`auto` (default)	Calls `navigator.geolocation.getCurrentPosition()` in `connectedCallback`. Browser prompts the user once per origin. Cached position up to 5 min old is reused. **Requires HTTPS** (Salesforce is HTTPS). On denial / timeout / unsupported browser, falls back silently to `originLatitude` / `originLongitude`.
`manual`	Always uses the provided `originLatitude` / `originLongitude`.

This means the default deployment works out of the box for any SE: the first time they open the page, they approve the browser prompt, and the map centers on them.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`Nearby Accounts`	
`listSubtitle`	String	`Accounts and prospects nearby`	Shown in the map's list view.
`limitCount`	Integer	`10`	Max accounts queried from Apex.
`recordTypeName`	String	—	Optional. RecordType `DeveloperName` on Account (leave empty for all).
`originMode`	String	`auto`	`auto` (browser geolocation, fallback to lat/lng) or `manual`.
`originLatitude`	String	`48.859215`	Fallback / manual latitude (decimal degrees). Defaults to central Paris (11e).
`originLongitude`	String	`2.379175`	Fallback / manual longitude.
`originLabel`	String	`My location`	Title of the origin marker.
`priorityFirstMarker`	Boolean	`false`	If true, the first account pin is shown in red.
`zoomLevel`	Integer	`13`	Initial map zoom.

Install

1. Deploy `_shared_apex/classes/SE_FR_NearbyAccountsController.cls` first (if not already present in the org).
2. Unzip `seFrNearbyAccountsMap.zip`, deploy the LWC bundle.
3. Drop `CCO FR – Nearby Accounts Map` on a Home or App page.
4. First load: accept the browser geolocation prompt. The map re-centers on you. If you prefer a fixed origin, set `originMode = 'manual'` and tune the lat/lng.

Data enrichment prerequisites

- The Apex query returns Accounts where `BillingStreet != null`. Accounts without a billing address are invisible on the map.
- **Geocoding precedence**: the component prefers `BillingLatitude` / `BillingLongitude` (set by Salesforce's data.com geocoding service or manually) and falls back to `Street + City + PostalCode + Country` only when lat/lng are missing. On a fresh SDO without data.com geocoding, server-side geocoding via Bing Maps is slow and can silently fail — **pre-seeding `BillingLatitude` / `BillingLongitude` on the target Accounts is the most reliable way to guarantee pins appear**.
- For a Paris-based demo, point the Accounts at Paris addresses and set `BillingLatitude` / `BillingLongitude` in the 48.85 / 2.37 neighbourhood. The `SE_FR_SDO` org has 12 Accounts pre-seeded in the 11th arrondissement — use those to validate.
- The distance label under each pin title is computed client-side via haversine from the origin point, so it's only accurate when lat/lng are present.

Component · Order Entry (`seFrOrderEntry`)

> **API name:** `seFrOrderEntry` · **Categories:** Sales · **Surfaces:** RecordPage · **Objects:** Account, Case, Visit__c · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_OrderEntryController

Summary: Full-grid order entry on an Account or Case with stock, AI-recommended quantities and discounts, persisted as real Order records.

Key configurable props / settings of seFrOrderEntry:

- Product columns (code, category, last order, stock, price)
- Currency code & symbol
- Order type defaults

SE benefit: Real product images appear in each row (read from `Product2.Image_URL__c` by default — works out-of-box on SDO). Reorder shortcut and stock visibility are visually striking demo moments.

seFrOrderEntry

Full-grid order entry component for an Account (or for a Case linked to an Account). Displays products with stock, price, AI-recommended quantity and discount, a running order total, and a confirmation modal. Saves as a real `Order` + `OrderItem` records.

Where to drop it

- **Target:** Lightning Record Page
- **Object:** Account, Case, or Visit__c (uses the Account when on an Account page, the Case's `AccountId` on a Case page, and the Visit's `Account__c` on a Visit__c page). On a Visit record, placing an order also publishes `order:done` to `sefr-visit-progress::<visitId>` in `localStorage` so `seFrVisitPlan` ticks its "Prise de commande" checklist step.
- **App Builder label:** `SE_FR — Order Entry`

Apex dependencies

- `SE_FR_OrderEntryController` — exposes `getProductsList(…)` and `createOrderFromGrid(…)`.

Standard fields used

- `Product2.Family` — product category column in the grid (falls back to "Uncategorized" if blank).
- `Order.SalesChannelId` — set from the `salesChannelId` property (lookup to `SalesChannel`).
- `Order.EndDate` — set from the delivery date picker.

Optional custom field

- `Product2.Image_URL__c` (URL) — if present, used as fallback to `ProductMedia.URI`. Gracefully skipped if absent.

Properties (highlights)

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`Order Entry`	
`cardIcon`	String	`standard:orders`	
`recordLimit`	Integer	`25`	Max products shown.
`currencyCode`	String	`USD`	Passed to `lightning-datatable` currency columns.
`currencySymbol`	String	`$`	Inline rendering next to prices.
`localeTag`	String	`en-US`	
`fullScreenTitleTemplate`	String	`Order entry for {account}`	Displayed in full-screen mode. `{account}` placeholder.
`noAccountMessage`	String	`Link an account to this case before starting an order.`	Shown when placed on a Case that has no `AccountId`.
`erpCheckboxLabel`	String	`Send directly to ERP`	Label of the final confirmation checkbox.
`filter1..5`	String	—	Dynamic SOQL fragments added to the `Product2` query (e.g. `Family = 'Widgets'`).
`salesChannelId`	String	—	Optional. 18-char Id of a `SalesChannel` record set on `Order.SalesChannelId` at creation.
`productImageFieldApiName`	String	`Image_URL__c`	Field on `Product2` holding an image URL. Schema-safe — skipped if the field is absent.
`productImageFallbackUrl`	String	—	URL shown when no image is found on the product or in `ProductMedia`.

Install

1. Deploy `classes/SE_FR_OrderEntryController.cls` first.
2. Unzip `seFrOrderEntry.zip`, deploy the LWC bundle.
3. Drop `SE_FR — Order Entry` on an Account or Case record page.
4. Configure card title, currency, filters.

Images produits (showcase)

Le tooltip du Cadencier lit `Product2.Image_URL__c`. Dans le showcase CCO FR, le champ, le permission set `CCO_FR_Product_Image` et la static resource `cpg_products` (15 packshots SVG) sont dans `_deploy/`, et `scripts/apex/seed-showcase-orders.apex` renseigne `Image_URL__c` (`/resource/cpg_products/<CODE>.svg`).

Component · Order Summary (`seFrOrderSummary`)

> **API name:** `seFrOrderSummary` · **Categories:** Service · **Surfaces:** RecordPage · **Objects:** Case · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_OrderSummaryController

Summary: Most recent Order linked to a Case with products, total, delivery info and edit / delete / submit actions.

Key configurable props / settings of seFrOrderSummary:

- Show / hide line item details
- Currency display
- Separator label

SE benefit: Clean visual summary that a rep can read aloud during a call without scrolling — great for the "I'm reading you the order back" moment.

seFrOrderSummary

Displays the **most recent Order** associated with the current Case. The Account is resolved first from `Case.AccountId`; if missing, from `Case.Contact.AccountId`. Shows products, total amount and delivery info, with actions to edit delivery details, delete, or submit (marks the Order status as `Activated`).

Where to drop it

- **Target:** Lightning Record Page
- **Object:** Case
- **App Builder label:** `SE_FR — Order Summary`

Apex dependencies

- `SE_FR_OrderSummaryController` — exposes `getOrderDetailsFromCase`, `submitOrderToERP`, `saveDeliveryDetails`, `deleteOrderRecord`.

Standard fields used

- `Case.AccountId`, `Case.ContactId` + `Contact.AccountId` — to resolve which Account to look up orders for.
- `Order.EndDate` — displayed as "estimated delivery date" and edited via the delivery form.
- `Order.Status` — set to `Activated` when the user clicks "Submit order".

Optional custom field

- `Product2.Image_URL__c` (URL) — if present, shows a thumbnail in the product list. Gracefully skipped.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`Linked Order`	
`cardIcon`	String	`standard:orders`	
`showBottomSeparator`	Boolean	`true`	Shows a horizontal "OR" divider at the bottom of the card.
`separatorLabel`	String	`OR`	Text inside the divider.
`currencyCode`	String	`USD`	
`successMessage`	String	`Order submitted.`	Toast on submit.
`deleteConfirmMessage`	String	`Delete this order?`	Browser `confirm()` prompt.
`emptyStateMessage`	String	`No order found for this case.`	Displayed when the Case has no resolvable Account or that Account has no Order.
`productImageFieldApiName`	String	`Image_URL__c`	Field on `Product2` holding an image URL. Schema-safe.
`productImageFallbackUrl`	String	—	URL used when no image is found on the product.

Replace action

Beyond the auto-resolved order (latest order of the Case's account / contact's account), clicking **Replace** opens a record picker so the user can manually select any Order. That choice is held in memory only — reloading the page reverts to the auto-resolved order. Use the "Back to default" link in the blue banner to clear the override.

Install

1. Deploy `classes/SE_FR_OrderSummaryController.cls`.
2. Unzip `seFrOrderSummary.zip`, deploy the LWC bundle.
3. Drop `SE_FR – Order Summary` on a Case record page.

Component · Pipeline Snapshot (`seFrPipelineSnapshot`)

> **API name:** `seFrPipelineSnapshot` · **Categories:** Sales · **Surfaces:** RecordPage · **Objects:** Account, Opportunity · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_PipelineSnapshotController

Summary: Account-level pipeline visualization with summary tiles and one column per Opportunity stage.

Key configurable props / settings of seFrPipelineSnapshot:

- Max opportunities, status filter
- Show / hide total
- Currency display

SE benefit: Sidebar-friendly width — fits the narrow right column without breaking. No setup needed: reads any open Opportunity on the Account.

seFrPipelineSnapshot (Pipeline Snapshot)

B2B — Account-level pipeline visualisation. Three summary tiles at the top (total pipeline, weighted total, opportunity count) and one column per `Opportunity.StageName` with the list of deals in each stage. Bilingual EN / FR.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Opportunity (on Opportunity, resolves the parent AccountId)
- **App Builder label:** `CCO FR – Pipeline Snapshot`

Apex dependency

`SE_FR_PipelineSnapshotController.getPipeline(recordId, objectApiName, limitCount, includeClosed)`.

Properties

NAME	DEFAULT	DESCRIPTION
`language`	`en`	`en` or `fr`. Translates the tile labels and the Stage column names (Prospecting → Prospection, etc.).
`cardTitle`	—	Override the default ("Pipeline Snapshot" / "Aperçu du pipeline").
`currencyCode`	`USD`	
`localeTag`	`en-US`	
`limitCount`	40	1–200.
`includeClosed`	`false`	Include Closed Won / Closed Lost columns.
`hideNewOppButton`	`false`	

Install

1. Deploy `classes/SE_FR_PipelineSnapshotController.cls`.
2. Unzip `seFrPipelineSnapshot.zip`, deploy the LWC bundle.
3. Drop `CCO FR – Pipeline Snapshot` on an Account or Opportunity record page.

Data enrichment prerequisites

The component is most impactful on an Account that owns **several Opportunities at different stages**. A fresh SDO often has:

- few Opps on a typical Account, or
- all Opps on the same Stage ("Closed Won" by default on Omega Inc., for example).

Component · Prompt Launcher (`seFrPromptLauncher`)

> **API name:** `seFrPromptLauncher` · **Categories:** Productivity · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_PromptLauncherController

Summary: Configurable AI panel running Salesforce Prompt Templates via Invocable Actions, with auto-filled record context.

Key configurable props / settings of seFrPromptLauncher:

- `promptsJson` · catalogue (apiName, label, icon, objects[], userInputs[], extraInputs)
- Auto record-type filtering (Account → Account summary, Home → free-text prompts)
- Auto-detect HTML / Markdown response · dynamic height
- `autoRunFirstPrompt` · trigger AI on page load
- `resultAccent` · blue / purple / green · `maxHeight` · optional cap
- `namedCredential` · default `Agentforce_API`

SE benefit: Default catalogue covers Account / Contact / Opportunity / Lead / Case summaries + free-text Summarize/Refine — drop on any record page, the right prompt shows up automatically. Save as Note attaches the AI output to the record in one click.

CCO FR - Prompt Launcher (`seFrPromptLauncher`)

> ⚠️ The bundle is still named `seFrPromptLauncher` for backward compatibility with FlexiPages that already reference it. The component itself is now a **Prompt Launcher**: the chat surface was retired because the Agent API isn't provisioned on most demo orgs.

A configurable AI panel that runs Salesforce **Prompt Templates** via the Invocable Actions endpoint. The SE picks which prompts to expose, the user clicks one, the response renders inline with HTML formatting.

Targets

- `lightning__AppPage`
- `lightning__HomePage`
- `lightning__RecordPage`

What it does

1. Shows a **pill switcher** at the top — one button per applicable prompt.
2. The component **filters** prompts to those compatible with the host record type (`objects` array in the config). On a Home Page, prompts with an empty `objects` array show.
3. If the active prompt requires user inputs (e.g. "Text to summarize"), they appear as a small form. **Record context is auto-filled** — you don't ask the user to type the recordId.
4. Click **Run**, the response renders in a colored panel with copy + save-as-Note actions.
5. **Re-run** with the same inputs in one click.
6. **Save as Note** persists the AI response on the current record (only on Record Pages).

Quick start

Drop on a **Record Page** (Account, Contact, Opportunity, Lead, Case) — the default catalogue auto-detects the record type and shows the right summary prompt.

Drop on a **Home Page** — the default catalogue shows "Summarize text" and "Refine text" (input-driven prompts that don't need a record).

For a custom catalogue, paste a JSON array in the **Prompts catalogue (JSON)** property.

Default catalogue

The component ships with a default catalogue covering the common SDO-shipped prompt templates:

PROMPT API NAME	VISIBLE LABEL	AVAILABLE ON
`einstein_gpt__summarizeAccountDefault`	Account summary	Account record pages
`einstein_gpt__summarizeContact`	Contact summary	Contact record pages
`einstein_gpt__summarizeDeal`	Deal summary	Opportunity record pages
`einstein_gpt__summarizeLead`	Lead summary	Lead record pages
`svc_emp_intelligence__SummarizeRecord`	Case summary	Case record pages
`einstein_gpt__summarizeText`	Summarize text	Anywhere (free-text input)
`einstein_gpt__refineText`	Refine text	Anywhere (free-text input)

To override, paste your own JSON array in the **Prompts catalogue (JSON)** property.

Prompt config — JSON shape

```
[
    {
        "apiName": "einstein_gpt__summarizeAccountDefault",
        "label": "Account summary",
        "icon": "utility:summarydetail",
        "objects": ["Account"],
        "recordInputName": "Input:Account"
    },
    {
        "apiName": "my_custom_template__competitorAnalysis",
        "label": "Competitor analysis",
        "icon": "utility:opportunity",
        "objects": ["Account"],
        "recordInputName": "Input:Account",
        "userInputs": [
            { "name": "competitor", "label": "Main competitor", "type": "text", "required": true }
        ]
    },
    {
        "apiName": "einstein_gpt__refineText",
        "label": "Refine text",
        "icon": "utility:magicwand",
        "objects": [],
        "userInputs": [
            { "name": "textToRephrase", "label": "Text to refine", "type": "textarea", "required": true }
        ]
    }
]
```

FIELD	REQUIRED	DESCRIPTION
`apiName`	yes	Prompt template DeveloperName (with namespace if any)
`label`	yes	Visible button label
`icon`	no	SLDS icon. Defaults to `utility:einstein` if omitted
`objects`	no	Array of host SObject API names. Empty/omitted → always show
`recordInputName`	no	Input name auto-filled with the host record's Id (e.g. `Input:Account`). Omit on Home Page prompts
`userInputs`	no	Array of business-level inputs the user types in. See below

`userInputs[]` shape:

```
{
    "name": "competitor",          // input name as expected by the prompt template
    "label": "Main competitor",    // visible label
    "type": "text",                // text | textarea | number | picklist
    "required": true,              // optional, defaults to false
    "placeholder": "Microsoft",    // optional
    "options": ["A", "B", "C"]     // for type=picklist only
}
```

The component **only asks for business-level inputs**. Technical inputs the prompt template expects (record id, prompt version id, internal flags) are filled automatically or omitted.

How to find available prompt templates on your org

```
sf apex run --target-org <your-org-alias> --apex-code 'HttpRequest req = new HttpRequest();
req.setEndpoint("callout:Agentforce_API/services/data/v62.0/actions/custom/generatePromptResponse");
req.setMethod("GET");
req.setHeader("Accept", "application/json");
HttpResponse res = new Http().send(req);
System.debug(res.getBody());'
```

The body lists every prompt template accessible to the user. Look at the `name` field for the `apiName` to plug into the JSON.

Properties

PROPERTY	DEFAULT	DESCRIPTION
`language`	`fr`	`fr` / `en`
`cardTitle`	–	Override
`cardIcon`	`standard:einstein`	SLDS icon
`namedCredential`	`Agentforce_API`	Routes the Invocable Action callout
`promptsJson`	– (uses default catalogue)	JSON array as documented above
`autoRunFirstPrompt`	`false`	When ON, the first applicable prompt runs automatically as soon as the page loads
`resultAccent`	`blue`	Result panel accent: `blue` / `purple` / `green`
`height`	`480`	Component height in pixels

Named Credential setup

The component calls `callout:Agentforce_API/services/data/v62.0/actions/custom/generatePromptResponse/...`. The Named Credential injects OAuth.

If `Agentforce_API` doesn't exist in your org, create it via Setup → Named Credentials. See the audit doc or any of the related Salesforce setup guides for the OAuth dance — same setup as for any Apex callout to the Salesforce REST API.

Troubleshooting

ERROR	CAUSE	FIX
`Prompt config is invalid`	JSON syntax error in `promptsJson`	Check the JSON in App Builder; the component validates and shows the parser message
`No prompt configured for this record type`	Host page object isn't covered by any catalogue entry	Add an entry with `objects: ["YourObject"]` or set `objects: []`
`HTTP 404` in the result panel	Prompt API name wrong, or template not deployed on the org	List templates with the SOQL command above and copy the exact `name`
`HTTP 401 / 403`	Named Credential / OAuth issue	Re-authorize the Named Credential in Setup
`Named Credential not found`	NC missing	Create it (see above)

SE benefits

- **Real AI responses** on demo orgs that don't have full Agentforce API enabled — leverages the standard Invocable Action endpoint that's available everywhere Einstein is.
- **Auto-detection of record context** — drop on an Account record page, the right summary prompt shows up. No per-page config needed for the common cases.
- **Multi-prompt switcher** — pose 1 component on a record page, the user has 2-3 AI buttons available without you needing 2-3 components.
- **Save as Note** — one click to attach the AI output to the current record. Demos the platform's content storage without leaving the page.
- **HTML rendering** — Salesforce's prompt templates often return rich text (links, bold, lists). The component renders them properly via `lwc:dom="manual"` (same pattern as Contact Card's prompt summary).

Component · Record Actions (`seFrRecordActions`)

> **API name:** `seFrRecordActions` · **Categories:** Transverse · **Surfaces:** RecordPage · **Objects:** Account, Contact, Opportunity, Case, Lead · **Data mode:** hybrid · **Mobile-ready:** yes · **Apex:** SE_FR_AccountActionsController

Summary: Compact record-page toolbar for Account, Contact, Lead, Opportunity and Case — one primary button (Screen Flow or standard New Task / Event / Case / Opportunity form) + an inline Einstein AI summary.

Key configurable props / settings of seFrRecordActions:

- Primary action launches any Screen Flow (passes recordId as input)
- Ships with a default Flow `CCO_FR_Start_Visit` — creates a standard Event, zero managed-package dep
- Einstein prompt summary — defaults to `einstein_gpt__summarizeAccountDefault` with `Input:Account`
- Auto-detects HTML vs markdown Einstein output
- Rework prompt input to work on Contact / Opportunity / Case / Lead
- Markdown mini-parser (headers, lists, bold / italic, inline code)
- SLDS-themed buttons (`lightning-button variant="brand"`) — picks up the theme accent
- Standard SLDS icons (`standard:task`, `utility:*`)

SE benefit: Drop on any record page and get both a one-click AI summary (soft-fails if Einstein is off) and a configurable primary action that launches your own Screen Flow — no custom code to glue a Flow button to the record context.

CCO FR - Record Actions

Formerly: `seFrAccountActions` (renamed when the component became multi-object).
Original source: DBI retail-execution demo (`dimAccountActions` , 2026-07)
Ported to library by: Lionel Braun
Library-integrated: 2026-10-15

Compact toolbar for a record page. Two features in one card:

1. **Primary action button** — launches a Screen Flow (configurable `primaryActionFlowApiName`). The current record Id is passed as the `recordId` input variable. The Flow runs inside a modal; closes on `FINISHED` / `FINISHED_SCREEN` / `ERROR` .
2. **Einstein AI summary** — invokes an Einstein Prompt Template via `ConnectApi.EinsteinLLM.generateMessagesForPromptTemplate` . Default template is `einstein_gpt__summarizeAccountDefault` with the current record passed as `Input:Account` . Response rendered client-side with an inline markdown-to-HTML parser (headers, bullet / numbered lists, bold, italic, inline code).

Why SEs love it

- **Zero schema setup** — works on a stock Account page immediately. Point `primaryActionFlowApiName` at any Screen Flow you already have, and the summary is useful without any custom fields.
- **Flow-driven primary action** — covers the "Start a visit", "Open a case", "Create an order" use case patterns without hardcoding any sObject. Point it at a `Start_Visit_From_Account` Flow and you get the DBI demo UX for free.
- **Soft-fails on Einstein** — if the prompt template isn't deployed or Einstein is off, the component toasts a warning but keeps rendering. The primary action keeps working.
- **Bilingual (default FR)** — labels, loading states, toasts all switch via `language = 'fr' | 'en'` .
- **Mobile-ready** — compact layout and touch-friendly buttons.

Key configuration

PROPERTY	DEFAULT	NOTES
`language`	`fr`	`fr` or `en`.
`cardTitle`	—	Dictionary default: `Actions rapides` / `Quick actions`.
`accentColor`	—	Optional CSS color for the icon badge + primary button.
`disablePrimaryAction`	`false`	Hide the primary button entirely.
`primaryActionLabel`	—	Dict default: `Démarrer une visite` / `Start visit`.
`primaryActionIcon`	`utility:routing_offline`	SLDS icon name.
`primaryActionType`	`flow`	`flow` launches the Screen Flow; `newRecord` opens the standard New form of `newRecordObjectApiName` (Task, Event, Case, Opportunity…) — same targets as the standard quick actions of the org (NewTask, NewEvent, NewCase, NewOpportunity, NewContact, NewLead, NewNote, LogACall, SendEmail).
`newRecordObjectApiName`	—	Object created in `newRecord` mode.
`newRecordDefaults`	—	`Field=Value` pairs separated by `|`; tokens `{recordId}`, `{objectApiName}`. Example on a Contact: `WhoId={recordId}|Subject=Rendez-vous`.
`primaryActionFlowApiName`	`CCO_FR_Start_Visit`	Screen Flow API name launched on click. **Default Flow shipped with the component** — creates a standard `Event` rattaché au record courant (zero managed-package dep). Clone and point at your own Flow to override.
`disableAiSummary`	`false`	Hide the AI summary button + output area.
`aiSummaryLabel`	—	Dict default: `Résumé IA` / `AI summary`.
`promptTemplateApiName`	`einstein_gpt__summarizeAccountDefault`	Prompt template DeveloperName.
`promptInputApiName`	`Input:Account`	Change to `Input:Contact` / `Input:Opportunity` when placed on other objects.
`autoRunOnLoad`	`false`	When ON, runs the prompt automatically on mount.

Apex

- `SE_FR_AccountActionsController.getPromptSummary(Id, String, String)` — thin wrapper on top of `ConnectApi.EinsteinLLM`. No Named Credential needed.

> **Which mode for which object?** The shipped Flow `CCO_FR_Start_Visit` creates a retail visit on an **Account** (B2B visit context). On Contact / Lead / Opportunity / Case, use `primaryActionType = newRecord` (e.g. Event with `WhoId={recordId}`, Task with `WhatId={recordId}`).

Shipped Flow

`CCO_FR_Start_Visit.flow-meta.xml` — Screen Flow lancé par défaut par le bouton primaire.

- Crée un `Event` standard rattaché au record courant via `WhatId` (fonctionne sur Account / Opportunity / Case / Lead).
- Champs saisis : Objet, Date/heure de début, Date/heure de fin, Lieu, Notes.
- Zéro dépendance au managed package Retail Execution / Field Service — utilise l'`Event` standard, universel.
- Variable input : `recordId` (String).
- Variable output : `newEventId` (String — Id de l'Event créé).
- Admin peut cloner et pointer `primaryActionFlowApiName` sur son propre Screen Flow pour créer un `Visit` custom, un `Case`, ou tout autre sObject.

Pattern conforme à la règle de compliance 10.14 ("Component ships with a default Flow"), voir `_build/LIB_COMPLIANCE_SPECS.md`.

Lineage / library-compliance notes

Port of `dimAccountActions` (DBI retail-execution demo, 2026-07). Changes applied to make it lib-compliant (see `_build/LIB_COMPLIANCE_SPECS.md`):

- All DIM / client references stripped (CSS variables renamed `--dim-*` → `--sefraa-*`, custom palette removed in favor of `accentColor` override).
- Hardcoded `Visit` sObject creation replaced by a configurable Flow launch (compliance rule 10.9 — Visit requires Field Service / Retail Execution managed package, so we don't ship with a hard dependency). Default Flow `CCO_FR_Start_Visit` shipped with the component creates a standard `Event` instead (compliance rule 10.14).
- Apex pivoted from HTTP callout to `ConnectApi.EinsteinLLM.generateMessagesForPromptTemplate` (same pattern as `seFrContactCard`). No Named Credential setup required.
- Full FR/EN i18n via internal `LABELS` dictionary + `t()` getter.
- Markdown mini-parser kept inline — flagged as a candidate for a shared `seFrMarkdown` util when a 3rd component needs it.

Component · Record Highlights (`seFrRecordHighlights`)

> **API name:** `seFrRecordHighlights` · **Categories:** Transverse · **Surfaces:** RecordPage · **Objects:** Account, Contact, Opportunity, Case, Lead, Order, Contract · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_ImageFileController, SE_FR_RecordHighlightsController

Summary: Custom highlights panel with round image, key fields and action buttons, working on 8 standard objects.

Key configurable props / settings of seFrRecordHighlights:

- `language` · en / fr
- `recordSource` · current / parent
- `accountFieldsList`, `contactFieldsList`
- `imageFieldApiName` · URL field on the record
- `maxQuickActions` · loaded from layout

SE benefit: Click the avatar to upload / replace the image instantly — no static resource, no public URL hosting, no custom field. The image is saved as a File on the record.

seFrRecordHighlights (Record Highlights)

Custom highlights panel for an **Account** or a **Contact** record page. Shows a round image, the record name, a configurable field strip and two action buttons.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Contact, Opportunity, Case, Lead, Order, Contract, Quote
- **App Builder label:** `CCO FR – Record Highlights`

Record source — which record gets displayed

RECORDSOURCE	WHAT IS DISPLAYED
`current` *(default)*	The record on the current page. Example: drop on Contact → shows the Contact.
`parent`	The parent Account linked to the current record. On an **Account** page, this resolves to the **Parent Account** via `ParentId`. Supported lookups: Contact→AccountId, Opportunity→AccountId, Case→AccountId, Lead→ConvertedAccountId, Order→AccountId, Contract→AccountId, Quote→AccountId.

Classic examples:

- Show the **Contact** on a Contact page → drop on Contact, `recordSource = current` (default).
- Show the **Account** on a Contact page → drop on Contact, `recordSource = parent`.
- Show the **parent Account** on an Account page (the hierarchy parent) → drop on Account, `recordSource = parent`.
- Show the **Account** on an Opportunity, Case, Order, Contract or Quote page → drop on that object, `recordSource = parent`.

When `parent` is selected but the lookup is empty, an inline message is shown ("This Contact is not linked to an Account.") — no card noise.

(Folder and technical component name stay `seFrRecordHighlights` for v1 compat — drop it from the palette under the master label above.)

Apex dependencies

None.

Behavior

- If `customImageUrl` is set, that URL is used.
- Otherwise the component reads `imageFieldApiName` on the current record (default `ImageURL__c`). Schema-safe: if the field doesn't exist, the image falls back silently.
- When no image is available, a large SLDS icon is shown in the circle — `standard:account` or `standard:contact` based on the current object.
- Buttons adapt to the object:
- Account: **Edit** + **View Account Hierarchy** (opens `/lightning/r/Account/<id>/hierarchy`).
- Contact: **Edit** + **Email** (triggers the standard `Contact.SendEmail` quick action).
- Toggle `disableRealButtons` to hide the real actions and show `fakeButtonLabels` (CSV) as demo buttons.
- Field strip is driven by one of two properties depending on the object: `accountFieldsList` or `contactFieldsList`.
- Image size (diameter in px) configurable via `imageSize` (default 90).

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`recordSource`	String	`current`	`current` or `parent`. See the table above.
`accountFieldsList`	String	`AccountNumber, Industry, Type, Phone`	Comma-separated field API names shown on Account.
`contactFieldsList`	String	`Title, Email, Phone, Department`	Comma-separated field API names shown on Contact.
`customImageUrl`	String	—	Direct image URL (overrides the record field).
`imageFieldApiName`	String	`ImageURL__c`	Field holding the record's image URL.
`imageSize`	Integer	`90`	Diameter of the round image, in pixels.
`disableRealButtons`	Boolean	`false`	When on, hide Edit/secondary action and show fake demo buttons.
`fakeButtonLabels`	String	`Create Quote, Schedule Visit`	Comma-separated labels for the demo buttons.

Legacy `fieldsList` property is preserved (for v1 pages) but marked deprecated — use `accountFieldsList` instead.

Install

1. Unzip `seFrRecordHighlights.zip`, deploy the LWC bundle.
2. Drop `CCO FR – Record Highlights` on an Account or Contact record page.

Component · Related Record Card (`seFrRelatedRecordCard`)

> **API name:** `seFrRelatedRecordCard` · **Categories:** Transverse · **Surfaces:** RecordPage · **Objects:** Account, Contact, Case, Opportunity, Order · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_ImageFileController, SE_FR_RelatedRecordCardController

Summary: Vertical sidebar card showing the counterpart record (Contact / Account) with key fields and avatar.

Key configurable props / settings of seFrRelatedRecordCard:

- `target` · auto / account / contact
- `fieldsCsv` per target
- Per-target image field (Contact + Account)

SE benefit: Click the avatar to upload an image for the related record — handy for setting an Account logo or a Contact picture without leaving the page. Default Contact image field `SDO_Cust360_Contact_Picture_URL__c` works out-of-box on SDO.

CCO FR - Related Record Card

Vertical card (Contact / Account avatar + key fields) showing the counterpart of the current record. Designed for a narrow sidebar column on Account, Contact, Case, Opportunity or Order record pages.

Pick behaviour

CURRENT RECORD	TARGET=AUTO DISPLAYS	DATA SOURCE
Account	Primary / first Contact	`Account.PersonContactId` (Person Account) → first child Contact
Contact	Account	`Contact.AccountId`
Case	Account	`Case.AccountId`
Opportunity	Account	`Opportunity.AccountId`
Order	Account	`Order.AccountId`

Force a specific target with `target=account` or `target=contact` (e.g. show the Contact behind a Case via `Case.ContactId` — set `target=contact` on a Case page).

Properties

PROPERTY	DEFAULT	DESCRIPTION
`language`	`fr`	`en` or `fr`. Controls titles, buttons, empty state.
`target`	`auto`	`auto` / `account` / `contact`.
`cardTitle`	*(language default)*	Override only if you want a custom title.
`cardIcon`	*(auto)*	SLDS icon name. Defaults to `standard:account` or `standard:contact`.
`fieldsCsv`	*(target-specific)*	Comma-separated API names. Contact: `Title,Department,Email,Phone,MobilePhone`. Account: `Industry,Type,Phone,Website,AnnualRevenue,NumberOfEmployees`. Unknown fields are silently skipped.
`imageFieldApiName`	`PhotoURL`	Works out-of-box for Contact. For Account, point to a custom image URL field (or leave; the card shows initials).

Visual behaviour

- Avatar: image if available, otherwise gradient circle with initials.
- Click on the header → opens the related record.
- Phone / email / url fields render as clickable links (`tel:`, `mailto:`, external URL).
- Empty state when the source record has no counterpart (e.g. a Case without `AccountId`).

Apex dependency

`SE_FR_RelatedRecordCardController` — deploy once per org.

Component · seFrRetailExecSchema (`seFrRetailExecSchema`)

> **API name:** `seFrRetailExecSchema` · **Categories:** — · **Surfaces:** — · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** no · **Apex:** none

CCO FR — Retail Execution Schema (`seFrRetailExecSchema`)

Socle de données du pattern Retail Execution de la lib.

Un `CustomObject` `Visit__c` + fields + permset. Rien d'autre. Ce bundle n'a pas de LWC — c'est le prérequis schema sur lequel les composants `seFrVisit*` (et le Flow `CCO_FR_Start_Visit` quand il crée des visites) s'appuient.

Pourquoi un sObject custom ?

Le pattern Retail Execution DIM / CGC s'appuie sur le sObject **standard** `Visit` du managed package **Retail Execution** (Consumer Goods Cloud / Industries). Mais la lib CCO FR est **zero managed-package dep** (rule 10.14). On ship donc notre propre `Visit__c` identique dans l'esprit (lifecycle, dates planned / check-in / check-out).

Si vous êtes sur une org qui a déjà le managed package Retail Execution, ne déployez pas ce bundle : pointez les composants `seFrVisit*` sur `Visit` à la place (modifier `<object>Visit__c</object>` → `<object>Visit</object>` dans les js-meta.xml).

Si vous êtes sur une org qui a déjà son propre `Visit__c`, ne déployez pas ce bundle non plus — adaptez les field API names dans les controllers Apex si besoin.

Contenu

```
seFrRetailExecSchema/
├── README.md
├── objects/
│   └── Visit__c/
│       ├── Visit__c.object-meta.xml           — AutoNumber "V-{0000}", Public RW, Activities + Feeds + History
│       └── fields/
│           ├── Account__c.field-meta.xml      — Lookup(Account), SetNull
│           ├── VisitState__c.field-meta.xml   — Picklist (Planned / In Progress / Completed / Cancelled)
│           ├── PlannedStartDateTime__c.field-meta.xml
│           ├── PlannedEndDateTime__c.field-meta.xml
│           ├── CheckInDateTime__c.field-meta.xml
│           ├── CheckOutDateTime__c.field-meta.xml
│           ├── Location__c.field-meta.xml     — Text(255)
│           ├── Notes__c.field-meta.xml        — LongTextArea
│           └── Summary__c.field-meta.xml      — LongTextArea (résumé IA)
└── permissionsets/
    └── CCO_FR_Retail_Exec.permissionset-meta.xml  — Full CRUD on Visit__c + all fields
```

Déploiement

```
sf project deploy start -d seFrRetailExecSchema/objects -d seFrRetailExecSchema/permissionsets -o <alias>
sf org assign permset -n "CCO_FR_Retail_Exec" -o <alias>
```

Composants qui en dépendent

- `seFrVisitSummaryAI` — résumé IA sur un record Visit__c
- *(à venir)* `seFrVisitKanban` — vue lifecycle Planned → In Progress → Completed sur Account
- *(à venir)* `seFrVisitShelfCompliance` — upload photo rayon + analyse IA (depuis page Visit__c)
- *(à venir)* `seFrVisitQuickOrder` — prise de commande rapide (depuis page Visit__c)
- Flow `CCO_FR_Start_Visit` (shipped par `seFrRecordActions`) — crée un `Visit__c` et navigue dessus

Lifecycle visité (convention)

ÉTAT	DÉCLENCHEUR	COMPOSANTS ACTIFS
`Planned`	Création via Flow `CCO_FR_Start_Visit`	infos (`PlannedStart/EndDateTime`)
`In Progress`	Check-in utilisateur (manuel ou geoloc) → stamp `CheckInDateTime__c`	all retail-exec LWCs
`Completed`	Check-out utilisateur → stamp `CheckOutDateTime__c` → optionnel : auto-résumé IA	`seFrVisitSummaryAI` affiche le résumé final
`Cancelled`	Manuel	read-only

Component · Revenue Dashboard (`seFrRevenueDashboard`)

> **API name:** `seFrRevenueDashboard` · **Categories:** Dashboards & KPIs · **Surfaces:** RecordPage · **Objects:** Account · **Data mode:** mock · **Mobile-ready:** no · **Apex:** none

Summary: 3-year revenue mini-dashboard with KPI tiles and a side-by-side monthly bar chart.

Key configurable props / settings of seFrRevenueDashboard:

- Months back, comparison year
- Bucket source field, currency code

SE benefit: Built-in YoY overlay — gives the "story" of growth or decline visually, without configuring a real Salesforce dashboard.

seFrRevenueDashboard

3-year revenue mini-dashboard with 3 KPI tiles and a monthly bar chart comparing three years side by side. Fully configurable — you can change labels, years, max scale, and provide a custom monthly dataset via JSON.

Where to drop it

- **Target:** Lightning Record Page
- **Object:** Account
- **App Builder label:** `SE_FR — Revenue Dashboard`

Apex dependencies

None.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`Delivered Revenue (3 years)`	
`cardIcon`	String	`standard:performance`	
`currencyCode`	String	`USD`	
`localeTag`	String	`en-US`	
`year1Label` / `year2Label` / `year3Label`	String × 3	`2024` / `2025` / `2026`	Chart legend + bar tooltips.
`kpi1Label` / `Value`	String / Integer	`YTD Revenue` / `38550`	Currency-formatted.
`kpi2Label` / `Value`	String / String	`YoY Trend` / `+14.2%`	Raw text.
`kpi3Label` / `Value`	String / Integer	`Previous Year Total` / `114200`	Currency-formatted.
`chartMaxScale`	Integer	`15000`	Y-axis maximum. Y-axis labels are auto-computed at 1/3 intervals.
`chartDataJson`	String (rich)	12-month sample	JSON array `[{"month":"Jan","y1":8200,"y2":8900,"y3":9500}, …]`.

Install

1. Unzip `seFrRevenueDashboard.zip`, deploy the LWC bundle.
2. Drop `SE_FR — Revenue Dashboard` on an Account record page.
3. Replace `chartDataJson` with your dataset.

Data enrichment prerequisites

The component is **purely driven by the `chartDataJson` property** — it does **not** query Orders or Opportunities automatically. Two paths:

- **Demo mode (recommended for pitches)**: leave the default sample data, or override `chartDataJson` in App Builder with a hand-crafted narrative (e.g. show a growth curve that matches the customer story you're telling).
- **Data-backed mode**: populate `chartDataJson` from real org data via an Apex invocable or a pre-processing Flow. Requires the SE to write the bridging logic.

If you want an automatic "derived from real Orders" variant, pair this component with `seFrMetricTile` instead, which can be fed from an Apex wire. `seFrRevenueDashboard` stays intentionally static for demo flexibility.

Component · Service Contracts (`seFrServiceContracts`)

> **API name:** `seFrServiceContracts` · **Categories:** Service · **Surfaces:** RecordPage · **Objects:** Account, Case, Contact, Opportunity, WorkOrder · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_ServiceContractsController

Summary: Active service contracts per Account with deadline countdown, trade badge, SLA and open work order counter.

Key configurable props / settings of seFrServiceContracts:

- Language (FR/EN)
- Card title override
- Card icon override

SE benefit: Shows the full contractor landscape for an account in one glance - deadlines, SLAs, open interventions, contact emails. Ideal for Field Service, property management and B2B service demos.

CCO FR - Service Contracts

Lists active service contracts linked to an Account with a deadline countdown, open work order counter, navigation to the record, and optional enriched columns (category badge, SLA, contractor email, scope). Click any row to navigate to the ServiceContract record.

Two modes — works out of the box, upgradable

Standard mode (zero custom fields — works on any SDO)

The component queries **only standard fields** (`Name` , `ContractNumber` , `StartDate` , `EndDate` , `Description`) and counts open WorkOrders using the standard `Status` field (anything not Completed / Closed / Canceled).

You get: contract list with name, number, **deadline countdown** (color-coded: green >30d, orange ≤30d, red = expired), description as scope, and open WO counter. Ready to use immediately.

Full mode (5 optional custom fields — original Thomas Plaindoux design)

When the custom fields below are detected on the org, the component **automatically** upgrades its display: colored category badges, SLA formatting, contractor email link, and custom intervention status counting.

Custom fields to create for Full mode:

On `ServiceContract` :

FIELD API NAME	TYPE	VALUES / DESCRIPTION
`Metier__c`	Picklist (restricted)	Trade/category labels. Example values: Plomberie, Electricite, Ascenseur, Chauffage, Espaces verts, Serrurerie, Peinture, Multi-services (adapt to your demo context)
`SLA_Heures__c`	Number (0 decimals)	SLA commitment in hours (e.g. 4, 24, 48, 72)
`Email_Prestataire__c`	Email	Contractor contact email
`Perimetre_Couvert__c`	TextArea (255)	Scope / perimeter description

On `WorkOrder` :

FIELD API NAME	TYPE	VALUES / DESCRIPTION
`Statut_Intervention__c`	Picklist	Intervention lifecycle. Open statuses (counted as red): Signalee, Mandatee, Planifiee, Reportee, Bloquee. Closed statuses (not counted): Realisee, Cloturee, Annulee

Data seeding for Full mode demo:

1. Create 3-5 `ServiceContract` records on an Account, each with a different `Metier__c` value, realistic `SLA_Heures__c` (4h for urgent, 48h for standard), an email, and a scope description.
2. Create 1-3 `WorkOrder` records per contract with `Statut_Intervention__c` set to open values (Signalee, Mandatee, Planifiee) to see the red counter.

Key features

- **Hybrid Apex** — dynamic SOQL detects available fields at runtime, never crashes on missing custom schema
- **Deadline countdown** — computed from `EndDate` , color-coded: green (>30 days), orange (≤30 days), red (expired)
- **Colored category badges** (Full mode) — deterministic palette rotation based on distinct `Metier__c` values
- **SLA formatting** (Full mode) — hours < 24 shown as `Xh` , otherwise `Xj Yh`
- **Open work orders** — red warning counter (standard Status or custom Statut_Intervention__c)
- **Scope / perimeter** — shows `Perimetre_Couvert__c` if present, falls back to standard `Description`
- **Navigation** — click on contract name navigates to ServiceContract record page
- **Bilingual** FR / EN via `language` prop

Properties

PROPERTY	TYPE	DEFAULT	DESCRIPTION
`language`	String	`fr`	`'fr'` or `'en'`
`cardTitle`	String	*(dict)*	Override card title
`cardIcon`	String	`standard:service_contract`	SLDS icon

Apex

- `SE_FR_ServiceContractsController` — cacheable wire, dynamic SOQL, returns `ContractDTO[]` with open work order counts and EndDate for deadline computation. Uses `Schema.SObjectType.*.fields.getMap()` to detect custom fields at runtime.

Component · Smart Recommendations (`seFrSmartRecommendations`)

> **API name:** `seFrSmartRecommendations` · **Categories:** Productivity · **Surfaces:** RecordPage · **Objects:** Account, Contact, Case, Order, Opportunity, Lead · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Context-aware Next Best Action panel with 1-6 recommendations, relevance score and per-card overrides.

Key configurable props / settings of seFrSmartRecommendations:

- Recommendations CSV (label + reason + icon)
- Einstein prompt template (optional)

SE benefit: Default narratives are tuned for SDO-style sales scenarios. Plug an Einstein prompt template to flip the same UI into a real AI demo without rewiring the layout.

seFrSmartRecommendations

Context-aware "Next Best Action" panel that shows 1–6 recommendations depending on the object type the record page is on. Each recommendation has a title, a reason, a fake relevance score, and an action button. Admins can override any recommendation's title and reason via properties.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Contact, Case, Order
- **App Builder label:** `SE_FR — Smart Recommendations`

Apex dependencies

None.

Display modes

- **Global** *(default)*: shows the first 2 recommendations for the current object type.
- **Targeted**: shows only the recommendations configured for a specific record ID. You can configure up to 3 target records, each with a comma-separated list of recommendation indices (e.g. `1,3,4`).

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`Smart Recommendations`	
`displayMode`	String (picklist)	`Global`	`Global` or `Targeted` .
`targetId1..3`	String × 3	—	Record Id that activates the matching `targetRecos*` list.
`targetRecos1..3`	String × 3	—	Comma-separated indices `1..6` to show on that record.
`customTitle1..6` / `customDesc1..6`	String × 12	—	Override default title / description per recommendation. Leave empty to use the built-in text for the current object type.

Install

1. Unzip `seFrSmartRecommendations.zip` , deploy the LWC bundle.
2. Drop `SE_FR — Smart Recommendations` on an Account / Contact / Case / Order record page.
3. Optionally override titles / descriptions to fit the customer context.

Component · Splash Banner (`seFrSplashBanner`)

> **API name:** `seFrSplashBanner` · **Categories:** Transverse · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Welcome banner with 8 animated background styles (waves, aurora, mesh, orbs, conic, geometric, constellation, grid) in pure CSS / SVG.

Key configurable props / settings of seFrSplashBanner:

- Title, subtitle, text size, alignment
- Background style (8 options)
- 3 colors (primary / secondary / tertiary)
- Height, animation speed
- Optional CTA button

SE benefit: 8 distinct visual moods — pick "Constellation" or "Conic" for AI demos, "Waves" for sober customer-success vibes, "Aurora" for premium / luxury. No images / static resources to upload.

CCO FR - Splash Banner (`seFrSplashBanner`)

Bannière d'accueil / splash screen avec fond animé. **8 styles de fond** au choix, tous en pur CSS + SVG inline (zéro librairie externe). Le SE configure juste un titre, un sous-titre optionnel et le style de fond — tout le reste est paramétrable depuis App Builder (couleurs, hauteur, vitesse, alignement, bouton CTA).

Targets

- `lightning__HomePage`
- `lightning__AppPage`
- `lightning__RecordPage`

Les 8 styles de fond

BGSTYLE	VIBE	CAS D'USAGE
`waves`	doux, organique (clin d'oeil aux vagues de Charly Ansel)	bannière welcome standard
`aurora`	aurores boréales, blend `screen`	luxe / premium / cosmétique
`mesh`	mesh gradient Stripe homepage	SaaS moderne, dashboard
`orbs`	sphères flottantes blurred (Apple keynote)	élégant, généraliste
`conic`	conic gradient qui tourne (Vercel)	flashy, dev-tool, AI
`geometric`	low-poly SVG triangulé qui pulse	tech, WWDC
`constellation`	points reliés type étoiles	data, AI, futuriste
`grid`	blueprint avec pulse + scan-line	tech, monitoring, "matrix-light"

Tous les fonds respectent `prefers-reduced-motion` (animations désactivées si l'utilisateur a activé la préférence d'accessibilité système).

Propriétés (App Builder)

PROPRIÉTÉ	DESCRIPTION
`title`	Titre principal (centré, gros). Émojis acceptés. **Supporte le markdown inline** (voir ci-dessous).
`subtitle`	Sous-titre optionnel sous le titre. **Supporte le markdown inline**.
`textSize`	`s` / `m` / `l` (défaut) / `xl`
`bgStyle`	Voir tableau ci-dessus. Défaut : `waves` .
`colorPrimary`	Couleur 1 (CSS hex, rgb, named). Défaut bleu Lightning `#0176d3` .
`colorSecondary`	Couleur 2. Défaut violet `#a445ff` .
`colorTertiary`	Couleur 3. Défaut rose `#ff6ec7` . Ignorée par `waves` (qui n'en utilise que 2).
`height`	Hauteur en pixels. Défaut 220.
`darkText`	Off (défaut, texte blanc) / On (texte noir).
`animationSpeed`	`slow` / `normal` (défaut) / `fast`
`alignment`	`center` (défaut) / `left` / `right`
`ctaLabel`	Label du bouton optionnel sous le texte.
`ctaUrl`	URL du bouton (Salesforce relative ou absolue).

Markdown inline dans `title` / `subtitle`

Un parseur léger (XSS-safe, aucune `innerHTML`) interprète 5 marqueurs dans `title` et `subtitle`.

SYNTAXE	RENDU	HTML PRODUIT
`**gras**`	**gras**	`<strong>`
`*italique*` ou `_italique_`	*italique*	`<em>`
`__souligné__`	souligné	`<u>`
`` `code` | `code` | `(fond translucide, police mono)`		
`~~barré~~` | `~~barré~~` | `<s>`		

Exemples :

- Bonjour, bienvenue sur **CCO FR Showcase** → *Bonjour, bienvenue sur* **CCO FR Showcase**
- Déploiement \ CCO_FR_Showcase\ **réussi** → mixe code + gras
- Alerte __critique__ : service dégradé → underline + emphase

Chaque segment est rendu comme un élément HTML natif via template for:each + lwc:if → aucun risque d'injection (zéro innerHTML, zéro lwc:dom="manual").

Conseils visuels

- Pour un effet **premium** : aurora + couleurs pastel (rose / violet / bleu) + darkText=false.
- Pour un effet **tech / Agentforce** : conic ou constellation + couleurs vives (bleu / violet / cyan).
- Pour un effet **discret** : waves ou orbs + une seule couleur de marque + animation slow.
- Pour une **landing page d'app** : mesh` + 3 couleurs de marque, hauteur 300px, CTA "Explorer".

Aucune dépendance Apex

Composant 100% front. Pas d'Apex requis. Aucun champ custom.

Component · Subscribers List (`seFrSubscribersList`)

> **API name:** `seFrSubscribersList` · **Categories:** Service · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_SubscribersListController

Summary: Live account team panel with profile photos, roles and record navigation.

Key configurable props / settings of seFrSubscribersList:

- Language (FR/EN)
- Source mode (live/mock)
- Card title override

SE benefit: Displays the team working on a record (Account owner, Opp team members) in one click - with photos, roles, and navigation to User profiles. Works out of the box on any SDO with no setup.

CCO FR - Subscribers List

Displays the team of Users linked to the current record — with profile photos (when available), Salesforce role badges, and clickable names that navigate to User record pages.

Where to drop it (and what shows)

SURFACE	WHAT YOU SEE (LIVE MODE)	DEFAULT MODE
Account record page ⭐	Account Owner + Users on OpportunityTeamMembers of all child Opps (deduplicated)	live
Opportunity record page ⭐	Opp Owner + OpportunityTeamMembers	live
Case record page	Case Owner + Account Owner (if different)	live
Lead / Contact / Order / any other record page	Record Owner only (lean output, useful as a 1-line "owner" panel)	live
App page	Mock data (pipe-separated names/roles via App Builder props)	mock
Home page	Mock data (same as App page)	mock

⭐ = richest scenario (recommended for demos).

How it works

Live mode (default — zero setup, works on any org)

The component queries Users related to the current record. The recordId-less surfaces (App / Home) automatically fall back to mock mode using the configured pipe-separated props.

Results are sorted by seniority (VP/Director first, then managers, then sales, then agents).

Profile photos are shown when the User has a custom photo uploaded; otherwise, a gradient-colored initials circle is displayed.

Mock mode (pipe-separated props)

Set `sourceMode` to `mock` in App Builder to use custom names/roles from properties. Useful for:

- App/Home pages (no recordId)
- Demo scenarios with specific data

Key features

- **Live Apex** — cacheable wire, multi-object compatible (Account, Opportunity, Case, any SObject)
- **Profile photos** — auto-detects custom uploaded photos vs default Salesforce avatar
- **Gradient initials** — subtle professional blue/purple palette when no photo available
- **Role badges** — shows UserRole.Name in a pill badge
- **Clickable names** — navigates to User record page
- **Smart sorting** — executives first, then by role seniority
- **Bilingual** FR / EN via `language` prop
- **Pagination** — 6 visible + expand button (round icon, library standard)

Properties

PROPERTY	TYPE	DEFAULT	DESCRIPTION
`language`	String	`fr`	`'fr'` or `'en'`
`cardTitle`	String	*(dict)*	Override card title (default: "Equipe du compte" / "Account Team")
`cardSubtitle`	String	*(auto)*	Override subtitle (auto = "N membres")
`cardIcon`	String	`standard:team_member`	SLDS icon
`sourceMode`	String	`live`	`'live'` (Apex query) or `'mock'` (pipe-separated props)
`contactNames`	String		[Mock] Pipe-separated names
`roles`	String		[Mock] Pipe-separated roles
`userIds`	String		[Mock] Pipe-separated User IDs (enables clickable names + photos)

Apex

- `SE_FR_SubscribersListController` — cacheable wire, multi-object detection via `getSObjectType()`, queries Owner + team relationships. Returns `TeamMemberDTO[]` with userId, name, role, photoUrl, initials.

Component · Telesales - Rep Home (`seFrTelesalesRepHome`)

> **API name:** `seFrTelesalesRepHome` · **Categories:** Dashboards & KPIs · **Surfaces:** AppPage, HomePage · **Objects:** Any · **Data mode:** hybrid · **Mobile-ready:** no · **Apex:** SE_FR_TelesalesController

Summary: Telesales rep home page with KPIs, live cases and orders tables, calls to make and 3 mini charts.

Key configurable props / settings of seFrTelesalesRepHome:

- Number of calls shown
- KPI tiles
- Quick action links

SE benefit: One template for Inside Sales Home — pre-composed, no need to wire 5 components manually in App Builder.

seFrTelesalesRepHome (Telesales — Rep Home)

B2B — Home / App page for a **telesales / inside-sales rep**. Greeting, 4 KPI tiles, **live cases table**, **live orders table**, calls to make (mock), 3 mini charts (channel / subject / monthly closed), training & news cards.

> **Tasks panel** lives in the dedicated sidebar component `seFrMyTasks` — drop it on the right column of the page to get the task list.

Where to drop it

- **Target:** Lightning Home Page, App Page (**not Record**)
- **App Builder label:** `CCO FR – Telesales – Rep Home`

Apex dependency

`SE_FR_TelesalesController` (bundled in `classes/`):

- `getIncomingCases(statusesCsv, ownerScope, limitCount)` — open Case records.
- `getOrdersToValidate(statusesCsv, ownerScope, limitCount)` — Order records by status.

Everything else on this dashboard (calls, news, mini-charts) stays mock JSON configurable via App Builder because there is no standard source of truth.

Dynamic data filters (App Builder)

PROPERTY	DEFAULT	NOTES
`caseStatusesCsv`	`New,Working,Waiting on Customer,Escalated`	Any Case.Status value on your org.
`caseOwnerScope`	`all`	`'mine'` filters on the running user — use `'all'` in a fresh SDO where demo cases aren't owned by the running user.
`caseLimit`	6	Up to 50.
`caseListView`	`Recent`	Used by the "View all" button.
`orderStatusesCsv`	`Draft`	Default matches "orders to validate".
`orderOwnerScope`	`all`	
`orderLimit`	6	
`orderListView`	`Recent`	

Columns on both datatables are now real Salesforce data: case/order number linked to the record, account linked to its record, date, channel (Case.Origin / Order.SalesChannel.SalesChannelName), status, amount for orders.

Styling

Shares the SE_FR palette declared at the top of the CSS (SLDS-aligned brand/success/warning/error colors). KPI tiles, bar charts and news cards all use the same palette.

Origin

Renamed from `seFrTelesalesDashboard` (v2.3 → v2.4). The old bundle is kept in the library as deprecated.

Component · Territory Map (`seFrTerritoryMap`)

> **API name:** `seFrTerritoryMap` · **Categories:** Geo & Field · **Surfaces:** AppPage, HomePage · **Objects:** Any · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_TerritoryMapController

Summary: Interactive territory map with geocoded Accounts, pipeline color coding, sidebar filters and CSV export.

Key configurable props / settings of seFrTerritoryMap:

- Owner / RecordType / amount range / stages / case status
- 2 configurable picklist filters (Type, Industry by default)
- Map height, map / list ratio, default center (France)

SE benefit: Pins are color-coded by open-pipeline tier (red top 20% / orange / green / grey) — instantly visualizes territory health. CSV export lets you pull the filtered list for follow-up reports.

CCO FR - Territory Map (`seFrTerritoryMap`)

Carte interactive du territoire commercial : Accounts géolocalisés via leur Billing Address, code couleur par tier de pipeline ouvert, filtres latéraux (Owner / RecordType / fourchette de montant ouvert / étapes opportunité), tuiles KPI et export CSV de la sélection visible.

Targets

- `lightning__HomePage`
- `lightning__AppPage`

> Pas de `lightning__RecordPage` : le composant est conçu pour une vue agrégée du territoire, pas pour une record page.

Apex

- `SE_FR_TerritoryMapController.getTerritoryAccounts(limitCount, recordTypeName, ownerScope, amountMin, amountMax, stagesCsv)` — renvoie une liste de `TerritoryAccount` enrichis (sommes / counts d'opportunités, count des cases ouverts) basés sur les Accounts ayant `BillingLatitude` / `BillingLongitude` non nuls.
- `getStageNames()` — picklist `OpportunityStage` .
- `getAccountRecordTypes()` — RecordTypes Account actifs.

Schema-safe : tous les champs sont des standards. Aucune dépendance custom requise.

Propriétés (App Builder)

PROPRIÉTÉ	DESCRIPTION
`language`	`'fr'` (défaut) / `'en'`
`cardTitle`	Titre du composant (override)
`limitCount`	Max accounts (1-200, défaut 100)
`defaultOwnerScope`	`mine` (défaut) / `all`
`defaultRecordType`	DeveloperName du RecordType Account pré-sélectionné
`defaultStagesCsv`	Étapes opportunité pré-sélectionnées (séparées par virgule)
`currencyCode`	Code ISO 4217 (défaut `EUR`)
`zoomLevel`	Zoom initial de la carte (défaut 6)
`filtersOpenByDefault`	Panneau de filtres ouvert par défaut

Couleurs des pins

- **Rouge** (top 20%) : pipeline ouvert élevé
- **Orange** (top 50%) : pipeline ouvert moyen
- **Vert** : pipeline ouvert faible mais > 0
- **Gris** : aucun pipeline ouvert

Les seuils sont calculés sur la liste visible (relatifs, pas absolus) — le top tier reste toujours saillant quel que soit le territoire.

KPIs affichés

- Nombre de comptes visibles
- Pipeline ouvert total (formaté compact, ex. `12,5 M €`)
- Total opportunités ouvertes

- Total cases ouverts

Export CSV

Le bouton `Exporter visible` génère un CSV (encodage UTF-8 BOM, séparateur virgule, guillemets pour les valeurs contenant des caractères spéciaux) téléchargé côté navigateur.

Comportements

- Click sur un pin → ouvre la fiche Account dans Lightning.
- Le panneau de filtres reste collapsable via l'icône entonnoir (variant `brand` quand ouvert).
- Si `defaultOwnerScope = mine` ne renvoie rien, l'Apex bascule automatiquement sur "tous owners" (utile sur les SDOs vierges).

Component · Timeline Phases (`seFrTimelinePhases`)

> **API name:** `seFrTimelinePhases` · **Categories:** Productivity · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Any · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Horizontal multi-phase timeline with date axis, 'Today' marker and done / pending state per phase.

Key configurable props / settings of seFrTimelinePhases:

- Up to 6 phases (label, date, status)
- Color theme

SE benefit: Visualizes a journey or process state without needing custom objects or flows — type the phases directly in App Builder.

CCO FR - Timeline Phases (`seFrTimelinePhases`)

Horizontal multi-phase timeline. Visualizes a journey, project, or sales-cycle with phases positioned on a date axis, a "Today" marker, and a done / pending state per phase.

Targets

- `lightning__RecordPage`
- `lightning__AppPage`
- `lightning__HomePage`

Quick start

Drop on an Account record page — defaults to a 5-phase sales cycle (Prospection → Découverte → Démo → Proposition → Closing). The vertical "Today" line auto-positions.

Customizing phases

Set `phasesJson` to a JSON array:

```
[
    { "label": "Onboarding",  "date": "2026-01-15", "done": true  },
    { "label": "Discovery",   "date": "2026-02-08", "done": true  },
    { "label": "Demo",        "date": "2026-03-12", "done": true  },
    { "label": "Proposal",    "date": "2026-04-22", "done": false },
    { "label": "Closing",     "date": "2026-05-30", "done": false }
]
```

Each phase: `label` (string), `date` (`YYYY-MM-DD`), `done` (boolean).

Default phase sets (when `phasesJson` is empty)

SCOPE	DEFAULT PHASES
`record` (default)	Sales cycle — Prospection → Découverte → Démo → Proposition → Closing
`home`	Fiscal milestones — Q1 kick-off → Q2 ramp-up → Q3 expansion → Q4 year-end

Properties

PROPERTY	DEFAULT	DESCRIPTION
`language`	`fr`	`fr` / `en` (drives default labels)
`scope`	`record`	`record` / `home` (drives default phases)
`cardTitle`	–	Override
`cardIcon`	`standard:timesheet`	SLDS icon
`phasesJson`	–	JSON array (overrides defaults)
`localeTag`	`fr-FR`	Locale used to format phase dates
`hideTodayMarker`	`false`	Hide the vertical "Today" line

SE benefits

- **Visualizes a journey or process state** without needing custom objects, flows, or path components.
- **Type the phases directly in App Builder** — paste a JSON array, see it render. Useful for "this customer is at step 3 of onboarding" demo moments.
- **"Today" marker auto-positioned** on the date axis — gives an instant sense of progress vs. plan.
- **Two default sets** (sales cycle for Account pages, fiscal milestones for Home pages) keep the component demo-ready out of the box.

Component · Visit Check-In (`seFrVisitCheckIn`)

> **API name:** `seFrVisitCheckIn` · **Categories:** Retail Execution · **Surfaces:** RecordPage · **Objects:** Visit__c · **Data mode:** live · **Mobile-ready:** yes · **Apex:** none

Summary: Check-in / Check-out terrain en un clic sur la visite, avec chrono et récapitulatif de durée.

Key configurable props / settings of seFrVisitCheckIn:

- cardTitle
- cardIcon
- language

SE benefit: Montrer en démo le cycle de vie d'une visite (Planned, In Progress, Completed) sans Apex ni Flow, uniquement avec updateRecord.

seFrVisitCheckIn

Check-in / Check-out pour `Visit__c`, piloté par `VisitState__c`.

Where to drop it

- **Target:** Lightning Record Page
- **Object:** Visit__c
- **App Builder label:** `CCO FR – Visit Check-In`

Behavior

VISITSTATE__C	UI	WRITE
Planned	Bouton Check-in	`CheckInDateTime__c = now`, state In Progress
In Progress	Bouton Check-out + temps écoulé (rafraîchi toutes les 30 s)	`CheckOutDateTime__c = now`, state Completed
Completed	Carte récap (durée, date de clôture) + Rouvrir	state In Progress, `CheckOutDateTime__c` vidé
Cancelled	Message + Replanifier	state Planned

Dependencies

- No Apex, no Flow: `updateRecord` from `lightning/uiRecordApi`.
- Permission set `CCO_FR_Showcase_Visitor` (Create/Edit on Visit__c + FLS).

Properties

`language` (fr/en), `cardTitle`, `cardIcon` (default `standard:activations`).

Component · Visit Kanban (`seFrVisitKanban`)

> **API name:** `seFrVisitKanban` · **Categories:** Retail Execution · **Surfaces:** RecordPage · **Objects:** Account · **Data mode:** live · **Mobile-ready:** no · **Apex:** SE_FR_VisitKanbanController

Summary: Kanban des visites du compte - glisser-deposer pour faire avancer une visite de Planifiee a Terminee.

Key configurable props / settings of seFrVisitKanban:

- cardTitle
- cardIcon
- language
- limitPerColumn

SE benefit: Montrez en un coup d'oeil le cycle de vie des visites terrain d'un compte et faites-le avancer d'un simple glisser-deposer, sans code.

CCO FR - Visit Kanban (`seFrVisitKanban`)

Kanban des `Visit__c` de l'Account courant : 4 colonnes `Planned` , `In Progress` , `Completed` , `Cancelled` (libelles FR/EN).

Target

- `lightning__RecordPage` sur `Account`

Fonctionnement

- Lecture : `getRelatedListRecords` (related list `Visits__r` , tri `PlannedStartDateTime__c`).
- Ecriture : `updateRecord` (LDS) sur `VisitState__c` , mise a jour optimiste, toast succes/erreur.
- Carte : nom (V-xxxx), debut planifie, lieu tronque a 30 caracteres, badge d'etat.
- Plus de 5 cartes (`limitPerColumn`) : chevron Voir plus / Show more.
- Bouton Nouvelle visite : lance le Flow `CCO_FR_Start_Visit` via `c/seFrFlowModal` . Masque si le Flow n'est pas actif (verifie par `SE_FR_VisitKanbanController.flowExists`).

Dependances

- Schema `seFrRetailExecSchema` (`Visit__c` , lookup `Account__c` , relationship `Visits`).
- `seFrFlowModal` (lib).

Proprietes

PROPRIETE	DEFAUT
`language`	`fr`
`cardTitle`	Visites / Visits
`cardIcon`	`standard:kanban`
`limitPerColumn`	`5`
`startVisitFlowApiName`	`CCO_FR_Start_Visit`

Component · Visit Plan (`seFrVisitPlan`)

> **API name:** `seFrVisitPlan` · **Categories:** Retail Execution · **Surfaces:** RecordPage · **Objects:** Visit__c · **Data mode:** live · **Mobile-ready:** yes · **Apex:** none

Summary: Checklist "Plan d'action" sur une visite terrain — démarre, séquence, clôture.

Key configurable props / settings of seFrVisitPlan:

- cardTitle
- cardIcon
- language

SE benefit: Raconter l'ensemble d'une visite terrain en un seul composant — check-in horodaté, checklist (relevé linéaire, produits, commande), compte-rendu via Flow — avec progression visible et bouton "Terminer" bloqué tant que l'obligatoire n'est pas fait.

seFrVisitPlan

Checklist dynamique "Plan d'action" posée sur une `Visit__c`. Pilote tout le cycle de vie d'une visite terrain depuis une seule carte : démarrer, cocher les étapes au fil de l'eau, clôturer avec compte-rendu.

Where to drop it

- **Target:** Lightning Record Page
- **Object:** `Visit__c`
- **App Builder label:** `CCO FR – Visit Plan`

Qu'est-ce qu'il fait

- **État de la visite** affiché en pill (Planifiée / En cours / Terminée) + timer "temps écoulé depuis le check-in" quand elle est en cours.
- **Bouton principal** contextuel :
- `Planifiée` → **Démarrer la visite** (passe `VisitState__c` à `In Progress`, horodate `CheckInDateTime__c`)
- `En cours` → **Terminer la visite** (si tout l'obligatoire est coché : passe en `Completed` + horodate `CheckOutDateTime__c` ; sinon : ouvre le Flow `CCO_FR_End_Visit`)
- `Terminée` → carte de résumé
- **Checklist "Plan d'action"** avec 5 étapes par défaut :

1. Check-in magasin *(mandatory, actionable — même action que le bouton principal)*
2. Relevé linéaire *(mandatory, toggle)*
3. Relevé produits *(mandatory, toggle)*
4. Commande *(optionnel, toggle)*
5. Compte-rendu *(mandatory, actionable — ouvre le Flow `CCO_FR_End_Visit` dans un modal)*

- **Progress bar** `doneCount/totalCount` qui se remplit au fil des cochages.
- **Progression persistée** en `localStorage` sous `sefr-visit-progress::<recordId>` — d'autres LWCs peuvent cocher des étapes en écrivant dans la même clé. Un polling 2s synchronise la UI.
- **Modal confirmation** sur l'annulation d'une visite planifiée (`deleteRecord`).

Properties

PROP	TYPE	DEFAULT	DESCRIPTION
`recordId`	Id	*(system)*	Id de la Visit__c courante
`language`	String	`fr`	`fr` ou `en`
`cardTitle`	String	—	Override du titre de la carte (défaut : Visite / Visit)
`cardIcon`	String	`standard:visit`	SLDS icon-name

Hooks

- Dépend de `Visit__c` (object custom lib) avec champs `VisitState__c` (picklist : Planned / In Progress / Completed / Cancelled), `CheckInDateTime__c`, `CheckOutDateTime__c`.
- Dépend du Flow `CCO_FR_End_Visit` (input `recordId` String) pour le compte-rendu.
- Écrit via `updateRecord` / `deleteRecord` du LDS — pas d'Apex.
- Toasts d'erreur sur échec `updateRecord`.

Intégration avec d'autres LWCs

Le composant lit/écrit sa progression dans `window.localStorage` à la clé `sefr-visit-progress::<visitId>`. Format :

```
{
  "checkin": { "done": true, "at": "2026-10-23T10:12:00.000Z" },
  "shelf":   { "done": true, "at": "2026-10-23T10:28:00.000Z" }
}
```

Un autre LWC (ex. `seFrVisitShelfCompliance` après submit d'un relevé) peut cocher la case `shelf` en écrivant dans cette clé — le polling 2s du composant Plan va la détecter et mettre la UI à jour. Idem pour `products` et `order`.

Historique

- **2026-10-23** : porté dans la lib depuis la démo DBI/DIM (`dimStartVisit`), rebrandé en préfixe `seFr*`, migré du standard `Visit` d'Industries Retail Execution vers l'object custom `Visit__c` de la lib (champs `VisitState__c` / `CheckInDateTime__c` / `CheckOutDateTime__c`).

Component · Visit Product Check (`seFrVisitProductCheck`)

> **API name:** `seFrVisitProductCheck` · **Categories:** Retail Execution · **Surfaces:** RecordPage · **Objects:** Visit__c · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_ProductCheckController

Summary: Relevé produits terrain depuis le Standard Pricebook — Présent / Rupture / prix constaté par produit.

Key configurable props / settings of seFrVisitProductCheck:

- cardTitle
- cardIcon
- language
- maxCount

SE benefit: Permet au commercial terrain de pointer en quelques secondes la présence rayon et le prix constaté de ses références catalogue, et coche automatiquement l'étape « Relevé produits » du plan de visite.

seFrVisitProductCheck (Visit Product Check)

Visit__c record page. Liste de produits actifs depuis le **Standard Pricebook** (fallback : tous les `Product2` actifs), avec pour chaque produit :

- Deux pills **Présent / Rupture** (toggle, mutuellement exclusifs)
- Un champ **prix constaté** (texte libre)
- Un champ **note** (facultatif)

Les saisies sont persistées en `localStorage` sous `sefr-product-check::<recordId>` (démo — pas de DML sur l'org). Dès la **première interaction** utilisateur, le composant publie `products:done` dans la clé partagée `sefr-visit-progress::<recordId>` → `seFrVisitPlan` coche automatiquement l'étape « Relevé produits ».

- App Builder label : `CCO FR – Visit Product Check`
- Apex (read-only) : `SE_FR_ProductCheckController.getProducts(recordId, maxCount)` — `WITH USER_MODE`, pas de DML.
- Objets utilisés : `Pricebook2` (lecture `IsStandard`), `PricebookEntry` (lecture `UnitPrice` + relation `Product2`), fallback direct sur `Product2`.
- Dépend de : étape « products » de `seFrVisitPlan` (synchro checklist via `sefr-visit-progress::<recordId>`).

Props App Builder

PROP	TYPE	DÉFAUT	DESCRIPTION
`language`	String	`fr`	`fr` ou `en`.
`cardTitle`	String	—	Override du titre (sinon : `Relevé produits / Product audit`).
`cardIcon`	String	—	Override de l'icône SLDS (sinon : `standard:product_item`).
`maxCount`	Integer	`12`	Nombre max de produits listés (clampé à 50).

Design choices

- **Standard Pricebook by default** : les orgs CPG démo ont rarement un Pricebook custom lié à chaque compte. Partir du Standard Pricebook est le fallback le plus universel et évite la dépendance à un champ custom sur `Account`.
- **Pas de DML** : la démo privilégie la rapidité et la fluidité ; la persistance locale rend le réglage trivial entre sessions sans polluer l'org.
- **Progression autopublic** : dès la première interaction (clic pill OU saisie prix/note), le composant publie une seule fois `products:done`. Pas de toast au moindre click, un seul au premier.

Component · Commande rapide (catalogue visuel) (`seFrVisitQuickOrder`)

> **API name:** `seFrVisitQuickOrder` · **Categories:** Retail Execution · **Surfaces:** AppPage, RecordPage · **Objects:** Visit__c, Account · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Visual product catalogue with contextual recommendations (out-of-stock, missing products, low shelf share) and a cart with line + global discount.

Key configurable props / settings of seFrVisitQuickOrder:

- Brand name (badges & recos)
- `seedProductsJson` · override the built-in CPG catalogue
- Currency symbol

SE benefit: Visual alternative to the fast-entry order pad — surfaces what to push during a store visit, based on what the visit just revealed.

seFrVisitQuickOrder (Quick Order — visual catalogue)

Visual order-taking component for a retail visit. Shows a product catalogue with images and badges, recommendations derived from the visit survey (out-of-stock products, missing references, low shelf share), and a cart with per-line and global discount.

Where to drop it

- **Target:** Lightning Record Page (Visit__c, Account) and App Page
- **App Builder label:** `CCO FR – Commande rapide (catalogue visuel)`

Apex dependencies

None. Without `seedProductsJson` it uses a generic CPG catalogue.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`language`	String	`fr`	`fr` or `en`
`cardTitle` / `cardIcon`	String	— / `standard:order_item`	Header overrides
`brandName`	String	`Ma marque`	Brand used for badges and recommendations
`currencySymbol`	String	`€`	
`seedProductsJson`	String	*(generic CPG)*	JSON array `{ id, code, name, family, price, imageUrl, stock, badge? }`

Component · Réassort auto (ruptures relevé) (`seFrVisitRestockOrder`)

> **API name:** `seFrVisitRestockOrder` · **Categories:** Retail Execution · **Surfaces:** RecordPage · **Objects:** Visit__c, Account · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_VisitRestockOrderController

Summary: Turns out-of-stock products found during the shelf survey into a Draft restock Order in one click.

Key configurable props / settings of seFrVisitRestockOrder:

- Default quantity per rupture
- Include price-alert products
- Currency / locale

SE benefit: Closes the loop of a store visit — the ruptures spotted during the product survey become an order on the visit's account without re-typing.

seFrVisitRestockOrder (Restock Order from ruptures)

Reads the out-of-stock products flagged by `seFrVisitProductCheck`, suggests a quantity per line, and creates an Order (Draft) + OrderItems on the visit's Account.

Where to drop it

- **Target:** Lightning Record Page — `Visit__c` or `Account` (on an Account, reads the ruptures of the account's latest visit)
- **App Builder label:** `CCO FR – Réassort auto (ruptures relevé)`

Apex dependency

`SE_FR_VisitRestockOrderController` — `getVisitContext`, `getRestockProducts`, `createRestockOrder` (bundled in `classes/`). Requires an active standard-pricebook entry per product.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`language`	String	`fr`	`fr` or `en`
`defaultQuantity`	Integer	`6`	Prefilled quantity per rupture
`includePriceAlerts`	Boolean	`false`	Also list products with an abnormal observed price
`currencySymbol` / `localeTag`	String	`€` / `fr-FR`	Formatting

Component · Visit Shelf Compliance (`seFrVisitShelfCompliance`)

> **API name:** `seFrVisitShelfCompliance` · **Categories:** Retail Execution · **Surfaces:** RecordPage · **Objects:** Visit__c · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_ShelfComplianceController

Summary: Photos de linéaire sur une visite, galerie et analyse Agentforce (mock en repli).

Key configurable props / settings of seFrVisitShelfCompliance:

- cardTitle
- cardIcon
- language
- maxFiles

SE benefit: Démo prête à l'emploi de conformité linéaire par la photo, avec analyse Agentforce simulée si la vision n'est pas configurée.

seFrVisitShelfCompliance (Visit Shelf Compliance)

Visit__c record page. Upload (lightning-file-upload), gallery of image files linked to the visit, and an Agentforce analysis button.

- App Builder label: `CCO FR – Visit Shelf Compliance`
- Apex (read-only): `SE_FR_ShelfComplianceController` (getPhotos, analyzeShelf). ConnectApi is Apex-only, hence the class.
- Mock-first: without `promptTemplateApiName` (or on any error) a canned 4-line result is shown after 1.5 s.

Component · Visit Shelf Space (`seFrVisitShelfSpace`)

> **API name:** `seFrVisitShelfSpace` · **Categories:** Retail Execution · **Surfaces:** RecordPage · **Objects:** Visit__c · **Data mode:** mock · **Mobile-ready:** yes · **Apex:** none

Summary: Relevé linéaire manuel — part de linéaire (PDL) marque vs concurrence par catégorie et segment, avec historique.

Key configurable props / settings of seFrVisitShelfSpace:

- language
- cardTitle
- cardIcon
- brandName
- competitorLabel
- seedJson

SE benefit: Pendant visuel du composant photo seFrVisitShelfCompliance — saisie manuelle de facings quand le vendeur n'a pas accès à la vision ou veut consolider l'évolution PDL vs mois précédent / A-1. Publie dans `sefr-visit-progress` : coche l'étape « Relevé linéaire » du plan de visite.

seFrVisitShelfSpace (Visit Shelf Space)

Relevé linéaire **manuel** sur une Visit__c. Saisie des **facings actuels** par catégorie / segment / marque (Ma marque vs Concurrence), avec historique **précédent** et **A-1**, et calcul automatique de la **PDL** (part de linéaire) globale + évolution en points.

- App Builder label : `CCO FR – Visit Shelf Space`
- 100% client-side — pas d'Apex. Les données sont persistées en `localStorage` pour la démo.
- Complémentaire de `seFrVisitShelfCompliance` (photo) : les deux cohabitent dans l'onglet **Relevé linéaire**.

Où le poser

- **Target** : Lightning Record Page
- **Object** : `Visit__c`
- **FormFactors** : Large + Small

- Sur Visit, au Save il publie `shelf:done` dans `localStorage` sous la clé `sefr-visit-progress::<visitId>` → coche l'étape « Relevé linéaire » du composant `seFrVisitPlan`.
- Il publie aussi `sefr-shelf-insights::<visitId>` (segments à faible PDL ou en recul) — à consommer par `seFrVisitSummaryAI` pour un debrief enrichi.

Props

NOM	TYPE	DÉFAUT	DESCRIPTION
`language`	String	`fr`	`fr` ou `en`. Bilingue (titres, PDL, unités « pts »…).
`cardTitle`	String	—	Override du titre de la carte. Défaut : « Relevé linéaire » / « Shelf audit ».
`cardIcon`	String	—	Override icône SLDS. Défaut : `standard:merchandising`.
`brandName`	String	`Ma marque`	Libellé pour les lignes « main » (ex: Danone, LU, DIM, Haribo…).
`competitorLabel`	String	—	Libellé des lignes « competitor ». Défaut : « Concurrence » / « Competition ».
`seedJson`	String	—	JSON Array pour remplacer le seed par défaut. Voir plus bas.

Modèle de données

Chaque ligne du relevé :

```
{
  "id": "1",
  "category": "Boissons rafraîchissantes",
  "segment": "Colas",
  "brand": "main",
  "facingsCurrent": null,
  "facingsPrev": 16,
  "facingsA1": 14,
  "facingsSegPrev": 48,
  "facingsSegA1": 46
}
```

- `brand` : `main` (= `brandName`) ou `competitor` (= `competitorLabel`).
- `facingsCurrent` est saisi par le vendeur, les autres sont historiques (figés).
- `facingsSegment` est recalculé auto à chaque saisie (somme des `facingsCurrent` du segment).

Calcul PDL

```
PDL = Σ facingsCurrent(main) ÷ Σ facingsSegment(main)
```

- Évolution = `PDL_actuelle − PDL_précédente` (en points, 1 décimale).
- Classe CSS appliquée : `--up` si > +0.5 pt, `--down` si < −0.5 pt, `--muted` sinon.

Seed custom (prop `seedJson`)

Pour un client particulier (ex: Danone, DIM, Haribo), passer un JSON Array avec les catégories/segments réels. Le composant reparse à chaque mount — si le JSON est invalide, repli silencieux sur le seed CPG épicerie par défaut.

Exemple Danone :

```
[
  {"id":"1","category":"Produits laitiers","segment":"Yaourts nature","brand":"main","facingsCurrent":null,"facin
  {"id":"2","category":"Produits laitiers","segment":"Yaourts nature","brand":"competitor","facingsCurrent":null,
]
```

Install

1. Déployer le LWC `seFrVisitShelfSpace` (pas d'Apex).
2. Dans App Builder, ouvrir la record page Visit__c, glisser `CCO FR – Visit Shelf Space`.
3. Configurer `brandName`, et optionnellement `seedJson` pour un catalogue client.

Inspiration

Dérivé du composant `dimShelfSpace` (SIC DBI/DIM, juin 2026). Adapté bilingue, prop-driven, palette SLDS neutre pour la lib.

Component · Resume de Visite IA (`seFrVisitSummaryAI`)

> **API name:** `seFrVisitSummaryAI` · **Categories:** Retail Execution · **Surfaces:** AppPage, HomePage, RecordPage · **Objects:** Visit__c, Account · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_VisitSummaryController

Summary: Résumé IA (Agentforce / Einstein) d'une visite terrain — synthèse, points clés et actions recommandées.

Key configurable props / settings of seFrVisitSummaryAI:

- language
- cardTitle
- cardIcon
- promptTemplateName

SE benefit: Transforme les données captées pendant la visite (linéaire, ruptures, commande, notes) en compte-rendu structuré prêt à partager, avec un fallback déterministe si aucun Prompt Template n'est configuré.

CCO FR — Visit Summary AI (`seFrVisitSummaryAI`)

Résumé **Agentforce / Einstein** d'une visite terrain, à poser sur la page record d'un **`Visit__c`** (sObject shipped par `seFrRetailExecSchema`). Zero managed package.

Dépendance

- ⚠️ Requiert le bundle **`seFrRetailExecSchema`** déployé (sObject `Visit__c` + fields + permset `CCO_FR_Retail_Exec`).
- Si l'org utilise le managed package Retail Execution (sObject `Visit` standard), cloner ce composant et remplacer `Visit__c` → `Visit` dans le controller Apex + le target du `.js-meta.xml` .

Ce que fait le composant

- Bouton "Générer le résumé" sur la page d'un `Visit__c` .
- Appelle un Prompt Template Einstein configuré par l'admin (optionnel), ou un **fallback déterministe** côté Apex (État + Account + durée + check-in/out + lieu + notes + propriétaire) si aucun template n'est fourni.
- Rendu structuré : Synthèse + Points clés + Actions recommandées.
- Bouton "Régénérer" + "Envoyer au manager" (stub UX — à câbler côté admin via un Flow / Task).

Props App Builder

PROP	TYPE	DEFAULT	RÔLE
`language`	String	`fr`	`fr` ou `en` .
`promptTemplateApiName`	String	*(vide)*	DeveloperName d'un **Flex Prompt Template** qui prend un `Input:Visit__c` et retourne un JSON `{ summary, keyPoints[], actions[] }` . Vide → fallback côté Apex.

Prompt Template attendu

Si vous câblez un template, il doit :

- avoir un paramètre `Input:Visit__c` typé sObject Visit__c
- renvoyer **du JSON pur** avec ce schéma :

```
{
  "summary": "Visite productive chez l'Acme, lifecycle avancé.",
  "keyPoints": ["Check-in à 09h12", "Objection prix levée", "3 produits commandés"],
  "actions": ["Envoyer la proposition sous 48h", "Planifier démo tech"]
}
```

Si le template renvoie du texte brut, le composant affiche le texte dans la section Synthèse (soft-fail avec un avertissement).

Fichiers

```
seFrVisitSummaryAI/
├── README.md
├── classes/
│   ├── SE_FR_VisitSummaryController.cls          — ConnectApi wrapper + fallback summary on Visit__c
│   └── SE_FR_VisitSummaryController.cls-meta.xml
└── lwc/
    └── seFrVisitSummaryAI/
        ├── seFrVisitSummaryAI.html
        ├── seFrVisitSummaryAI.js
        ├── seFrVisitSummaryAI.css
        └── seFrVisitSummaryAI.js-meta.xml       — target Visit__c
```

Compliance

- ✅ Depend uniquement de `Visit__c` shipped par la lib (via `seFrRetailExecSchema`)
- ✅ `isExposed=true`, 3 cibles (RecordPage/AppPage/HomePage)
- ✅ Bilingue FR/EN via `@api language`
- ✅ `WITH USER_MODE` dans la SOQL fallback (sécurité)
- ✅ Soft-fail si Einstein indisponible (toast warning + fallback)

Origine

Portage libéré de `dimVisitSummaryAI` (archive `dbi-cg-demo-2026-10-21`). Toute la plomberie DIM-specific (localStorage `dim-visit-*`, Apex `DIM_VisitSummary`, structure KPI retail-spé) a été retirée au profit d'un contrat universel Visit__c-based.

Component · Voice Note Taker (`seFrVoiceNoteTaker`)

> **API name:** `seFrVoiceNoteTaker` · **Categories:** Geo & Field · **Surfaces:** RecordPage · **Objects:** Account, Contact, Lead, Opportunity, Visit__c · **Data mode:** live · **Mobile-ready:** yes · **Apex:** SE_FR_VoiceNoteController

Summary: Dictate a voice note via the Web Speech API and save it as a completed Task linked to the current record.

Key configurable props / settings of seFrVoiceNoteTaker:

- Auto-save vs review-first
- Transcript language

SE benefit: Speech-to-text via the browser `SpeechRecognition` API — no Einstein / external service dependency. Demoable on any org as long as Chrome is the browser.

seFrVoiceNoteTaker

Dictate a voice note using the browser's Web Speech API, edit it manually if needed, and save it as a completed `Task` linked to the current record. Works on Account, Contact, Lead or Opportunity — the recordId is routed to `Task.WhoId` for Contact/Lead, `Task.WhatId` otherwise.

Where to drop it

- **Target:** Lightning Record Page
- **Objects:** Account, Contact, Lead, Opportunity
- **App Builder label:** `CCO FR – Voice Note Taker`

Apex dependency

- `SE_FR_VoiceNoteController.saveVoiceNoteForRecord(recordId, noteText, taskSubject)` (in `_shared_apex/`).

Browser requirement

Voice recognition relies on `window.SpeechRecognition` / `webkitSpeechRecognition`. Works in Chrome, Edge and Safari — Firefox shows the unsupported-browser message.

Task created

FIELD	VALUE
`Subject`	`taskSubject` property (default `Visit notes (voice dictation)`)
`Description`	The note text (transcribed speech + manual edits)
`Status`	`Completed`
`ActivityDate`	Today
`Priority`	`Normal`
`WhoId` or `WhatId`	the current record, routed by object type

The activity feed component (to be built later) will display `Task.Description` verbatim when the Task was created by this component.

Properties

NAME	TYPE	DEFAULT	DESCRIPTION
`cardTitle`	String	`Voice Note Taker`	
`cardIcon`	String	`standard:voice_call`	SLDS icon.
`speechLocale`	String	`en-US`	BCP 47 locale for speech recognition.
`taskSubject`	String	`Visit notes (voice dictation)`	Subject on the created Task.
`recordingHint`	String	`Listening… Speak now.`	Shown while recording.
`textareaLabel` / `textareaPlaceholder`	String × 2	English defaults	Customize the editable area.
`startButtonLabel` / `stopButtonLabel` / `saveButtonLabel`	String × 3	English defaults	Button labels.
`unsupportedBrowserMessage`	String	`Voice recognition is not supported by your browser. Use Google Chrome.`	Fallback message.
`successMessage`	String	`Note saved as a Task successfully.`	Success toast message.

Install

1. Deploy `_shared_apex/classes/SE_FR_VoiceNoteController.cls` first.
2. Unzip `seFrVoiceNoteTaker.zip`, deploy the LWC bundle.
3. Drop `CCO FR – Voice Note Taker` on an Account / Contact / Lead / Opportunity record page.