```
No.     Time                Source              Destination         Protocol Length Info
   1967 06:24:09.436775     192.168.0.10        205.171.3.65        DNS      78     Standard query 0x2f9c A analytics.ietf.org
Frame 1967: 78 bytes on wire (624 bits), 78 bytes captured (624 bits) on interface \Device\NPF_{3F3DB8EB-1AC0-401B-8543-3316F86ED445}, id 0
Ethernet II, Src: RivetNet_ea:43:59 (9c:b6:d0:ea:43:59), Dst: Calix_88:88:71 (ec:4f:82:88:88:71)
Internet Protocol Version 4, Src: 192.168.0.10, Dst: 205.171.3.65
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 64
    Identification: 0x8b9c (35740)
    000. .... = Flags: 0x0
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 128
    Protocol: UDP (17)
    Header Checksum: 0x1d72 [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 192.168.0.10
    Destination Address: 205.171.3.65
User Datagram Protocol, Src Port: 62859, Dst Port: 53
    Source Port: 62859
    Destination Port: 53
    Length: 44
    Checksum: 0xe52a [unverified]
    [Checksum Status: Unverified]
    [Stream index: 5]
    [Timestamps]
    UDP payload (36 bytes)
Domain Name System (query)
    Transaction ID: 0x2f9c
    Flags: 0x0100 Standard query
    Questions: 1
    Answer RRs: 0
    Authority RRs: 0
    Additional RRs: 0
    Queries
        analytics.ietf.org: type A, class IN
            Name: analytics.ietf.org
            [Name Length: 18]
            [Label Count: 3]
            Type: A (Host Address) (1)
            Class: IN (0x0001)
    [Response In: 2104]
```