

USED MEDIAS LLC

EMBEDDED SYSTEMS DIVISION

Engineering Documentation

cyd-os

DOCUMENT	REVISION	STATUS	CLASSIFICATION
cyd-os	—	—	Internal

Purpose of this set

These reports record the design of cyd-os in enough detail that the project can be picked up cold — by someone else, or by the author after six months away — without re-deriving decisions from the source.

Each report states **what was decided, what it was measured against, and what remains unverified**. Claims that were tested on hardware are marked as such. Claims taken from documentation or reasoning are marked separately, because on a from-scratch kernel the difference between "this is true" and "this should be true" is the difference between a working boot and a silent reboot.

Index

ID	Title	Covers
UM-CYDOS-001	System Architecture and Scope	Layer model, what is built vs borrowed, the isolation problem, why a bytecode VM
UM-CYDOS-002	Boot Chain and Image Format	ROM → 2nd stage → kernel, image header, measured boot trace
UM-CYDOS-003	Xtensa ABI Selection	Windowed vs call0, codegen evidence, consequences for the scheduler
UM-CYDOS-004	Memory Map and Allocation Policy	ESP32 regions, our layout, the bootloader overlap risk
UM-CYDOS-005	Build and Flash Pipeline	Toolchain, flags and why each one, reproducing a build, why not PlatformIO
UM-CYDOS-006	Milestone 0 Verification Report	Test method, captured output, pass/fail per assertion
UM-CYDOS-007	Development Roadmap M1–M5	Each milestone, its risks, and its exit criteria
UM-CYDOS-008	Milestone 1 Verification Report	Vectors, timer source and level choice, interrupt entry/exit, measured results
UM-CYDOS-009	Milestone 2 Verification Report	Task model, context frame, scheduler, the zero-overhead <code>LOOP</code> defect, watchdog correction

Reading order

New to the project: **001** → **002** → **004** → **003**. That gives the shape of the system, how it starts, where things live, and why the calling convention is unusual.

Picking up implementation work: **006** (what is known-good) then **007** (what is next and what it will break).

Reproducing a build: **005** alone is sufficient.

Status summary as of this revision

Item	State
Milestone 0 — kernel boots, self-checks pass	Complete, verified on hardware
Milestone 1 — timer interrupt, tick counter	Complete, verified on hardware
Milestone 2 — native task switching	Complete, verified on hardware — 1,200+ switches, zero corruption
Version control	Initialised 2026-08-14
JTAG debug probe	Ordered, not in hand
Bootloader IRAM overlap	Closed — investigated and disproved, UM-CYDOS-004 §5
Panic handler	Closed — exercised deliberately with an <code>111</code> instruction; prints EXCCAUSE/EPC and halts
Watchdogs	Closed — measured armed, now disabled and read back, UM-CYDOS-009 §8

Standing rule for interrupt handlers — clear `PS.EXCM` before calling C. Hardware sets `EXCM` on interrupt entry, and while it is set the Xtensa zero-overhead loop-back is disabled: a hardware loop body executes once and falls through to whatever sits at `LEND`. GCC emits these loops for ordinary counted C loops, so this silently degrades **every C function reachable from a handler** — drivers and the VM interpreter included, not just the scheduler where it was found. `_handler_level3` now clears it; any future handler must do the same. UM-CYDOS-009 §6.