FAV ENERGY SOLUTIONS

COMMERCIAL & INDUSTRIAL

Energy Storage System



Versatile Energy & Grid-Free Capability

- Multi-energy integration for diverse applications
- Seamless transition: on/off -grid switching under 20ms, uninterrupted power for critical loads
- Black start: self-starting in extreme conditions without gird or solar power

Integrated Design & Energy Installation

- All-in-one design, factory pre-integration
- LFP 314Ah cells: more stable system, higher energy density
- Scalable expansion from 2h to 8h (60kW/406kWh)
- Supports up to 10 cabinets in parallel (600kW/1MWh)

Smart Operation & Cost Efficient

- Remote OTA optimization
- Intelligent monitoring & remote diagnostics
- Compatible EMS for unified management across multiple sites
- Reduces operational costs

Enhanced Safety & Multiple Protection

- IP55 rating, C3/C4 corrosion resistance
- Cooling system in battery compartment
- Fire & aerosol integration with ventilation
- 5 Year Warranty for lifecycle safety

POWER
29.9/50/125 KW
Hybrid Inverter

CAPACITY
60~261 kWh

5 YEAR WARRANTY

High Energy Density
LFP 314Ah Cells

Intelligent Protection
Multiple safety detections

Rapid Expansion
Modular & Scalable design

Advanced Safety
Aerosol fire suppression

IP55 Protection
Robust for harsh evnironments

TECHNICAL SPECIFICATIONS

DC INPUT	
Max. PV Array Power@STC	29.9/30/50 kWp
Max. DC Voltage	1000V
MPPT Voltage Range	180V~850V
Max. DC Input Current	4*45A
MPPT Channels / Strings per Channel	4-way / 2 strings per way (total 8 strings)

BATTERY	
Battery Type	LiFePO4
Rated Energy	60~100 kWh
Battery Voltage Range	169V~213V / 275V~350V
Max. Charge/Discharge Current	150A

AC OUTPUT (ON-GRID)	
Rated AC Power	29.9/30/50 kW
Max. Apparent Power	33/33/55 kVA
Rated AC Voltage	3L+N+PE, 380V/400V
Rated Frequency	50Hz/60Hz
Total Harmonic Distortion	<3%

AC INPUT (ON-GRID)	
Rated AC Voltage	3L+N+PE, 380V/400V
Max. Input Current	80/80/200A
Frequency	50Hz/60Hz

PROTECTIONS
Integrated protections: PV string monitoring, insulation resistance detection, residual current monitoring, AC/DC protection, AFCI, RSD, surge protection (Type II) and more.

GENERAL PARAMETERS	
Cooling Method	HVAC (Battery) / Smart fan (Inverter)
Ingress Protection	Battery: IP55, Inverter: IP66
Operating Temperature	-30°C ~ 50°C (45°C~50°C with derating)
Communication	Ethernet / WiFi / 4G (Optional)
Dimensions (H*W*D)	1900*1200*1340 mm
Weight	1300 kg
Warranty	5 Years

* Specifications are subject to change without notice.

OPTIONAL EXPANSION CABINET

FAVBS100 OPTIONAL



Model	DC Expansion Cabinet
Battery	LiFePO4-314Ah
Capacity	100kWh
Maximum Charge/Discharge Current	150A
Voltage Range	280V~360V
Battery Configuration	IP20S*5
Firefighting System	Smoke & temperature sensors + aerosol
Dimensions (H*W*D)	1900*682*1340 mm
Weight	1100 kg

WHY FAVBS100?

HIGH PERFORMANCE
Hybrid inverter with high efficiency and stable output for commercial & industrial applications.

SAFE & RELIABLE
Multi-layer protection, intelligent monitoring and advanced fire safety.

FLEXIBLE & SCALABLE
Modular design supports expansion from 2h to 8h (60kW/406kWh) and up to 10 cabinets in parallel.

SMART OPERATION
Remote monitoring, OTA updates and EMS compatibility for maximum efficiency.

GREEN & SUSTAINABLE
LFP battery with long cycle life and high energy density for a cleaner future.

High Energy Density — LFP 314Ah Cells

Intelligent Protection — Multiple safety detections

Rapid Expansion — Modular & scalable design

Advanced Safety — Aerosol fire suppression

IP55 Protection — Robust for harsh environments

FAV ENERGY SOLUTIONS

B-66/A, S.I.T.E, Area,
Karachi, Pakistan.
+92 21 32550093-98
www.favenergysolution.com

FAV Energy Solutions
WhatsApp business account