



Learn

Project Astra

NetApp

November 17, 2020

This PDF was generated from <https://docs.netapp.com/us-en/project-astra/learn/learn/validated-vs-standard.html> on November 17, 2020. Always check docs.netapp.com for the latest.



Table of Contents

- Learn 1
 - Validated vs Standard Apps 1
 - Define a custom app 2

Learn

Validated vs Standard Apps

There are two types of applications you can bring to Astra: Validated and Standard. Learn the difference between these two categories, and the potential impacts on your projects and strategy.



It's tempting to think of these two categories as "supported" and "unsupported." But as you will see, there is no such thing as an "unsupported" app in Astra. You can add any app to Astra, although validated apps have more infrastructure built around their Astra workflows compared to standard apps.

Validated Apps

Validated apps for the Astra Beta Program are:

- MySQL 0.3.22
- MariaDB 14.14
- PostgreSQL 11.7
- Jenkins 2.249.1 LTS

The short list of validated apps represents applications that Astra recognizes. The Astra QA team has analyzed and confirmed these apps to be fully tested to restore.

Validated apps have also been checked by the Astra Development team, which creates custom workflows to help ensure the safety and consistency of your data. For example, when Astra takes a backup of a PostgreSQL database, it first quiesces the database. After the backup is complete, Astra restores the database to normal operation.

No matter which type of app you use with Astra, always test the backup and restore workflow yourself to ensure that you can meet your disaster recovery requirements.

Let us know what apps you would like to see validated in the future. [Contact us through the Feedback email address on the Support page.](#)

Standard Apps

Any other app, including custom programs, is considered a standard app. You can add and manage standard apps through Astra. You can also create basic crash-consistent Snapshots and Backups of a standard app. However, these have not been QA-tested to restore the app to its original state.

Define a custom app

Creating a custom app lets you group elements of your Kubernetes cluster into a single app.

A custom app gives you more granular control over what to include in a Astra operation, including:

- Clone
- Snapshot
- Backup
- Protection Policy

In most cases you will want to use Astra's features on your entire app. However, you can also create a custom app to use these features by the labels you assign to Kubernetes objects in a namespace.

To create a custom app, go to the Apps page and click + **Define custom app**.

As you make your selections, the Custom App window will show you which resources will be included or excluded from your custom app. This helps you make sure you are choosing the correct criteria for defining your custom app.

[A screenshot of the Define Custom App pop-up window showing which resources will and won't be included in the custom app]

In the above example, one resource (the pod `nginx-pod0` labeled `deployment:canary`) will be included in the custom app. Two pods (`nginx-pod` and `nginx-pod2` both labeled `deployment:stable`) will be excluded.



Custom apps can only be created within a specified namespace on a single cluster. The Astra beta program does not support the ability for a custom app to span multiple namespaces or clusters.

A label is a key/value pair you can assign to Kubernetes objects for identification. Labels make it easier to sort, organize, and find your Kubernetes objects. To learn more about Kubernetes labels, [see the official Kubernetes documentation](#).



Overlapping policies for the same resource under different names can cause data conflicts. If you create a custom app for a resource, be sure it's not being cloned or backed up under any other policies.

Example: Separate Protection Policy for canary release

In this example, the devops team is managing a canary release deployment. Their cluster has three pods running NginX. Two of the pods are dedicated to the stable release. The third pod is for the canary release.

The devops team's Kubernetes admin adds the label `deployment=stable` to the stable release pods. She adds the label `deployment=canary` to the canary release pod.

[A screenshot of the result of running 'kubectl get pods --namespace=nginx-app --show-labels' showing the Kubernetes labels on the three pods.]

The team's stable release includes a requirement for hourly snapshots and daily backups. The canary release is more ephemeral, so they want to create a less aggressive, short-term Protection Policy for anything labeled `deployment=canary`.

In order to avoid possible data conflicts, the admin will create two custom apps: one for the canary release, and one for the stable release. This keeps the backups, snapshots, and clone operations separate for the two groups of Kubernetes objects.

After she adds the cluster to the Astra beta program, her next step is to define a custom app. To do this, she clicks the + **Define custom app** button on the Apps page.

In the pop-up window which appears, she sets `devops-canary-deployment` as the app name. She chooses the cluster in the **Compute** drop-down, then the app's namespace from the **Namespace** drop-down.

At this point, she can either type `deployment=canary` in the **Labels** field, or select that label from the resources listed below.

After defining the custom app for the canary deployment, she repeats the process for the stable deployment.

When she has finished creating the two custom apps, she can treat these resources as any other Astra application. She can clone them, create backups and snapshots, and create a custom Protection Policy for each group of resources based on her Kubernetes labels.

Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.