# Define a custom app

Project Astra

Erika Barcott November 11, 2020

This PDF was generated from https://docs.netapp.com/us-en/project-astra/learn/define-custom-app.html on November 17, 2020. Always check docs.netapp.com for the latest.



# **Table of Contents**

Define a custom app		1
Example: Separate Protection Policy for canar	ry release	2

## Define a custom app

Creating a custom app lets you group elements of your Kubernetes cluster into a single app.


A custom app gives you more granular control over what to include in a Astra operation, including:

- Clone
- Snapshot
- Backup
- Protection Policy

In most cases you will want to use Astra's features on your entire app. However, you can also create a custom app to use these features by the labels you assign to Kubernetes objects in a namespace.

To create a custom app, go to the Apps page and click + **Define custom app**.

As you make your selections, the Custom App window will show you which resources will be included or excluded from your custom app. This helps you make sure you are choosing the correct criteria for defining your custom app.



In the above example, one resource (the pod nginx-pod0 labeled deployment:canary) will be included in the custom app. Two pods (nginx-pod and nginx-pod2 both labeled deployment:stable) will be excluded.



Custom apps can only be created within a specified namespace on a single cluster. The Astra beta program does not support the ability for a custom app to span multiple namespaces or clusters.

A label is a key/value pair you can assign to Kubernetes objects for identification. Labels make it easier

to sort, organize, and find your Kubernetes objects. To learn more about Kubernetes labels, see the official Kubernetes documentation.



Overlapping policies for the same resource under different names can cause data conflicts. If you create a custom app for a resource, be sure it's not being cloned or backed up under any other policies.

### **Example: Separate Protection Policy for canary release**

In this example, the devops team is managing a canary release deployment. Their cluster has three pods running NginX. Two of the pods are dedicated to the stable release. The third pod is for the canary release.

The devops team's Kubernetes admin adds the label deployment=stable to the stable release pods. She adds the label deployment=canary to the canary release pod.

```
:~$ kubectl get pods --namespace=nginx-app --show-labels
NAME
                               RESTARTS
                                           AGE
                                                 LABELS
             READY
                     STATUS
nginx-pod0
                                                 deployment=canary,run=nginx-pod0
             1/1
                     Running
                                           50s
nginx-pod1
             1/1
                     Running
                                           45s
                                                 deployment=stable,run=nginx-pod1
                               0
nginx-pod2
                     Running
                                           41s
                                                 deployment=stable,run=nginx-pod2
             1/1
                  :~$
```

The team's stable release includes a requirement for hourly snapshots and daily backups. The canary release is more ephemeral, so they want to create a less aggressive, short-term Protection Policy for anything labeled deployment=canary.

In order to avoid possible data conflicts, the admin will create two custom apps: one for the canary release, and one for the stable release. This keeps the backups, snapshots, and clone operations separate for the two groups of Kubernetes objects.

After she adds the cluster to the Astra beta program, her next step is to define a custom app. To do this, she clicks the + **Define custom app** button on the Apps page.

In the pop-up window which appears, she sets devops-canary-deployment as the app name. She chooses the cluster in the **Compute** drop-down, then the app's namespace from the **Namespace** drop-down.

At this point, she can either type deployment=canary in the **Labels** field, or select that label from the resources listed below.

After defining the custom app for the canary deployment, she repeats the process for the stable deployment.

When she has finished creating the two custom apps, she can treat these resources as any other Astra application. She can clone them, create backups and snapshots, and create a custom Protection Policy for each group of resources based on her Kubernetes labels.

### **Copyright Information**

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval systemwithout prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

#### **Trademark Information**

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.