



# Install Kubectl to Control a Kubernetes Cluster

## Project Astra

Ben Cammett  
September 23, 2020

This PDF was generated from <https://docs.netapp.com/us-en/project-astra/solutions/install-kubectl.html> on November 17, 2020. Always check docs.netapp.com for the latest.

# Table of Contents

- Install Kubectl to Control a Kubernetes Cluster ..... 1
  - Windows..... 1
  - Mac OS..... 2
  - External Linux Server..... 2

# Install Kubectl to Control a Kubernetes Cluster

Kubectl is the command line interface for interacting with a Kubernetes cluster.

## Overview

Kubectl gets its cluster connection and login information from the cluster's `kubeconfig` file. In order to use kubectl you will need to:

1. Install kubectl on your local machine.
2. Download the cluster's kubeconfig file.
3. Move the kubeconfig file to your user directory, then update your shell's environment.

More kubectl documentation can be found [on the official Kubernetes site](#).

## Windows

The easiest way to install kubectl on Windows is to use [the Chocolatey package manager](#). You can install Chocolatey with a single command from a PowerShell or cmd window. The installation instructions for both Administrator and non-Administrator rights are [here on the Chocolatey website](#).

After you have installed Chocolatey, open PowerShell or cmd, then install kubectl with the command:

```
choco install kubernetes-cli
```

Move to your home directory:

```
cd C:\users\[your username]
```

For example:

```
cd C:\users\jdoe
```

Create the `.kube` directory:

```
mkdir .kube
```

Move to the `.kube` directory:

```
cd .kube
```

Download your cluster's `kubeconfig` file. Move this file to the `C:\users\yourusername\.kube` directory. Then update your shell environment to call the file:

```
$env:KUBECONFIG="C:\users\[your username]\.kube\[kubeconfig file name]"
```

For example:

```
$env:KUBECONFIG="C:\users\jdoe\.kube\kubeconfig"
```

## Mac OS

You can install `kubectl` on MacOS using either the [Homebrew](#) or [Macports](#) package managers.

To install with Homebrew, open a Terminal window and use the command:

```
brew install kubernetes-cli
```

To install with Macports, open a Terminal window and use the command:

```
port install kubectl
```

Download your cluster's `kubeconfig` file. Move this file to your home directory:

```
mv /Users/username/Downloads/kubeconfig /Users/username/
```

Then update your shell environment to call the file:

```
export KUBECONFIG=/Users/username/kubeconfig
```

## External Linux Server

Another option is to SSH to a server, install `kubectl`, then use it to control your Kubernetes cluster. If you have access to a Linux server, there are several advantages to this approach:

- If you have root on the server, you will be able to install the Kubernetes software without having to deal with any desktop computer permissions problems.

- Speaking of computer permissions issues, it's often the case that in order to run Kubernetes on a Windows computer, you need to run PowerShell on Windows as Administrator. If you are not able to run applications with administrator rights, you can avoid the issue by connecting to a Linux server with SSH and running kubectl from there.
- If you frequently find yourself using several different computers, you can SSH to the server from anywhere. This saves you from having to install Kubernetes on every machine you use.
- If you have customized your SSH program to your liking (fonts, colors, etc.) it can be nicer to use it than the stock terminal or PowerShell window.

To install kubectl on a Linux server, follow the instructions for your distribution.

## Ubuntu, Debian, and HypriotOS

Install with the commands:

```
sudo apt-get update && sudo apt-get install -y apt-transport-https

curl -s https://packages.cloud.google.com/apt/doc/apt-key.gpg | sudo apt-key add -

echo "deb http://apt.kubernetes.io/ kubernetes-xenial main" | sudo tee -a
/etc/apt/sources.list.d/kubernetes.list

sudo apt-get update

sudo apt-get install -y kubectl
```

## CentOS, RHEL, and Fedora

Install with the commands:

```
cat <<EOF > /etc/yum.repos.d/kubernetes.repo
[kubernetes]
name=Kubernetes
baseurl=https://packages.cloud.google.com/yum/repos/kubernetes-el7-x86_64
enabled=1
gpgcheck=1
repo_gpgcheck=1
gpgkey=https://packages.cloud.google.com/yum/doc/yum-key.gpg
https://packages.cloud.google.com/yum/doc/rpm-package-key.gpg
EOF

yum install -y kubectl
```

Download your cluster's **kubeconfig** file. Upload the file to the server. Then update your shell

environment to call the file:

```
export KUBECONFIG=/path/to/kubeconfig
```

For example:

```
export KUBECONFIG=/usr/home/jdoe/kubeconfig
```

## Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.