EXPERIMENT NO-6

main.c

Clear Run

```c

#include <stdio.h>

int main()
{
    int n, i, time = 0, completed = 0;
    int bt[10], rt[10], p[10], wt[10], tat[10];
    int highest, min;

    printf("Enter number of processes: ");
    scanf("%d", &n);

    for(i = 0; i < n; i++)
    {
        printf("Enter burst time and priority of P%d: ", i+1);
        scanf("%d %d", &bt[i], &p[i]);
        rt[i] = bt[i];
    }

    while(completed < n)
    {
        highest = -1;
        min = 9999;

        for(i = 0; i < n; i++)
        {
```

Output

```
Enter number of processes: 3
Enter burst time and priority of P1: 5 2
Enter burst time and priority of P2: 3 1
Enter burst time and priority of P3: 2 3

Process BT  Priority    WT  TAT
P1  5   2       3   8
P2  3   1       0   3
P3  2   3       8   10
```

main.c

Clear Run

```c

        if(highest == -1)
            break;

        rt[highest]--;
        time++;

        if(rt[highest] == 0)
        {
            completed++;
            tat[highest] = time;
            wt[highest] = tat[highest] - bt[highest];
        }
    }

    printf("\nProcess\tBT\tPriority\tWT\tTAT\n");

    for(i = 0; i < n; i++)
    {
        printf("P%d\t%d\t%d\t\t%d\t%d\n",
        i+1, bt[i], p[i], wt[i], tat[i]);
    }

    return 0;
}

```

Output

```
Enter number of processes: 3
Enter burst time and priority of P1: 5 2
Enter burst time and priority of P2: 3 1
Enter burst time and priority of P3: 2 3

Process BT  Priority    WT  TAT
P1  5   2       3   8
P2  3   1       0   3
P3  2   3       8   10
```