

```
1  Jun 19 16:22 58% 3.5 79 B/s
+ R1
R1(config)#ip route 192.168.20.0 255.255.255.0 10.10.10.2
R1(config)#end
R1#wr
R1#write
*Jun 19 09:20:20.615: %SYS-5-CONFIG_I: Configured from console by console
R1#write memo
R1#write memory
Warning: Attempting to overwrite an NVRAM configuration previously written
by a different version of the system image.
Overwrite the previous NVRAM configuration?[confirm]
Building configuration...
[OK]
R1#show ip interface brief
Interface IP-Address OK? Method Status Protocol
FastEthernet0/0 192.168.10.1 YES manual up up
FastEthernet1/0 10.10.10.1 YES manual up up
FastEthernet1/1 unassigned YES unset administratively down down
R1#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
+ - replicated route, % - next hop override

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 10.10.10.0/30 is directly connected, FastEthernet1/0
L 10.10.10.1/32 is directly connected, FastEthernet1/0
192.168.10.0/24 is variably subnetted, 2 subnets, 2 masks
C 192.168.10.0/24 is directly connected, FastEthernet0/0
L 192.168.10.1/32 is directly connected, FastEthernet0/0
S 192.168.20.0/24 [1/0] via 10.10.10.2
R1#
```

```
1  Jun 19 16:24 58% 3.7 198 B/s
+ R2
R2#
*Jun 19 09:24:07.599: %SYS-5-CONFIG_I: Configured from console by console
R2#wr
R2#write memo
R2#write memory
Warning: Attempting to overwrite an NVRAM configuration previously written
by a different version of the system image.
Overwrite the previous NVRAM configuration?[confirm]
Building configuration...
[OK]
R2#show ip interface brief
Interface IP-Address OK? Method Status Protocol
FastEthernet0/0 192.168.20.1 YES manual up up
FastEthernet1/0 10.10.10.2 YES manual up up
FastEthernet1/1 unassigned YES unset administratively down down
R2#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
+ - replicated route, % - next hop override

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 10.10.10.0/20 is directly connected, FastEthernet1/0
L 10.10.10.2/32 is directly connected, FastEthernet1/0
S 192.168.10.0/24 [1/0] via 10.10.10.1
192.168.20.0/24 is variably subnetted, 2 subnets, 2 masks
C 192.168.20.0/24 is directly connected, FastEthernet0/0
L 192.168.20.1/32 is directly connected, FastEthernet0/0
R2#
```

```
1 2 Jun 19 16:27 56% 3.5 3 KB/s
+ ZabbixServer
R1 x R2 x ZabbixServer x Client1 x Client2 x
Trying 127.0.0.1...
Connected to localhost.
Escape character is '^]'.

ZabbixServer> ip 192.168.10.10/24 192.168.10.1
Checking for duplicate address...
ZabbixServer : 192.168.10.10 255.255.255.0 gateway 192.168.10.1

ZabbixServer> save
Saving startup configuration to startup.vpc
. done

ZabbixServer> 
```

```
1 2 Jun 19 16:27 57% 3.3 87 KB/s
+ Client1
R1 x R2 x ZabbixServer x Client1 x Client2 x
Trying 127.0.0.1...
Connected to localhost.
Escape character is '^]'.

Client1> ip 192.168.20.10/24 192.168.20.1
Checking for duplicate address...
sClient1 : 192.168.20.10 255.255.255.0 gateway 192.168.20.1

Client1> save
Saving startup configuration to startup.vpc
. done

Client1> 
```

```
1 2 Jun 19, 16:27 58% 3.5 3 KB/s
+ Client2
R1 x R2 x ZabbixServer x Client1 x Client2 x
Trying 127.0.0.1...
Connected to localhost.
Escape character is '^]'.

Client2> ip 192.168.20.20/24 192.168.20.1
Checking for duplicate address...
Client2 : 192.168.20.20 255.255.255.0 gateway 192.168.20.1

Client2> save
Saving startup configuration to startup.vpc
. done

Client2>
```