

Aria Smart Lock — Owner's Manual

Aria Home · SKU ARIA-LOCK · lock · \$199

This manual covers the Aria Smart Lock (model ARIA-LOCK) only. Other Aria products have their own manuals; procedures and error codes are not interchangeable between models.

1. Specifications

Fits	most single-cylinder deadbolts; keeps your existing keys
Access	app, auto-unlock by proximity, schedules for guests
Radio	Bluetooth LE; Wi-Fi through the Aria Hub or Aria Wi-Fi Bridge
Motor	auto-lock after 30 seconds to 30 minutes
Battery	4 × AA alkaline, about 6 months

2. In the box

Lock body, mounting plate, three tailpiece adapters, 4 AA batteries, screws.

3. Setup

1. Remove the interior thumb-turn of your deadbolt; keep the exterior side and keys.
2. Fit the adapter that matches your tailpiece (D, cross, or square).
3. Attach the mounting plate, then slide the lock body on until it clicks.
4. Insert 4 AA batteries; the lock calibrates by turning fully both ways.
5. Pair in the Aria app over Bluetooth, then add the Wi-Fi Bridge for remote access.

4. Status light

Green flash: unlocked.

Red flash: locked.

Amber double flash: battery low.

Blue breathing: pairing.

5. Power and battery

Aria Smart Lock: 4 × AA alkaline, about 6 months. Lithium AA is not recommended (voltage curve fools the gauge).

6. Troubleshooting

Aria Smart Lock — Lock sticks or grinds in cold weather. The deadbolt is binding in the strike plate; the motor cannot push through. Loosen the strike plate screws a quarter turn and re-run Calibrate from

lock settings. Lubricate the bolt with dry graphite, not oil.

Aria Smart Lock — Auto-unlock does not trigger. Auto-unlock needs Location Always and Bluetooth on; it arms only after you have been more than 200 meters away.

Aria Smart Lock — Says Jammed in the app. Door was not fully closed. Close it, then tap Retry.

Aria Smart Lock — Battery lasts only a few weeks. Auto-lock set to under 1 minute doubles motor cycles; set to 5 minutes or use door-sense.

7. Error codes

Aria Smart Lock error L-01: Calibration failed — remove and reseal the lock body, then Calibrate again.

Aria Smart Lock error L-04: Bolt blocked — the door is misaligned; check the strike plate.

Aria Smart Lock error L-07: Battery critical — fewer than 10 operations remain.

8. Factory reset

To factory reset the Aria Smart Lock: Remove the batteries, hold the reset button inside the battery bay while reinserting them, keep holding for 10 seconds until the light turns blue.

9. Warranty and compatibility

The Aria Smart Lock carries a two-year standard warranty covering manufacturing defects, from the delivery date. Unwanted returns follow the Aria Home returns policy: 14 days from delivery for the Aria Smart Lock (security devices have a 14-day window). Damage caused by the customer is handled as a warranty repair, not a refund.

Works with: Aria app, Aria Hub, Aria Wi-Fi Bridge, Google Home, Amazon Alexa, Apple Home via Hub.