

Smart Thermostat V2 — Owner's Manual

Aria Home · SKU ARIA-THERM-V2 · thermostat · \$159

This manual covers the Smart Thermostat V2 (model ARIA-THERM-V2) only. Other Aria products have their own manuals; procedures and error codes are not interchangeable between models.

1. Specifications

Display	3.0-inch OLED, 320×320
Sensors	temperature, humidity, occupancy radar, ambient light
HVAC support	2H/2C conventional, dual-fuel, heat pump with aux
Wiring	R, C, W1, W2, Y1, Y2, G, O/B, AUX — works without a C-wire using the included Power Bridge
Temperature range	45–95 °F setpoint, accuracy ±0.3 °F
Wi-Fi	2.4 GHz and 5 GHz

2. In the box

Thermostat, trim plate, Power Bridge, screws, wire labels.

3. Setup

1. If you have no C-wire, install the Power Bridge at the furnace control board first.
2. Mount the base, seat each wire, then click the display on.
3. The V2 supports 5 GHz Wi-Fi; either band works.
4. Scan the QR code in the Aria app and follow the equipment wizard.

4. Status light

Soft white glow: occupied, idle.

Amber sweep: heating.

Blue sweep: cooling.

Purple: auxiliary heat running.

Red outline: wiring fault — see the app for the terminal.

5. Power and battery

Smart Thermostat V2: 24 V AC with or without a C-wire (Power Bridge). Internal backup cell keeps time for 48 hours.

6. Troubleshooting

Smart Thermostat V2 — Furnace short-cycles after install. The Power Bridge is on the wrong terminals; it goes on W and Y at the control board, never at the thermostat.

Smart Thermostat V2 — Occupancy shows Away while someone is home. The radar needs clear line of sight; move furniture more than 3 feet away or lower Sensitivity.

Smart Thermostat V2 — Aux heat runs too often. Raise the Aux lockout temperature in Settings > Equipment > Heat pump balance.

7. Error codes

Smart Thermostat V2 error V2-01: Power Bridge not detected — check the bridge LED is green at the furnace.

Smart Thermostat V2 error V2-05: Y2 called with single-stage compressor — set Stages to 1 in the equipment wizard.

Smart Thermostat V2 error V2-09: Radar sensor blocked — clean the front panel.

8. Factory reset

To factory reset the Smart Thermostat V2: Press and hold the display for 15 seconds until it shows Restoring, then release.

9. Warranty and compatibility

The Smart Thermostat V2 carries a two-year standard warranty covering manufacturing defects, from the delivery date. Unwanted returns follow the Aria Home returns policy: 30 days from delivery for the Smart Thermostat V2 (most devices have a 30-day window). Damage caused by the customer is handled as a warranty repair, not a refund.

Works with: Aria app, Google Home, Amazon Alexa, Apple Home, Matter over Wi-Fi.