

CSE427s - 8 Spark
Introduction

43% (3/7)

- ✗ 1. ~~File~~ `textFile()` used to read the data...
- ☒ A is an action
 - ☐ B is a transformation
 - ☒ C (re)partitions the RDD
- ✓ 2. ~~File~~ `flatMap()` used to split the lines of text is...
- ☐ A is an action
 - ☒ B is a transformation
 - ☐ C (re)partitions the RDD
- ✓ 3. ~~File~~ `map()` used to create a pair RDD is...
- ☐ A is an action
 - ☒ B is a transformation
 - ☐ C (re)partitions the RDD
- ✗ 4. ~~File~~ `reduceByKey()` used to add the counts...
- ☐ A is an action
 - ☒ B is a transformation
 - ☐ C (re)partitions the RDD
- ✓ 5. ~~File~~ `take()` used to display some of the computed counts...
- ☒ A is an action
 - ☐ B is a transformation
 - ☐ C (re)partitions the RDD
- ✗ 6. ~~File~~ Transformations in Spark are only executed when triggered by an Action.
- ☐ A True
 - ☒ B False
- ✗ 7. ~~File~~ Repartitioning in Spark is equivalent to Group & Sort in MapReduce.
- ☐ A True
 - ☒ B False